

Problem Statement

You are given an array of n strings, all of the same length.

We may choose any deletion indices, and we delete all the characters in those indices for each string.

For example, if we have `strs = ["abcdef", "uvwxyz"]` and deletion indices, then the final array after deletions is `["bef", "vyz"]`.

Suppose we chose a set of deletion indices `answer` such that after deletions, the final array has every string (row) in lexicographic order (i.e., $(strs[0][0] \leq strs[0][1] \leq \dots \leq strs[0][strs[0].length - 1])$, and $(strs[1][0] \leq strs[1][1] \leq \dots \leq strs[1][strs[1].length - 1])$, and so on). Return *the minimum possible value of answer.length*.

Input Format

First line contains single integer n , where n is the size of vector `strs`.

Second line contains the element of vector `strs`.

Output Format

Print *the minimum possible value of answer.length*.

Constraints

- $n == strs.length$
- $1 \leq n \leq 100$
- $1 \leq strs[i].length \leq 100$
- `strs[i]` consists of lowercase English letters

Sample Testcase 0

Testcase Input

```
2
babca bbazb
```

Testcase Output

```
3
```

Explanation

After deleting columns 0, 1, and 4, the final array is `strs = ["bc", "az"]`.
Both these rows are individually in lexicographic order (ie. `strs[0][0] <= strs[0][1]` and `strs[1][0] <= strs[1][1]`).
Note that `strs[0] > strs[1]` - the array `strs` is not necessarily in lexicographic order.

Sample Testcase 1

Testcase Input

```
4
abc def ghi xyz
```

Testcase Output

```
0
```

Explanation

All rows are already lexicographically sorted.

CODE

```
#include<bits/stdc++.h>
using namespace std;

int dp[100][101];

// i is the current column and j is the prev column
int solve(string strs[], int n, int i, int j)
{
    if(i == strs[0].size())
        return 0;

    if(dp[i][j+1] != -1)
        return dp[i][j+1];

    int left = solve(strs, n, i+1, j) + 1;
    int right = 1e9;
    if(j == -1) {
        right = solve(strs, n, i+1, i);
    } else {
        int r;
        for(r=0; r<n; r++) {
            if(strs[r][i] < strs[r][j])
                break;
        }
        if(r == n)
            right = solve(strs, n, i+1, i);
    }

    return dp[i][j+1] = min(left, right);
}

int main() {
    int n;
```

```
    cin >> n;
    string strs[n];
    for(int i=0; i<n; i++) {
        cin >> strs[i];
    }
    memset(dp, -1, sizeof(dp));
    cout << solve(strs, n, 0, -1);
    return 0;
```

```
}
```

Here's an explanation of the code:

1.The code uses dynamic programming to solve the problem efficiently. It maintains a 2D array `dp` to store the results of subproblems. `dp[i][j]` represents the minimum number of deletions needed to make the substring consisting of columns from `i` to the end lexicographically ordered, given that the previous column was column `j`.

2.The `solve` function is a recursive function that calculates the minimum number of deletions for a specific substring of columns.

3.In the `main` function, it first reads the input values. It reads the integer `n`, which represents the number of strings in the array, and then reads the `n` strings into the `strs` array.

4.It initializes the `dp` array with -1 to indicate that no results have been computed yet.

5.It calls the `solve` function with the initial parameters `i = 0` (starting from the first column) and `j = -1` (no previous column). The result of the `solve` function is the minimum number of deletions needed to make all strings in the array lexicographically ordered.

6.The `solve` function itself is defined as follows:

- If `i` has reached the end of the columns (`strs[0].size()`), it returns 0 because no further deletions are needed.
- If the result for the current position `dp[i][j+1]` is already computed, it returns that result.
- It calculates two possibilities:
 - `left` represents the case where the current column is deleted, so we increment `i` by 1, and the previous column `j` remains the same.
 - `right` represents the case where the current column is not deleted. To check this, it iterates through all rows `r` and checks if the character in the current column `i` is lexicographically smaller than the character in the previous column `j`. If it is, it breaks the loop, indicating that the current column cannot be retained to maintain lexicographical order. If `r` reaches `n`, it means all rows satisfy the condition, and `right` can be calculated by recursively calling `solve` with the current column `i` and updating `j` to the current column `i`.
- The function returns the minimum of `left` and `right` as the result and stores it in `dp[i][j+1]`.

7.Finally, the `main` function prints the result obtained from the `solve` function, which represents the minimum number of deletions needed to make all strings lexicographically ordered.