
REVISION HISTORY

Rev. A INITIAL RELEASE



BOARD CHARACTERISTICS

Copper Layer Count: 6 Board Thickness: 1.6000 mm

Board overall dimensions: 102.3000 mm x 60.0000 mm

Min track/spacing:0.0900 mm / 0.0900 mmMin hole diameter:0.2500 mmCopper Finish:ENIGImpedance Control:NoCastellated pads:NoPlated Board Edge:No

Edge card connectors: No

	Lage cara connectors.										
	Layer Name	Туре	Material	Thickness (mm)	Color	Epsilon R	Loss Tangent				
Ц	F.Silkscreen	Top Silk Screen	Not specified	0 mm	White	1	0				
1	F.Paste	Top Solder Paste		0 mm		1	0				
	F.Mask	Top Solder Mask	Not specified	0.01 mm	Green	3.3	0				
	F.Cu (Signal)	copper		0.035 mm		1	0				
	Dielectric	prepreg	FR4	0.1 mm	Not specified	4.5	0.02				
	In1.Cu (Ground)	copper		0.0152 mm		1	0				
	Dielectric	core	Copper	0.5548 mm	#D2960FFF	4.5	0.02				
	In2.Cu (Signal)	copper		0.0152 mm		1	0				
	Dielectric	prepreg	FR4	0.1 mm	Not specified	4.5	0.02				
	In3.Cu (Ground)	copper		0.035 mm		1	0				
	Dielectric	core	FR4	0.5548 mm	Not specified	4.5	0.02				
	In4.Cu (Power)	copper		0.035 mm		1	0				
	Dielectric	prepreg	FR4	0.1 mm	Not specified	4.5	0.02				
	B.Cu (Ground)	copper		0.035 mm		1	0				
	B.Mask	Bottom Solder Mask	Not specified	0.01 mm	Green	3.3	0				
	B.Paste	Bottom Solder Paste		0 mm		1	0				
	B.Silkscreen	Bottom Silk Screen	Not specified	0 mm	White	1	0				

NOTES: UNLESS OTHERWISE SPECIFIED

1: MANUFACTURE TO IPC CLASS 2

1590N1 BASEBOARD - PCBA		PCB		RELEASED		
© Alessandro Rizzoni	APPROVED BY		DATE OF ISSU	-	SHEET 1/1	

С

.1×17"