
# RBE 500 Midterm

Arjan Gupta

### Problem 1

Derive the rotation matrix  $\mathbb{R}^1_2$  (you can leave sines and cosines as is).



### Solution

Since the x-axis remains the same in the rotation, we know this is a basic 3D rotation matrix representing a rotation about the x-axis. However, using the right-hand screw rule, we see that the angle  $\theta$  here is negative. So, by using equation 2.7 (page 43) of our main textbook, the rotation matrix is given by,

$$R_{2}^{1} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos(-\theta) & -\sin(-\theta) \\ 0 & \sin(-\theta) & \cos(-\theta) \end{bmatrix}$$

$$R_{2}^{1} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos\theta & \sin\theta \\ 0 & -\sin\theta & \cos\theta \end{bmatrix}$$

#### Problem 2

Find the coordinates of point p expressed in frame 1 (i.e.  $p^1$ ) given the following.

$$H_1^2 = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & 0.9553 & 0.2955 & -0.9553 \\ 0 & -0.2955 & 0.9553 & 0.2955 \\ 0 & 0 & 0 & 1 \end{bmatrix}, \ p^2 = \begin{bmatrix} 2 \\ 5 \\ 0 \end{bmatrix}$$

#### Solution

From our knowledge of homogeneous transformations, we know that

$$P^2 = H_1^2 P^1$$

Where 
$$P^2 = \begin{bmatrix} p^2 \\ 1 \end{bmatrix}$$
 and  $P^1 = \begin{bmatrix} p^1 \\ 1 \end{bmatrix}$ .

However, we want to find  $P^1$ , so we apply the inverse of H to both sides,

$$P^2 = H_1^2 P^1$$
$$\left(H_1^2\right)^{-1} P^2 = P^1$$

We know that 
$$H_1^2 = \begin{bmatrix} R_1^2 & d_1^2 \\ 0 & 1 \end{bmatrix}$$
, where  $R_1^2 = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 0.9553 & 0.2955 \\ 0 & -0.2955 & 0.9553 \end{bmatrix}$  and  $d_1^2 = \begin{bmatrix} -1 \\ -0.9553 \\ 0.2955 \end{bmatrix}$ .

For accuracy while computing the inverse of  $H_1^2$ , we use equation 2.67 of the book (page 63). Therefore,

$$(H_1^2)^{-1} = \begin{bmatrix} (R_1^2)^T & -(R_1^2)^T d_1^2 \\ 0 & 1 \end{bmatrix}$$

. We use the following MATLAB code for this computation.

```
1 % Calculation code for problem 2 of the RBE500 Midterm
2
3 clear; close all; clc;
4
5 P2 = [2;5;0;1];
6
7 R2_1 = [1 0 0; 0 0.9553 0.2955; 0 -0.2955 0.9553];
8 d2_1 = [-1; -0.9553; 0.2955];
9 H_inv = [R2_1' (-R2_1'*d2_1); zeros(1,3) 1];
10
11 P1 = H_inv*P2
```

Which gives us the answer,

$$P^1 = \begin{bmatrix} 3.0000 \\ 5.7764 \\ 1.4775 \\ 1.0000 \end{bmatrix}$$

# Problem 3