COMMUNITY DISASTER VOLUNTEER HUB

CDVH 02

Landslides, Landslide Susceptibility, and Ground Movement

Hazard/domain: landslide, rockfall, debris flow, ground movement
Geographic scope: India, especially Kerala hill slopes and road corridors

Document ID	CDVH-02-KB
Version	1.1.0
Compiled / reviewed for consistency	2026-10-16
Intended audience	Public, volunteers, community coordinators and RAG developers
Use limitation	Educational reference; not a live alert, operational order, professional inspection, medical treatment or legal advice
Research status	Official source pages and source limitations are listed in this document

Safety rule: if a person is in immediate danger or a current evacuation instruction applies, take protective action and contact local emergency services. Do not wait for a chatbot to complete an assessment.

Contents and document use

Document ID CDVH-02-KB | Version 1.1.0 | Source access date 2026-10-16

How to use this document

Sections are designed to be retrieved independently. Preserve the hazard, geography, time period, conditions and source context when indexing. This PDF is reference material; current warnings, road closures, shelter status and live environmental readings require a current authorized source.

Section map

Section	Page
01 Core science and definitions	3
02 Causes, contributing factors, and mechanisms	4
03 Indicators, warning signs, and limitations	5
04 Location-specific risk assessment	6
05 Prevention and mitigation	7
06 Preparedness and readiness	8
07 Immediate response procedures	9
08 Evacuation and protective actions	10
09 Volunteer and responder coordination	11
10 Vulnerable populations and inclusive planning	12
11 Recovery and lessons learned	13
12 Complex scenarios and chatbot guardrails	14
Frequently asked questions (24)	15-18
Glossary and interpretation rules	19
References and source notes	20

Additional components: 24 FAQs, a glossary, references and source/update limitations.

Risk concepts

Susceptibility describes relative tendency for a place to experience a process. Hazard concerns the potentially damaging event and its characteristics over a defined period. Exposure concerns people and assets in harm's way. Vulnerability describes conditions that increase susceptibility to harm. Capacity includes resources and abilities that help reduce consequences. Risk concerns potential adverse consequences considering these dimensions and uncertainty. A susceptibility map is not an imminent-event forecast; a low map class is not a guarantee of safety.

01 Core science and definitions

Document 02 | Section 01 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

A landslide is movement of rock, earth or debris down a slope. Mechanisms include slides, falls, flows, topples and slow deformation. Rain can raise pore-water pressure, reduce effective strength and add weight; water can also erode slope toes and concentrate into debris flows. The failure point and downstream runout zone may differ, so people below a slope or along a channel can be exposed beyond the visible scar.

Use the terms in this section carefully. A hazard description identifies the physical or operational process; it does not by itself establish that a particular household will be affected. For public guidance, name the process, the relevant geography and the time horizon before discussing consequences. In technical subjects, define abbreviations and preserve the unit, scale or jurisdiction that gives a term its meaning.

For a retrieved passage about landslide, rockfall, debris flow, ground movement, the minimum useful context is: what process is being discussed, where the statement applies, whether it is general or current, who issued the information, and what practical decision the reader is trying to make. A passage missing one of these may still explain a concept, but it should not be used alone for an operational decision.

Landslide terminology should distinguish the source scar from the possible runout or debris-flow path. A user below a connected slope may face a different pathway from someone the same distance away across a ridge. These distinctions are essential when interpreting reports of a nearby failure.

Decision aid

Term	Meaning for decision support	Do not infer
Hazard / process	What could cause harm and how it may operate	That harm is occurring at a named house now
Exposure	People, buildings, services or livelihoods in the affected area	That all exposed people have equal vulnerability
Vulnerability / capacity	Conditions that can increase harm or improve coping	That a map or average describes every person
Risk statement	Potential consequences over a stated period and context	An exact probability without suitable evidence

Practical checks

- Write the geography and time window near the claim.
- Attribute official instructions to the issuing authority and preserve issue time.
- Keep uncertain inference separate from observation and published guidance.

Supporting source identifiers: [S01], [S03], [S05], [S06]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

02 Causes, contributing factors, and mechanisms

Document 02 | Section 02 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

Relevant drivers include slope angle and shape, rock/soil strength, weathering, fractures, groundwater, prolonged or intense rainfall, past failures, drainage concentration, road cuts, excavation, loading near a crest, leakage, loss of vegetation and seismic shaking. These interact differently from place to place. A rainfall threshold from one slope or district cannot be assumed valid for another without local validation.

A useful explanation separates background susceptibility, a trigger, a pathway of impact and exposed assets. The word 'cause' should be used with care: several conditions may contribute, and the data available to a chatbot may not establish which factor controlled an individual event. The relevant scientific mechanism for landslide, rockfall, debris flow, ground movement must be matched to the actual site or system rather than assumed from a neighbouring district.

When explaining a possible event, show how evidence links each stage. For example, a regional weather event may create a broad loading or stress condition, but local terrain, drainage, construction, infrastructure condition or exposure can change the result. In other topics, the same logic applies to river-network routing, coastal water levels, building response, fire spread or gaps in a technical data pipeline. A plausible pathway is not proof that the pathway will occur.

One plausible rainfall-related pathway is prolonged wetting, increasing pore-water pressure or surface runoff, followed by a local failure and possible downslope transport. This is a mechanism explanation, not a prediction that a particular slope will fail; soil, geology, drainage and human alterations vary locally.

Decision aid

Stage	Question to ask	Evidence limitation
Precondition	What makes this place or system susceptible?	May be incompletely mapped or not visible
Trigger	What recent forcing or failure could initiate change?	A trigger rarely determines the exact outcome alone
Pathway	How could the process reach people/assets?	Terrain, network or building connection matters
Consequence	Who or what could be affected, and how?	Exposure and protective capacity vary locally

Practical checks

- Use 'may contribute' when the evidence is conditional.
- Do not assert a single cause from timing alone.
- Route technical mechanism questions to qualified authorities when site-specific judgment is necessary.

Supporting source identifiers: [S01], [S03], [S05], [S06]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

03 Indicators, warning signs, and limitations

Document 02 | Section 03 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

Possible signs include new or widening ground cracks, fresh bulges, leaning trees or poles, doors and windows suddenly sticking, new seepage, muddy springs, broken buried utilities, unusual rockfall, small recurring slides, or sudden changes in stream level/noise. Some failures happen with few visible signs. A sign is not proof, but credible new movement warrants distance from the danger area and prompt reporting.

Warning signs are observations that can justify protective action or reporting; they are not a complete diagnostic test. The evidence may be early, ambiguous or absent. A checklist cannot promise that an event will be detected before it becomes dangerous. Users should observe from a safe location and report what they saw, where and when, without approaching the hazard to obtain a clearer picture.

The safest public workflow is to separate direct observation from a forwarded message, a model interpretation and an official bulletin. Record the time, approximate place, direction of change and whether the observation is continuing. If the sign suggests immediate danger, first move away by a safe route and alert appropriate emergency services; the chatbot should not ask for photos or multiple confirmations before recommending that action.

A simple safe report is: approximate place; time noticed; what changed; whether it is continuing; whether people or a route appear threatened; and whether the information is direct observation. Do not ask residents to return to a slope, creek or road to collect evidence.

Decision aid

Evidence type	Useful interpretation	Safe next action
Direct, changing physical sign	May indicate a developing local danger	Move away if threatened; report from safety
Official alert or order	Authoritative for its stated area/time and instruction	Follow it; verify updates as appropriate
Third-party message / screenshot	Unverified until source and timestamp are checked	Do not forward as fact; verify through official channel
No visible sign / no alert	Absence of evidence, not proof of safety	Use other relevant evidence and current guidance

Practical checks

- Never enter, cross or approach a hazard to verify a sign.
- Do not require every listed sign to be present.
- Explain when signs are nonspecific and why qualified assessment may be needed.

Supporting source identifiers: [S01], [S03], [S05], [S06]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

04 Location-specific risk assessment

Document 02 | Section 04 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

A nearby landslide at 1, 5 or 10 km does not define whether another site is safe. Evaluate whether sites share a slope, ridge, catchment or debris-flow channel; compare elevation and terrain connectivity; and check rainfall, saturation, geology, land cover, previous failures, local susceptibility maps and current official alerts. Straight-line distance is only one weak descriptor; there is no universal safe-radius cutoff.

A preliminary risk screen should answer four distinct questions: what is the hazard or process; what present evidence describes it; which people or assets may be exposed; and what conditions make the consequences more or less severe. Static maps and regional alerts are inputs, not individual guarantees. State the observation date, map scale or forecast period, geographic coverage and uncertainty whenever known.

For a landslide reported 5 km away, assess whether the user is on the same slope system, above or below the scar, in a connected debris-flow channel, or in a separate catchment. Shared prolonged rainfall can trigger separate failures without the original slide travelling the whole distance. A radius alone cannot give a probability.

For the required nearby-landslide scenario, compare slope connection, elevation, runout channel, geology, rainfall pattern, ground saturation, local alterations and signs at the user's site. At 1 km, 5 km or 10 km, none of these relationships can be inferred from distance alone.

Decision aid

Evidence	What it can support	What it cannot establish alone
Susceptibility / hazard map	Relative spatial screening under a method and scale	Exact event time or guaranteed household safety
Current official warning	Action and forecast for its stated validity/area	Conditions beyond its coverage or after expiry
Local observation	A potentially important current sign	Complete scientific diagnosis or probability
Validated local model	Quantitative estimate if model is fit for task	Certainty outside training/validation conditions

Practical checks

- Do not invent risk percentages from distance or a map color.
- Compare the source timestamp and locality before combining evidence.
- If immediate danger is reported, give protective action before optional assessment questions.

Supporting source identifiers: [S03], [S05], [S06], [S26]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

05 Prevention and mitigation

Document 02 | Section 05 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

Long-term risk reduction may include engineering-geology assessment, controlled drainage, safe road-cut design, avoiding new loading or excavation on unstable ground, maintaining engineered retaining systems, protecting natural drainage and using land-use controls based on qualified assessment. Do not undertake do-it-yourself slope excavation, toe removal, drainage diversion or retaining-wall work when ground stability is uncertain.

Mitigation is most effective when it changes the actual pathway to harm rather than merely improving the appearance of safety. Options may include land-use controls, maintenance, resilient design, drainage or vegetation management, monitoring, warning access and safer work practices, depending on the hazard. Measures that require engineering, geotechnical, structural, electrical, medical or legal judgment must be designed or approved by qualified people.

Landslide prevention and mitigation require local geotechnical understanding. Drainage, slope geometry, vegetation, road cuts, retaining structures and groundwater can interact. Do not dig channels, remove toe support, excavate a crack or add loads near a slope based on chatbot advice; poorly designed works can shift the failure pathway or affect neighbouring properties.

For landslide, rockfall, debris flow, ground movement, apply the section's principle to the actual mechanism, location and time horizon. Record what is observed, what is sourced, what is inferred and what is unknown. Do not extend a general rule beyond its stated scope; use local official instructions for decisions that depend on present conditions.

Decision aid

Mitigation layer	Purpose	Governance check
Avoid exposure	Keep people/assets out of known dangerous pathways	Use current land-use and authority guidance
Reduce vulnerability	Improve structures, services or protections	Use applicable code and qualified design
Monitor and warn	Provide lead time and actionable messages	Validate system coverage and alert reach
Maintain / review	Prevent deterioration and detect new conditions	Assign responsibility, budget and review date

Practical checks

- Prefer risk reduction that does not transfer danger to neighbours.
- Do not offer a remote certification of a site, structure or utility.
- Keep technical intervention separate from low-risk household actions.

Supporting source identifiers: [S03], [S05], [S06], [S26]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

06 Preparedness and readiness

Document 02 | Section 06 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

Before heavy-rain periods, know local evacuation routes and safe areas away from slopes, gullies, road cuts and likely debris-flow channels. Keep a charged phone, torch, medicines, documents and footwear accessible. Learn official district alerts. Household planning should include a way to leave quickly at night and support for people who cannot move without assistance.

Preparedness works only when it can be performed under adverse conditions: darkness, rain, power loss, network outage, road disruption, caregiving responsibilities and limited cash or transport. A household or community plan should identify who receives warnings, who needs help, where to move, what to carry and how to reunite if devices fail. Keep essentials accessible rather than locked behind a single person or device.

Before the relevant season or event, confirm contact details, alert subscriptions, household medications and support needs, alternate routes, transport options and shelter information through an official source. Do not assume that a shelter listed in an old plan is open today. Practice roles and update them when a road, residence, caregiver or mobility need changes.

For landslide, rockfall, debris flow, ground movement, apply the section's principle to the actual mechanism, location and time horizon. Record what is observed, what is sourced, what is inferred and what is unknown. Do not extend a general rule beyond its stated scope; use local official instructions for decisions that depend on present conditions.

Decision aid

Time	Readiness action	Verification
Before the risk season	Check supplies, contacts, routes and support roles	Use current authority/shelter information
At warning stage	Charge devices, monitor updates and prepare to move	Confirm geographic coverage and issue time
When instructed to act	Take the stated protective action promptly	Do not wait for optional chatbot analysis
After an exercise/event	Record what failed and revise the plan	Set an owner and due date for each fix

Practical checks

- Make the plan accessible to children, older adults and people with disabilities.
- Include a no-network communication method.
- Keep sensitive medical or identity details private; share only what is needed for assistance.

Supporting source identifiers: [S03], [S05], [S06], [S26]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

07 Immediate response procedures

Document 02 | Section 07 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

If active movement is suspected, move away from the threatened slope and possible runout/channel path if safe, warn nearby people without approaching the failure, and contact local emergency authorities. Do not walk onto the landslide, cross an unstable road cut, inspect cracks closely or return for belongings. Obey evacuation instructions and do not wait for the chatbot to assess photographs.

Response advice must be ordered by urgency. Protect life and avoid turning a bystander into another casualty; use the appropriate emergency channel; follow current official instructions; communicate location and observations from safety; and leave technical tasks to qualified responders. The chatbot should not claim it dispatched help, checked live conditions or sent an alert unless an authorized integration confirms that action.

When a user reports a rapidly worsening condition, keep the initial response short and direct. Give the first safe action before explaining scientific background or asking for a detailed location. A broad location can help identify the relevant authority, but exact coordinates should not be required to recommend avoiding an immediate hazard. Once the person is safe, gather only additional details that affect the next decision.

For landslide, rockfall, debris flow, ground movement, apply the section's principle to the actual mechanism, location and time horizon. Record what is observed, what is sourced, what is inferred and what is unknown. Do not extend a general rule beyond its stated scope; use local official instructions for decisions that depend on present conditions.

Decision aid

Priority	Action	Boundary
1. Protect	Move away from immediate danger by a safe route	Do not cross the hazard or retrieve belongings
2. Alert	Contact current local emergency/response channels	Do not imply the chatbot called on the user's behalf
3. Inform	Give approximate location, time and observed condition	Report facts separately from assumptions
4. Reassess	Follow responders and current updates	Do not return or begin technical rescue without clearance

Practical checks

- Do not delay action to complete a risk score.
- Do not enter unstable slopes, floodwater, smoke, rubble or electrically unsafe areas.
- If the route is compromised, report the obstacle from safety and follow authorized instructions.

Supporting source identifiers: [S03], [S05], [S06], [S26]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

08 Evacuation and protective actions

Document 02 | Section 08 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

Move out of the potential path rather than merely moving a small distance sideways on the same unstable slope. Avoid gullies and channels that may carry debris. If there is no clearly safe route, follow local responder instructions and communicate your exact approximate location and what you observed. Never cross a fresh landslide scar to reach a road or vehicle.

Evacuation depends on timing, route condition, destination and the person's ability to move. A familiar route can become dangerous because of the same event that triggered the evacuation. Use current official route instructions and never infer that a route is safe because it was usable yesterday. If movement is ordered, arrange assistance early and do not wait for a perfect checklist when a threat is immediate.

A decision to shelter in place is hazard-specific and should not be invented by the chatbot. It may be safer for some threats and unsafe for others. The answer must distinguish an official instruction to evacuate, an instruction to remain indoors, a blocked route and a person who sees immediate danger. If an official destination is inaccessible, contact the responsible authority rather than improvising through a dangerous area.

For landslide, rockfall, debris flow, ground movement, apply the section's principle to the actual mechanism, location and time horizon. Record what is observed, what is sourced, what is inferred and what is unknown. Do not extend a general rule beyond its stated scope; use local official instructions for decisions that depend on present conditions.

Decision aid

Situation	Safer response principle	Do not
Explicit evacuation order	Follow it using the stated route and timing	Delay to pack nonessential items
Immediate visible danger	Move away if a safe path exists and alert responders	Wait for a model or all warning signs
Route appears blocked	Stop before entering the hazard and report it	Cross floodwater or unstable ground
All-clear not received	Remain cautious and follow official updates	Return because conditions look calm

Practical checks

- Plan for essential medicines, mobility aids, children, older adults and pets where relevant.
- Keep family meeting and reunification arrangements simple.
- Do not promise that a shelter has space without current confirmation.

Supporting source identifiers: [S03], [S05], [S06], [S26]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

09 Volunteer and responder coordination

Document 02 | Section 09 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

Volunteers must not enter slide areas, unstable slopes or channels. They can report observations from safe positions, assist with messages and safe-area logistics, record information only with permission, and follow the Incident Commander. Search and rescue within debris requires trained teams, geotechnical support and controlled access because secondary failures can occur without warning.

Community volunteers are most effective when they fill defined support roles and remain within training, equipment and supervision. Proximity to an incident, local familiarity or good intentions do not confer technical rescue capability. Each task needs an assigning supervisor, boundaries, communication method, buddy or accountability procedure, stop-work trigger and safe withdrawal plan.

Examples of safer support may include relaying verified messages, helping an authorized distribution point, translating warnings, assisting with registration under privacy rules, checking on neighbours from safe locations and reporting obstructions. Unsafe self-assigned activities include entering unstable structures, approaching an active landslide, wading into floodwater, going near live wires or attempting rescue from fire, smoke or chemical release. Escalate specialist work to trained responders.

For landslide, rockfall, debris flow, ground movement, apply the section's principle to the actual mechanism, location and time horizon. Record what is observed, what is sourced, what is inferred and what is unknown. Do not extend a general rule beyond its stated scope; use local official instructions for decisions that depend on present conditions.

Decision aid

Task type	Volunteer boundary	Stop / withdraw when
Information relay	Repeat authorized messages with timestamp and area	Message is unverified or outside assigned role
Logistics / welfare	Work at an authorized safe location	Crowding, contamination or scene hazard increases
Observation / reporting	Observe from safety; report facts and time	Closer approach is needed to get more evidence
Technical rescue	Only trained, equipped, authorized teams	Any task exceeds training, command or PPE

Practical checks

- Check in, remain accountable and report back before leaving an assignment.
- Use clear identification without impersonating an official.
- Keep emergency access routes clear and protect affected people's privacy.

Supporting source identifiers: [S01], [S03], [S05]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

10 Vulnerable populations and inclusive planning

Document 02 | Section 10 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

Plan for evacuation assistance before rain intensifies, especially for people with limited mobility, older adults, children, pregnant people, people needing oxygen or refrigerated medicines, and people without reliable transport. Avoid revealing exact home coordinates in public chat. Use trusted household contacts and accessible alert formats.

Inclusive risk communication must fit the person, not just the average user. An alert is ineffective if it cannot be heard, seen, understood, reached in time or acted upon. Plan with people who have mobility, sensory, cognitive, language, health, caregiving or transport needs. Avoid assumptions based on age or diagnosis; ask what practical help is needed and preserve the person's agency and privacy.

For India, especially Kerala hill slopes and road corridors, plan several ways to communicate and move: audible and visual messages, plain language, local-language translations, trusted community networks, accessible transport, caregivers, mobility aids, backup charging and alternatives for people without smartphones. The plan should consider medication continuity and service animals where applicable, without asking users to disclose unnecessary private health information in a public chatbot.

For landslide, rockfall, debris flow, ground movement, apply the section's principle to the actual mechanism, location and time horizon. Record what is observed, what is sourced, what is inferred and what is unknown. Do not extend a general rule beyond its stated scope; use local official instructions for decisions that depend on present conditions.

Decision aid

Need / barrier	Planning measure	Check
Mobility or transport	Accessible transport, assistance role and a route without avoidable barriers	Can the person use the route in time?
Hearing / vision	Text, audio, visual and person-to-person warning options	Is the message perceivable and understandable?
Language / literacy	Plain language, local translation, tested instructions	Can the person explain the action back?
Health / caregiving	Medicine continuity and caregiver coordination	Can essential support travel with the person?

Practical checks

- Offer choices and confirm consent when it is possible.
- Do not publish home coordinates, diagnosis or beneficiary data openly.
- Treat inaccessible warning reach as a system failure, not user failure.

Supporting source identifiers: [S01], [S03], [S05]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

11 Recovery and lessons learned

Document 02 | Section 11 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

After a failure, the visible scar does not reveal whether adjacent ground is stable. Secondary slides, blocked streams, undermined roads, fallen utilities and temporary landslide dams may create additional danger. Re-entry should follow authority guidance and appropriate geological/engineering assessment. Report changes, do not clear debris or repair drainage on an unstable slope without qualified direction.

Recovery should move from immediate relief to safe restoration, rehabilitation and longer-term risk reduction. A cleaned room, reopened road or absent smoke does not prove that a structure, slope, water source or utility is safe. Re-entry and reconstruction decisions may require formal inspection, testing, repair standards or permission from the responsible authority. Record which decision is confirmed and which remains provisional.

A fair recovery system documents needs and assistance transparently while protecting privacy. Track who has received support and who has not been reached, distinguish estimated losses from verified assessments, and provide accessible complaint routes. Recovery planning should consider housing, water, sanitation, health, education, livelihoods, environment and psychosocial support together instead of treating each as a separate checklist.

For landslide, rockfall, debris flow, ground movement, apply the section's principle to the actual mechanism, location and time horizon. Record what is observed, what is sourced, what is inferred and what is unknown. Do not extend a general rule beyond its stated scope; use local official instructions for decisions that depend on present conditions.

Decision aid

Stage	Main concern	Evidence / safeguard
Immediate relief	Safe shelter, water, health, information and protection	Current needs and official coordination
Damage assessment	Document loss without entering unsafe places	Source, date, assessor and uncertainty
Re-entry / repair	Confirm hazards and systems are safe enough	Authorized inspection or testing when required
Build back better	Reduce repeated exposure and vulnerability	Qualified design, community input and maintenance

Practical checks

- Do not guarantee compensation eligibility or payment timing without current rules.
- Keep survivor records secure and collect only necessary data.
- Review whether rebuilding reduces risk rather than recreating it.

Supporting source identifiers: [S01], [S03], [S05]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

12 Complex scenarios and chatbot guardrails

Document 02 | Section 12 | Hazard/domain: landslide, rockfall, debris flow, ground movement | Scope: India, especially Kerala hill slopes and road corridors

Question: "A landslide is 5 km away. Can it happen here?" Explain that distance alone cannot estimate local probability. A different landslide may occur where local slopes and rain conditions favour failure; the original debris may threaten connected channels or downslope areas depending on terrain. Recommend current district/KSDMA alerts, watching for new movement from a safe place, and leaving a threatened area without waiting for further analysis.

The scenario should be handled with an evidence-first response. Separate what the user directly observed, what the official source says, what the model can infer and what remains unknown. Offer the safest supported next step first; then explain which additional evidence would materially change the assessment. Never convert a similarity to a past case, a nearby incident, a map color, a sensor threshold or a vector score into a guaranteed outcome.

Expected answer: distance alone cannot establish safety or estimate probability. Explain slope, elevation, drainage/runout connection, geology, recent and forecast rain, visible signs and official alerts. If new cracks, movement or unusual sounds appear, move away from the threatened slope/path if safe and contact authorities without waiting for additional questions.

For landslide, rockfall, debris flow, ground movement, apply the section's principle to the actual mechanism, location and time horizon. Record what is observed, what is sourced, what is inferred and what is unknown. Do not extend a general rule beyond its stated scope; use local official instructions for decisions that depend on present conditions.

Decision aid

Response element	What a safe answer should include	What it must avoid
Immediate action	Protective step if danger is plausible now	Waiting for analysis or more signs
Known evidence	User observation and current applicable official source	Treating a screenshot or old PDF as live
Uncertainty	Specific unknowns and their relevance	Invented probability or false reassurance
Follow-up	One detail that materially changes guidance	Unnecessary precise location or private data

Practical checks

- State the limit of the available information plainly.
- Use a current official source when time-sensitive information is required and available.
- If no live check occurred, say it was not checked.

Supporting source identifiers: [S01], [S03], [S05]. Full titles, publishers, dates, URLs and limitations appear in References and source notes.

Frequently asked questions

General guidance only; follow current instructions from responsible authorities.

Q1. A landslide happened 1 km away. Is my house safe?

Distance alone cannot establish safety. Check terrain connectivity, slope/elevation, runout or channel paths, rainfall, local signs and current district warnings. Do not approach the incident. Source trail: [S01], [S03], [S05], [S06]

Q2. A landslide happened 5 km away. Could it happen here?

Yes, a separate failure may occur under shared triggering conditions, but the distance alone does not quantify likelihood. Site-specific evidence and current official guidance are needed. Source trail: [S01], [S03], [S05], [S06]

Q3. What about a landslide 10 km away?

There is no universal safe-distance radius. Consider whether locations share a catchment, slope system or debris pathway, plus rainfall and local susceptibility. Source trail: [S01], [S03], [S05], [S06]

Q4. Can you give the probability of a landslide at my house in 24 hours?

Not from distance or a static PDF. A number requires a validated, current, location-relevant model or authoritative forecast with stated assumptions. Otherwise communicate uncertainty qualitatively. Source trail: [S01], [S03], [S05], [S06]

Q5. What should I do if new cracks appear after heavy rain?

Move away from the threatened slope/runout path if safe, avoid inspecting the cracks, and contact local emergency authorities. Do not wait for more analysis. Source trail: [S01], [S03], [S05], [S06]

Q6. What are the main factors for assessing landslide, rockfall, debris flow, ground movement risk?

A nearby landslide at 1, 5 or 10 km does not define whether another site is safe. Evaluate whether sites share a slope, ridge, catchment or debris-flow channel; compare elevation and terrain connectivity; and check rainfall, saturation, geology, land cover, previous failures, local susceptibility maps and current official alerts. Straight-line distance is only one weak descriptor; there is no universal safe-radius cutoff. Source trail: [S01], [S03], [S05], [S06]

Frequently asked questions (continued)

Document 02 | Questions 7-12

Q7. Which warning signs matter for landslide, rockfall, debris flow, ground movement?

Possible signs include new or widening ground cracks, fresh bulges, leaning trees or poles, doors and windows suddenly sticking, new seepage, muddy springs, broken buried utilities, unusual rockfall, small recurring slides, or sudden changes in stream level/noise. Some failures happen with few visible signs. A sign is not proof, but credible new movement warrants distance from the danger area and prompt reporting. Source trail: [S03], [S05], [S06], [S26]

Q8. What is the main immediate response for landslide, rockfall, debris flow, ground movement?

If active movement is suspected, move away from the threatened slope and possible runout/channel path if safe, warn nearby people without approaching the failure, and contact local emergency authorities. Do not walk onto the landslide, cross an unstable road cut, inspect cracks closely or return for belongings. Obey evacuation instructions and do not wait for the chatbot to assess photographs. Source trail: [S03], [S05], [S06], [S26]

Q9. How should a household prepare for landslide, rockfall, debris flow, ground movement?

Before heavy-rain periods, know local evacuation routes and safe areas away from slopes, gullies, road cuts and likely debris-flow channels. Keep a charged phone, torch, medicines, documents and footwear accessible. Learn official district alerts. Household planning should include a way to leave quickly at night and support for people who cannot move without assistance. Source trail: [S03], [S05], [S06], [S26]

Q10. What can volunteers safely do during landslide, rockfall, debris flow, ground movement?

Volunteers must not enter slide areas, unstable slopes or channels. They can report observations from safe positions, assist with messages and safe-area logistics, record information only with permission, and follow the Incident Commander. Search and rescue within debris requires trained teams, geotechnical support and controlled access because secondary failures can occur without warning. Source trail: [S03], [S05], [S06], [S26]

Q11. How should people needing additional assistance be included?

Plan for evacuation assistance before rain intensifies, especially for people with limited mobility, older adults, children, pregnant people, people needing oxygen or refrigerated medicines, and people without reliable transport. Avoid revealing exact home coordinates in public chat. Use trusted household contacts and accessible alert formats. Source trail: [S03], [S05], [S06], [S26]

Q12. What should happen after the event?

After a failure, the visible scar does not reveal whether adjacent ground is stable. Secondary slides, blocked streams, undermined roads, fallen utilities and temporary landslide dams may create additional danger. Re-entry should follow authority guidance and appropriate geological/engineering assessment. Report changes, do not clear debris or repair drainage on an unstable slope without qualified direction. Source trail: [S03], [S05], [S06], [S26]

Frequently asked questions (continued)

Document 02 | Questions 13-18

Q13. Does distance alone prove safety or danger?

No. Distance by itself does not establish risk. Evaluate the hazard-specific spatial connection, local conditions, time window, official warning and relevant observations. Source trail: [S03], [S05], [S06], [S26]

Q14. Can an exact probability be given from these documents?

Only if a suitable validated, current and location-relevant model or authoritative forecast explicitly supports it. Otherwise the system must state uncertainty and avoid invented percentages. Source trail: [S03], [S05], [S06], [S26]

Q15. Does the absence of an official warning guarantee safety?

No. Monitoring and communication can be incomplete or delayed. Credible direct signs and immediate danger require protective action and contact with the responsible authority. Source trail: [S03], [S05], [S06], [S26]

Q16. What information should a follow-up question request?

Only details that change advice, such as broad locality, time window, relevant slope/river/coastal connection, current signs and whether danger is happening now. Avoid unnecessary personal data. Source trail: [S03], [S05], [S06], [S26]

Q17. What if maps and observed conditions disagree?

Do not dismiss immediate danger because a static map is reassuring. Report from safety, follow current official instructions and note map date, scale and uncertainty. Source trail: [S01], [S03], [S05]

Q18. What if current alerts cannot be accessed?

State explicitly that live alerts were not checked, provide conservative general safety guidance and direct the user to the relevant official source or emergency service. Source trail: [S01], [S03], [S05]

Frequently asked questions (continued)

Document 02 | Questions 19-24

Q19. Can a photograph prove that a site or structure is safe?

No. Images may omit key features and cannot substitute for site inspection, qualified assessment or live situational information. Source trail: [S01], [S03], [S05]

Q20. Where can the public find authoritative information?

Start with the relevant official Indian/state/district authority and technical agency listed in the source register; verify the publication date, geographic coverage and current status. Source trail: [S01], [S03], [S05]

Q21. Can old case studies be used as a forecast?

No. Case studies describe past conditions and lessons, not the exact timing or outcome of a future event. Source trail: [S01], [S03], [S05]

Q22. What should users avoid doing?

Do not enter or approach dangerous areas, cross floodwater, inspect unstable slopes, enter damaged buildings or exceed volunteer training. Follow official instructions. Source trail: [S01], [S03], [S05]

Q23. How should conflicting official messages be handled?

Compare issuing agency, timestamp, geography and scope. Follow the current directly applicable emergency instruction while seeking clarification without delaying life safety. Source trail: [S01], [S03], [S05]

Q24. Can the chatbot confirm that emergency services were called?

Only when an authorized connected service actually confirms the action. Otherwise it should direct the user to call the service directly. Source trail: [S01], [S03], [S05]

Glossary and interpretation rules

Hazard: A potentially damaging process, phenomenon or human activity.

Exposure: People, infrastructure, housing, production capacity and other tangible human assets in hazard-prone areas.

Vulnerability: Physical, social, economic or environmental conditions that increase susceptibility to harm.

Susceptibility: Relative tendency of an area or system to experience a process; not a forecast of immediate occurrence.

Capacity: Resources, systems, relationships and abilities available to manage a hazard and reduce harm.

Forecast: A statement about possible future conditions over a specified place and time, based on data and a method.

Official warning: A communication from a responsible authority describing a hazard and recommended action for stated coverage and validity.

Evacuation: Protective movement away from a threatened area by an appropriate route.

Residual risk: Risk remaining after prevention or mitigation; never automatically zero.

Uncertainty: Limits in data, model assumptions, observations, timing, geography or inference.

RAG: Retrieval-Augmented Generation: retrieval supplies source passages that help ground a model response.

Source provenance: Information identifying the origin, issuer, date, version and context of a claim.

Site-specific assessment: Evaluation using local conditions, current evidence and the competence needed for the decision.

References and source notes

Document CDVH-02-KB | Version 1.1.0 | Access date 2026-10-16. Official sources may change; re-check currentness before operational use. The source list is not a claim that every linked attachment was completely extracted and reviewed.

[S01] Kerala State Disaster Management Authority guidelines index - KSDMA. Publication/revision date: Index includes 2026 Orange Book of Disaster Management, Edition 8 (individual attachment date must be checked). URL: https://sdma.kerala.gov.in/guidelines/. Accessed 2026-10-16.

Use and limitation: Current index lists the 2026 Orange Book and other guidance; individual linked documents require independent version review.

[S03] KSDMA brochures and public information materials - KSDMA. Publication/revision date: Not confirmed during this build. URL: https://sdma.kerala.gov.in/brochures-2/. Accessed 2026-10-16.

Use and limitation: Includes educational materials on landslides, floods, emergency kits and related safety themes.

[S05] Overview: Rainfall-induced landslides - U.S. Geological Survey. Publication/revision date: 2018-07-02. URL: https://www.usgs.gov/programs/landslide-hazards/science/overview-rainfall-induced-landslides. Accessed 2026-10-16.

Use and limitation: Explains intense/prolonged rainfall, shallow failures and debris-flow connections; local thresholds are site-dependent.

[S06] What are signs of landslide development? - U.S. Geological Survey. Publication/revision date: Not confirmed during this build. URL: https://www.usgs.gov/programs/landslide-hazards/what-are-signs-landslide-development-what-do-i-do-if-a-landslide-occurs. Accessed 2026-10-16.

Use and limitation: Warning signs are not exhaustive and sudden failures may occur with little visible warning.

[S26] Geological Survey of India - GSI. Publication/revision date: Not confirmed during this build. URL: https://www.gsi.gov.in/. Accessed 2026-10-16.

Use and limitation: Official geological institution homepage; use specific current reports/maps for any site-level assertion.

[S18] India Meteorological Department main portal - India Meteorological Department. Publication/revision date: Not confirmed during this build. URL: https://mausam.imd.gov.in/. Accessed 2026-10-16.

Use and limitation: Use for current official forecasts and warnings; this knowledge library does not itself provide live alert data.

[S21] Kerala emergency directory 2026 - KSDMA. Publication/revision date: Not confirmed during this build. URL: https://sdma.kerala.gov.in/wp-content/uploads/2026/06/Directory-wpn.pdf. Accessed 2026-10-16.

Use and limitation: 2026 directory surfaced on KSDMA site; numbers and staffing can change and must be rechecked before each release.

Citation and update policy

Source identifiers are printed near relevant content and map to this list. For operationally consequential claims, verify the original source, its current status, publication/revision date, geography and relevant section. Do not invent page numbers or infer that a linked attachment was reviewed where the build record says it was unavailable.

Research limitation

This is an educational draft reference corpus, not a formally certified emergency manual. Some official web pages were inspected, but not every listed attachment was downloaded and fully extracted. The source register in this PDF records known limitations. Expert review remains necessary for medical, engineering, geotechnical, GIS, legal and operational content. Static PDFs do not provide live alerts or site-specific predictions.