CouriersPlease

Domestic Pickup

API Documentation

Version Control

Version	Date	Notes	Author
1.0.0	18/04/2017	Initial version.	Jeff Embro (CouriersPlease)
1.0.1	15/08/201	Change minimum total weight from 1kg to 0.1kg.	Kalpesh Pandya (CouriersPlease)
1.0.2	04/04/2025	Update samples. Add additional information.	Silvio Mueller (CouriersPlease)

Contents

Contents

Version Control 2
Contents 3
Overview 4
Format 4
URLs 4
Sandbox 4
https://api-testcouriersplease.com.au/v2/domestic/bookPickup 4
Production 4
Security 4
API Access 4
Authentication 5
Sample request header using CURL 5
Encryption 5
API Request 6
Parameters 6
Sample Request HTTP 7
Request 7
Request Header 7
Request Body (1 Connote) 8
Request Body (multiple Connotes) 9
API Response 10
API Response Codes 10
API Response Object 10
Sample Response (200 - Success) 10
Sample Response (404 – Not Found)) 11
Sample Response (401 - Unauthorized) 11
Sample Response (400 – Bad Request) 11
Sample Response (500 – Error) 11
Trouble Shooting 12
Possible causes of errors. 12
Possible Solutions to Errors 13

Overview

This document defines the API in which E-Merchants can book a pickup with Couriers Please and obtain a booking number. The booking number should be stored alongside the pickup suburb and postcode for future reference. When enquiring about a pickup booking these three values should be provided to customer service.

Format

Request	JSON	
Response	JSON	XML Response Discontinued 2024
HTTP Method	POST	
Authorization	BASIC	Combination of account number and API Key

URLs

Sandbox

While developing and testing use the sandbox URL:

https://api-test.couriersplease.com.au/v2/domestic/bookPickup

Production

After deploying to live use the production URL:

https://api.couriersplease.com.au/v2/domestic/bookPickup

Security

API Access

API security is controlled by CouriersPlease. CouriersPlease controls the following:

1. Access to Sandbox environment.
2. Access to Production environment.
3. Access to each individual API.
4. Hourly/Daily/Monthly limits.

If you require security changes then please contact CouriersPlease API support:

Email apisupport@couriersplease.com.au or connect@couriersplease.com.au

Authentication

API Validation is performed through HTTP Basic Authentication using the CouriersPlease Account Number and Authorization Token.

Username: CouriersPlease Account Number

Password: Sandbox or Production Token provided from the CouriersPlease API Developer Portal

When using HTTP Basic Authentication, the Username and Password must be Base64 encoded in the header.

If your CouriersPlease Account Number is W99999 and your token is ABC123456789 your Authentication Header would be “Authorization: Basic W99999:ABC123456789” before encoding it. Once encoded, it should look as follows: “Authorization: Basic Vzk5OTk5OkFCQzEyMzQ1Njc4OQ==”

Sample request header using CURL

```
curl \
--location 'https://api-test.couriersplease.com.au/v2/domestic/bookPickup’\
--header 'Content-Type: application/json' \
--header 'Authorization: Basic Vzk5OTk5OkFCQzEyMzQ1Njc4OQ=' \
--data '{}’
```

Encryption

The API Endpoints and Portal are encrypted using SSL as follows:

SSL Attribute	**SSL Detail**
Signature Hash Algorithm	sha256
Public Key	RSA (2048 Bits)

API Request

This section contains the parameters and examples of a Domestic Book Pickup API request

Parameters

Name	Mandatory/Optional	Type	Content
readyDateTime	**Mandatory**	**Date/Time**	Format yyyy-MM-dd hh:mm tt Example: 2025-04-05 01:30 PM See notes 1 and 2
accountName	**Optional**	**String**	Maximum Length: 18 For use by third party providers (3PLs and Aggregators).
contactName	**Mandatory**	**String**	Max Length: 15 Person to contact at pickup location.
contactEmail	**Mandatory**	**String**	Valid email address of contact at pickup location.
specialInstructions	**Optional**	**String**	Max Length: 15 Pickup instructions. Example: “Use back door”
consignmentCount	**Mandatory**	**Integer**	Range: 1 to 9999
consignmentCode	**See Note 3**	**String**	Required if ConsignmentCount=1 Max Length: 25 Consignment Number for item(s) being picked up.
totalItemCount	**Mandatory**	**Integer**	Range: 1 to 9999
totalWeight	**Mandatory**	**Double/Float**	Range: 0.1 to 9999
pickup	**Mandatory**	**Object**	This object contains the pickup address details.
phoneNumber	**Mandatory**	**Integer**	Phone Number
companyName	**Mandatory**	**String**	Company Name Max Length: 19 If the sender is not a business then add the sender name instead.
address1	**Mandatory**	**String**	Address Line 1 Max Length: 19
address2	**Optional**	**String**	Address Line 2 Max Length: 19
address3	**Optional**	**String**	Address Line 3 Max Length: 19
suburb	**Mandatory**	**String**	A valid Australian suburb (see note 5)
postcode	**Mandatory**	**Integer**	A valid Australian postcode (see note 5)
delivery	**See Note 4**	**Object**	This object contains the Delivery address details.

companyName	**Optional**	**String**	Company Name Max Length: 19 Enter a value in this field if the delivery location is a business.
address1	**Mandatory**	**String**	Address Line 1 Max Length: 19
address2	**Mandatory**	**String**	Address Line 2 Max Length: 19
suburb	**Mandatory**	**String**	A valid Australian suburb (see note 5)
postcode	**Mandatory**	**Integer**	A valid Australian postcode (see note 5)

Note 1: If a past date is entered the date value will be automatically changed to the current date and time. It is recommended that date validation is coded into your system to only allow a future date and time.

Note 2: The franchisee will be advised of the pickup request at the date/time passed in the request. The pickup will occur after this time.

Note 3: If there is only one consignment to be picked up then the consignment number must be entered into this field.

Note 4: If there is only one consignment then the "delivery" object is mandatory. If there is more than on consignment, then this object can be omitted.

Note 5: Use the "Locations" API to obtain a valid suburb and/or postcode. Alternatively, a Location Master file can be downloaded from the Couriers Please website under the "Resources" menu at https://www.couriersplease.com.au/

Sample Request HTTP

Below is a sample request that returns JSON. The HTTP Request Header must contain application (example: "Accept: application/json"). The username and password are Base64 encoded in the authorization header as specified in the Authentication section of this document.

Request

POST https://api-test.couriersplease.com.au/v1/domestic/bookPickup HTTP/1.1

Request Header

Host: api-test.couriersplease.com.au Accept: application/json
Content-Type: application/json
Authorization: Basic Vzk5OTk5OkFCQzEyMzQ1Njc4OQ== Content-Length: 462

Request Body (1 Connote)


```
{
  "accountName": "Aggregator Co.",
  "contactName": "John Tester",
  "contactEmail": "test@test.com.au",
  "readyDateTime": "2025-02-28 01:30 PM",
  "specialInstructions": "Entry at Rear",
  "consignmentCount": "1",
  "consignmentCode": "CPWL55000000638-TEST",
  "totalItemCount": "1",
  "postcode": "3000",
  "totalWeight": "4",
  "pickup": {
    "phoneNumber": "02 11112222",
    "companyName": "Test Company",
    "address1": "TEST Building 1",
    "address2": "32 Somewhere St",
    "address3": "Level 2",
    "postcode": "2142",
    "suburb": "Rosehill"
  },
  "delivery": {
    "companyName": "Delivery Co.",
    "address1": "88 Delivery Avenue",
    "address2": "Unit B",
    "postcode": "3000",
    "suburb": "MELBOURNE"
  }
}
```


Note: If multiple consignments are being shipped from one address, then please book one pickup for multiple consignments (see example on the next page). Do not book multiple pickups on the same day unless there are multiple pickup addresses.

Request Body (multiple Connotes)


```
{
   "accountName": "Aggregator Co.",
   "contactName": "John Tester",
   "contactEmail": "test@test.com.au",
   "readyDateTime": "2025-02-28 01:30 PM",
   "specialInstructions": "Entry at Rear",
   "consignmentCount": "3",
   "consignmentCode": null,
   "totalItemCount": "4",
   "postcode": "3000",
   "totalWeight": "4",
   "pickup": {
      "phoneNumber": "02 11112222",
      "companyName": "Test Company",
      "address1": "TEST Building 1",
      "address2": "32 Somewhere St",
      "address3": "Level 2",
      "postcode": "2142",
      "suburb": "Rosehill"
  }
}
```

API Response

Each request will return both an HTTP Status Code and a Response Code, which can be used to understand if the request was successfully processed. The response code will be in JSON.

API Response Codes

Code	Response
200	Success
401	Authentication failed
403	Requesting server IP address is blocked
404	No data found
429	Number of allowable requests exceeded
500	Error in process or service unavailable

Check the trouble shooting guide at the end of this document for more information on error responses.

API Response Object

A successful API response, where HTTPS Status Code = 200 and Response Code = SUCCESS, will return an object with field names as follows:

Field Name	Description
jobNumber	This is the Booking Number that should be quoted when following up on a pickup

Sample Response (200 - Success)

```
{
  "responseCode": "SUCCESS",
  "msg": "",
  "data": {
    "jobNumber": "24171"
  }
}
```

Sample Response (404 – Not Found))


```
{
   "responseCode": "404",
   "msg": "Data not found",
   "data": null
}
```


Sample Response (401 - Unauthorized)


```
{
"responseCode": "UNAUTHORIZED",
"msg": "Not a valid token.",
"data": ""
}
```


(Note: An invalid API key was used)

Sample Response (400 – Bad Request)


```
{
   "responseCode": "Invalid input",
   "msg": "Data Validation Error",
   "data": {
      "errors": [
         {
            "type": "Required Field",
            "field": "pickup.postcode",
            "description": "Please enter pickup postcode."
         }
      ]
   }
}
```


(Note: The postcode for the pickup address was missing)

Sample Response (500 – Error)


```
{
   "responseCode": "500",
   "msg": "Internal Server Error",
   "data": null
}
```


(Note: API was offline)

Trouble Shooting

This section highlights the possible causes of API errors and possible solutions for them.

Further assistance can be obtained by sending an email to the below addresses:

Email apisupport@couriersplease.com.au or connect@couriersplease.com.au

Possible causes of errors.

Below is a table of errors and possible causes. The following page has a list of possible solutions.

Error Code	Value	Possible Causes
400	Bad Request	Missing postcode/ suburb or other required fields. Date is too far in the future or past. Decimal places in Integer fields for Item Count and Consignment Count Example: "consignmentCount": "3.00",
401	Unauthorised	Using Test credentials in Production environment. Using Production credentials in Test environment. Incorrect Account Number or API Key. Incorrect Authentication Type.
403	Forbidden	Invalid character (example: /) in request. Incomplete request. Incorrect request structure. Requesting Server Address may be blocked
404	Not found	This error is unlikely when using the Booking API
408	Request Timeout	API is not responding (various reasons). Too many requests being passed at the same time.
500	Internal Server Error	Server may be offline

Possible Solutions to Errors

The table below contains to most common solutions to API errors.

Error Code	Value	Possible Solutions
400	Bad Request	Check request for errors such as empty fields and decimal points. Check the date and time is current and in the correct format.
401	Unauthorised	Check the credentials being used are correct Contact Couriers Please to confirm credentials
403	Forbidden	Check request for errors such as invalid characters. Check hosting server is not in a blacklisted country.
404	Not found	Check with Couriers Please API Support
408	Request Timeout	Test using a single request to see if API is online Check with Couriers Please API Support.
500	Internal Server Error	Check API parameters are correct. Check availability of service with Couriers Please