


Callbacks vs Promises vs Async/Await

తెలుగు లో
JavaScript



Callbacks
vs
Promises
vs
Async/Await

All are
same?

```
console.log('Venkatesh');  
setTimeout(() => {  
  console.log('Mogili');  
}, 1000);  
console.log('JS Course');
```

Venkatesh

Mogili

JS Course



```
fetch('url')  
  .then((res) => res.json())  
  .then((response) => console.log(response));
```



Why should we use Async-Await
If we already have Promises?

1

Callbacks



VENKATESH MOGILI
#Web Guru

"I will call back later!"

A callback is a function passed as an argument to another function

This technique allows a function to call another function

A callback function can run after another function has finished



```
setTimeout(() => {  
  console.log('Hello World!');  
}, 1000);
```

1

Callback Examples



VENKATESH MOGILI
#Web Guru

```
function step1(value, callback) {  
  callback(value + 10, false);  
}
```

```
function step2(value, callback) {  
  callback(value + 10, true);  
}
```

```
function step3(value, callback) {  
  callback(value + 10, false);  
}
```

```
step1(10, function(result1, error) {  
  if (!error) {  
    step2(result1, function(result2, error) {  
      if (!error) {  
        step3(result2, function(result3, error) {  
          console.log('Result: ' + result3);  
        });  
      }  
    });  
  }  
});
```

1

Callback Hell Solution-1



VENKATESH MOGILI
#Web Guru

✓ Write Comments

```
/*  
1. Passing 10 as the initial value to Step1  
2. If there is no error, then passing the result to Step2  
3. If there is no error again, then passing the result to Step3  
4. Finally, printing the result.  
*/  
step1(10, function(result1, error) {  
    if (!error) {  
        step2(result1, function(result2, error) {  
            if (!error) {  
                step3(result2, function(result3, error) {  
                    console.log('Result: ' + result3);  
                });  
            }  
        });  
    }  
});
```

1

Callback Hell Solution-2



VENKATESH MOGILI
#Web Guru

VENKATESH MOGILI

✓ Split Callbacks into Smaller functions

```
step1(10, function(result1, error) {  
  if (!error) {  
    return result1;  
  }  
});
```

```
function step1(value, callback) {  
  let result1 = callback(value + 10, false);  
  step2(result1, function(result2, error) {  
    if (!error) {  
      return result2;  
    }  
  });  
}
```

```
function step2(value, callback) {  
  let result2 = callback(value + 10, false);  
  step3(result2, function(result3, error) {  
    if (!error) {  
      return result3;  
    }  
  });  
}
```

```
function step3(value, callback) {  
  let result3 = callback(value + 10, false);  
  console.log(result3);  
}
```


2

Callback Hell Solution-3



VENKATESH MOGILI
#Web Guru

VENKATESH MOGILI

✓ Using Promises

```
function step1(value, error) {  
  return new Promise((resolve, reject) => {  
    if (!error) {  
      resolve(value + 10);  
    } else {  
      reject('Something went wrong');  
    }  
  });  
}  
  
function step2(value, error) {  
  return new Promise((resolve, reject) => {  
    if (!error) {  
      resolve(value + 10);  
    } else {  
      reject('Something went wrong');  
    }  
  });  
}
```

```
function step3(value, error) {  
  return new Promise((resolve, reject) => {  
    if (!error) {  
      resolve(value + 10);  
    } else {  
      reject('Something went wrong');  
    }  
  });  
}
```

```
step1(10, false)  
  .then((result1) => step2(result1, false))  
  .then((result2) => step3(result2, false))  
  .then((result3) => console.log(result3))  
  .catch((error) => console.log(error));
```


2

Promises



VENKATESH MOGILI
#Web Guru

"I Promise a Result!"

"Producing code" is code that can take some time

"Consuming code" is code that must wait for the result

A Promise is a JavaScript object that links producing code and consuming code



```
const p1 = Promise.resolve('Like If you understood callbacks');
const p2 = 100;
const p3 = new Promise((resolve, reject) => {
  setTimeout(resolve, 1000, 'Subscribe for more updates');
});

Promise.all([ p1, p2, p3 ]).then((values) => console.log(values));
```

Promise.all([promises])

2

Promises



VENKATESH MOGILI
#Web Guru

Available Promise State and Values

- ✓ Pending (undefined)
- ✓ Fulfilled (resolved value)
- ✓ Rejected (reason for rejection)

Available Promise methods

- ✓ Promise.all([promises])
- ✓ Promise.allSettled([promises])
- ✓ Promise.any([promises])
- ✓ Promise.race([promises])



2

Promises Example



VENKATESH MOGILI
#Web Guru

```
fetch('https://api.github.com/users')
  .then((response) => response.json())
  .then((result) => console.log(result));
```

```
axios.get('https://api.github.com/users').
  then((result) => console.log(result.data));
```

```
(30) [{...}, {...}, {...}, {...}, {...}, {...}, {...}, {...}, {...}, {...}, {...}, {...}, {...},
{...}, {...}, {...}] i
▶ 0: {login: "mojombo", id: 1, node_id: "MDQ6VXN1cjE=", avatar_url: "ht
▶ 1: {login: "defunkt", id: 2, node_id: "MDQ6VXN1cjI=", avatar_url: "ht
▶ 2: {login: "pjhyett", id: 3, node_id: "MDQ6VXN1cjM=", avatar_url: "ht
▶ 3: {login: "wycats", id: 4, node_id: "MDQ6VXN1cjQ=", avatar_url: "ht
▶ 4: {login: "ezmobius", id: 5, node_id: "MDQ6VXN1cjU=", avatar_url: "ht
▶ 5: {login: "ivey", id: 6, node_id: "MDQ6VXN1cjY=", avatar_url: "http
▶ 6: {login: "evanphx", id: 7, node_id: "MDQ6VXN1cjY=", avatar_url: "ht
▶ 7: {login: "vanpelt", id: 17, node_id: "MDQ6VXN1cjE3", avatar_url: "ht
▶ 8: {login: "wayneeseguin", id: 18, node_id: "MDQ6VXN1cjE4", avatar_u
▶ 9: {login: "brynary", id: 19, node_id: "MDQ6VXN1cjE5", avatar_url: "ht
▶ 10: {login: "kevinclark", id: 20, node_id: "MDQ6VXN1cjIw", avatar_ur
▶ 11: {login: "technoweenie", id: 21, node_id: "MDQ6VXN1cjIx", avatar_
▶ 12: {login: "macournoyer", id: 22, node_id: "MDQ6VXN1cjIy", avatar_t
▶ 13: {login: "freesia", id: 23, node_id: "MDQ6VXN1cjIz", avatar_url: "ht
```



2

What is the need of Async/Await?



VENKATESH MOGILI
#Web Guru

➤ Chaining of Promises

```
step1(10, false)
  .then((result1) => step2(result1, false))
  .then((result2) => step3(result2, false))
  .then((result3) => console.log(result3))
  .catch((error) => console.log(error));
```


3

Async/Await




VENKATESH MOGILI
#Web Guru

"async and await make promises easier to write"

async makes a function return a Promise

await makes a function wait for a Promise

```
const morningRoutine = async (startTime) => {
```



```
}
```

```
async function result() {
  let result1 = step1(10, false);
  console.log(result1);
}
result();
```

```
▼ Promise {<fulfilled>: 20} ⓘ
  ► __proto__: Promise
    [[PromiseState]]: "fulfilled"
    [[PromiseResult]]: 20
```

```
async function result() {
  let result1 = await step1(10, false);
  let result2 = await step2(result1, false);
  let result3 = await step3(result2, false);
  console.log(result3);
}
```


Summary



VENKATESH MOGILI
#Web Guru

- ✓ All The 3 are same except syntax difference
- ✓ Promises have resolve , reject states
- ✓ Async function always returns a promise
- ✓ Await will take the promise and converts to actual result.

Thank you for watching



Subscribe

and



Stay Tuned

For more updates...



VENKATESH MOGILI

#Web Guru