Exp:8

Aim: Design and Train a CNN on Fashion-MNIST Dataset

1. Dataset Source

The dataset used for this experiment is the Fashion-MNIST dataset.

🔗 GitHub Link:
https://github.com/zalandoresearch/fashion-mnist

2. Dataset Description

Fashion-MNIST is an image classification dataset consisting of grayscale images of clothing items.

- **Total images:** 70,000
  - Training: 60,000
  - Testing: 10,000
- **Image size:** 28 × 28 pixels
- **Number of classes:** 10

Classes:

T-shirt/top, Trouser, Pullover, Dress, Coat, Sandal, Shirt, Sneaker, Bag, Ankle boot

Features:

- Pixel values (0–255 grayscale intensity)

Target Variable:

- Label (0–9 corresponding to clothing category)

3. Mathematical Formulation of the Algorithm

A Convolutional Neural Network (CNN) uses the following operations:

1. Convolution Operation

Feature extraction using filters:

$Output = Input * Kernel + Bias$Output=Input∗Kernel+Bias

2. Activation Function (ReLU)

Introduces non-linearity:

$f(x)$=max(0,x)f(x)=max(0,x)

3. Pooling (Max Pooling)

Reduces dimensions:

$Output$=max($region$)Output=max(region)

4. Fully Connected Layer

Final classification:

$y = Wx + b$y=Wx+b

5. Softmax Function

Converts output into probabilities:

$P(yi) = ezi \sum ezj$P(yi)=∑ezjezi

6. Loss Function (Cross-Entropy)

Measures error:

$Loss = -\sum y \log(y\hat{})$Loss=−∑ylog(y^)

4. Algorithm Limitations

- Requires large datasets for better performance
- High computational cost (needs GPU for faster training)
- Can overfit if model is too complex
- Not suitable for very small datasets
- Difficult to interpret compared to simple models

5. Methodology / Workflow

Steps followed in the experiment:

1. Load dataset from TensorFlow
2. Normalize pixel values (0–255 → 0–1)
3. Reshape images for CNN input
4. Build CNN model:
    - Convolution layer
    - Pooling layer
    - Fully connected layer
5. Compile model using optimizer and loss function
6. Train model using training data
7. Evaluate model using test data
8. Visualize accuracy and loss

Workflow Diagram



6. Performance Analysis

The model performance is evaluated using:

1. Accuracy

$Accuracy = \frac{Correct\ Predictions}{Total\ Predictions}$ Accuracy=Total PredictionsCorrect Predictions

2. Loss

- Measures difference between actual and predicted values

Observations:

- Training accuracy increases with epochs
- Validation accuracy stabilizes around **85%–90%**
- Model performs well on most classes
- Slight confusion between similar items (e.g., shirt vs t-shirt)

7. Hyperparameter Tuning

Hyperparameters adjusted:

Parameter	Value

Epochs	5–10
Batch Size	32
Filters	32, 64
Kernel Size	(3×3)
Optimizer	Adam

Tuning Impact:

- Increasing epochs → improves accuracy
- More filters → better feature extraction
- Proper batch size → stable training
- Adam optimizer → faster convergence

Output



Model: "sequential"

Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 26, 26, 32)	320
max_pooling2d (MaxPooling2D)	(None, 13, 13, 32)	0
conv2d_1 (Conv2D)	(None, 11, 11, 64)	18,496
max_pooling2d_1 (MaxPooling2D)	(None, 5, 5, 64)	0
flatten (Flatten)	(None, 1600)	0
dense (Dense)	(None, 64)	102,464
dense_1 (Dense)	(None, 10)	650

Total params: 365,792 (1.40 MB)
Trainable params: 121,930 (476.29 KB)
Non-trainable params: 0 (0.00 B)
Optimizer params: 243,862 (952.59 KB)



Conclusion

The CNN model successfully classified Fashion-MNIST images with good accuracy. It demonstrates the effectiveness of deep learning in image classification tasks.