STRINGS

Single quoted strings

```
groovy> package com.app
groovy> class GroovyStringExample1 {
groovy> static void main(args)
groovy> {
groovy>         String s1 = 'Javatpoint'
groovy>         println s1
groovy>         println 'This is tutorial on Groovy at ' + s1
groovy> }
groovy> }

Javatpoint
This is tutorial on Groovy at Javatpoint
```

Double quoted strings:

```
groovy> package com.app
groovy> class GroovyStringExample2 {
groovy> static void main(args)
groovy> {
groovy>         String s1 = "Javatpoint"
groovy>         println s1
groovy>         println "This is tutorial on Groovy at " + s1
groovy> }
groovy> }

Javatpoint
This is tutorial on Groovy at Javatpoint
```

```
groovy> package com.app
groovy> class GroovyStringExample3 {
groovy> static void main(args)
groovy> {
groovy>         String s1 = "Javatpoint"
groovy>         println "This is tutorial on Groovy at ${s1} "
groovy>         println "This is tutorial on Groovy at $s1 "
groovy> }
groovy> }

This is tutorial on Groovy at Javatpoint
This is tutorial on Groovy at Javatpoint
```

T*riple* quoted strings:

```
groovy> package com.app
groovy> class GroovyStringExample4 {
groovy> static void main(args)
groovy> {
groovy>         String s1 = '''This is groovy tutorial and we are learning string'''
groovy>         println s1
groovy> }
groovy> }

This is groovy tutorial and we are learning string
```

```
groovy> package com.app
groovy> class GroovyStringExample5 {
groovy> static void main(args)
groovy> {
groovy> String s1 = '''This is line 1
groovy> This is line 2
groovy> This is line 3
groovy> This is line 4
groovy> This is line 5'''
groovy> println s1
groovy> }}

This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
```

```
groovy> package com.app
groovy> class GroovyStringExample6 {
groovy> static void main(args)
groovy> {
groovy>         String s1 = """This is groovy tutorial and we are learning string"""
groovy>         println s1
groovy> }
groovy> }

This is groovy tutorial and we are learning string
```

```
groovy> package com.app
groovy> class GroovyStringExample7 {
groovy> static void main(args)
groovy> {
groovy> String s1 = """This is line 1
groovy> This is line 2
groovy> This is line 3
groovy> This is line 4
groovy> This is line 5"""
groovy>         println s1
groovy> }
groovy> }

This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
```

```
groovy> package com.app
groovy> class GroovyStringExample8 {
groovy> static void main(args)
groovy> {
groovy> String s1 = """This is line 1
groovy> This is line 2
groovy> This is line 3
groovy> This is line 4
groovy> This is line 5"""
groovy> println """Hello $s1"""
groovy> println """Hey $s1"""
groovy> }
groovy> }

Hello This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
Hey This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
```

```
groovy> package com.app
groovy> class GroovyStringExample9 {
groovy> static void main(args)
groovy> {
groovy> String s1 = /This is groovy tutorial and we are learning string/
groovy> println s1
groovy> }
groovy> }

This is groovy tutorial and we are learning string
```

```
groovy> package com.app
groovy> class GroovyStringExample11 {
groovy> static void main(args)
groovy> {
groovy> String s1 = /This is line 1
groovy> This is line 2
groovy> This is line 3
groovy> This is line 4
groovy> This is line 5/
groovy>         println s1
groovy> }}

This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
```

```
groovy> package com.app
groovy> class GroovyStringExample11 {
groovy> static void main(args)
groovy> {
groovy> String s1 = /This is line 1
groovy> This is line 2
groovy> This is line 3
groovy> This is line 4
groovy> This is line 5/
groovy> println """Hello ${s1}"""
groovy> println """Hey $s1"""
groovy> }}

Hello This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
Hey This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
```

DECISION MAKING:

1. IF Statement:

GroovyConsole

File Edit View History Script Help

```
1  class GroovyDecisionMakingExample1 {
2
3      static void main(args) {
4          int a = 10
5          if (a<50) {
6           println("javatpoint");
7        }
8
9      }
10 }
```

```
groovy> class GroovyDecisionMakingExample1 {
groovy>
groovy>     static void main(args) {
groovy>         int a = 10
groovy>         if (a<50) {
groovy>          println("javatpoint");
groovy>       }
groovy>
groovy>     }
groovy> }

javatpoint
```

2. IF- ELSE:

GroovyConsole

File Edit View History Script Help

```
class GroovyDecisionMakingExample3 {
    static void main(args) {
        int a = 20
      if (a<50) {
         println("The value is less than 50");
      } else {
         println("The value is greater than 50");
      }
    }
}
```

```
groovy> class GroovyDecisionMakingExample3 {
groovy>     static void main(args) {
groovy>         int a = 20
groovy>       if (a<50) {
groovy>          println("The value is less than 50");
groovy>       } else {
groovy>          println("The value is greater than 50");
groovy>       }
groovy>     }
groovy> }

The value is less than 50
```

3.NESTED – IF:

GroovyConsole

File Edit View History Script Help

```
class GroovyDecisionMakingExample5 {

    static void main(args) {
        int a = 20
      if (a>50) {
         println("The value is less than 50");
      } else
      if (a>10) {
         println("The value is greater than 10 and greater than 50");
      } else {
         println("The value of a is less than 10");
      }
    }
}
```

```
The value is greater than 10 and greater than 50
```

4. SWITCH STATEMENTS:

GroovyConsole

File Edit View History Script Help

```
class GroovyDecisionMakingExample6 {
    static void main(args) {
       int a = 4
      switch(a) {
         case 1:
            println("Monday");
            break;
         case 2:
            println("Tuesday");
            break;
         case 3:
            println("Wednesday");
            break;
         case 4:
            println("Thursday");
            break;
        case 5:
            println("Friday");
            break;
        case 6:
            println("Saturday");
            break;
         default:
            println("Sunday");
            break;
      }
```

```
Thursday
```