CSCI2010U MIDTERM - SIDE A: CODE YOU CAN WRITE, TRACES, RECURSION, SEARCHING

HOW TO ANSWER

Print / return? Make a table: one row per pass or call, one column per variable. Run it line by line.
Fill a blank: copy the matching template; check start, stop test, step, names.
Write a method: 1) what to return, 2) a variable (count / sum / min), 3) loop or recursion, 4) return AFTER the loop. Test it on the example.

JAVA ESSENTIALS

Array: index from **0**; `a.length` (no brackets); last = `a[a.length-1]`; `a[a.length]` crashes. `int[] a = new int[5];` (all 0) or `{5,2,9}`. Size is fixed.
String: `s.length()`, `s.charAt(i)`, `s.substring(1)` ("hello" gives "ello"), `s.substring(1,3)` ("el", end not included), `s1.compareTo(s2)` (negative = s1 first). Case matters.
`n%10` = last digit, `n/10` drops it (5072: 2 and 507). `i % k == 0` = divisible by k. 7 / 2 = 3, 7 % 2 = 1. `==` compares, `=` assigns.
Defaults: int 0, boolean false, objects null. An int method returns a number (or throws), never null.
Arrays and objects pass a reference copy, so a method changes the SAME array (no return needed). Primitives pass a copy.
A `static` method cannot use instance fields or `this`. Strings are not arrays: `s[i]` fails; `+=` works on Strings, not arrays.
`javac F.java` makes F.class; `java F` runs `public static void main(String[] args)`.

COUNT, MIN, SUM, MULTIPLES (Lab 1)

```
int count = 0;                  // before loop
for (int i = 0; i < a.length; i++) {
  if (a[i] >= target) {   // equal counts
    count++;
  }
}
return count;                   // after loop
```

countAtLeast({25,10,40,25}, 25): yes, no, yes, yes = **3**. Count above 4 in {5,2,9,2}: yes, no, yes, no = **2**.

```
int min = a[0];                 // not 0
for (int i = 1; i < a.length; i++) {
  if (a[i] < min) {
    min = a[i];
  }
}
int sum = 0;
for (int i = 0; i < a.length; i++) {
  sum += a[i];
}
for (int i = start; i <= end; i++) {
  if (i % mult == 0) {          // multiples
    System.out.println(i);
  }
}
```

REVERSE

```
void reverseArray(int[] a) {  // in place
  int l = 0;
  int r = a.length - 1;
  while (l < r) {
    int t = a[l];
    a[l] = a[r];
    a[r] = t;
    l++;
    r--;
  }
}                   // {1,2,3,4} -> 4 3 2 1
String reverse(String s) {
  String out = "";
  for (int i = s.length() - 1; i >= 0; i--) {
    out += s.charAt(i);
  }
  return out;                   // "abc" -> "cba"
}
```

ORDER THE STEPS

```
insert: check range -> i = a.length-1
  -> while i > idx: a[i] = a[i-1], i--
  -> a[idx] = val
binary search: low > high return NOT_FOUND
  -> mid -> equal? return mid -> recurse a half
TOH: n == 0 return -> TOH(n-1,start,temp,goal)
  -> print move -> TOH(n-1,temp,goal,start)
delete: check range -> i = idx+1
  -> while i < length: a[i-1] = a[i] -> GAP
```

BUBBLE SORT (L1, L2)

```
for (int i = A.length - 1; i > 0; i--) {
  for (int j = 0; j < i; j++) {
    if (A[j + 1] < A[j]) {
      int temp = A[j];          // swap
      A[j] = A[j + 1];
      A[j + 1] = temp;
    }
  }
}
```

`i` is FIXED during a pass; `j` moves. n elements: n-1 passes. Descending: use `A[j+1] > A[j]`. After pass k the last k are locked. Worst case O(n^2).

start	pass 1	pass 2	pass 3	pass 4
4 2 3	2 3 4	2 3 4		
3 1 2	1 2 3	1 2 3		
5 2 4 1	2 4 1 5	2 1 4 5	1 2 4 5	
8 1 6 4 9	1 6 4 8 9	1 4 6 8 9	1 4 6 8 9	1 4 6 8 9

n	i starts	passes	pass 1 compares	j max
4	3	3	3	2
5	4	4	4	3
6	5	5	5	4

Compares: 4+3+2+1 = 10 for 5 elements, n(n-1)/2. Sorted {1,2,3}: 3 compares, 0 swaps. Reversed {3,2,1}: 3 compares, 3 swaps.

SEARCHING (L6, L10)

```
for (int i = 0; i < A.length; i++) {
  if (A[i] == val) {
    return i;
  }
}
return -1;        // best O(1), worst O(n)
```

Binary search: array must be SORTED

```
bs(a, val, low, high):
  if (low > high) return NOT_FOUND;
  int mid = (low + high) / 2;
  if (val == a[mid]) return mid;
  else if (val < a[mid])
    return bs(a, val, low, mid - 1);
  else
    return bs(a, val, mid + 1, high);
// start bs(a, val, 0, a.length - 1)  O(log n)
```

a = {1,3,5,7,9,11,13}. Each step: low, high, mid = a[mid].

find	steps	result
11	0,6,3=7 go right; 4,6,5=11	5
3	0,6,3=7 go left; 0,2,1=3	1
5	0,6,3=7; 0,2,1=3; 2,2,2=5	2
4	0,6,3=7; 0,2,1=3; 2,2,2=5, high=1	NOT_FOUND

ARRAY INSERT / DELETE (L10)

```
insert(a, idx, val):
  for (int i = a.length - 1; i > idx; i--) {
    a[i] = a[i - 1];            // shift RIGHT
  }
  a[idx] = val;                 // last falls off
delete(a, idx):
  for (int i = idx + 1; i < a.length; i++) {
    a[i - 1] = a[i];            // shift LEFT
  }
  a[a.length - 1] = GAP;
```

example	steps
insert 50 at 1 in 4 6 8 10	4 6 8 8; 4 6 6 8; 4 50 6 8 (2 shifts)
delete idx 1 in 5 6 7 8	5 7 7 8; 5 7 8 8; 5 7 8 GAP (2 shifts)

Worst idx = 0 gives O(n); best idx = last gives O(1); a[i] is O(1).

PERFECT SQUARE (L6, L9)

v0 `while (i <= n)` O(n). v1 `while (i*i <= n)` O(sqrt n). v2 doubles i, then binary search: O(log n).

n	v0 loops	v1 loops	answer
10	10	3 (i=1,2,3)	No
20	20	4 (i=1..4)	No
16	4	4	Yes

MORE WHOLE METHODS

```
boolean isSorted(int[] a) {
  for (int i = 1; i < a.length; i++)
    if (a[i - 1] > a[i]) return false;
  return true;    // empty or 1 element: true
}
int countDivisible(int lo, int hi, int k) {
  int count = 0;
  for (int i = lo; i <= hi; i++)
    if (i % k == 0) count++;
  return count;   // (1, 11, 3) = 3
}
```

RECURSION (L7, Lab 4)

Needs a **base case** (smallest problem, returns) and a **recursive case** (calls itself on a SMALLER problem). No base case = StackOverflowError.
Trace: go DOWN (calls wait), then back UP using the value from below. `sumTo(2)` means the SUM 1+2 = 3, not the number 2. Countdown n..0 = n+1 calls.
Print BEFORE the call = going down (3,2,1). Print AFTER = coming up (1,2,3).

```
int sumTo(int n) {
  if (n == 0) return 0;
  return n + sumTo(n - 1);
}           // (0)=0 (1)=1 (2)=3 (3)=6
void down(int n) {      // down(3): 3 2 1
  if (n == 0) return;
  System.out.println(n);
  down(n - 1);
}
void up(int n) {              // up(3): 1 2 3
  if (n == 0) return;
  up(n - 1);
  System.out.println(n);
}
void test(int n) {   // test(2): A2 A1 B1 B2
  if (n == 0) return;
  System.out.println("A" + n);
  test(n - 1);
  System.out.println("B" + n);
}
int sumDigits(int n) {
  if (n == 0) return 0;
  return n % 10 + sumDigits(n / 10);
}           // (72) = 2 + (7 + 0) = 9
int countDigits(int n) {
  if (n < 10) return 1;
  return 1 + countDigits(n / 10);
}           // (472) = 1 + (1 + 1) = 3
```

```
String rev(String s) {
  if (s.length() <= 1) return s;
  return rev(s.substring(1))
         + s.charAt(0);
}   // "abc": rev("bc") + a
    // = (rev("c") + b) + a = "cba"
boolean isPal(String t) {
  int n = t.length();
  if (n <= 1) return true;
  if (t.charAt(0) != t.charAt(n - 1))
    return false;
  return isPal(t.substring(1, n - 1));
}   // "abba": a=a, "bb": b=b, "" true
    // "abca": a=a, "bc": b!=c false (2 calls)
int f(int n) {
  if (n <= 1) return 1;
  return f(n - 1) + f(n - 2);
}   // f(2)=2 f(3)=3 f(4)=5; 9 calls for f(4)
```

```
TOH(n, start, goal, temp):
  if (n == 0) return;
  TOH(n - 1, start, temp, goal);
  print start --> goal;
  TOH(n - 1, temp, goal, start);
call TOH(n, "A", "C", "B");  moves = 2^n - 1
n=2: A-B A-C B-C
n=3: A-C A-B C-B A-C B-A B-C A-C
```

WRITE A RECURSIVE METHOD IN 4 STEPS

```
1 base case: smallest input, return directly
2 one piece of work: n%10, first letter, n
3 call yourself on a SMALLER input:
  n/10, n-1, substring(1)
4 combine: return piece + the call
A loop stop condition = the base case
```

LOOPS TO BIG-O

code	Big-O
`return a[5];`	O(1)
one loop `i<n`	O(n)
two loops one after the other	O(n)
loop inside loop, both to n	O(n^2)
inner `j<i` inside `i<n`	O(n^2)
`while (n>1) n=n/2;`	O(log n)
`for (i=1;i<n;i*=2)`	O(log n)
inner loop of 5, outer to n	O(n)
3 nested loops to n	O(n^3)
n + n^2 steps	O(n^2)
T(n) = 6n^2+30n+11	O(n^2)

CSCI2010U MIDTERM - SIDE B: OOP, INTERFACES, BIG-O, LISTS, EXPLAIN WHY

INHERITANCE (L3, L4, Lab 2)

`extends`. Test "is a": Manager IS AN Employee, never the reverse. A subclass can add and **override**.

`super(...)` must be the FIRST line of the constructor (runs the parent constructor).

Parent `private` fields are not visible in the child: use the getter.

In an override, `super.m()` = parent version. Plain `m()` = itself, forever = **StackOverflowError** (runtime).

```
class Pet {
  private String name;
  public Pet(String name) { this.name = name; }
  public String getName() { return name; }
  public String sound() { return "..."; }
}
class Dog extends Pet {
  private int tricks;
  public Dog(String name, int tricks) {
    super(name);              // first line
    this.tricks = tricks;
  }
  @Override
  public String sound() { return "Woof"; }
  public String describe() {
    return getName() + " knows " + tricks;
  }
}
class LoudDog extends Dog {
  public LoudDog(String n, int t) {
    super(n, t);
  }
  @Override
  public String sound() {
    return super.sound() + "!";
  }
}
// Cat: same pattern, sound() returns "Meow"
Pet[] p = { new Pet("A"), new Dog("B", 1),
            new LoudDog("C", 2) };
for (Pet x : p) {
  System.out.println(x.sound());
}         // prints:  ...   Woof   Woof!
```

```
class LimitedCounter extends Counter {
  // private int limit;
  public LimitedCounter(String name,
      int limit) {
    super(name);
    this.limit = limit;
  }
  @Override
  public void increment() {
    if (getCount() < limit) {
      super.increment();
    }
  }
}
// Manager: super(salary, name); bonus = 0;
// getSalary: super.getSalary() + bonus
```

POLYMORPHISM (L4)

A parent variable can hold a child object. The version that RUNS is the object's own class.

Read right to left with "is a". A parent variable cannot call child-only methods.

Making an object: declare a REFERENCE (an address), create the object with `new` on the **HEAP**, link them.

code	result
`Pet p = new Dog("B",1);`	OK (Dog is a Pet)
`p.sound()`	runs Dog: Woof
`p.describe()`	COMPILE error
`Dog d = new Pet("A");`	COMPILE error
`Pet[] arr`	holds Pet, Dog, Cat
`void feed(Pet x)`	accepts any Pet child

EXPLAIN WHY

Equal to target counts: "at least" means >=.

super(name) vs super.increment(): the first sets the parent's private state (first line only); the second calls the parent version of an overridden method.

new Person() fails: abstract, cannot be instantiated, even with a constructor.

Comparable and Arrays.sort: sort calls compareTo to decide the order. implements = many roles; extends = one parent.

Loop stop vs base case: both are the condition where work ends, and every step moves toward it.

Why private fields? Only methods can change state, so the class controls how data is read and changed.

COMPILE OR RUNTIME?

situation	error
override calls itself (no `super.`)	RUNTIME StackOverflow
`a[4]` on length 4	RUNTIME ArrayIndex…
`new Shape()` (abstract)	COMPILE
concrete class missing an abstract method	COMPILE
child reads parent private field	COMPILE
`return null` in an int method	COMPILE

ABSTRACT CLASS (L5, Lab 3)

```
abstract class Shape {
  public abstract double area();  // no body
}
class Square extends Shape {
  private double s;
  public Square(double s) { this.s = s; }
  @Override
  public double area() { return s * s; }
}
new Shape()                 // ERROR (abstract)
Shape b = new Square(2);    // OK
class Triangle extends Shape { }  // ERROR
  // fix: write area() OR abstract class
```

Cannot instantiate an abstract class, even with a constructor. A constructor can NOT be abstract. Mixes concrete + abstract methods; can have static methods.

A child must write ALL abstract methods or be abstract itself. Non-abstract = **concrete**.

WRITE A WHOLE CLASS (Roster)

```
class Roster {
  private String[] names;
  private int size;
  public Roster(int capacity) {
    names = new String[capacity];
    size = 0;
  }
  public void add(String name) {
    if (size == names.length)
      throw new IndexOutOfBoundsException();
    names[size] = name;
    size++;
  }
  public String get(int index) {
    if (index < 0 || index >= size)
      throw new IndexOutOfBoundsException();
    return names[index];
  }
  public int size() { return size; }
}
```

INTERFACE AND compareTo

```
class Student implements Comparable<Student> {
  private String name;
  public Student(String name) {
    this.name = name;
  }
  @Override
  public int compareTo(Student o) {
    return name.compareTo(o.name);
  }
}
// Strings use compareTo; numbers use
// Integer.compare(pages, o.pages)
class Employee extends Person
    implements Comparable<Employee> { ... }
Arrays.sort(arr);
// Maya, Alex, Priya -> Alex, Maya, Priya
```

Returns **negative** if this comes first, **0** if equal, **positive** if after. `Arrays.sort` uses it; order does NOT come from insertion order.

Interface = a list of promises (a ROLE); all methods abstract. `implements` MANY, `extends` only ONE (diamond problem: two parents, which method?).

Generics `<T>` restrict the type: `ArrayList<String>` holds Strings only.

ACCESS AND PACKAGES

access	public	protected	none	private
same class	Y	Y	Y	Y
same pkg, subclass	Y	Y	Y	N
same pkg, other	Y	Y	Y	N
diff pkg, subclass	Y	Y	N	N
diff pkg, other	Y	N	N	N

Package: first line `package x;`, class names unique per package, no statement = default package, `java.lang` (System, Math, String) auto-imported, `java.util` has Arrays and Random. Course uses mostly public and private.

ALGORITHMS AND BIG-O (L6 to L9)

Algorithm = finite, deterministic (same input, same output), effective, implementable in any language. Pseudocode is for humans. **Time** = count steps; **space** = memory; time matters most.

T(n) = steps for input size n. Each line costs a constant; `end` and comments not counted. A loop header runs ONE MORE time than its body.

Linear search: best (first spot) O(1), worst (missing) `an+b` = O(n). We use **worst case**: an upper-bound guarantee that happens often.

Ladder, slow to fast: **1, log n, sqrt n, n, n log n, n^2, n^3, 2^n, n!**

Definition: f(n) = O(g(n)) if there are positive c and n0 with 0 <= f(n) <= c*g(n) for all n >= n0. g is an UPPER bound; O(g) is a SET.

Drop constants and small terms: 4n^2+20n+9 = O(n^2); 3+5n^2+7n^3 <= 15n^3 so O(n^3).

True/False rule: simplify, then LEFT = O(RIGHT) is true if left is the same or EARLIER on the ladder.

claim	answer
5n+20 = O(n)	T
n^2 = O(n)	F
n = O(n^3)	T
2^n = O(n^3)	F
3n+4 = O(n^2)	T
n log n = O(n^2)	T
3^n = O(n^3)	F
n^3 = O(3^n)	T
3+5n+18n^2 = O(n) / O(n^2)	F / T

T(n) AND BIG-O, WORKED

```
linear search: line 1 for: c1(t+1)
  line 2 if: c2*t | line 3 return i: c3
  line 6 return -1: c4     (t = body runs)
best t=1: 2*c1 + c2 + c3 = constant = O(1)
worst t=n: c1(n+1) + c2*n + c4
  = (c1+c2)n + c1 + c4 = O(n)
3n+5 = O(n): 3n+5 <= 8n for n>=1 (c=8, n0=1)
n^2+n = O(n^2): <= 2n^2 for n>=1 (c=2)
3+5n^2+7n^3 <= 3n^3+5n^3+7n^3 = 15n^3
```

LISTS (L11)

Ordered = each element has a position (not sorted by value). Head = start, tail = end.

Interface says WHAT (add, addLast, get, isEmpty, size, toString); the implementation says HOW (ArrList uses an array).

`size` = stored now, `maxSize` = capacity. A bad index throws **IndexOutOfBoundsException** (unchecked, runtime). The slide checks `index > size`; the correct test is `index >= size`.

```
ArrList() { this(DEFAULT_SIZE); }  // 10
ArrList(int capacity) {
  maxSize = capacity;
  size = 0;
  listArray = (T[]) new Object[capacity];
}
get(i): if (i < 0 || i >= size)
    throw new IndexOutOfBoundsException();
  return listArray[i];
add(e, i): shift RIGHT from the end
  for (k = last; k > i; k--)
    listArray[k] = listArray[k - 1];
  listArray[i] = e;
  if (size < maxSize) size++;
addLast(e) when FULL: shift LEFT
  for (k = 1; k < listArray.length; k++)
    listArray[k - 1] = listArray[k];
```

add at head = array INSERT (shift right), O(n). addLast on a full list = shift left, O(n).

QUICK FACTS

expression	result
`Arrays.toString(new int[3])`	[0, 0, 0]
`"Hello".charAt(1)`	'e'
`a[3]` on {4,8,15}	Array IndexOutOfBounds
`int a[3];` or `new int[]`	does NOT compile
`char c = s[0];` (String s)	does NOT compile
`static int f(){return null;}`	does NOT compile
`7 / 2 + " " + 7 % 2`	3 1

Constructor: `public Person(String name, int age) { this.name = name; this.age = age; }`

Terms: object = state (fields) + behaviour (methods) + identity. Encapsulation = private fields + public methods.