

===== Day-01 : Spring Boot & Microservices =====

- 1) What is Spring Boot ?
- 2) Why Spring Boot ?
- 3) Advantages with Spring Boot
- 4) What type of apps we can build using boot ?

===== What is Spring Boot ? =====

=> Spring Boot is an approach to develop spring framework based applications with less configurations.

=> Spring Boot is an extension for existing spring framework.

=> Spring Boot internally uses spring framework only.

=> Spring Boot supports rapid application development.

Spring Boot = (Spring + Auto Config) - xml config

===== What type of applications we can create using boot ? =====

=> By using this spring boot we can develop several types of applications

- a) stand-alone app
- b) web application (C2B)
- c) distributed application (B2B)

(webservices / rest apis)

===== Spring Boot Advantages =====

- 1) POM starters
- 2) Dependency Version Conflicts solution
- 3) Embedded Servers
- 4) Auto Configuration
- 5) Actuators....

===== What is POM starter ? =====

=> pom starters are used to simplify maven or gradle configurations

=> We have several pom starters

- a) spring-boot-starter-web
- b) spring-boot-starter-data-jpa
- c) spring-boot-starter-mail

d) spring-boot-starter-security

Note: when we add pom starter boot will take care of dependency version.

```
=====
Embedded Servers
=====
```

=> Spring Boot will provide servers to run our application

- a) tomcat (default)
- b) jetty
- c) netty

```
=====
Auto Configuration
=====
```

=> It is one of the most imp feature in spring boot

=> Boot will identify configurations required for the application based on pom starters and it will provide that configuration in runtime.

```
=====
Actuators
=====
```

=> To monitor and manage our application

=> Production Ready Features

- /health
- /beans
- /mappings
- /configProps
- /heapdump
- /threaddump

```
=====
Day-02 : Developing Spring Boot Apps
=====
```

=> We can develop in 2 ways

a) Spring Initializr website (start.spring.io)

- > Create Project
- > Download as zip file
- > Extract zip file
- > Import into IDE as Maven project

b) IDE (STS/IntelliJ)

```
=====
Spring Boot Application Folder Structure
=====
```

src/main/java => To write application source code

- Application.java (Start class & Entry Point)

src/main/resources => To keep application config file

- application.properties

src/test/java => To write junit test cases

- ApplicationTest.java

src/test/resources => To keep unit test config files

Maven Dependencies => libraries downloaded

target => byte code (.class files)

pom.xml => Maven config file

=====
What is start class in Spring Boot ?
=====

=> Start class is entry point for boot application execution

=> It is also called as main class in spring boot

=> When we create boot application, start class will be created by default.

```
@SpringBootApplication
public class Application {

    public static void main(String[] args) {
        SpringApplication.run(Application.class, args);
    }

}
```

=====
What is @SpringBootApplication annotation?
=====

=> This is used at start class of spring boot...

=> This is equal to 3 annotations

- a) @SpringBootConfiguration
- b) @EnableAutoConfiguration
- c) @ComponentScan

=====
What is @ComponentScan annotation ?
=====

=> It is used to scan the project and identify spring beans available in the application.

=> Component Scanning works based on base-package of application.

Note: The package which contains start class of spring boot is called as base package.

=> The packages which are starting with base package name are called as sub packages.

```
in.ashokit
    - Application.java
```

```
in.ashokit.service
in.ashokit.dao
in.ashokit.controller
in.ashokit.util
```

```
com.ashokit ----- will not be scanned
```

=====
Q) Can we configure more than one base package in the app ?
=====

```
@SpringBootApplication
@ComponentScan(basePackages = { "in.ashokit", "com.tcs" })
public class Application {

    public static void main(String[] args) {
        SpringApplication.run(Application.class, args);
    }

}
```

=====

Q) How to represent java class as Spring Bean ?

=====

@Component : To represent java class as spring bean

@Service : To represent java class as spring bean

@Repository : To represent java class as spring bean

@Configuration : To represent java class as configuration class

@Bean : To customize objs creation process (method level)

@Controller : To handle http requests in web app (c2b)

@RestController : To handle http requests in rest apis

@ComponentScan : To scan spring beans in our applications

=====

Q) What is run () method in spring boot start class ?

=====

=> It is entrypoint for boot application execution

- Bootstrap context
- starting listeners
- prepare Environment
- printing banner
- create context (IOC)
- prepare context
- call runners
- return ioc

=====

What is banner in Spring Boot ?

=====

=> Logo which is printing on console is called banner

=> By default spring logo will be printed on console

=> We can customize banner text by creating "banner.txt"

File location : src/main/resources

=> Banner works based on modes

- a) console (default)
- 2) log (print in log file)
- 3) off

=> We can banner mode like below in application.properties file

spring.main.banner-mode=off

=====

How IoC will be started in boot application ?

=====

=> run () method is responsible to start IOC in boot app

=> run () method will use predefined class to start IOC based on pom starter

default app (standalone) : spring-boot-starter

Class : AnnotationConfigApplicationContext

web app : spring-boot-starter-web (tomcat)

Class: AnnotationConfigServletWebServerApplicationContext

reactive app : spring-boot-starter-webflux (netty)

Class : AnnotationConfigReactiveWebServerApplicationContext

=====

What is Runner in Spring Boot ?

=====

=> Runner is used to execute logic only once when application started.

=> We have 2 types of runners in spring boot

- a) ApplicationRunner
- b) CommandLineRunner

@Component

```
public class MyAppRunner implements ApplicationRunner{

    @Override
    public void run(ApplicationArguments args) throws Exception {
        System.out.println("my runner executed....");
        // logic
    }
}
```

Useases : insert data in db, delete staging tables data, setup cache.

=====

Day-5 : Autowiring

=====

=> It is used to perform dependency injection

=> Injecting one bean object into another bean object is called as dependency injection.

=> We can perform dependency injection in 3 ways

- 1) setter injection
- 2) constructor injection
- 3) field injection

Note: IoC container is responsible to perform dependency injection.

=> IOC will manage and collaborate bean objects

```
=====
What is Spring Bean ?
=====
```

=> The java class which is managed by IoC is called as spring bean.

```
=====
What is Constructor injection ?
=====
```

=> Injecting dependent bean object into target bean object using target class constructor is called as CI.

=> To enable this we will write `@Autowired` at constructor level.

Note: When we have only one parameterized constructor in target class then `@Autowired` is optional.

```
@Service
public class UserService {

    private UserDao userDao;

    public UserService() {
        System.out.println("UserService:: default - constructor");
    }

    @Autowired
    public UserService(UserDao userDao) {
        System.out.println("UserService:: param - Constructor");
        this.userDao = userDao;
    }

    public void getName(int id) {
        String findName = userDao.findName(id);
        System.out.println("Name ::" + findName);
    }

}
```

```
=====
What is setter injection ?
=====
```

=> Injecting dependent bean object into target bean object using target class setter method is called as SI.

=> To enable this we will write `@Autowired` at setter method level.

```
@Service
public class UserService {

    private UserDao userDao;

    public UserService() {
        System.out.println("UserService:: default - constructor");
    }

    @Autowired
    public void setUserDao(UserDao userDao) {
        this.userDao = userDao;
    }

    public void getName(int id) {
        String findName = userDao.findName(id);
        System.out.println("Name ::" + findName);
    }

}
```

```
}
```

```
=====
What is field injection ?
=====
```

=> Injecting dependent bean object into target bean object using target bean variable is called as field injection.

Note: Internally IOC will use reflection api to perform field injection.

```
@Service
public class UserService {

    @Autowired
    private UserDao userDao;

    public void getName(int id) {
        String findName = userDao.findName(id);
        System.out.println("Name ::" + findName);
    }

}
```

Note: Using reflection api we can access private variables outside of the class.

```
public class User {

    private int age = 20;

    public int getAge() {
        return age;
    }

}

public class Test {

    public static void main(String[] args) throws Exception {

        Class<?> clz = Class.forName("in.ashokit.bean.User");

        Object object = clz.newInstance();

        Field ageField = clz.getDeclaredField("age"); // loading variable
        ageField.setAccessible(true); // making variable accessible
        ageField.set(object, 50); // setting value to variable

        User u = (User) object;
        int age = u.getAge();
        System.out.println("User Age :: " + age);

    }

}
```

```
=====
Autowiring modes
=====
```

=> Autowiring works based on modes

- 1) byName : Based on variable name it will identify dependent bean
- 2) byType : Based on variable datatype it will identify dependent bean.

```
=====
What is @Qualifier annotation ?
=====
```

=> It is used to identify dependent bean based on bean name

```
@Component
public class Robot {

    @Autowired
    @Qualifier("chip64")
    private IChip chip;

}
```

Note: IChip is an interface which is having 32bit & 64bit implementation classes.

=> Based on above configuration it will inject the bean whose name is "chip64"

```
=====
Q) What is Ambiguity problem in Autowiring ?
=====
```

=> If one interface having more than one impl class then we will get ambiguity problem in "byType" mode.

=> To resolve byType ambiguity problem we can use @Primary annotation.

=> The bean which is having @Primary annotation will get highest priority for autowiring.

```
=====
What is Bean scope
=====
```

=> Bean scope represents how many objects should be created for spring bean.

=> By default every spring bean is singleton (only one object)

=> We can customize bean scope using @Scope annotation

=> prototype scope represents every time new object.

Note: For singleton beans objects will be created when ioc container starting.

```
@Component
@Scope("prototype")
public class Robot {
    //logic
}
```

```
=====
@SpringBootApplication
```

- @SpringBootConfiguration
- @EnableAutoConfiguration
- @ComponentScan

```
@Configuration
@Bean
@Component
@Service
@Repository
@Autowired
```


@Qualifier
 @Primary
 @Scope

=====
 CI ---> target class constructor
 =====

=> dependent bean is mandatory to create target bean

=> if dependent bean not available then target bean can't created.

=> first dependent bean obj will be created then only target bean object will be created.

=====
 SI --> target class setter method
 =====

=> First target bean object will be created then dependent object obj will be created.

=> After target bean creation using target bean obj setter method will be called (optional)

=====
 FI --> target class variable
 =====

=> IOC will use reflection api to perform FI.

=> Field Injections is simple to write.

=> IOC violating oops principles.

=> It is giving chance to violate Single Responsibility principle.

=====
 Summary
 =====

1) What is Spring Boot

2) Spring Boot Advantages

- pom starters
- auto configuration
- embedded servers
- actuators

3) First Boot Application

4) Boot Application Folder Structure (Maven)

5) What is start class in Spring Boot

- @SpringBootApplication
- SpringApplication.run ()

6) What is Component Scanning

7) How run () method works internally

- bootstrap our app
- start listeners
- prepare env
- print banner
- create IOC
- call runners
- return IOC

8) How to customize banner in boot app

9) How ioc will start in boot application ?

10) Runners in Spring Boot

- Application Runner
- Commandline Runner

11) Spring Boot Annotations

- @SpringBootApplication
- @Configuration
- @Bean
- @Component
- @Service
- @Repository

12) Bean Scopes (@Scope)

- singleton
- prototype
- request
- session

13) Autowiring

- byName
- byType
- @Autowired
- @Qualifier
- @Primary

14) What is Dependency Injection

- Constructor Injection
- Setter Injection
- Field Injection

15) What is IOC container