

PROFESSIONALS CHECKLIST – DETAIL DRAWING

URBAN PLANNING DEPARTMENT

Housing Development Corporation Limited
HDC Building, Hulhumalé, Republic of Maldives
Hotline 1516 T +960 335 3535
E hello@hdc.mv W www.hdc.mv

GENERAL INFORMATION

Lot number:			
Lot owner/developer name:		Contact number:	

DESIGNER / CHECKER

REGISTRATION NUMBER

Preliminary architect:		
Preliminary engineer:		
Licensed Architect:		
Licensed Engineer:		
Architectural checker:		
Structural checker:		

1. SUBMISSION DOCUMENTS

☐ Drawing approval form
☐ Architectural & structural drawings in PDF format (minimum 200 DPI) with valid architectural & structural checker's stamp & signature
☐ Architectural checker's certificate (minimum 200 DPI)
☐ Structural checker's certificate (minimum 200 DPI)
☐ Architectural and structural checker stamps (minimum 200 DPI)
☐ AutoCAD file of the drawing in DWG format
☐ Structural calculations

- ☐ Foundation Protection Method with the assigned structural engineer's name & signature
- ☐ Visual Soil Inspection Report with the assigned structural engineer's name & signature (if applicable)
- ☐ Manufacturer's lift specifications (if applicable)

2. DESIGNER TITLE BLOCK

- ☐ Designer title block provided on all architectural & structural drawings
- ☐ Lot number provided
- ☐ Assigned architect name provided
- ☐ Assigned structural engineer name provided

3. LOCATION PLAN

- ☐ Tallies with the location plan provided in the agreement/registry drawings
- ☐ North sign shown

4. SITE PLAN

- ☐ Drawing title and scale provided
(1:200, 1:100, 1:50 and if the plot area is greater than 10,000sqft 1:500)
- ☐ Site measurements annotated on all sides
- ☐ Site measurements tally with the plot map provided in the agreement drawings
- ☐ Surrounding context labeled (surrounding buildings/open spaces & roads)
- ☐ North sign marked
- ☐ Plot area mentioned
- ☐ Built-up area mentioned and identified
- ☐ Open area mentioned
- ☐ Openings identified
- ☐ Setback lines identified with measurements

- | |
|---|
| ☐ Setback measurements tally with the setback plan provided in the guidelines |
| ☐ All developments of the plot identified in case of multiple developments or development phases |

5. FLOOR PLANS

- | |
|---|
| ☐ Drawing title and scale provided (1:100, 1:50) |
| ☐ Ingress and egress of vehicles up to the road shown on ground floor plan |
| ☐ All spaces labeled |
| ☐ All doors and windows labeled |
| ☐ All doors and window labels tally with the door/window schedule |
| ☐ Elevation marks provided |
| ☐ Section line provided |
| ☐ Grid lines provided |
| ☐ Boundary wall is shown on the ground floor plan where applicable |
| ☐ Column locations tally with structural drawings |

6. ROOF PLAN

- | |
|--|
| ☐ Drawing title and scale provided (1:100, 1:50) |
| ☐ Roof plan submitted |
| ☐ Roof overhang annotated |
| ☐ Roof overhang does not exceed 450mm to the setback where applicable |

7. SECTION & ELEVATIONS

- | |
|--|
| ☐ Drawing title and scale provided (1:500, 1:200, 1:100) |
| ☐ Tally with floor plans |
| ☐ Section provided from the highest point of the building |

- ☐ Floor-to-floor height annotated on the section
- ☐ Minimum 2.7m clear height to slab/ceiling soffit level is provided for all habitable spaces
- ☐ Floor levels marked
- ☐ Total building height annotated
- ☐ Total building height is within the maximum allowable limit as per guidelines
- ☐ Total building height annotated to the roof apex level
- ☐ Section is cut through the stair well
- ☐ Foundation depth annotated in sectional drawing

8. DOOR/WINDOW SCHEDULE

- ☐ Drawing title and scale provided (1:100, 1:50, 1:20, 1:10, 1:5, 1:2, 1:1)
- ☐ Floor finish levels marked
- ☐ All labels tally with floor plans
- ☐ Minimum 1m height provided from FFL to the bottom of the window except the ground floor & balconies
- ☐ Doors & windows opening/swing/fixed glass indicated
- ☐ Material details provided

9. VENTILATION

- ☐ Ventilation schedule submitted
- ☐ All ventilation voids open to the sky

Size of all ventilation voids along the plot boundary line is a minimum of 0.75m in length and 0.6m in clear width
- ☐ Size of all ventilation voids within the plot has a clear dimension of minimum 0.6m on all sides
- ☐ 10% natural ventilation provided in all habitable spaces

- ☐ 15% natural ventilation provided in all habitable spaces (if applicable)
- ☐ Data provided in the ventilation schedule tallies with the drawings
- ☐ Mechanical ventilation labeled where it's provided and direction is indicated correctly

10. STAIR DETAILS

- ☐ Drawing title and scale provided (1:100, 1:50, 1:20, 1:10, 1:5, 1:2, 1:1)
- ☐ Minimum stair railing height of 850mm is provided
- ☐ Stair railing material & size provided
- ☐ Step & rise measurements provided
- ☐ Stair reinforcement details provided
- ☐ Stair landings meets minimum safety requirements – 1.2m height & child safety provided in the case where horizontal railings are provided

11. BALCONY RAILING DETAILS

- ☐ Drawing title and scale provided (1:100, 1:50, 1:20, 1:10, 1:5, 1:2, 1:1)
- ☐ Railing height annotated from finished floor level
- ☐ Minimum height of 1.2m provided from finished floor level
- ☐ Balcony railing spacing does not exceed 125mm c/c
- ☐ Balcony railing material & size provided
- ☐ Additional children safety is provided if horizontal railings are provided
- ☐ Railing fixing detail provided

12. BOUNDARY & PARAPET WALL DETAILS

- ☐ Drawing title and scale provided (1:100, 1:50, 1:20, 1:10, 1:5, 1:2, 1:1)
- ☐ Boundary & parapet wall details provided
- ☐ Material and dimension provided

- ☐ Reinforcement details provided (if applicable)
- ☐ Tallies with floor plan
- ☐ Wall height annotated from finished floor level
- ☐ Height complies with the development guidelines
- ☐ No part of the structure exceeds plot boundary

13. STRUCTURAL DRAWINGS

- ☐ Drawing title and scale provided
(Plans 1:100, 1:50
Details 1:100, 1:50, 1:20, 1:10, 1:5, 1:2, 1:1)
- ☐ Foundation plan submitted
- ☐ Foundation depth indicated on the foundation plan or section
- ☐ All columns & beams are labelled
- ☐ No structural component exceeds the plot boundary
- ☐ All voids/ducts tally with architectural plans
- ☐ Beam/truss plans submitted
- ☐ Floor structural plans submitted with structural notes
- ☐ Roof structural plans submitted with structural notes
- ☐ Structural details submitted
- ☐ Structural details tallies with the structural drawings

14. LIFT

- ☐ Drawing title and scale provided
- ☐ Lift wall reinforcement details provided
- ☐ Lift pit depth identified
- ☐ Manufacturer's lift specifications provided if:

The height of the lift machine room exceeds 4m from the maximum allowed height

Cargo lift provided

Vehicle lift provided

15. GENERAL REQUIREMENTS

- ☐ FSI/GFA complies with the development guidelines
- ☐ Parking numbers provided as per the development guidelines
- ☐ Parking slot sizes provided as per the development guidelines
- ☐ Building height does not exceed the maximum allowable height
- ☐ PWD ramp details provided with a slope of minimum 1:10 or 1:12 (if applicable)
- ☐ Vehicle ramp details provided with a slope of minimum 1:8 or 1:10 (if applicable)
- ☐ Setback provided as per the development guidelines
- ☐ The roof slab or covered area for void/lift machine room not extruded into the setback area
- ☐ No doors/windows exceed the plot line when opened
- ☐ Manufacturer's specifications provided if a mechanical parking system is proposed
- ☐ Minimum clear height of 2.2m achieved to beam bottom level if a basement is provided
- ☐ Minimum 1m setback is provided if a fully submerged basement protrudes into the setback area (if applicable)
- ☐ Full drawing set should be in gray scale/ black and white

16. ADDITIONAL POINTS FOR HULHUMALE INDUSTRIAL DRAWINGS

- ☐ The usage of the spaces mentioned in the drawing complies with the uses allowed in the zones mentioned in the guideline
- ☐ Setback area not covered above at any level
- ☐ Minimum 60% area of the total development used for industrial purposes
- ☐ Maximum 40% area of the total development used for support facilities

- ☐ Not more than 20% of the permissible 60% of the industrial area has been utilized as a showroom
- ☐ A maximum length of 200mm cladding extruded to setback (if applicable)
- ☐ Lift machine room height does not exceed 7m from maximum allowable height
- ☐ No additional structure is provided outside the covered area of the terrace
- ☐ 10% of GFA allocated for uses designated by HDC from the portion exceeding 18.5m building height

17. ADDITIONAL POINTS FOR THILAFUSHI INDUSTRIAL DRAWINGS

- ☐ All habitable spaces have a minimum clear height of 2.7m
- ☐ All spaces except habitable spaces have a minimum clear height of 2.4m
- ☐ Setback area not covered above at any level
- ☐ Maximum height for the covered area in terrace does not exceed 4.5m
- ☐ Manufacturer's lift specifications provided if the lift machine room exceeds 4.5m in height
- ☐ Lift machine room height does not exceed 7m from maximum allowable height
- ☐ In the case where mechanical parking is provided; manufacturer's lift specifications submitted
- ☐ If front boundary wall length is 40m or more; gate width does not exceed 6m
- ☐ If front boundary wall length is less than 40m; gate width does not exceed 50%
- ☐ No gate placed in the corner of the plot (only applicable to corner lots)
- ☐ Supporting facilities does not exceed 40% of the intended use of the development/plot
- ☐ Supporting facility types complies with the guideline
- ☐ Not more than 10% of the permissible 40% of the support area has been utilized for accommodation
- ☐ Accommodation provided in a way that each person gets 38sqft from the habitable space room
- ☐ Soak pit location identified on ground floor plan

18. ADDITIONAL POINTS FOR HULHUMALE RESIDENTIAL PLOTS

- ☐ Minimum 2.7m clear height (up to slab/ceiling soffit) achieved in all habitable spaces
- ☐ Minimum 2.2m clear height (up to beam soffit level) achieved in basement
- ☐ Maximum height for the covered area in terrace does not exceed 4m
- ☐ Manufacturer's lift specifications provided if the lift machine room exceeds 4m in height
- ☐ Minimum 2.5 width provided for garage entrance and does not exceed 3m if the gate is installed at boundary (plot line)
- ☐ Minimum 2.5 width provided for garage entrance and does not exceed 50% of the plot's front length if the gate is installed at building line
- ☐ Car parking only allowed if a minimum 400sqft space is provided
- ☐ Parking location provided as per setback plans
- ☐ Urban furniture (pool, planter box, benches, etc.) is not be more than 0.3m in height from NGL
- ☐ Kitchen hood provided onto setback max 600mm from building wall & above the building
- ☐ Pergola/ trellis provided as per the guidelines
- ☐ 1.2m fence provided for open restaurants
- ☐ Garbage room is a minimum of 1.5% of building foot print area and minimum 1.5 clear height if under the stairs
- ☐ Garbage room is a minimum of 3% of building foot print area exceeds 3000 sqft and minimum 1.5 clear height if under the stairs
- ☐ Corner lots can be protruded from front and side from 11.8m from NGL (only Neighbourhood 1)
- ☐ Only motorbike parking allowed into setback area (only if building height is below 18.5m)
- ☐ 80% projection into side setback for corner plots with a side setback towards the road
- ☐ PWD ramp 1:10 – 1:12 and PWD accessibility for any public space in ground and first non-residential spaces (minimum 900mm)

☐ Terrace coverage does not exceed 2/3 of the terrace area excluding stair/lift area
☐ Storage size is not more than 45sqft (4.18sqm)
☐ GPON duct size: 200x400mm
☐ Ground floor dedicated for parking (only if building height is from 18.5m upto 30.5m) <i>If basement is fully dedicated for parking, ground floor can be used for non-residential use.</i>
☐ 1 st floor dedicated for non-residential use (only if building height is from 18.5m upto 30.5m)
☐ 1.2m access road provided for NI plots after subdivision
☐ Setbacks are maintained and as per the regulation after plot-subdivision and plot merging.
☐ After plot subdivision, height is within the maximum allowable limit as per the regulation.

DECLARATION

Lot number:			
Submission Type:		Date:	

I hereby declare that the submitted drawings comply with all relevant regulations, guidelines and safety standards. Should the drawings be found non-compliant with the Laws/ Regulations and planning guidelines/ controls set by HDC and relevant authorities I acknowledge that I will be penalized in accordance with the Construction Industry practitioners' regulation.

Architectural Checker

Name:

Address:

ID Card No:

Email Address:

Registration No:

Signature:

I hereby declare that the submitted structural drawings comply with all relevant regulations, guidelines and safety standards. Should the drawings be found non-compliant with the Laws/ Regulations and planning guidelines/ controls set by HDC and relevant authorities I acknowledge that I will be penalized in accordance with Article 24 and 25 of the Construction practitioners' regulation.

Structural Checker

Name:

Address:

ID Card No:

Email Address:

Registration No:

Signature: