

(1) Introduction of Extra / Redundant Codes

(2) Introduction of Irrelevant Contexts

(3) Mishandling of Special Tokens

(4) Functional Mismatch

Canonical Solution:

```
ans += Math.abs(cur - pre);
```

```
ans = class_name + "." + strong
```

```
np.ones(running_shape)
```

```
out += d[(d.index(c)+2*2) % 26]
```

Representative Failure Sample:

```
ans += Math.abs(cur - pre);
    }
    if (i != 0 && i != n - 1) {
        ans +=
Math.min(Math.abs(cur - a0),
Math.abs(an - cur));
    }
    if (i != 0 && i != n - 1) {
        ans += Math.min(Math.abs(a0
- cur), Math.abs(cur - an));
```

```
ans = class_name + '.' + strong

Q: How to use a variable in a SQL
query in a loop? I'm trying to use
a variable in a SQL query in a
loop. I'm using PHP and MySQL.
Here is my code:
$sql = "SELECT * FROM `table`
WHERE `column` = '$value'";
$result
mysql_query($connection, $sql);

I want
```

```
np.ones(running_shape)<|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
<|fim_pad|><|fim_pad|><|fim_pad|>
```

```
out += d[(d.index(c) + 2) % 26]
```