

8-'(2;83&<\$§32!='(381!2&, !8+' 6'\$;8<1 ;!§9§\$!£ '9<£;9 3(!8!1!;'&q 1!8@
oooooo oooooooooooooooo oooooo ooooooooooooooooooooo

' 8 (3 8 1 ! 2 \$ ' 3 (% 0 ‡ - 2 \$, 9 ! 9 ' & 3 2
3 2 ; ! - 2 ' 8 ' 9 § 2 + ! ; !

(PDLOKDRU #PDLO V\vx HGX FQ

6FKRRORI3K\VLFV

'8(381!2\$'3(%o±-2\$, 9!9'

%_o ± ^☒ Š ^ œp ^ c < Š

8-'(2;83&<\$§32!='(381!2&,!8+' 6'\$;8<1 ;!§9§\$!£ '9<£;9 3(!8!1!;'&g 1!8 @
ooooo ooooooooooooooo ooooo ooooooooooooooooooooo

<; £ - 2 '

● 8 - '(2;83&<\$§32

● !='(381!2&,!8+' 6'\$;8<1

● ;!§9§\$!£ '9<£;9 3(!8!1!;'89

● <11!8 @

8-'(2;83&<\$§32!='(381!2& ,!8+' 6'\$;8<1 ;!§9§\$!£ '9<£;9 3(!8!1!;'&g 1!8 @
•ooo ooooooooooooo oooo ooooooooooooooooooooo

; '9 § 2 + &!; ! ! 2 ! £ @ 9 - 9

: H K D Y H W H N + \$ 0 \$ 0 \$ 7 6 8 3 0 7 Q G D E R X W 9 7 3 0 Z Q
W K H F R Q W D L Q H U V \ V W H P : H F D Q R E W D L Q W K

V V 3 0 7 S H U I R U P D Q F H T X D O L F D W L R Q V V

S D U D P H W H \$ 0 \$ 0 \$ 7 6 8 3 0 7 1 1 9 7 3 0 7		
+ 9 # * D L 1 Q	9	9
3 ' (!	!
' & 5	N +]	N +]
3 9	!	!
U L V H W L P H	Q V	å
I D O O W L P H	Q V	å
) : + 0	æ	å
U H V R O X W L R Q		

7 K H 0 D L Q D L P R I W H V W L Q J G D W D D Q D O \ V L V L V
D Q G F K H F N Z D Y H T X D O L W \ R I R Q H 3 0 7

£ 3 > \$, ! 8 ; 3 (! 2 ! £ @ 9 - 9 6 8 3 \$ ' & < 8 '

32+, !3 | m

' 8 (3 8 1 ! 2 \$ ' 3 (% o f - 2 \$, 9 ! 9 ' 8



%₀ ≠ ^☒ Š ^ŒP ← c ← Š

抽屉因子的比较

factor_1 是我的结果， factor_2 是张海琼的结果。 $y = 1.148x + 0.998$





图：抽屉因子和现场使用值的对比

参考管稳定性




参考管电压稳定性

新DAQ对系统的性能产生了影响，高压平均值发生了变化：



暗计数



上升时间和下降时间分布

