Noise Spectrum and Photon Response of MCP-PMT

- based on the onsite PMT testing data

Email: zhaor25@mail2.sysu.edu.cn

School of Physics





Outline


Brief Introduction


2 traing and test of CNN

Summary

photon response characters of MCP PMT

The typical waveform and charge spectrum of MCP PMT@gain = 10^7 [dark noise]







In the state of t

01pe

the "long tail" of charge spectrum, unexpected "big signals"





(S: HAMAMATSU

图: MCP

CNN

select the time interval before "trigger window".





图: tags of typical waveform from CNN



classification of events in one test

01pe

the 0.1pe case




图: tags of typical waveform from CNN




图: classification of events in one test

01pe

the 1pe case





图: tags of typical waveform from CNN



classification of events in one test

the expected photon number

If we do a "cut" is the charge spectrum@0.25 spe, the averager photon number μ can be acquired by 1

$$\mu = -\ln(\frac{N_0}{N})\tag{1}$$

where N_0 is the number of pedestal (0 p.e) events, N is the total event number.

However, if we know explicitly the photon number of specific event, the μ value is :

$$\mu = 1 \times \mathbf{n}_1 + 2 \times \mathbf{n}_2 + \dots + \mathbf{N} \times \mathbf{n}_{\mathbf{N}} \tag{2}$$


where n_N is the number of N p.e events.

¹E. H. Bellamy et al /Nucl. Instr. and Meth. m Phys . Res. A 339 (1994) 468-476

input of CNN


training data slecetion and pre-process:

- random selection from different PMTs
- 1.5<QDC<1.7 for 1p.e
- 3.1<QDC<3.3 for 2p.e
- 4.7<QDC<4.9 for 3p.e
- 81ns ROI \rightarrow 9×9 2D image
- normalization




CNN parameters

- 30k training waveform samples
- 2 convolution layers
- 4 output tags
- accuracy $\simeq 0.95$





results of cnn



: HAMAMATSU PMT

results of cnn




图: NNVT PMT

summary

- PSD by CNN provide a new option for PDE evaluation.
- can achieve sim0.95 acuuracy with the traditional method using simple NN.
- much faster than tradition methods in PDE evaluation.
- CNN can ectract more infromation from waveforms.

to list:

- refine the training samples and network structure.
- compare the accuracy in more details, for example using the reference tubes in container system.
- improve the input data quality.

THANKS

BACK-UP