

Errors

When an error occurs during an API request, you will receive:

- An HTTP error status (in the 400-500 range)
- A JSON response containing more information about the error

A typical error response looks like this:

```
{
  "error": "VENUE_AND_ONLINE",
  "error_description": "You cannot both specify a venue and set online_event",
  "status_code": 400
}
```

See below for descriptions of what each line means:

Example	Description
{	
"error": "VENUE_AND_ONLINE",	"VENUE_AND_ONLINE" is an example of a constant string value for the error. This constant value is what you should base your error handling logic on, because this string won't change depending on the locale or as the API changes over time.
"error_description": "You cannot both specify a venue and set online_event",	"You cannot both specify a venue and set online_event" is an example of an error description value. This string usually contains a description of the error, and should only be displayed to developers, not your users.
"status_code": 400	400 is an example of a status code value. This value mirrors the HTTP status code you will receive. It's included for convenience, in case your HTTP client makes it difficult to get status codes, or has one error handler for all error codes.
}	

Common Errors

You can find a listing of the individual errors for each endpoint on their endpoint entries, but there are also some common errors that all endpoints might return:

Status Code	Text	Description
301	PERMANENTLY_MOVED	Resource must be retrieved from a different URL.
400	ACTION_NOT_PROCESSED	Requested operation not processed.
400	ARGUMENTS_ERROR	There are errors with your arguments.
400	BAD_CONTINUATION_TOKEN	Invalid continuation token passed.
400	BAD_PAGE	Page number does not exist or is an invalid format (e.g. negative).

400	BAD_REQUEST	The resource you're creating already exists.
400	INVALID_ARGUMENT	Invalid argument value passed.
400	INVALID_AUTH	Authentication/OAuth token is invalid.
400	INVALID_AUTH_HEADER	Authentication header is invalid.
400	INVALID_BATCH	Batched request is missing or invalid.
400	INVALID_BODY	A request body that was not in JSON format was passed.
400	UNSUPPORTED_OPERATION	Requested operation not supported.
401	ACCESS_DENIED	Authentication unsuccessful.
401	NO_AUTH	Authentication not provided.
403	NOT_AUTHORIZED	User has not been authorized to perform that action.
404	NOT_FOUND	Invalid URL.
405	METHOD_NOT_ALLOWED	Method is not allowed for this endpoint.
409	REQUEST_CONFLICT	Requested operation resulted in conflict.
429	HIT_RATE_LIMIT	Hourly rate limit has been reached for this token. Default rate limits are 2,000 calls per hour.
500	EXPANSION_FAILED	Unhandled error occurred during expansion; the request is likely to succeed if you don't ask for expansions, but contact developer support if this problem persists.
500	INTERNAL_ERROR	Unhandled error occurred in Eventbrite. Contact developer support if this problem persists.