



fx public.new_customer

Documentation Dell DVD Store

Schema public

Name new_customer

Function to add a new customer.

▼ Input/Output

Mode		Name	Data type
1	OUT	Returns	integer
Returns customerid.			
2	IN	firstname_in	character varying
The customer's first name.			
3	IN	lastname_in	character varying
The customer's last name.			
4	IN	address1_in	character varying
The first line of an address.			
5	IN	address2_in	character varying
An optional second line of an address.			
6	IN	city_in	character varying
The name of the city.			
7	IN	state_in	character varying
Standard state or province code.			
8	IN	zip_in	character varying
The postal code or ZIP code of the address (where applicable).			
9	IN	country_in	character varying
The country name.			
10	IN	region_in	smallint
Region id.			
11	IN	email_in	character varying
The customer's email address.			



12	IN	phone_in	character varying	The telephone number for the address.
13	IN	creditcardtype_in	integer	Credit card expiration date type.
14	IN	creditcard_in	character varying	Credit card identification number.
15	IN	creditcardexpiration_in	character varying	Credit card expiration date.
16	IN	username_in	character varying	Account username.
17	IN	password_in	character varying	Account password.
18	IN	age_in	smallint	The customer's age.
19	IN	income_in	integer	The customer's income.
20	IN	gender_in	character varying	M = Male, F = Female

▼ Script

```
CREATE OR REPLACE FUNCTION public.new_customer(firstname_in character varying, lastname_in cl
    RETURNS integer
    LANGUAGE plpgsql
    AS $function$
    DECLARE
        customerid_out INTEGER;
        age_int INTEGER;
        income_int INTEGER;
    BEGIN
        -- IF age_in = '' THEN age_int:=0 ; ELSE age_int := CAST (age_in AS INT); END IF;
        -- IF income_in = '' THEN income_int:=0; ELSE income_int := CAST (income_in AS INT); END ]
    BEGIN
        INSERT INTO CUSTOMERS (
            firstname,
            lastname,
            email,
            phone,
            username,
            password,
            address1,
            address2,
            city,
            state,
            zip,
```



```
        creditcard,
        creditcardexpiration,
        age,
        income,
        gender
    )
VALUES (
    firstname_in,
    lastname_in,
    email_in,
    phone_in,
    username_in,
    password_in,
    address1_in,
    address2_in,
    city_in,
    state_in,
    zip_in,
    country_in,
    region_in,
    creditcardtype_in,
    creditcard_in,
    creditcardexpiration_in,
    age_int,
    income_int ,
    gender_in
)
RETURNING customerid INTO customerid_out;
RETURN customerid_out;
EXCEPTION
    WHEN unique_violation THEN
        RETURN 0;
END;
-- RETURN -1;
END;
$function$
```

Exported: 2018-11-09 16:14, Last imported: 2018-08-06 09:39