
Institute for Informatics
Georg-August-Universität Göttingen

Databases and Information Systems



The MONDIAL Database

GEORG-AUGUST-UNIVERSITÄT GÖTTINGEN

The MONDIAL LOD (Linked Open Data) Service [Experimental]

This is the LOD service of the Mondial database.
Linked Open data services are primarily intended for RDF clients (use e.g. `rapper <url>` for accessing it as RDF data).
This service additionally provides some HTML functionality for illustration:

- Main page (i.e., http://www.semwebtech.org/mondial/10/).
  - HTML: the manual.
  - RDF: URIs of all resources in Mondial
- Mondial Resources' URIs
  (e.g. http://www.semwebtech.org/mondial/10/countries/D/provinces/Niedersachsen/cities/Göttingen/)
  - HTML: a table of all triples where the resource occurs at subject or object position.
  - RDF: all triples where the resource occurs at subject or object position.
- Mondial Classes and Properties URIs
  (e.g. http://www.semwebtech.org/mondial/10/meta%23locatedAt)
  (note: the "#" must be escaped as %23 when sending a URL of the form .../qname#localpart)
  - HTML: a table of all triples where the resource occurs at predicate position.
  - The complete ontology of mondial metadata
- SPARQL endpoint at `http://www.semwebtech.org/mondial/10/sparql`, e.g.
  http://www.semwebtech.org/mondial/10/sparql?query=select%20distinct%20?C%20where%20%7B%5B%5D%20a%20?C%7D%20LIMIT%20100
  or
  http://www.semwebtech.org/mondial/10/sparql?query=select%20distinct%20?C%20where%20%7B?C%20a%20%3Chttp://www.semwebtech.org/mondial/10/meta%23Country%3E%7D
  or
  http://www.semwebtech.org/mondial/10/sparql?query=select%20distinct%20?C%20?L%20where%20%7B?C%20a%20%3Chttp://www.semwebtech.org/mondial/10/meta%23Country%3E;%20%3Chttp://www.semwebtech.org/mondial/10/meta%23localname L%7D
  (when pasting URLs into a Web browser, they must be completely percent-encoded; here is an encoding service).
  - HTML: the result of the SPARQL query
  - SPARQL: result as answer bindings in SPARQL Query Results XML Format (set of tuples of bindings in XML) (described at https://www.w3.org/TR/rdf-sparql-XMLres/); this functionality is e.g. used in SPARQL `SERVICE <url> { pattern }` expressions.
  - RDF: Note that RDF clients like the rapper tool do not understand that format (the answer bindings are intended to be consumed by SPARQL e
- SPARQL query SPARQL queries