



SLE500S / SLE500E

Air compressors for use with SLE infant ventilators



When the smallest thing matters

Accessible Air...

The SLE500E and SLE500S air compressors are an ideal air source for all SLE ventilators when piped compressed air is not available or when you need a back-up air source for added protection.

Easily accessible filters and indicators make regular maintenance simple and cost effective.

Both compressors are also available with the heavy-duty SD30 compressor trolley (see opposite page) that allows the compressor to be integral with the ventilator.

All compressors are supplied with 4 wheels (2 with brakes) and 4 rubber feet. You can choose what to fit when the compressor is commissioned. If the compressor is to be used on the SD30 trolley then you must fit the rubber feet.

Standard features include:

- > Medical grade dry, clean, oil-free air
- > Portable, when fitted with wheels
- > 60 l/min maximum flow rates
- > Quiet operation
- > Low maintenance
- > Main gas supply automatic back-up mode (SLE500 S only)



SLE500E

The *Easy* Choice

When value is important, the SLE500E is your choice of compressor. This new design features a simplified case, with no complicated controls or dials.

The compact, powder-coated, wipe-clean case is free of all buttons and controls.

Designed to run quietly and with minimum vibration, the SLE500E is perfect as a 'switch it on and forget it' compressor.

Long maintenance intervals mean low running costs.

The rear features an on/off switch, power indicator, mechanical hour counter and an outlet pressure gauge



SLE500S

The *Smart* Choice

The SLE500S is the 'big brother' of the family and includes a number of extra options as standard.

There is an 'air in' connector on the back that can be connected to a wall outlet. In the event of wall gas failure when plugged in, the SLE500S will automatically start up ensuring a continuous supply of air.



A digital display on the top of the compressor can be selected to show the output pressure, temperature or total hours and features alarm indicators for a variety of conditions.

Specifications & Part Numbers

	SLE500E	SLE500S
		
Model	Part No.	Part No.
230 V / 50 Hz	L0500/E01	L0500/S01
230 V / 60 Hz	L0500/E02	L0500/S02
100 V / 50/60 Hz	L0500/E03	L0500/S03
Specifications	SLE500E	SLE500S
Output flow	60 l/min @ 3.5 bar	
Peak flow	200 l/min* @ 3 bar	
Noise level dB(A)	48–51 (depending on model)	
Mode of operation	Continuous - S1	
Air filtration	5 µm	
Air tank capacity	2 litres	
Dew point depression at 3 bar, 20°C	5°C under the ambient temperature	
Dew point depression at 3 bar, 20°C, with membrane dryer (*)	N/A	10°C under the ambient temperature
Outlet connection	DISS 1160-A (3/4"-16 UNF)	
Wall connection	Optional upgrade	Yes
Classification according to MDD93/42/EEC, 2007/47/EC	Class IIb	
Dimensions (w x d x h) (**)	440 x 350 x 420 mm	445 x 355 x 440 mm
Weight (**)	34 kg	30 kg
Included accessories	Instructions for use, 4 wheels, (2 lockable), 4 rubber feet, 3 m black air hose (NIST to DISS)	

* Optional upgrade ** Without wheels • Specifications subject to change without notice



Heavy-duty Trolley

If you want to save space we can also supply the **SD30** trolley which allows a ventilator to be mounted above the compressor.

This trolley comes with a top plate to accept an SLE5000 or SLE4000 ventilator plus two medi-rails for attaching accessories. Midway down the pole is a humidifier bracket to accept a standard humidifier.

Comes with 4 wheels (front 2 lockable) and requires compressor to be fitted with rubber feet.

Part No.: LSD30/000/001

 +44 (0)20 8681 1414

 +44 (0)20 8649 8570

 sales@sle.co.uk

 www.sle.co.uk

SLE Limited
Twin Bridges Business Park
232 Selsdon Road
South Croydon
Surrey
CR2 6PL
UK



When the smallest thing matters