

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.preprocessing import LabelEncoder, StandardScaler

# Load dataset
df = pd.read_csv('/content/titanic.csv')

# Show first 5 rows
print("First 5 Rows:")
print(df.head())

# Check missing values
print("\nMissing Values:")
print(df.isnull().sum())

# Fill missing values
df['Age'] = df['Age'].fillna(df['Age'].mean())
df['Embarked'] = df['Embarked'].fillna(df['Embarked'].mode()[0])

# Drop Cabin column
df.drop(columns=['Cabin'], inplace=True)

# Encode categorical columns
encoder = LabelEncoder()

df['Sex'] = encoder.fit_transform(df['Sex'])
df['Embarked'] = encoder.fit_transform(df['Embarked'])

# Standardize numerical columns
scaler = StandardScaler()

df[['Age', 'Fare']] = scaler.fit_transform(df[['Age', 'Fare']])

# Final cleaned data
print("\nCleaned Data:")
print(df.head())

# Boxplot
plt.figure(figsize=(8,5))
sns.boxplot(data=df[['Age', 'Fare']])
plt.title("Boxplot for Outliers")
plt.show()

print("\nTask completed successfully!")
```

First 5 Rows:

	PassengerId	Survived	Pclass	\
0	1	0	3	
1	2	1	1	
2	3	1	3	
3	4	1	1	
4	5	0	3	

	Name	Sex	Age	SibSp	\
0	Braund, Mr. Owen Harris	male	22.0	1	
1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	
2	Heikkinen, Miss. Laina	female	26.0	0	
3	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	
4	Allen, Mr. William Henry	male	35.0	0	

	Parch	Ticket	Fare	Cabin	Embarked
0	0	A/5 21171	7.2500	NaN	S
1	0	PC 17599	71.2833	C85	C
2	0	STON/O2. 3101282	7.9250	NaN	S
3	0	113803	53.1000	C123	S
4	0	373450	8.0500	NaN	S

Missing Values:

PassengerId	0
Survived	0
Pclass	0
Name	0
Sex	0
Age	177
SibSp	0
Parch	0
Ticket	0