Spec:
- **minReadySeconds**   <integer>
   Minimum number of seconds for which a newly created pod should be ready
   without any of its container crashing, for it to be considered available.
   Defaults to 0 (pod will be considered available as soon as it is ready)

- **paused**   <boolean>
   Indicates that the deployment is paused.

- **progressDeadlineSeconds**   <integer>
   The maximum time in seconds for a deployment to make progress before it is
   considered to be failed. The deployment controller will continue to process
   failed deployments and a condition with a ProgressDeadlineExceeded reason
   will be surfaced in the deployment status. Note that progress will not be
   estimated during the time a deployment is paused. Defaults to 600s.

- **replicas**   <integer>
   Number of desired pods. This is a pointer to distinguish between explicit
   zero and not specified. Defaults to 1.

- **revisionHistoryLimit** <integer>
   The number of old ReplicaSets to retain to allow rollback. This is a
   pointer to distinguish between explicit zero and not specified. Defaults to
   10.
- **selector**   <Object> -required-
   Label selector for pods. Existing ReplicaSets whose pods are selected by
   this will be the ones affected by this deployment. It must match the pod
   template's labels.
   • **matchExpressions**   <[]Object>
   matchExpressions is a list of label selector requirements. The requirements
   are ANDed.

   • **matchLabels** <map[string]string>
   matchLabels is a map of {key,value} pairs. A single {key,value} in the
   matchLabels map is equivalent to an element of matchExpressions, whose key
   field is "key", the operator is "In", and the values array contains only
   "value". The requirements are ANDed.

- **strategy**   <Object>
   The deployment strategy to use to replace existing pods with new ones.
   • **rollingUpdate**   <Object>
   Rolling update config params. Present only if DeploymentStrategyType =
   RollingUpdate.

   • **type** <string>
   Type of deployment. Can be "Recreate" or "RollingUpdate". Default is
   RollingUpdate.
- **template**   <Object> -required-
   Template describes the pods that will be created.