JOINT TELESEMINAR 2012

WebGL on Mobile Devices

William Weilgard Francis Almnes, *University of Oslo*Kent Andjic, *University of Oslo*Matthias Armbruster *University of Mannheim*and Paul Robert Ernst Steinhilber, *University of Mannheim*

Abstract—The abstract goes here, e.g. http://www.phdcomics.com/comics/archive.php?comicid=1121.

Index Terms—WebGL, mobile computing, teleseminar.

1 Introduction

The technologies which allow people to interact with the world around them evolve constantly. Whereas it was common to simply display information in a static form in the early days of the web, at present an ever increasing amount of content is presented in dynamic and interactive ways.

In the effort to expand internet browser functionality to natively support three-dimensional graphics, HTML5, WebGL have been developed. Many web sites already offer functionalities which were previously only found in native applications, e.g. word processing using Google Docs [1] or creating presentation using 280 Slides [2], thus narrowing "the gap between them" [3]. A native usage of 3d-functionality enhances these "web applications" even further.

"Augmented Reality (AR) has been defined broadly as combining real and computergenerated digital information into the users view of the physical and interactive real world in such a way that they appear as one environ-

- William W. F. Almnes: wwalmnes@student.matnat.uio.no
- Marko Andjic: marko.andjic@usit.uio.no
- Matthias Armbruster: marmbrus@rumms.uni-mannheim.de
- Paul R. E. Steinhilber: psteinhi@mail.uni-mannheim.de
- Daniel Schön: schoen@informatik.uni-mannheim (advisor)
 Submitted just before April 23, 2012.

ment, thus providing a bridge between digital information and the physical world" ([4], [5], [6], [7] via [8]). Application areas of AR can be as broad as ranging from health care [9] to education [10] to tourism [11]. The topic has gained momentum thanks to the rise in smartphone usage. "To make the world itself the user interface [...] may revolutionize the way information is accessed and presented to people in the future [4], [7].

The rise of smartphones is growing with a fast and still accelerating pace, enabled ways of displaying information in a new way in a truly mobile context to many people [12], [13]. They offer a much higher power than feature phones and even claim to offer the "real web" experience with "real browsers" [14]. There are differences, however, between the way information can be accessed from a desktop system and a mobile device, influenced by factors like screen size, processing power, and input methods.

3d-support on mobile devices is still in an early phase. Adobe abandoned Flash in late 2011 [15], leaving WebGL as the main (method) of providing interactive 3d content on the mobile web, even if it is still in an initial phase.

This paper analyzes the status quo and potentials of WebGL on mobile devices (regarding performance and human-computer-interaction.)

The paper is structured as follows: Chapter 2 gives background information on relevant topics, i.e. augmented reality, WebGL, and

JOINT TELESEMINAR 2012 2

human-computer-interation (HCI) with mobile devices and their evaluation criteria; Chapter 3 gives implementation details of the the WebGL environment used to capture the status quo; Chapter 4 presents the evaluation as well as limitations to this study; and Chapter 5 gives a summary of the results and presents future research opportunities.

2 BACKGROUND

2.1 WebGL

- 2.1.1 Design
- 2.1.2 Mobile WebGL
- 2.1.3 Status Quo
- 2.1.4 Evaluation criteria

2.2 Augmented Reality

- 2.2.1 History
- 2.2.2 Categories
- 2.2.3 Native apps and web applications
- 2.2.4 WebGL usage
- 2.2.5 Evaluation criteria

2.3 UI and UX Research

3 IMPLEMENTATION

http://www.phdcomics.com/comics/archive.php?comicid=1476.

4 EVALUATION

5 Conclusion

The conclusion goes here.

APPENDIX A

Appendix one text goes here.

APPENDIX B

Appendix two text goes here.

REFERENCES

- [1] (2012, March). [Online]. Available: https://docs.google.com
- [2] (2012, March). [Online]. Available: http://280slides.com/ Editor/
- [3] D. Golubovic, G. Miljkovic, S. Miucin, Z. Kaprocki, and V. Velisavljev, "Webgl implemenation in webkit based web browser on android platform," in *Telecommunications Forum (TELFOR)*, 2011, pp. 1139–1142.
- [4] T. Höllerer and S. Feiner, "Mobile augmented reality," in *Telegeoinformatics: Location-Based Computing and Services*. Taylor and Francis Books Ltd, 2004.
- [5] E. Klopfer and K. Squire, "Environmental detectives the development of an augmented reality platform for environmental simulations," Educational Technology Research and Development, vol. 56, no. 2, pp. 203–228, 2007.
- [6] J. Vallino, "Interactive augmented reality," Ph.D. dissertation, University of Rochester, 1998.
- [7] P. Wellner, W. Mackay, and R. Gold, "Back to the real world," *Communications of the ACM*, vol. 36, no. 7, pp. 24–26, 1993.
- [8] T. Olsson and K. Väänänen-Vainio-Mattila, "Expected user experience with mobile augmented reality services. workshop of mobile augmented reality," in *MobileHCI* 2011, 2011.
- [9] W. L. D. Lui, D. Browne, L. Kleeman, T. Drummond, and W. H. Li, "Transformative reality: Augmented reality for visual prostheses," in 10th IEEE International Symposium on Mixed and Augmented Reality (ISMAR), 2011.
- [10] F. Mannuß, J. Rubel, C. Wagner, F. Bingel, and A. Hinkenjann, "Augmenting magnet field lines for school experiments," in 10th IEEE International Symposium on Mixed and Augmented Reality (ISMAR), 2011.
- [11] A. Mulloni, H. Seichter, and D. Schmalstieg, "User experiences with augmented reality aided navigation on phones," in 10th IEEE International Symposium on Mixed and Augmented Reality (ISMAR), 2011.
- [12] (2012, March). [Online]. Available: http://www.mobilephonedevelopment.com/archives/1149
- [13] (2012, March). [Online]. Available: http://blog.nielsen. com/nielsenwire/?p=29786
- [14] S. Wellman. (2012, March). [Online]. Available: http://www.informationweek.com/blog/229215818
- [15] (2012, March). [Online]. Available: http://blogs.adobe.com/flashplatform/2011/11/ flash-to-focus-on-pc-browsing-and-mobile-apps-adobe-to-more-aggr html