



WEB & APPS

CONTENTS

▶ 1 • Drop it in	2
▶ 2 • Self-hosting the font	3
▶ 3 • Fields	4
▶ 4 • Tailwind	4
▶ 5 • Sass	5
▶ 6 • JS / design tokens	5
▶ 7 • Non-negotiables in code	5
▶ 8 • Charts	6
▶ 9 • Performance	6
▶ 10 • Checklist	7

SEC.01

1 • DROP IT IN

HTML

```
<link rel="stylesheet" href="https://ripostelabs.xyz/brand/riposte-brand.css">
```

Or vendor it – copy `../brand/riposte-brand.css` into the project. One file: tokens, a base layer, and every pattern class.

Minimum viable page:

HTML

```
<!doctype html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Thing · Riposte Laboratories</title>
  <link rel="stylesheet" href="/brand/riposte-brand.css">
</head>
<body>
  <header class="pagehead">
    <div class="inner">
      <div class="kicker">Riposte Laboratories</div>
      <h1>Thing</h1>
      <p>One sentence saying what it is and what it counters.</p>
    </div>
  </header>

  <main class="wrap section">
    <div class="sethead"><span class="no" aria-hidden="true">SEC.01</span>
      <h2>Overview</h2>
      <span class="tag" aria-hidden="true">// what this is</span></div>
    <p class="lead">The bold lead paragraph.</p>
    <p>Body copy. Bold the numbers that matter: <b>14.46 Wh</b>.</p>
  </main>

  <div class="checker" aria-hidden="true"></div>
```

```
<footer class="colophon">
  <div class="l">&copy; 2026 Riposte Laboratories Inc. &middot; All rights reserved.</div>
  <div class="r">parry &#9851; riposte &#9851; recycle &#9851; repeat</div>
</footer>
</body>
</html>
```

SEC. 02 2 • SELF-HOSTING THE FONT

The CDN `@import` at the top of the stylesheet is the zero-config path – fine for prototypes, artifacts and internal tools. For production, self-host: it’s faster, it works offline, and it doesn’t leak visitors to a third party.

The subsets are in `../assets/fonts/`. Copy them to `/fonts/`, delete the `@import` line, and use:

CSS

```
@font-face{font-family:"JetBrains Mono";font-style:normal;font-weight:400 800;font-display:swap;
  src:url(/fonts/jetbrains-mono-latin.woff2) format("woff2");
  unicode-range:U+0000-00FF,U+0131,U+0152-0153,U+02BB-02BC,U+02C6,U+02DA,U+02DC,
                U+0304,U+0308,U+0329,U+2000-206F,U+20AC,U+2122,U+2191,U+2193,
                U+2212,U+2215,U+FEFF,U+FFFD;}
```

Preload only the latin subset; the others fetch lazily via `unicode-range`. `crossorigin` is required even same-origin – fonts are always fetched in anonymous CORS mode, so omitting it causes a duplicate fetch:

HTML

```
<link rel="preload" href="/fonts/jetbrains-mono-latin.woff2" as="font" type="font/woff2" crossorigin>
```

SEC.03

3 • FIELDS

Any element can carry a field. They nest correctly.

HTML

```
<section data-theme="dark">    <!-- ink field: bone text, bone rules, teal accent -->
<section class="pinkfield">    <!-- full pink: everything bone, ink labels -->
<div data-theme="light">      <!-- bone island inside a dark subtree -->
```

Everything in the stylesheet reads semantic variables, so patterns invert for free. If a component doesn't invert, it's because it hardcoded `-ink` or `-pink` where it should have used `-text` or `-accent`.

System dark mode is not wired up by default – the brand's dark field is an editorial choice (a section that **should** be ink), not a user preference. If a product genuinely needs `prefers-color-scheme`, opt in explicitly:

CSS

```
@media (prefers-color-scheme: dark) { :root { /* copy the [data-theme="dark"] block */ } }
```

SEC.04

4 • TAILWIND

JS

```
// tailwind.config.js
module.exports = { presets: [require('./brand/tailwind.preset.js')] };
```

Gives you `bg-ink`, `text-bone`, `border-pink`, `shadow-pop`, `bg-triband`, `tracking-kicker`,

max-w-measure, duration-snap, and friends. The preset forces every borderRadius value to 0, so rounded-lg is a no-op – deliberately.

The preset covers tokens only. For patterns (.spec, .verdict, .colophon, the bands), load riposte-brand.css alongside it.

SEC.05

5 • SASS

SCSS

```
@use 'brand/tokens' as rl;
.thing { background: rl.$rl-bone; border: 2px solid rl.$rl-ink; }
```

SEC.06

6 • JS / DESIGN TOKENS

../brand/tokens.json is the source of truth – colour, type scale, spacing, tracking, effects, motion, logo geometry, glyphs, fixed strings. Feed it to Style Dictionary or import it directly. ../palettes/riposte.json is a flat name → hex map if that's all you need.

SEC.07

7 • NON-NEGOTIABLES IN CODE

CSS

```
/* radius */           border-radius: 0;           /* always */
/* structural rule */  border: 2px solid var(--line);
/* divider */         border-bottom: 1px dashed var(--line-dashed);
/* hover pop */        transform: translate(-2px,-2px); box-shadow: 4px 4px 0 var(--pink);
```

Never:

- ▶ a `border-radius` other than 0
- ▶ a `box-shadow` with a non-zero blur radius
- ▶ a second font family
- ▶ `rgba()` tints of an accent to fake a lighter shade
- ▶ a fourth accent colour

Body copy never sits on `-pink` or `-teal`. Those fills are 3.16:1 and 2.27:1 against bone. Use `-pink-deep` / `-teal-deep`, or put ink on marigold (8.12:1). See `../docs/07-accessibility.md` RL-BRAND-001-A11Y.

SEC.08

8 • CHARTS

Load the `dataviz` guidance, then substitute the Riposte palette. Categorical series in rotation: `pink` → `orange` → `teal` → `ink` → `bone-dim`. Beyond five, add the `-deep` variants; beyond eight, the chart is wrong – split it or use a table.

Flat fills, 2px borders, no gridlines, no gradients, no drop shadows. Direct-label where possible instead of relying on a legend, and never encode meaning in colour alone.

SEC.09

9 • PERFORMANCE

- ▶ One font family, three weights, `font-display: swap`
- ▶ No icon font – glyphs and inline SVG only
- ▶ No JS required for anything visual; the marquee is CSS
- ▶ The whole stylesheet is a single file with no build step
- ▶ `@media (prefers-reduced-motion: reduce)` is already handled

SEC.10

10 • CHECKLIST

- ☐ `riposte-brand.css` linked or vendored
- ☐ Font self-hosted (production) and latin subset preloaded with `crossorigin`
- ☐ `footer.colophon` present
- ☐ Decorative bands `aria-hidden="true"`
- ☐ SEC.NN chips and corner marks `aria-hidden="true"`
- ☐ Uppercase via `text-transform`, not typed
- ☐ `node scripts/build.js --check` passes if tokens were touched

SOURCE `tools/web.md` SHA `930ca59b5d6c` BUILT 2026-08-15