MLOPS Platform

(Curated for DadmaTech Co.)

API Documentation

Green codes are mandatory, and Blue codes are optional

Model Registry

Scenario 1: Adding a model to the model registry

From S3

```
curl -X 'POST' \
  'http://mlopsapipilot.aip.sharif.ir/models/add_model' \
  -H 'accept: application/json' \
  -H 'Authorization: Bearer ${AUTH_TOKEN}' \
  -H 'Content-Type: application/json' \
  -d '{
  "source_type": "s3",
  "model_name": "myqwen",
  "source_path": "Qwen/Qwen3-0.6B",
  "category": "Text Generation" # or "Image Classification",
  "source_s3": {
    "endpoint_url": "<ENDPOINT_URL>",
    "access_key": "<ACCESS_KEY>",
    "secret_key": "<SECRET_KEY>",
    "bucket_name": "<BUCKET_NAME>"
  },
  "code_path": "",
  "version": "my_ver",
  "tags": []
}'
```

Scenario 2: Check the progress of models to be added and get the ID of the added model

```
curl -X 'GET' \
'http://mlopsapipilot.aip.sharif.ir/models/task/42a6537f-bb08-413e-9a
3e-9b841df051a6/progress' \
```

```
  -H 'accept: application/json' \
  -H 'Authorization: Bearer ${AUTH_TOKEN}'
```

Scenario 3: List user models

```
curl -X 'POST' \
  'http://mlopsapipilot.aip.sharif.ir/models/models' \
  -H 'accept: application/json' \
  -H 'Authorization: Bearer ${AUTH_TOKEN}' \
  -H 'Content-Type: application/json' \
  -d '{
  "verbose": false
}'
```

Scenario 4: Delete a model

You can delete a model using this api. Also, if you intend to delete only a specific version of the model, provide the version in the payload.

```
curl -X 'DELETE' \
  'http://mlopsapipilot.aip.sharif.ir/models/model' \
  -H 'accept: application/json' \
  -H 'Authorization: Bearer ${AUTH_TOKEN}' \
  -H 'Content-Type: application/json' \
  -d '{
  "model_name": "myqwen",
  "version": "my_ver"
}'
```

Scenario 5: List model categories

You can list the categories for registered models

```
curl -X 'GET' \
  'https://mlopsapipilot.aip.sharif.ir/models/categories' \
  -H 'accept: application/json' \
```

```
  -H 'Authorization: Bearer ${AUTH_TOKEN}' \
  -H 'Content-Type: application/json'
```

Scenario 6: List model ingestion tasks
You can see the list of ingestion tasks done by the user.

```
curl -X 'GET' \
  'https://mlopsapipilot.aip.sharif.ir/models/tasks' \
    -H 'accept: application/json' \
  -H 'Authorization: Bearer ${AUTH_TOKEN}' \
  -H 'Content-Type: application/json'
```

Data Ingestion

Scenario 1: Add a general dataset (without restructuring it):

For S3:

```
curl -X 'POST' \
  'http://mlopsapipilot.aip.sharif.ir/data/s3' \
  -H 'accept: application/json'   \
  -H 'Authorization: Bearer ${AUTH_TOKEN}' \
  -H 'Content-Type: application/json' \
  -d '{
  "s3_file_path": "Your S3 file path (in your own S3 bucket)",
  "dataset_name": "dataset_name",
  "private": false,
  "dataset_type": "text_generation", #["text_generation"
,"image_classification" ,"general"]

  "s3_source": {
    "access_key": "your s3 credentials",
    "secret_key": "your s3 credentials",
    "endpoint_url": "your s3 credentials",
    "bucket_name": "your s3 credentials"
  },
  "restructure": false # set false for your already prepared parquet
files.
}'
```

Scenario 2: View the status of the specific ingestion task:

```
curl -X 'POST' \
  'http://mlopsapipilot.aip.sharif.ir/data/task-status' \
  -H 'accept: application/json' \
  -H 'Authorization: Bearer ${AUTH_TOKEN}' \
  -H 'Content-Type: application/json'
  -d '{
  "task_id": "{task_id}"
}'
```

Scenario 3: View the console log of the specific ingestion task:

```
      curl -X 'POST' \
        'http://mlopsapipilot.aip.sharif.ir/data/task-report' \
        -H 'accept: application/json' \
        -H 'Authorization: Bearer ${AUTH_TOKEN}' \
        -H 'Content-Type: application/json'
        -d '{
        "task_id": "{task_id}",
      “log_lines”: 100
}'
```

Scenario 4: View all user tasks:

```
curl -X 'POST' \
        'http://mlopsapipilot.aip.sharif.ir/data/tasks' \
        -H 'accept: application/json'  \
        -H 'Authorization: Bearer ${AUTH_TOKEN}' \
        -H 'Content-Type: application/json'
        -d '{
        "limit": 50 –->The number of tasks shown in the response.
      }'
```

Scenario 5: View all user datasets

```
      curl -X 'POST' \
        'http://mlopsapipilot.aip.sharif.ir/data/list-datasets' \
        -H 'accept: application/json' \
        -H 'Authorization: Bearer ${AUTH_TOKEN}' \
        -H 'Content-Type: application/json'
        -d '{}'
```

Scenario 6: Download a specific dataset with the user-requested version :

```
curl -X 'POST' \
  'http://mlopsapipilot.aip.sharif.ir/data/download-dataset'
  -H 'accept: application/json' \
  -H 'Authorization: Bearer  ${AUTH_TOKEN}' \
  -H 'Content-Type: application/json' \
  -d '{
  "dataset_name": "{dataset_name}",
  "download_method": "presigned_urls",
  "expiration": 3600,
  "version": "latest"
}'
```

Training

Scenario 1: Custom repository training

Note that the git repo should be from the user GitLab in AIP.

```
curl -X POST mlopsapipilot.aip.sharif.ir/trainer/task/start \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer <User Auth>" \
  -d '{
    "repo_url":
"https://<GIT_USERNAME>:<GIT_TOKEN>@gitpilot.aip.sharif.ir/user/somegit.git",
    "entry_point": "<ENTRY_POINT>"
  }'
```

Scenario 2: Finetune LLM with standard script

```
curl -X POST mlopsapipilot.aip.sharif.ir/trainer/preset \
-H "Content-Type: application/json" \
  -H "Authorization: Bearer <User Auth>" \
  -d '{
    "config": {
      "task": "llm_finetuning",
      "model_name": "<model registry name>",
      "model": { "load_model": "True", "save_model": "True" },
      "dataset_name": "<dataset name>",
      "train": {
        "batchsize": 4,
        "epochs": 20,
        "lr": 0.02,
        "system_prompt": "<system prompt>"
      }
    }
  }'
```

Scenario 3: Custom repository training with hyperparameters

The “General” keyword in the payload is fixed and required and is there for planned future updates.

```
curl -X POST mlopsapipilot.aip.sharif.ir/trainer/task/start \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer <User Auth>" \
  -d '{
    "repo_url":
"https://<GIT_USERNAME>:<GIT_TOKEN>@gitpilot.aip.sharif.ir/user/somegit.git",
    "entry_point": "<ENTRY_POINT>",
"hyperparams": {
    "General": {
      "epochs":        { "section": "General", "name": "epochs",
"value": "5" },
      "learning_rate": { "section": "General", "name": "learning_rate",
"value": "0.0005" }
    }
  }
  }'
```

Scenario 4: User wants to see the logs of their training

```
curl -X POST mlopsapipilot.aip.sharif.ir/trainer/task/log \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer <User Auth>" \
  -d '{
    "task_id": "<task id>",
    "type": "log"
  }'
```