


Understanding real-world scenes for human-like machine perception

Armin Mustafa and Adrian Hilton,
{a.mustafa}@surrey.ac.uk , Website: <https://arminmustafa.github.io/>

MOTIVATION

The rise of autonomous machines has led to an increasing demand for machine perception of real-world to be more human-like. Existing machine perception methods suffer from following limitations:


1. Limited to controlled environments such as indoor, static and rigid objects;
2. No temporal coherence pose major challenges.




CONTRIBUTIONS

1. Method to estimate scene flow, 4D mesh and 2D semantic video segmentation from multi-view videos.
2. Joint semantic scene flow, co-segmentation, and reconstruction of dynamic objects for general scenes.
3. Semantic tracklets for long-term 4D reconstruction by enforcing spatial and temporal coherence in semantic labelling for improved scene ow of video across wide-timeframes.
4. Improved flow, segmentation, and reconstruction of dynamic scenes from multiple moving cameras.

METHODOLOGY



Joint semantic segmentation, reconstruction and flow framework.




$$E(l, d, m) = \delta E_{\text{semantic}}(l, d) + \alpha E_{\text{data}}(d) + \gamma E_{\text{smooth}}(d) + \beta E_{\text{motion}}(m) + \eta E_{\text{contrast}}(l, d) + \gamma E_{\text{color}}(l)$$


ACKNOWLEDGEMENTS

This research was supported by the Royal Academy of Engineering Research Fellowship RF-201718-17177, and the EPSRC Platform Grant on Audio-Visual Media Research EP/P022529.

RESULTS



Comparison of segmentation on public datasets against state-of-the-art methods: TcMVS [1], CRF-RNN [2] and SCV [3]. Green and Red regions represent errors.



Temporal and semantic coherence results using proposed approach on multiple datasets. Comparison is shown with 4DMatch [4], Deepflow [5] and Simpleflow [6].

REFERENCES

1. Mustafa, A., Kim, H., Guillemot, J.Y., Hilton, A.: Temporally coherent 4d reconstruction of complex dynamic scenes. In: The IEEE Conference on Computer Vision and Pattern Recognition (CVPR) (2016)
2. Tsai, Y.H., G.Zhong, Yang, M.H.: Semantic cosegmentation in videos. In: European Conference on Computer Vision (ECCV), pp. 760(775) (2016).
3. Zheng, S., Jayasumana, S., Romera-Paredes, B., Vineet, V., Su, Z., Du, D., Huang, C., Torr, P.: Conditional random fields as recurrent neural networks. In: The IEEE International Conference on Computer Vision (ICCV) (2015).
4. Mustafa, A., Kim, H., Hilton, A.: 4d match trees for nonrigid surface alignment. In: European Conference on Computer Vision (ECCV) (2016)
5. Weinzaepfel, P., Revaud, J., Harchaoui, Z., Schmid, C.: Deepflow: Large displacement optical ow with deep matching. In: The IEEE International Conference on Computer Vision (ICCV), pp. 1385(1392) (2013)
6. Tao, M.W., Bai, J., Kohli, P., Paris, S.: Simpleflow: A non-iterative, sublinear optical ow algorithm. Eurographics 2012