

# Unicode declarations for L<sup>A</sup>T<sub>E</sub>X documents.

Mark Armstrong

May 25, 2020

## Contents

<b>1</b>	<b>About this file</b>	<b>2</b>
1.1	Usage . . . . .	2
1.2	Required L <sup>A</sup> T <sub>E</sub> X packages . . . . .	3
1.3	Contributing to this document . . . . .	4
1.4	The Emacs Lisp script . . . . .	4
1.5	Sample symbols . . . . .	4
<b>2</b>	<b>Blackboard, Calligraphic, and Bold-font</b>	<b>4</b>
2.1	Blackboard . . . . .	4
2.1.1	Lowercase Latin . . . . .	4
2.1.2	Uppercase Latin . . . . .	7
2.1.3	Arabic Numerals . . . . .	7
2.1.4	Greek . . . . .	8
2.2	Calligraphic . . . . .	9
2.2.1	Lowercase Latin . . . . .	9
2.2.2	Uppercase Latin . . . . .	12
2.3	Bold-font . . . . .	12
2.3.1	Lowercase Latin . . . . .	12
2.3.2	Uppercase Latin . . . . .	13
2.4	<b>B</b> old <b>C</b> alligraphic . . . . .	13
2.4.1	Lowercase Latin . . . . .	13
2.4.2	Uppercase Latin . . . . .	14
<b>3</b>	<b>Other letters or letterlike symbols</b>	<b>15</b>
<b>4</b>	<b>Greek alphabet</b>	<b>15</b>
4.1	Normal . . . . .	15
4.2	var-variants INCOMPLETE . . . . .	17
<b>5</b>	<b>Sub-, Super-, Under-, and Over-scripts</b>	<b>17</b>
5.1	Subscripts . . . . .	17
5.1.1	Lowercase alphabet . . . . .	17
5.1.2	Numeric . . . . .	17
5.1.3	Other . . . . .	18
5.2	Superscripts . . . . .	18
5.2.1	Uppercase alphabet . . . . .	18
5.2.2	Lowercase alphabet . . . . .	18
5.2.3	Numeric . . . . .	19
5.2.4	Other . . . . .	19

<b>6</b>	<b>Punctuation and Delimiters</b>	<b>19</b>
6.1	Dots . . . . .	19
6.2	Dashes . . . . .	19
6.3	Parentheses, braces and brackets . . . . .	19
6.4	Other paired delimiters . . . . .	20
6.5	Whitespace . . . . .	20
<b>7</b>	<b>Logic</b>	<b>20</b>
7.1	Prepositional . . . . .	20
7.2	Predicate . . . . .	20
7.3	Model —Entailment . . . . .	21
<b>8</b>	<b>Sets, relations and functions</b>	<b>21</b>
8.1	Sets . . . . .	21
8.2	Relation operators . . . . .	21
8.3	Function operators . . . . .	21
8.4	Relations . . . . .	21
8.4.1	Equality like . . . . .	21
8.4.2	Order like . . . . .	22
<b>9</b>	<b>Generic or other operators</b>	<b>22</b>
9.1	Arrows . . . . .	22
9.2	“o”-operators . . . . .	22
9.3	Punctuation-like . . . . .	23
9.4	Others . . . . .	23
<b>10</b>	<b>Check- &amp; X-marks, and Primes &amp; Ticks</b>	<b>23</b>

# 1 About this file

In order to write L<sup>A</sup>T<sub>E</sub>X documents using unicode in the source code, we must often tell L<sup>A</sup>T<sub>E</sub>X what we want the unicode characters to be rendered as.

There are at least two ways to inform L<sup>A</sup>T<sub>E</sub>X of unicode character translations;

- `\DeclareUnicodeCharacter`; this command does not work with XeLaTeX or LuaLaTeX, which I use.
- `\newunicodechar`; this command is provided by the `newunicodechar` package, which may not be pre-installed for all L<sup>A</sup>T<sub>E</sub>X users.

This collection uses the second.

## 1.1 Usage

This file generates (via Org Babel tangling) the file `unicode.sty`.

To use it, either place it in the same directory as your `.tex` file, and require it via `\usepackage{unicode}`.

Alternatively, place it in your `texmf` directory to allow global usage on your system. That directory is commonly located at the following locations on various OS’s.

- Linux
  - `~/texmf/tex/latex/local/`
- Mac OS X
  - `/Users/<user name>/Library/texmf/tex/latex/local/`

- Windows 10 (and miktex)
  - C:\Users\<user name>\Appdata\Local\MikTeX\<number>\tex\latex\local\
- Windows Vista/7
  - C:\Users\<user name>\texmf\tex\latex\local\
- Windows XP
  - C:\Documents and Settings\<user name>\texmf\tex\latex\local\

By default, we assume the standard `pdflatex` typesetting engine is used, if you are using XeLaTeX or LuaLaTeX, then simply declare:

```
\pdflatexfalse
```

## 1.2 Required L<sup>A</sup>T<sub>E</sub>X packages

Of course we require the `newunicodechar` package to use that command.

```
\usepackage{newunicodechar}
```

```
\usepackage{ifxetex, ifluatex} % Also used in agda.sty: xifthen
```

```
% https://tex.stackexchange.com/questions/47576/combining-ifxetex-and-ifluatex-with-the-logical-or-op
```

```
\newif\ifpdflatex
```

```
\ifxetex
```

```
  \pdflatexfalse
```

```
\else
```

```
  \ifluatex
```

```
    \pdflatexfalse
```

```
  \else
```

```
    \pdflatextrue
```

```
  \fi
```

```
\fi
```

```
%\newif\ifpdflatex
```

```
%\pdflatextrue
```

```
%% To use other typesetting engines, declare the following:
```

```
%% \pdflatexfalse
```

The `unicode-math` package “provides a complete implementation of unicode maths for XeLaTeX and LuaLaTeX”.

```
\ifpdflatex
```

```
  \usepackage{pifont}
```

```
  \usepackage{stmaryrd}
```

```
  \usepackage{amsmath, amssymb, amsthm, latexsym, amscd, enumerate, bbm, etex, nicefrac, mathrsfs}
```

```
\else
```

```
  \usepackage{unicode-math}
```

```
\fi
```

### 1.3 Contributing to this document

This document is written in Emacs using Org mode. While the exported PDF version, etc., show a collection of L<sup>A</sup>T<sub>E</sub>X source blocks, these are in fact generated by an Emacs Lisp script below.

That means that contributions to this document should modify the Emacs Lisp script, not `unicode.sty` or the `LATEX` source blocks themselves.

## 1.4 The Emacs Lisp script

In this document, several lists of unicode character, L<sup>A</sup>T<sub>E</sub>X translation pairs are declared, and then “wrapped” into `latex` source blocks, using this function to map the pairs into `newunicodechar` declarations.

## 1.5 Sample symbols

[illegible]

## 2 Blackboard, Calligraphic, and Bold-font

These lists are most likely complete, unless I have missed some characters aside from Latin letters, Greek letters and Arabic numerals which should be included.

For Agda users, the unicode symbols may be entered using the following sequences:

Blackboard	<code>\b</code> <i>x</i>
Calligraphic	<code>\M</code> <i>c</i> <i>x</i>
Bold-font	<code>\M</code> <b><i>I</i></b> <i>x</i>
Bold Calligraphic	<code>\M</code> <b><i>C</i></b> <i>x</i>

$$\backslash\text{DeclareMathAlphabet}\backslash\text{mathbfcal}\{\text{OMS}\}\{\text{cmsy}\}\{\text{b}\}\{\text{n}\}$$

## 2.1 Blackboard

### 2.1.1 Lowercase Latin

```

\ifpdflatex
  \newunicodechar{a}{\ensuremath{\mathbbm{a}}}
\else
  \newunicodechar{a}{\ensuremath{\mathbb{a}}}
\fi
\ifpdflatex
  \newunicodechar{b}{\ensuremath{\mathbbm{b}}}
\else
  \newunicodechar{b}{\ensuremath{\mathbb{b}}}
\fi
\ifpdflatex

```

```

\newunicodechar{c}{\ensuremath{\mathbbm{c}}}
\else
\newunicodechar{c}{\ensuremath{\mathbb{c}}}
\fi
\ifpdflatex
\newunicodechar{d}{\ensuremath{\mathbbm{d}}}
\else
\newunicodechar{d}{\ensuremath{\mathbb{d}}}
\fi
\ifpdflatex
\newunicodechar{e}{\ensuremath{\mathbbm{e}}}
\else
\newunicodechar{e}{\ensuremath{\mathbb{e}}}
\fi
\ifpdflatex
\newunicodechar{f}{\ensuremath{\mathbbm{f}}}
\else
\newunicodechar{f}{\ensuremath{\mathbb{f}}}
\fi
\ifpdflatex
\newunicodechar{g}{\ensuremath{\mathbbm{g}}}
\else
\newunicodechar{g}{\ensuremath{\mathbb{g}}}
\fi
\ifpdflatex
\newunicodechar{h}{\ensuremath{\mathbbm{h}}}
\else
\newunicodechar{h}{\ensuremath{\mathbb{h}}}
\fi
\ifpdflatex
\newunicodechar{i}{\ensuremath{\mathbbm{i}}}
\else
\newunicodechar{i}{\ensuremath{\mathbb{i}}}
\fi
\ifpdflatex
\newunicodechar{j}{\ensuremath{\mathbbm{j}}}
\else
\newunicodechar{j}{\ensuremath{\mathbb{j}}}
\fi
\ifpdflatex
\newunicodechar{k}{\ensuremath{\mathbbm{k}}}
\else
\newunicodechar{k}{\ensuremath{\mathbb{k}}}
\fi
\ifpdflatex
\newunicodechar{l}{\ensuremath{\mathbbm{l}}}
\else
\newunicodechar{l}{\ensuremath{\mathbb{l}}}
\fi
\ifpdflatex
\newunicodechar{m}{\ensuremath{\mathbbm{m}}}
\else

```

```

\newunicodechar{m}{\ensuremath{\mathbb{m}}}
\fi
\ifpdflatex
\newunicodechar{n}{\ensuremath{\mathbb{m}{n}}}
\else
\newunicodechar{n}{\ensuremath{\mathbb{n}}}}
\fi
\ifpdflatex
\newunicodechar{o}{\ensuremath{\mathbb{m}{o}}}
\else
\newunicodechar{o}{\ensuremath{\mathbb{o}}}}
\fi
\ifpdflatex
\newunicodechar{p}{\ensuremath{\mathbb{m}{p}}}
\else
\newunicodechar{p}{\ensuremath{\mathbb{p}}}}
\fi
\ifpdflatex
\newunicodechar{q}{\ensuremath{\mathbb{m}{q}}}
\else
\newunicodechar{q}{\ensuremath{\mathbb{q}}}}
\fi
\ifpdflatex
\newunicodechar{r}{\ensuremath{\mathbb{m}{r}}}
\else
\newunicodechar{r}{\ensuremath{\mathbb{r}}}}
\fi
\ifpdflatex
\newunicodechar{s}{\ensuremath{\mathbb{m}{s}}}
\else
\newunicodechar{s}{\ensuremath{\mathbb{s}}}}
\fi
\ifpdflatex
\newunicodechar{t}{\ensuremath{\mathbb{m}{t}}}
\else
\newunicodechar{t}{\ensuremath{\mathbb{t}}}}
\fi
\ifpdflatex
\newunicodechar{u}{\ensuremath{\mathbb{m}{u}}}
\else
\newunicodechar{u}{\ensuremath{\mathbb{u}}}}
\fi
\ifpdflatex
\newunicodechar{v}{\ensuremath{\mathbb{m}{v}}}
\else
\newunicodechar{v}{\ensuremath{\mathbb{v}}}}
\fi
\ifpdflatex
\newunicodechar{w}{\ensuremath{\mathbb{m}{w}}}
\else
\newunicodechar{w}{\ensuremath{\mathbb{w}}}}
\fi

```

```

\ifpdflatex
  \newunicodechar{x}{\ensuremath{\mathbbm{x}}}
\else
  \newunicodechar{x}{\ensuremath{\mathbb{x}}}
\fi
\ifpdflatex
  \newunicodechar{y}{\ensuremath{\mathbbm{y}}}
\else
  \newunicodechar{y}{\ensuremath{\mathbb{y}}}
\fi
\ifpdflatex
  \newunicodechar{z}{\ensuremath{\mathbbm{z}}}
\else
  \newunicodechar{z}{\ensuremath{\mathbb{z}}}
\fi

```

### 2.1.2 Uppercase Latin

```

\newunicodechar{A}{\ensuremath{\mathbb{A}}}
\newunicodechar{B}{\ensuremath{\mathbb{B}}}
\newunicodechar{C}{\ensuremath{\mathbb{C}}}
\newunicodechar{D}{\ensuremath{\mathbb{D}}}
\newunicodechar{E}{\ensuremath{\mathbb{E}}}
\newunicodechar{F}{\ensuremath{\mathbb{F}}}
\newunicodechar{G}{\ensuremath{\mathbb{G}}}
\newunicodechar{H}{\ensuremath{\mathbb{H}}}
\newunicodechar{I}{\ensuremath{\mathbb{I}}}
\newunicodechar{J}{\ensuremath{\mathbb{J}}}
\newunicodechar{K}{\ensuremath{\mathbb{K}}}
\newunicodechar{L}{\ensuremath{\mathbb{L}}}
\newunicodechar{M}{\ensuremath{\mathbb{M}}}
\newunicodechar{N}{\ensuremath{\mathbb{N}}}
\newunicodechar{O}{\ensuremath{\mathbb{O}}}
\newunicodechar{P}{\ensuremath{\mathbb{P}}}
\newunicodechar{Q}{\ensuremath{\mathbb{Q}}}
\newunicodechar{R}{\ensuremath{\mathbb{R}}}
\newunicodechar{S}{\ensuremath{\mathbb{S}}}
\newunicodechar{T}{\ensuremath{\mathbb{T}}}
\newunicodechar{U}{\ensuremath{\mathbb{U}}}
\newunicodechar{V}{\ensuremath{\mathbb{V}}}
\newunicodechar{W}{\ensuremath{\mathbb{W}}}
\newunicodechar{X}{\ensuremath{\mathbb{X}}}
\newunicodechar{Y}{\ensuremath{\mathbb{Y}}}
\newunicodechar{Z}{\ensuremath{\mathbb{Z}}}

```

### 2.1.3 Arabic Numerals

```

% For double stroke digits with pdflatex
\usepackage[bbgreek1]{mathbbol}
\DeclareSymbolFontAlphabet{\mathbbl}{bbold}

\ifpdflatex
  \newunicodechar{1}{\ensuremath{\mathbbl{1}}}

```

```

\else
  \newunicodechar{1}{\ensuremath{\mathbb{1}}}
\fi
\ifpdflatex
  \newunicodechar{2}{\ensuremath{\mathbb{1}{2}}}
\else
  \newunicodechar{2}{\ensuremath{\mathbb{2}}}
\fi
\ifpdflatex
  \newunicodechar{3}{\ensuremath{\mathbb{1}{3}}}
\else
  \newunicodechar{3}{\ensuremath{\mathbb{3}}}
\fi
\ifpdflatex
  \newunicodechar{4}{\ensuremath{\mathbb{1}{4}}}
\else
  \newunicodechar{4}{\ensuremath{\mathbb{4}}}
\fi
\ifpdflatex
  \newunicodechar{5}{\ensuremath{\mathbb{1}{5}}}
\else
  \newunicodechar{5}{\ensuremath{\mathbb{5}}}
\fi
\ifpdflatex
  \newunicodechar{6}{\ensuremath{\mathbb{1}{6}}}
\else
  \newunicodechar{6}{\ensuremath{\mathbb{6}}}
\fi
\ifpdflatex
  \newunicodechar{7}{\ensuremath{\mathbb{1}{7}}}
\else
  \newunicodechar{7}{\ensuremath{\mathbb{7}}}
\fi
\ifpdflatex
  \newunicodechar{8}{\ensuremath{\mathbb{1}{8}}}
\else
  \newunicodechar{8}{\ensuremath{\mathbb{8}}}
\fi
\ifpdflatex
  \newunicodechar{9}{\ensuremath{\mathbb{1}{9}}}
\else
  \newunicodechar{9}{\ensuremath{\mathbb{9}}}
\fi
\ifpdflatex
  \newunicodechar{0}{\ensuremath{\mathbb{1}{0}}}
\else
  \newunicodechar{0}{\ensuremath{\mathbb{0}}}
\fi

```

#### 2.1.4 Greek

There are unfortunately not many included in Unicode.



```

\ifpdflatex
  \newunicodechar{TODO}{\ensuremath{TODO}}
\else
  \newunicodechar{TODO}{\ensuremath{\mathbb{\Gamma}}}}
\fi
\ifpdflatex
  \newunicodechar{TODO}{\ensuremath{TODO}}
\else
  \newunicodechar{TODO}{\ensuremath{\mathbb{\gamma}}}}
\fi
\ifpdflatex
  \newunicodechar{TODO}{\ensuremath{TODO}}
\else
  \newunicodechar{TODO}{\ensuremath{\mathbb{\Pi}}}}
\fi
\ifpdflatex
  \newunicodechar{TODO}{\ensuremath{TODO}}
\else
  \newunicodechar{TODO}{\ensuremath{\mathbb{\pi}}}}
\fi
\ifpdflatex
  \newunicodechar{TODO}{\ensuremath{TODO}}
\else
  \newunicodechar{TODO}{\ensuremath{\mathbb{\Sigma}}}}
\fi

```

## 2.2 Calligraphic

### 2.2.1 Lowercase Latin

```

\ifpdflatex
  \newunicodechar{a}{\ensuremath{a}}
\else
  \newunicodechar{a}{\ensuremath{\mathcal{a}}}}
\fi
\ifpdflatex
  \newunicodechar{b}{\ensuremath{b}}
\else
  \newunicodechar{b}{\ensuremath{\mathcal{b}}}}
\fi
\ifpdflatex
  \newunicodechar{c}{\ensuremath{c}}
\else
  \newunicodechar{c}{\ensuremath{\mathcal{c}}}}
\fi
\ifpdflatex
  \newunicodechar{d}{\ensuremath{d}}
\else
  \newunicodechar{d}{\ensuremath{\mathcal{d}}}}
\fi
\ifpdflatex
  \newunicodechar{e}{\ensuremath{e}}
\else

```

```

\newunicodechar{e}{\ensuremath{\mathcal{e}}}
\fi
\ifpdflatex
\newunicodechar{f}{\ensuremath{f}}
\else
\newunicodechar{f}{\ensuremath{\mathcal{f}}}
\fi
\ifpdflatex
\newunicodechar{g}{\ensuremath{g}}
\else
\newunicodechar{g}{\ensuremath{\mathcal{g}}}
\fi
\ifpdflatex
\newunicodechar{h}{\ensuremath{h}}
\else
\newunicodechar{h}{\ensuremath{\mathcal{h}}}
\fi
\ifpdflatex
\newunicodechar{i}{\ensuremath{i}}
\else
\newunicodechar{i}{\ensuremath{\mathcal{i}}}
\fi
\ifpdflatex
\newunicodechar{j}{\ensuremath{j}}
\else
\newunicodechar{j}{\ensuremath{\mathcal{j}}}
\fi
\ifpdflatex
\newunicodechar{j}{\ensuremath{j}}
\else
\newunicodechar{j}{\ensuremath{\mathcal{k}}}
\fi
\ifpdflatex
\newunicodechar{l}{\ensuremath{l}}
\else
\newunicodechar{l}{\ensuremath{\mathcal{l}}}
\fi
\ifpdflatex
\newunicodechar{m}{\ensuremath{m}}
\else
\newunicodechar{m}{\ensuremath{\mathcal{m}}}
\fi
\ifpdflatex
\newunicodechar{n}{\ensuremath{n}}
\else
\newunicodechar{n}{\ensuremath{\mathcal{n}}}
\fi
\ifpdflatex
\newunicodechar{o}{\ensuremath{o}}
\else
\newunicodechar{o}{\ensuremath{\mathcal{o}}}
\fi

```

```

\ifpdflatex
  \newunicodechar{p}{\ensuremath{p}}
\else
  \newunicodechar{p}{\ensuremath{\mathcal{p}}}
\fi
\ifpdflatex
  \newunicodechar{q}{\ensuremath{q}}
\else
  \newunicodechar{q}{\ensuremath{\mathcal{q}}}
\fi
\ifpdflatex
  \newunicodechar{r}{\ensuremath{r}}
\else
  \newunicodechar{r}{\ensuremath{\mathcal{r}}}
\fi
\ifpdflatex
  \newunicodechar{s}{\ensuremath{s}}
\else
  \newunicodechar{s}{\ensuremath{\mathcal{s}}}
\fi
\ifpdflatex
  \newunicodechar{t}{\ensuremath{t}}
\else
  \newunicodechar{t}{\ensuremath{\mathcal{t}}}
\fi
\ifpdflatex
  \newunicodechar{u}{\ensuremath{u}}
\else
  \newunicodechar{u}{\ensuremath{\mathcal{u}}}
\fi
\ifpdflatex
  \newunicodechar{v}{\ensuremath{v}}
\else
  \newunicodechar{v}{\ensuremath{\mathcal{v}}}
\fi
\ifpdflatex
  \newunicodechar{w}{\ensuremath{w}}
\else
  \newunicodechar{w}{\ensuremath{\mathcal{w}}}
\fi
\ifpdflatex
  \newunicodechar{x}{\ensuremath{x}}
\else
  \newunicodechar{x}{\ensuremath{\mathcal{x}}}
\fi
\ifpdflatex
  \newunicodechar{y}{\ensuremath{y}}
\else
  \newunicodechar{y}{\ensuremath{\mathcal{y}}}
\fi
\ifpdflatex
  \newunicodechar{z}{\ensuremath{z}}

```

```

\else
  \newunicodechar{z}{\ensuremath{\mathcal{z}}}
\fi

```

## 2.2.2 Uppercase Latin

```

\newunicodechar{A}{\ensuremath{\mathcal{A}}}
\newunicodechar{B}{\ensuremath{\mathcal{B}}}
\newunicodechar{C}{\ensuremath{\mathcal{C}}}
\newunicodechar{D}{\ensuremath{\mathcal{D}}}
\newunicodechar{E}{\ensuremath{\mathcal{E}}}
\newunicodechar{F}{\ensuremath{\mathcal{F}}}
\newunicodechar{G}{\ensuremath{\mathcal{G}}}
\newunicodechar{H}{\ensuremath{\mathcal{H}}}
\newunicodechar{I}{\ensuremath{\mathcal{I}}}
\newunicodechar{J}{\ensuremath{\mathcal{J}}}
\newunicodechar{K}{\ensuremath{\mathcal{K}}}
\newunicodechar{L}{\ensuremath{\mathcal{L}}}
\newunicodechar{M}{\ensuremath{\mathcal{M}}}
\newunicodechar{N}{\ensuremath{\mathcal{N}}}
\newunicodechar{O}{\ensuremath{\mathcal{O}}}
\newunicodechar{P}{\ensuremath{\mathcal{P}}}
\newunicodechar{Q}{\ensuremath{\mathcal{Q}}}
\newunicodechar{R}{\ensuremath{\mathcal{R}}}
\newunicodechar{S}{\ensuremath{\mathcal{S}}}
\newunicodechar{T}{\ensuremath{\mathcal{T}}}
\newunicodechar{U}{\ensuremath{\mathcal{U}}}
\newunicodechar{V}{\ensuremath{\mathcal{V}}}
\newunicodechar{W}{\ensuremath{\mathcal{W}}}
\newunicodechar{X}{\ensuremath{\mathcal{X}}}
\newunicodechar{Y}{\ensuremath{\mathcal{Y}}}
\newunicodechar{Z}{\ensuremath{\mathcal{Z}}}

```

## 2.3 Bold-font

### 2.3.1 Lowercase Latin

```

\newunicodechar{a}{\ensuremath{\mathbf{a}}}
\newunicodechar{b}{\ensuremath{\mathbf{b}}}
\newunicodechar{c}{\ensuremath{\mathbf{c}}}
\newunicodechar{d}{\ensuremath{\mathbf{d}}}
\newunicodechar{e}{\ensuremath{\mathbf{e}}}
\newunicodechar{f}{\ensuremath{\mathbf{f}}}
\newunicodechar{g}{\ensuremath{\mathbf{g}}}
\newunicodechar{h}{\ensuremath{\mathbf{h}}}
\newunicodechar{i}{\ensuremath{\mathbf{i}}}
\newunicodechar{j}{\ensuremath{\mathbf{j}}}
\newunicodechar{k}{\ensuremath{\mathbf{k}}}
\newunicodechar{l}{\ensuremath{\mathbf{l}}}
\newunicodechar{m}{\ensuremath{\mathbf{m}}}
\newunicodechar{n}{\ensuremath{\mathbf{n}}}
\newunicodechar{o}{\ensuremath{\mathbf{o}}}
\newunicodechar{p}{\ensuremath{\mathbf{p}}}

```

```

\newunicodechar{q}{\ensuremath{\mathbf{q}}}
\newunicodechar{r}{\ensuremath{\mathbf{r}}}
\newunicodechar{s}{\ensuremath{\mathbf{s}}}
\newunicodechar{t}{\ensuremath{\mathbf{t}}}
\newunicodechar{u}{\ensuremath{\mathbf{u}}}
\newunicodechar{v}{\ensuremath{\mathbf{v}}}
\newunicodechar{w}{\ensuremath{\mathbf{w}}}
\newunicodechar{x}{\ensuremath{\mathbf{x}}}
\newunicodechar{y}{\ensuremath{\mathbf{y}}}
\newunicodechar{z}{\ensuremath{\mathbf{z}}}

```

### 2.3.2 Uppercase Latin

```

\newunicodechar{A}{\ensuremath{\mathbf{A}}}
\newunicodechar{B}{\ensuremath{\mathbf{B}}}
\newunicodechar{C}{\ensuremath{\mathbf{C}}}
\newunicodechar{D}{\ensuremath{\mathbf{D}}}
\newunicodechar{E}{\ensuremath{\mathbf{E}}}
\newunicodechar{F}{\ensuremath{\mathbf{F}}}
\newunicodechar{G}{\ensuremath{\mathbf{G}}}
\newunicodechar{H}{\ensuremath{\mathbf{H}}}
\newunicodechar{I}{\ensuremath{\mathbf{I}}}
\newunicodechar{J}{\ensuremath{\mathbf{J}}}
\newunicodechar{K}{\ensuremath{\mathbf{K}}}
\newunicodechar{L}{\ensuremath{\mathbf{L}}}
\newunicodechar{M}{\ensuremath{\mathbf{M}}}
\newunicodechar{N}{\ensuremath{\mathbf{N}}}
\newunicodechar{O}{\ensuremath{\mathbf{O}}}
\newunicodechar{P}{\ensuremath{\mathbf{P}}}
\newunicodechar{Q}{\ensuremath{\mathbf{Q}}}
\newunicodechar{R}{\ensuremath{\mathbf{R}}}
\newunicodechar{S}{\ensuremath{\mathbf{S}}}
\newunicodechar{T}{\ensuremath{\mathbf{T}}}
\newunicodechar{U}{\ensuremath{\mathbf{U}}}
\newunicodechar{V}{\ensuremath{\mathbf{V}}}
\newunicodechar{W}{\ensuremath{\mathbf{W}}}
\newunicodechar{X}{\ensuremath{\mathbf{X}}}
\newunicodechar{Y}{\ensuremath{\mathbf{Y}}}
\newunicodechar{Z}{\ensuremath{\mathbf{Z}}}

```

## 2.4 Bold Calligraphic

*% For bold calligraphic letters*

```
\DeclareMathAlphabet\mathbfcal{OMS}{cmsy}{b}{n}
```

### 2.4.1 Lowercase Latin

```

\newunicodechar{-}{\ensuremath{\mathbfcal{a}}}
\newunicodechar{[}{\ensuremath{\mathbfcal{b}}}
\newunicodechar{]}{\ensuremath{\mathbfcal{c}}}
\newunicodechar{[}{\ensuremath{\mathbfcal{d}}}
\newunicodechar{]}{\ensuremath{\mathbfcal{e}}}
\newunicodechar{f}{\ensuremath{\mathbfcal{f}}}

```

```

\newunicodechar{\}{\ensuremath{\mathbfcal{g}}}
\newunicodechar{\langle}{\ensuremath{\mathbfcal{h}}}
\newunicodechar{\rangle}{\ensuremath{\mathbfcal{i}}}
\newunicodechar{\|}{\ensuremath{\mathbfcal{j}}}
\newunicodechar{\||}{\ensuremath{\mathbfcal{k}}}
\newunicodechar{\updownarrow}{\ensuremath{\mathbfcal{l}}}
\newunicodechar{\Updownarrow}{\ensuremath{\mathbfcal{m}}}
\newunicodechar{\backslash}{\ensuremath{\mathbfcal{n}}}
\newunicodechar{\}]{\ensuremath{\mathbfcal{o}}}
\newunicodechar{\sqrt{\hspace{0.5em}}}{\ensuremath{\mathbfcal{p}}}
\newunicodechar{\text{II}}{\ensuremath{\mathbfcal{q}}}
\newunicodechar{\nabla}{\ensuremath{\mathbfcal{r}}}
\newunicodechar{\mathcal{f}}{\ensuremath{\mathbfcal{s}}}
\newunicodechar{\sqcup}{\ensuremath{\mathbfcal{t}}}
\newunicodechar{\sqcap}{\ensuremath{\mathbfcal{u}}}
\newunicodechar{\sqsubseteq}{\ensuremath{\mathbfcal{v}}}
\newunicodechar{\sqsupseteq}{\ensuremath{\mathbfcal{w}}}
\newunicodechar{\S}{\ensuremath{\mathbfcal{x}}}
\newunicodechar{\text{†}}{\ensuremath{\mathbfcal{y}}}
\newunicodechar{\text{‡}}{\ensuremath{\mathbfcal{z}}}

```

#### 2.4.2 Uppercase Latin

```

\newunicodechar{\mathcal{A}}{\ensuremath{\mathbfcal{A}}}
\newunicodechar{\mathcal{B}}{\ensuremath{\mathbfcal{B}}}
\newunicodechar{\mathcal{C}}{\ensuremath{\mathbfcal{C}}}
\newunicodechar{\mathcal{D}}{\ensuremath{\mathbfcal{D}}}
\newunicodechar{\mathcal{E}}{\ensuremath{\mathbfcal{E}}}
\newunicodechar{\mathcal{F}}{\ensuremath{\mathbfcal{F}}}
\newunicodechar{\mathcal{G}}{\ensuremath{\mathbfcal{G}}}
\newunicodechar{\mathcal{H}}{\ensuremath{\mathbfcal{H}}}
\newunicodechar{\mathcal{I}}{\ensuremath{\mathbfcal{I}}}
\newunicodechar{\mathcal{J}}{\ensuremath{\mathbfcal{J}}}
\newunicodechar{\mathcal{K}}{\ensuremath{\mathbfcal{K}}}
\newunicodechar{\mathcal{L}}{\ensuremath{\mathbfcal{L}}}
\newunicodechar{\mathcal{M}}{\ensuremath{\mathbfcal{M}}}
\newunicodechar{\mathcal{N}}{\ensuremath{\mathbfcal{N}}}
\newunicodechar{\mathcal{O}}{\ensuremath{\mathbfcal{O}}}
\newunicodechar{\mathcal{P}}{\ensuremath{\mathbfcal{P}}}
\newunicodechar{\mathcal{Q}}{\ensuremath{\mathbfcal{Q}}}
\newunicodechar{\mathcal{R}}{\ensuremath{\mathbfcal{R}}}
\newunicodechar{\mathcal{S}}{\ensuremath{\mathbfcal{S}}}
\newunicodechar{\mathcal{T}}{\ensuremath{\mathbfcal{T}}}
\newunicodechar{\mathcal{U}}{\ensuremath{\mathbfcal{U}}}
\newunicodechar{\mathcal{V}}{\ensuremath{\mathbfcal{V}}}
\newunicodechar{\mathcal{W}}{\ensuremath{\mathbfcal{W}}}
\newunicodechar{\mathcal{X}}{\ensuremath{\mathbfcal{X}}}
\newunicodechar{\mathcal{Y}}{\ensuremath{\mathbfcal{Y}}}
\newunicodechar{\mathcal{Z}}{\ensuremath{\mathbfcal{Z}}}

```

### 3 Other letters or letterlike symbols

```
\newunicodechar{\ell}{\ensuremath{\ell}}
```

### 4 Greek alphabet

#### 4.1 Normal

```
\newunicodechar{\alpha}{\ensuremath{\alpha}}
\ifpdflatex
  \newunicodechar{A}{\ensuremath{A}}
\else
  \newunicodechar{A}{\ensuremath{\Alpha}}
\fi
\newunicodechar{\beta}{\ensuremath{\beta}}
\ifpdflatex
  \newunicodechar{B}{\ensuremath{B}}
\else
  \newunicodechar{B}{\ensuremath{\Beta}}
\fi
\newunicodechar{\gamma}{\ensuremath{\gamma}}
\newunicodechar{\Gamma}{\ensuremath{\Gamma}}
\newunicodechar{\delta}{\ensuremath{\delta}}
\newunicodechar{\Delta}{\ensuremath{\Delta}}
\newunicodechar{\epsilon}{\ensuremath{\epsilon}}
\ifpdflatex
  \newunicodechar{E}{\ensuremath{E}}
\else
  \newunicodechar{E}{\ensuremath{\Epsilon}}
\fi
\newunicodechar{\zeta}{\ensuremath{\zeta}}
\ifpdflatex
  \newunicodechar{Z}{\ensuremath{Z}}
\else
  \newunicodechar{Z}{\ensuremath{\Zeta}}
\fi
\newunicodechar{\eta}{\ensuremath{\eta}}
\ifpdflatex
  \newunicodechar{H}{\ensuremath{H}}
\else
  \newunicodechar{H}{\ensuremath{\Eta}}
\fi
\newunicodechar{\theta}{\ensuremath{\theta}}
\newunicodechar{\Theta}{\ensuremath{\Theta}}
\newunicodechar{\iota}{\ensuremath{\iota}}
\ifpdflatex
  \newunicodechar{I}{\ensuremath{I}}
\else
  \newunicodechar{I}{\ensuremath{\Iota}}
\fi
\newunicodechar{\kappa}{\ensuremath{\kappa}}
\ifpdflatex
```

```

\newunicodechar{K}{\ensuremath{K}}
\else
\newunicodechar{K}{\ensuremath{\Kappa}}
\fi
\newunicodechar{\lambda}{\ensuremath{\lambda}}
\newunicodechar{\Lambda}{\ensuremath{\Lambda}}
\newunicodechar{\mu}{\ensuremath{\mu}}
\ifpdflatex
\newunicodechar{M}{\ensuremath{M}}
\else
\newunicodechar{M}{\ensuremath{\Mu}}
\fi
\newunicodechar{\nu}{\ensuremath{\nu}}
\ifpdflatex
\newunicodechar{N}{\ensuremath{N}}
\else
\newunicodechar{N}{\ensuremath{\Nu}}
\fi
\newunicodechar{\xi}{\ensuremath{\xi}}
\newunicodechar{\Xi}{\ensuremath{\Xi}}
\ifpdflatex
\newunicodechar{o}{\ensuremath{o}}
\else
\newunicodechar{o}{\ensuremath{\omicron}}
\fi
\ifpdflatex
\newunicodechar{O}{\ensuremath{O}}
\else
\newunicodechar{O}{\ensuremath{\Omicron}}
\fi
\newunicodechar{\pi}{\ensuremath{\pi}}
\newunicodechar{\Pi}{\ensuremath{\Pi}}
\newunicodechar{\rho}{\ensuremath{\rho}}
\ifpdflatex
\newunicodechar{P}{\ensuremath{P}}
\else
\newunicodechar{P}{\ensuremath{\Rho}}
\fi
\newunicodechar{\sigma}{\ensuremath{\sigma}}
\newunicodechar{\Sigma}{\ensuremath{\Sigma}}
\newunicodechar{\tau}{\ensuremath{\tau}}
\ifpdflatex
\newunicodechar{T}{\ensuremath{T}}
\else
\newunicodechar{T}{\ensuremath{\Tau}}
\fi
\newunicodechar{v}{\ensuremath{\upsilon}}
\newunicodechar{\Upsilon}{\ensuremath{\Upsilon}}
\newunicodechar{\phi}{\ensuremath{\phi}}
\newunicodechar{\Phi}{\ensuremath{\Phi}}
\newunicodechar{\chi}{\ensuremath{\chi}}
\ifpdflatex

```



```

\newunicodechar{X}{\ensuremath{X}}
\else
\newunicodechar{X}{\ensuremath{\Chi}}
\fi
\newunicodechar{\psi}{\ensuremath{\psi}}
\newunicodechar{\Psi}{\ensuremath{\Psi}}
\newunicodechar{\omega}{\ensuremath{\omega}}
\newunicodechar{\Omega}{\ensuremath{\Omega}}

```

## 4.2 var-variants

INCOMPLETE

Note that some of the default Agda input entries are in this list, rather than the default above.

Also, `varbeta` is missing here; it requires a choice of some other package to add support for it.

```

\newunicodechar{\varepsilon}{\ensuremath{\varepsilon}}
\newunicodechar{\vartheta}{\ensuremath{\vartheta}}
\newunicodechar{\varkappa}{\ensuremath{\varkappa}}
\newunicodechar{\varpi}{\ensuremath{\varpi}}
\newunicodechar{\varsigma}{\ensuremath{\varsigma}}
\newunicodechar{\varphi}{\ensuremath{\varphi}}

```

## 5 Sub-, Super-, Under-, and Over-scripts

Note that while the alphabetic lists are complete, **there are missing letters**, because unfortunately Unicode does not have characters for every letter subscript and superscript.

### 5.1 Subscripts

Note there are no uppercase letter subscripts.

#### 5.1.1 Lowercase alphabet

```

\newunicodechar{a}{\ensuremath{{}_a}}
\newunicodechar{e}{\ensuremath{{}_e}}
\newunicodechar{h}{\ensuremath{{}_h}}
\newunicodechar{i}{\ensuremath{{}_i}}
\newunicodechar{j}{\ensuremath{{}_j}}
\newunicodechar{k}{\ensuremath{{}_k}}
\newunicodechar{l}{\ensuremath{{}_l}}
\newunicodechar{m}{\ensuremath{{}_m}}
\newunicodechar{n}{\ensuremath{{}_n}}
\newunicodechar{o}{\ensuremath{{}_o}}
\newunicodechar{p}{\ensuremath{{}_p}}
\newunicodechar{r}{\ensuremath{{}_r}}
\newunicodechar{s}{\ensuremath{{}_s}}
\newunicodechar{t}{\ensuremath{{}_t}}
\newunicodechar{u}{\ensuremath{{}_u}}
\newunicodechar{v}{\ensuremath{{}_v}}
\newunicodechar{x}{\ensuremath{{}_x}}

```

#### 5.1.2 Numeric

```

\newunicodechar{0}{\ensuremath{{}_0}}
\newunicodechar{1}{\ensuremath{{}_1}}

```

```

\newunicodechar{2}{\ensuremath{{}_2}}
\newunicodechar{3}{\ensuremath{{}_3}}
\newunicodechar{4}{\ensuremath{{}_4}}
\newunicodechar{5}{\ensuremath{{}_5}}
\newunicodechar{6}{\ensuremath{{}_6}}
\newunicodechar{7}{\ensuremath{{}_7}}
\newunicodechar{8}{\ensuremath{{}_8}}
\newunicodechar{9}{\ensuremath{{}_9}}

```

### 5.1.3 Other

```

\newunicodechar{+}{\ensuremath{{}_+}}
\newunicodechar{-}{\ensuremath{{}_-}}
\newunicodechar{=}{\ensuremath{{}_=}}

```

## 5.2 Superscripts

### 5.2.1 Uppercase alphabet

```

\newunicodechar{A}{\ensuremath{{}^A}}
\newunicodechar{B}{\ensuremath{{}^B}}
\newunicodechar{D}{\ensuremath{{}^D}}
\newunicodechar{E}{\ensuremath{{}^E}}
\newunicodechar{G}{\ensuremath{{}^G}}
\newunicodechar{H}{\ensuremath{{}^H}}
\newunicodechar{I}{\ensuremath{{}^I}}
\newunicodechar{J}{\ensuremath{{}^J}}
\newunicodechar{K}{\ensuremath{{}^K}}
\newunicodechar{L}{\ensuremath{{}^L}}
\newunicodechar{M}{\ensuremath{{}^M}}
\newunicodechar{N}{\ensuremath{{}^N}}
\newunicodechar{O}{\ensuremath{{}^O}}
\newunicodechar{P}{\ensuremath{{}^P}}
\newunicodechar{R}{\ensuremath{{}^R}}
\newunicodechar{T}{\ensuremath{{}^T}}
\newunicodechar{U}{\ensuremath{{}^U}}
\newunicodechar{V}{\ensuremath{{}^V}}
\newunicodechar{W}{\ensuremath{{}^W}}

```

### 5.2.2 Lowercase alphabet

```

\newunicodechar{a}{\ensuremath{{}^a}}
\newunicodechar{b}{\ensuremath{{}^b}}
\newunicodechar{c}{\ensuremath{{}^c}}
\newunicodechar{d}{\ensuremath{{}^d}}
\newunicodechar{e}{\ensuremath{{}^e}}
\newunicodechar{f}{\ensuremath{{}^f}}
\newunicodechar{g}{\ensuremath{{}^g}}
\newunicodechar{h}{\ensuremath{{}^h}}
\newunicodechar{i}{\ensuremath{{}^i}}
\newunicodechar{j}{\ensuremath{{}^j}}
\newunicodechar{k}{\ensuremath{{}^k}}
\newunicodechar{l}{\ensuremath{{}^l}}

```

```

\newunicodechar{m}{\ensuremath{{}^{\mathrm{m}}}}
\newunicodechar{n}{\ensuremath{{}^{\mathrm{n}}}}
\newunicodechar{o}{\ensuremath{{}^{\mathrm{o}}}}
\newunicodechar{p}{\ensuremath{{}^{\mathrm{p}}}}
\newunicodechar{r}{\ensuremath{{}^{\mathrm{r}}}}
\newunicodechar{s}{\ensuremath{{}^{\mathrm{s}}}}
\newunicodechar{t}{\ensuremath{{}^{\mathrm{t}}}}
\newunicodechar{u}{\ensuremath{{}^{\mathrm{u}}}}
\newunicodechar{v}{\ensuremath{{}^{\mathrm{v}}}}
\newunicodechar{w}{\ensuremath{{}^{\mathrm{w}}}}
\newunicodechar{x}{\ensuremath{{}^{\mathrm{x}}}}
\newunicodechar{y}{\ensuremath{{}^{\mathrm{y}}}}
\newunicodechar{z}{\ensuremath{{}^{\mathrm{z}}}}

```

### 5.2.3 Numeric

```

\newunicodechar{0}{\ensuremath{{}^{\mathrm{0}}}}
\newunicodechar{1}{\ensuremath{{}^{\mathrm{1}}}}
\newunicodechar{2}{\ensuremath{{}^{\mathrm{2}}}}
\newunicodechar{3}{\ensuremath{{}^{\mathrm{3}}}}
\newunicodechar{4}{\ensuremath{{}^{\mathrm{4}}}}
\newunicodechar{5}{\ensuremath{{}^{\mathrm{5}}}}
\newunicodechar{6}{\ensuremath{{}^{\mathrm{6}}}}
\newunicodechar{7}{\ensuremath{{}^{\mathrm{7}}}}
\newunicodechar{8}{\ensuremath{{}^{\mathrm{8}}}}
\newunicodechar{9}{\ensuremath{{}^{\mathrm{9}}}}

```

### 5.2.4 Other

```

\newunicodechar{+}{\ensuremath{{}^{\mathrm{+}}}}
\newunicodechar{-}{\ensuremath{{}^{\mathrm{-}}}}
\newunicodechar{=}{\ensuremath{{}^{\mathrm{=}}}}

```

## 6 Punctuation and Delimiters

### 6.1 Dots

```

\newunicodechar{...}{\ensuremath{\ldots}}
\newunicodechar{⋯}{\ensuremath{\cdots}}
\newunicodechar{⋮}{\ensuremath{\vdots}}

```

### 6.2 Dashes

```

\newunicodechar{-}{\ensuremath{\text{--}}}
\newunicodechar{--}{\ensuremath{\text{---}}}

```

### 6.3 Parentheses, braces and brackets

Note there are a few different braces I translate the same way. Braces and parentheses themselves are special characters in Agda, so they cannot be used in names.

```

\newunicodechar{(|)}{\ensuremath{(\!|\!)}}
\newunicodechar{(|)}{\ensuremath{|\!\!)}}

```

```

\newunicodechar{<}{\ensuremath{\langle}}
\newunicodechar{>}{\ensuremath{\rangle}}
\newunicodechar{{}{\ensuremath{\{\!|\!}}
\newunicodechar{}}{\ensuremath{\!\!|\}}
\newunicodechar{<<}{\ensuremath{\langle\!\!\langle}}
\newunicodechar{>>}{\ensuremath{\rangle\!\!\rangle}}
\newunicodechar{{ }{\ensuremath{\{\,}}
\newunicodechar{ }{\ensuremath{\,\}}}
\newunicodechar{{ }{\ensuremath{\{\,}}
\newunicodechar{ }{\ensuremath{\,\}}}
\newunicodechar{[! ]{\ensuremath{[!\,]}}
\newunicodechar{[! ]{\ensuremath{[!\,]}}}

```

## 6.4 Other paired delimiters

```

\newunicodechar{⌈}{\ensuremath{\ulcorner}}
\newunicodechar{⌋}{\ensuremath{\urcorner}}
\newunicodechar{⌌}{\ensuremath{\llcorner}}
\newunicodechar{⌍}{\ensuremath{\lrcorner}}
\newunicodechar{⌈}{\ensuremath{\lceil}}
\newunicodechar{⌋}{\ensuremath{\rceil}}
\newunicodechar{⌊}{\ensuremath{\lfloor}}
\newunicodechar{⌋}{\ensuremath{\rfloor}}

```

## 6.5 Whitespace

Non-breaking space. Though it may appear as a normal space, it is in fact a  $\sim$  in the  $\text{\LaTeX}$  —in classic  $\text{\LaTeX}$  one writes  $\backslash,$ .

```

\newunicodechar{ }{\ensuremath{\sim}}

```

I am a very long line whose words are separated by non-breaking spaces so I should run off the page at least at any reason

# 7 Logic

## 7.1 Propositional

```

\newunicodechar{≡}{\ensuremath{\equiv}}
\newunicodechar{¬}{\ensuremath{\neg}}
\newunicodechar{≠}{\ensuremath{\not\equiv}}
\newunicodechar{∨}{\ensuremath{\lor}}
\newunicodechar{∧}{\ensuremath{\land}}
\newunicodechar{⇒}{\ensuremath{\;\;\rightarrow\;}}
\newunicodechar{⇐}{\ensuremath{\;\;\leftarrow\;}}
\newunicodechar{⇔}{\ensuremath{\iff}}
\newunicodechar{⇔}{\ensuremath{\iff}}

```

## 7.2 Predicate

```

\newunicodechar{∀}{\ensuremath{\forall}}
\newunicodechar{∃}{\ensuremath{\exists}}

\newunicodechar{ | }{\ensuremath{\,\,\mid\,\,}}
\newunicodechar{ • }{\ensuremath{\,\,\bullet\,\,}}

```

## 7.3 Model —Entailment

```
\newunicodechar{\vdash}{\ensuremath{\vdash}}
\newunicodechar{\dashv}{\ensuremath{\dashv}}
\newunicodechar{\vDash}{\ensuremath{\vDash}}
```

# 8 Sets, relations and functions

## 8.1 Sets

```
\newunicodechar{\emptyset}{\ensuremath{\emptyset}}
\newunicodechar{\emptyset}{\ensuremath{\emptyset}}
\newunicodechar{\in}{\ensuremath{\in}}
\newunicodechar{\notin}{\ensuremath{\notin}}
\newunicodechar{\ni}{\ensuremath{\ni}}
\newunicodechar{\subseteq}{\ensuremath{\subseteq}}
\newunicodechar{\cap}{\ensuremath{\cap}}
\newunicodechar{\cup}{\ensuremath{\cup}}
\newunicodechar{\uplus}{\ensuremath{\uplus}}
\newunicodechar{\uplus}{\ensuremath{\uplus}}
```

## 8.2 Relation operators

```
\newunicodechar{\top}{\ensuremath{\top}}
\newunicodechar{\bot}{\ensuremath{\bot}}
\newunicodechar{\sqcup}{\ensuremath{\sqcup}}
\newunicodechar{\sqcap}{\ensuremath{\sqcap}}
\newunicodechar{\backslash}{\ensuremath{\backslash}}
\newunicodechar{/}{\ensuremath{/}}
```

## 8.3 Function operators

```
\newunicodechar{\circ}{\ensuremath{\circ}}
\newunicodechar{\mapsto}{\ensuremath{\mapsto}}
\newunicodechar{\hookrightarrow}{\ensuremath{\hookrightarrow}}
```

## 8.4 Relations

### 8.4.1 Equality like

Along with negations where they exist. Note that equivalences are within the 7 section.

```
\newunicodechar{\neq}{\ensuremath{\neq}}
\newunicodechar{\doteq}{\ensuremath{\doteq}}
\newunicodechar{\stackrel{?}{=}}{\ensuremath{\stackrel{?}{=}}}
\newunicodechar{\cong}{\ensuremath{\cong}}
\newunicodechar{\ncong}{\ensuremath{\ncong}}
\newunicodechar{\simeq}{\ensuremath{\simeq}}
\newunicodechar{\not\simeq}{\ensuremath{\not\simeq}}
\newunicodechar{\approx}{\ensuremath{\approx}}
\newunicodechar{\not\approx}{\ensuremath{\not\approx}}
\newunicodechar{\sim}{\ensuremath{\sim}}
\newunicodechar{\not\sim}{\ensuremath{\not\sim}}
\newunicodechar{:=}{\ensuremath{:=}}
```

### 8.4.2 Order like

```
\newunicodechar{≤}{\ensuremath{\leq}}
\newunicodechar{⩵}{\ensuremath{\nleq}}
\newunicodechar{≥}{\ensuremath{\geq}}
\newunicodechar{⩶}{\ensuremath{\ngeq}}
\newunicodechar{⩴}{\ensuremath{\nless}}
\newunicodechar{⩷}{\ensuremath{\ngtr}}
\newunicodechar{≤}{\ensuremath{\leqq}}
\newunicodechar{⩵}{\ensuremath{\lneqq}}
\newunicodechar{≥}{\ensuremath{\geqq}}
\newunicodechar{⩶}{\ensuremath{\gneqq}}
\newunicodechar{⩷}{\ensuremath{\lessssim}}
\newunicodechar{⩸}{\ensuremath{\gtrsim}}
\newunicodechar{⊆}{\ensuremath{\sqsubset}}
\newunicodechar{⊆}{\ensuremath{\sqsubseteq}}
\newunicodechar{⊇}{\ensuremath{\sqsupset}}
\newunicodechar{⊇}{\ensuremath{\sqsupseteq}}
\newunicodechar{|}{\ensuremath{\mid}}
```

## 9 Generic or other operators

### 9.1 Arrows

```
\newunicodechar{→}{\ensuremath{\rightarrow}}
\newunicodechar{→}{\ensuremath{\rightarrow}}
\newunicodechar{→}{\ensuremath{\rightarrow}}
\newunicodechar{↘}{\ensuremath{\rightsquigarrow}}
\newunicodechar{←}{\ensuremath{\leftarrow}}
\newunicodechar{↔}{\ensuremath{\leftrightarrows}}
\newunicodechar{↑}{\ensuremath{\uparrow}}
\newunicodechar{↓}{\ensuremath{\downarrow}}
\newunicodechar{↓↓}{\ensuremath{\downarrow\downarrow}}
\newunicodechar{→}{\ensuremath{\longrightarrow}}
\newunicodechar{←}{\ensuremath{\longleftarrow}}
```

### 9.2 “o”-operators

INCOMPLETE

Agda users invoke `\ox` and `\Ox`.

```
\newunicodechar{⊕}{\ensuremath{\oplus}}
\newunicodechar{⊕}{\ensuremath{\bigoplus}}
\newunicodechar{⊖}{\ensuremath{\ominus}}
\newunicodechar{⊗}{\ensuremath{\otimes}}
\newunicodechar{⊗}{\ensuremath{\bigotimes}}
\newunicodechar{⊘}{\ensuremath{\oslash}}
\newunicodechar{⊙}{\ensuremath{\odot}}
\newunicodechar{⊙}{\ensuremath{\bigodot}}
\newunicodechar{⊙}{\ensuremath{\circledcirc}}
\newunicodechar{⊗}{\ensuremath{\circledast}}
\newunicodechar{⊖}{\ensuremath{\circleddash}}
```

The “directed aggregation” operator  $\text{‘}\oplus\text{’}$  is obtained with the Agda input method using `\r`.

```
\DeclareMathOperator{\VCCompose}{\longrightarrow\hspace{-3.5ex}\oplus\;}
\newunicodechar{\oplus}{\ensuremath{\!\!\!\VCCompose\!}}
```

### 9.3 Punctuation-like

The ‘:’ below is a “ghost colon” that Agda users enter with `\:`. Its function is to provide an identifier that looks like a colon, but is not a colon —which is a reserved syntactical item in Agda. Main uses of the ghost colon are for quantifier notation to indicate the type of dummy variables.

- We almost always want to display it as a normal colon.

```
\newunicodechar{!}{\ensuremath{!!!}}
\newunicodechar{:}{\ensuremath{:}}
```

### 9.4 Others

Probably some of these belong somewhere else.

```
\newunicodechar{.}{\ensuremath{\cdot}}
\newunicodechar{\infty}{\ensuremath{\infty}}
\ifpdflatex
  \newunicodechar{::}{\ensuremath{::}}
\else
  \newunicodechar{::}{\ensuremath{\Colon}}
\fi
```

## 10 Check- & X-marks, and Primes & Ticks

```
\newunicodechar{\checkmark}{\ensuremath{\checkmark}}
\newunicodechar{\times}{\ensuremath{\times}}

\newunicodechar{'}{'}
\newunicodechar{''}{''}
\newunicodechar{'}{\ensuremath{'}}
\newunicodechar{"}{\ensuremath{' '}}
```