

ArmoredSoftware Architecture

Perry Alexander Andy Gill Prasad Kuklarni
Leon Searl

Information and Telecommunication Technology Center
The University of Kansas
{palexand, andygill, prasatk, lsearl}@ku.edu

November 9, 2013

Contents

1	Introduction	2
2	System Architecture	4
2.1	Measurement	4
2.2	Attestation	4
2.2.1	TPM and vTPM	6
2.3	Appraisal	6
2.3.1	Migration	6
2.4	Access Control	6
3	Component Interaction	6

List of Figures

1	AS Architecture	3
2	System Architecture	3
3	Architecture component interaction	4
4	Attestation request processing	5
5	Attestation evidence processing	5

List of Tables

Abstract

This document describes the evolving ArmoredSoftware architecture.

1 Introduction

The objective of ARMORED SOFTWARE is to *provide a portable trusted computing capsule for applications executing in the cloud*. This capsule, referred to as *armor*, provides three major functions:

Appraisal – Request and assess measurement information from the operational environment and other armored components.

Measurement – Gather run-time measurement information from its application

Attestation – Assemble and deliver evidence to appraisers in a manner that assures measurement integrity

Figure 1 graphically depicts the major architectural components of a protected application. The *application* is the application to be protected by the infrastructure. The *measurement* component performs measurement operations on the running application while the *attestation* component gathers measurements and delivers them with cryptographic assurance of integrity and confidentiality. The *appraisal* component requests information from the environment and other components to assess the overall operational environment. *Access control* governs access to all critical resources in the protected application to assure secrets are preserved and enforce information flow restrictions.

Figure 2 graphically represents the interaction among protected components while figure 3 shows the sequencing of interactions during appraisal. A component's appraisal module will request information from a second component's attestation module. The attestation model will select an attestation protocol that instructs the measurer what information to gather and in what sequence. The attestation module packages measurement results in a evidence packet that is return to the appraiser requesting information. The appraiser then assesses cryptographic signatures and encryption to determine the trustworthiness of the measurements, then assesses measurements to determine the trustworthiness of the component being appraised. Note that the same process occurs when appraising the component's operational environment.




Figure 1: AS Architecture




Figure 2: System Architecture




Figure 3: Architecture component interaction

2 System Architecture

2.1 Measurement

2.2 Attestation

Figure 4 graphically shows the processing of an attestation request by an ArmoredSoftware attestation component. The attestation request specifies information requested by an appraiser. Upon receipt, the *Attestation Protocol Selector* or *AP Selector* identifies one or more *Attestation Protocols* that could satisfy the appraisers request. The protocol is passed to the *AP Instantiation* process that selects specific mechanisms for achieving individual requests in the AP. The resulting protocol instance is passed to *AP Execution* where it is executed by: (i) making requests to the component’s vTPM; making requests to another components attestation service; or (iii) invoking the measurer on the component’s associated application.

The results of request to the vTPM, another attestation component, and the local measurer are returned as vTPM quotes, evidence packages, and measurements respectively. The AP Execution component monitors execution and collects various results for processing by the AP Instantiation component. AP Instantiation assembles individual measurement, vTPM and appraisal results into a package representing information requested in the attestation request. The




Figure 4: Attestation request processing

AP Selection component uses cryptographic techniques to provide assurances to the appraiser requesting information that evidence can be trusted. Finally, the evidence package is returned to the requesting appraiser where it is evaluated.




Figure 5: Attestation evidence processing

2.2.1 TPM and vTPM

2.3 Appraisal

2.3.1 Migration

2.4 Access Control

3 Component Interaction