FlowPilot: An Agentic Research Assistant for End-to-End Flow Process Design

Amirreza Mottafegh[a,†], Mincheol Park[b,†], Jun-young Jo[b], Jin Suk Myung[a], Boyoung Y. Park[b,*], and Gwang-Noh Ahn[a,*]

a Digital Chemical Research Center, Korea Research Institute of Chemical Technology, 141 Gajeong-ro, Yuseong-gu, Daejeon 34114, Republic of Korea

b Department of Biomedical and Pharmaceutical Sciences, Kyung Hee University, Seoul 02447, South Korea

†Amirreza Mottafegh and Mincheol Park contributed equally to this work.

ABSTRACT

Designing a continuous-flow synthesis requires chemical objectives, transport, operating conditions and available equipment to be considered together. Here we present FlowPilot, an agentic research assistant that supports this end-to-end design task from a batch protocol and the researcher's laboratory constraints. Standardized dialogue establishes the design brief; chemistry-aware retrieval and a handbook-derived rule base inform candidate generation; and a specialist council reviews alternatives alongside deterministic engineering calculations. The resulting process configuration connects feed compositions, stage conditions, equipment assignments and an inspectable topology, with records retained for experimental feedback. Across three chemistry cases, five generator models and three repeats, a matched architecture comparison produced 90 designs evaluated against 14 fixed criteria by separate LLM judges. Mean benchmark scores increased from 0.794 for one-shot generation to 0.917 for FlowPilot, while judge-reported critical flags decreased from 98 to 4. Laboratory implementation of photoredox Giese addition/oxidation and telescoped DPDTC-mediated amidation gave 97–98% and 68–86% NMR yields, respectively. Together, these studies demonstrate how coordinated chemical reasoning, quantitative checks and equipment-aware design can support researcher-led development of connected flow processes.

INTRODUCTION

Continuous-flow chemistry allows synthesis to be organized around controlled mixing, heating, irradiation and contact between phases.[1-4] These capabilities have broadened access to photochemical, electrochemical and gas–liquid transformations and enabled routes to pharmaceutical intermediates.[5-10]

Connecting reaction stages can further reduce intermediate handling and support multistep or on-demand production.[11-14] For the researcher, however, the opportunity is accompanied by a design problem: choosing an arrangement of streams, reactors and controls that realizes the chemistry with the instruments actually available.[15-16] A batch protocol establishes a starting point for this task, but does not specify the continuous process that should be built.

The difficulty lies in the coupling between decisions. Reactor geometry affects irradiation, heat and mass transfer, and pressure loss, while adding a reagent between reactors changes both composition and downstream flow.[17-21] Gas delivery couples stoichiometry to phase behavior and makes the reference conditions used for volumetric flow and residence time consequential.[22] In a telescoped synthesis, incomplete conversion upstream also changes the material available for the next transformation. Integrated apixaban synthesis and photochemical routes to sartan intermediates illustrate the coordination required across reaction stages and hardware.[23-24] An effective design assistant must therefore reason about the connected process, rather than recommend each operating parameter in isolation.

Choosing among these coupled options also requires practical flow-chemistry experience: recognizing when a familiar reaction becomes limited by photon penetration, anticipating precipitation or catalyst retention, and deciding which batch-handling steps have a chemical purpose. Such judgments concern which model or operating assumption is appropriate, not only whether an equation has been evaluated correctly. Flow-development guides and reactor-selection toolboxes organize part of this expertise, but applying it still requires attention to the specific chemistry and apparatus.[3-4,12,21] A data-driven predictor, a simulator or a fixed calculation can support that decision without, on its own, supplying the complete experimental context. For an agentic assistant, a central challenge is therefore to make documented experience available at the point where a design choice is made, while retaining its source, assumptions and limits of transferability.

Digital methods address complementary parts of this challenge. Computer-aided synthesis planning identifies reaction routes,[25-27] process simulation evaluates connected unit operations,[28-29] and Bayesian or active-learning methods guide experimental optimization.[30-34] AI-informed robotic flow synthesis links planning to physical execution,[35] while modular platforms such as RoboChem-Flex and LLM-assisted UV-visible auto-reactometry extend automated optimization and screening.[36-37] Alongside these developments, researchers need support in formulating the initial process itself: specifying feeds, selecting compatible equipment and defining a defensible operating region before an experimental campaign can refine it.

Large language models (LLMs) offer a way to connect that design intent to specialist tools through natural-language interaction. ChemCrow and Coscientist combine chemical reasoning with tool use and experimentation, whereas El Agente coordinates computational chemistry workflows.[38-40] Co-Scientist and Paper2Agent extend collaborative scientific reasoning and the reuse of computational methods.[41-42] Closer to laboratory execution, ACRA links literature procedures to executable chemical descriptions and available hardware; AutoLabs combines clarification and self-correction for liquid handling; and PRISM incorporates simulation feedback before robotic execution.[43-45] These studies establish the value of agents as coordinators of scientific work, not merely generators of chemical text.

Flow chemistry and process development are already part of this emerging scope. Chat-microreactor uses literature-derived information for flow-pattern prediction and microreactor design guidance,[46] and SapoMind combines recommendations with experimental optimization of continuous-flow lanolin saponification.[47] LLM-RDF addresses end-to-end synthesis development through agents for literature search, experimental design, execution, analysis and interpretation, including reactor-design tasks.[48] Multi-agent process-design systems provide complementary capabilities: Tian et al. generate topologies and parameters for simulation flowsheets,[49] and the CeProAgents preprint integrates knowledge extraction, conceptual design and parameter optimization.[50] Together, these studies show how chemical agents increasingly connect reactor and process design to broader synthesis-development workflows.

The relevant question is how such capabilities are organized around a laboratory-specific process. The CAAF preprint explores deterministic constraint checking and candidate revision, including a constructed flow-reactor problem,[51] while El Agente Gráfico and La Agente Óptima investigate structured scientific execution and agent-supervised optimization.[52-53] For researcher-led flow development, this direction calls for a common representation linking the intended chemistry, the quantitative conditions of each stage and the equipment that can realize them. It should also allow the researcher to express priorities, inspect competing designs and return experimental observations without losing the assumptions behind an earlier proposal. The scope and reported validation of directly related systems are compared in Table S1.

Here we introduce FlowPilot as an agentic research assistant for end-to-end flow-process design. The researcher supplies a batch procedure, available instruments and a design objective; standardized follow-up questions establish missing requirements, experimental evidence and hypotheses. FlowPilot combines three complementary knowledge functions: retrieval supplies relevant published examples, a handbook-derived rule base supplies engineering principles and cautions, and LLM reasoning interprets their relevance to the current reaction and inventory. Together, these resources provide an explicit, source-linked representation of documented flow-design experience, rather than a substitute for the researcher's

experimental judgment. A specialist council then develops and reviews alternative connected configurations with quantitative tools, from deciding where reagents and gases enter to selecting stage conditions and assigning equipment. End-to-end denotes this integrated design workflow; experimental implementation and interpretation remain researcher-led.

The organizing principle is that chemical interpretation, engineering consistency and equipment feasibility must inform one another. Retrieved precedents guide candidate choices but do not establish transferable kinetics; engineering tools recalculate dependent quantities; and council specialists examine chemical, kinetic, fluidic and safety implications before selection. A shared final record connects stage and stream conditions to the equipment list and diagram, making the proposal available for inspection and subsequent revision. This structure is important because fluent chemical reasoning can coexist with elementary errors or overconfidence,[54] and model-guided optimization can still produce invalid suggestions within a defined search space.[55] For a design assistant, success must therefore be assessed at the level of the complete proposed process.

We evaluate FlowPilot at three complementary levels: the alignment of retrieved precedents with the chemistry plan, the quality of delivered designs relative to matched one-shot generation, and the implementation of connected processes in the laboratory. The architecture comparison uses several model families, a fixed outcome-based rubric and separate evaluator calls; internal ablations examine the contribution of council review and candidate exploration. Two experimental sequences then probe distinct design challenges. Photoredox Giese addition followed by oxidation requires a controlled change from an oxygen-free to an oxygen-fed environment, whereas DPDTC-mediated amidation requires coordinated activation, interstage reagent addition and downstream conversion without intermediate isolation. Together, these assessments examine whether the proposed architecture supports coherent process development, beyond producing plausible reaction instructions.

RESULTS

Coordinating chemistry, engineering and laboratory equipment

FlowPilot begins by making the researcher's process-development problem explicit (Figure 1). A protocol supplies chemical facts, whereas the objective, inventory and follow-up answers define what the proposed process should achieve and what the laboratory can support. The confirmed input package keeps measured evidence separate from hypotheses and missing information. The upstream chemistry module identifies the transformations, stage boundaries, incompatible feeds and sensitivities that shape the design space. Literature retrieval and handbook-derived knowledge then inform an initial quantitative proposal.

In this way, a desired chemical outcome is developed into a set of connected operations rather than treated as a request to rewrite the batch procedure.

The council evaluates alternatives where those operations interact (Figure 1d). A Designer proposes candidate configurations; Chemistry, Kinetics, Fluidics and Safety specialists examine transformation fidelity, reaction-time plausibility, transport, hardware and hazards. The Skeptic examines contradictions and unsupported assumptions, and the Orchestrator selects among the reviewed candidates. A shorter residence time, for example, is not considered independently of the reactor volume, achievable feed rate or chemical evidence supporting that exposure. When operating choices change, deterministic calculations update the dependent quantities before the revised candidate is assessed. The review record retains disagreement, rejected alternatives and selection rationales, allowing the researcher to distinguish a constraint-driven decision from an exploratory hypothesis.

Equipment assignment is part of this design process rather than a final list appended to it. Available pump channels, reactor dimensions, thermal limits and compatible irradiation modules constrain which operating points can be realized. The selected proposal is reconciled into a common final record containing the streams, stages, equipment assignments and process graph. Numerical views and the diagram derive from that record; unresolved requirements and earlier calculations remain identifiable as diagnostics. This links what the researcher would assemble to the quantities used to assess it, and preserves a basis for incorporating later experimental observations. Figures S1–S2 and Tables S2–S3 describe the data contracts and provenance mechanisms.




Figure 1. *FlowPilot system architecture. User inputs are converted into a chemistry plan and an initial engineering proposal, supported by flow-chemistry literature and handbook knowledge. The seven-agent council generates and reviews candidate designs, records structured verdicts, and proposes bounded revisions. The selected candidate is reconciled with engineering calculations and laboratory inventory before a process-flow diagram, protocol, report, confidence assessment, and supporting citations are returned. The illustrated recipe card and candidate/revision budgets are schematic, not common settings for every campaign. The audited rule-base export derives from six source texts (ESI Section 3); the approximate handbook count in the overview is illustrative. Computational validation denotes consistency checking, not experimental performance or authorization to operate.*

Grounding design choices in literature and engineering knowledge

Candidate design requires both chemical precedents and general engineering knowledge. FlowPilot's curated literature resource contains 464 classified records spanning thermal synthesis, photoredox catalysis, heterogeneous photocatalysis, cross-coupling, oxidation/reduction and other reaction classes (Figure 2). The recorded hardware includes capillary and coil reactors, microreactors, photoreactors and packed beds, with fluoropolymers prominent among reported tubing materials. Explicit inlet-stream counts are available for 154 processes; two- and three-stream configurations account for 91 and 30 records, respectively. These annotations help relate a chemical plan to alternative ways of supplying reagents and arranging reactors, without prescribing a default topology or treating an absent annotation as evidence that an operation is unnecessary.

The complementary handbook-derived resource contains 2,537 structured rules covering reactor design, heat transfer, catalysts, residence time, photochemistry, materials, scale-up, pressure, mixing and safety (Figure 2e–f). These rules provide engineering context when a close chemical analogue is unavailable or when a candidate must be evaluated beyond reaction identity. Coverage is uneven: heat-transfer rules are densely associated with thermal synthesis and cross-coupling, whereas photochemistry rules concentrate in photoredox and photocycloaddition classes. The rule store therefore informs interpretation and review rather than functioning as a universally validated predictive model; only the checks implemented in the calculation layer act as deterministic constraints. Figures S3–S4 and Table S4 report the frozen corpus and computed rule-base coverage.




Figure 2. *Literature corpus and engineering rule-base coverage. (a-d) Reaction classes, reactor types, reported materials, and inlet-stream configurations in the curated flow-chemistry corpus; explicit inlet-stream counts are available for 154 records. (e) Category and severity distribution within the 2,537-rule engineering knowledge base. (f) Recorded associations between rule categories and chemistry classes. Full categorical exports and field-specific availability are reported in Figures S3–S4 and Table S4; associations indicate knowledge coverage rather than independent validation of every rule.*

Retrieving precedents that reflect the chemistry plan

A broad corpus is useful only if the retrieved records reflect the process under consideration. FlowPilot therefore enriches the search with reaction class, mechanism, catalyst family, solvent and wavelength from the chemistry plan (Figure 3a). Search progresses from mechanism- and phase-filtered paired

records to relaxed filters and, when necessary, the full corpus; field-aware ranking then orders the candidates (Figure 3; Table S5). This allows the assistant to seek closely related evidence while retaining a route to broader analogies when exact matches are sparse. We examined the contribution of query enrichment and metadata reranking in separate retrospective analyses using stored corpus embeddings, rather than treating corpus size alone as evidence of retrieval quality.

In the two query-enrichment examples, chemically specific term counts increased from 7 to 15 and from 7 to 14 (Figure 3b). A separate rank analysis evaluated 20 neighbors for each of 80 corpus queries, giving 1,600 query–result pairs. Adding the metadata score changed 401 ranks (25.1%) relative to embedding-only ordering. These changes quantify reranking activity, not an independent measure of reaction relevance.

In a separate family-alignment analysis, the mean proportion of top-five records sharing the query's recorded catalyst family increased from 40.0% to 95.0% for iridium, 42.7% to 90.7% for organic dyes, 77.3% to 94.7% for ruthenium, 87.1% to 98.6% for TiO2, and 45.0% to 60.0% for ZnO (Figure 3c); the corresponding query counts were 8, 15, 15, 14 and 4. The effect was therefore not uniform across families, but the ranking more often retained the chemistry descriptors requested by the plan. Because catalyst-family metadata contribute to the score, this measures alignment with those descriptors, not independent proof that reaction times or yields transfer between systems. Retrieved records remain evidence for council assessment rather than ready-made operating instructions. Figure 3d illustrates the ranking change; Figure S5 and Tables S5–S6 give the analyses and their scope.




Figure 3. *Retrieval workflow and retrospective metadata-alignment analyses. (a) Operational query enrichment, metadata-filter relaxation, and field-aware ranking. (b) Two examples of query enrichment, showing counts of chemically specific terms. (c) Mean fraction of the top five retrieved records with the same recorded photocatalyst family as the query; n denotes query count. (d) An illustrative iridium-query ranking. The analyses in (c–d) use stored embeddings and the offline scoring implementation described in Methods and ESI Section 3.2. Missing family labels are unassigned metadata, not verified chemical mismatches; displayed percentage gains are percentage-point differences.*

Architecture effects on flow-process design quality

We next asked whether coordinating these capabilities improves the delivered process design beyond what the same LLM can produce in one response (Figure 4a). The three benchmark chemistries were selected to expose complementary process-design demands while using one unchanged assessment rubric.

Cu/C-catalyzed azide–alkyne cycloaddition (CuAAC) tests whether catalyst strategy, liquid-feed preparation and heated, pressurized operation remain consistent when a batch procedure is converted into a proposed apparatus. Oxidation of Fmoc-L-methionine tests the coordination of photocatalyst, irradiation and oxygen delivery, including the distinction between total air flow and reactive oxygen equivalents. Hydrogenolysis of N-diphenylmethylazetidin-3-ol adds a gas–liquid–solid contact problem, for which catalyst-bed placement, pressure control and the definition of contact time must agree. These contrasts challenge different assumptions even when a model correctly recognizes the transformation.

Selected after pilot development, the cases act as a retrospective stress test of connected design, rather than a representative survey of synthetic chemistry or a competition to predict published yields. For each case, one-shot generation and FlowPilot received the same protocol, objective, authoritative inventory and requested final-output structure. The one-shot baseline received the complete design brief, not merely a short chemistry question. Applicable criteria were selected by fixed rules rather than adjusted to favor a chemistry or architecture; source records were excluded from FlowPilot retrieval, although this does not establish their absence from model pretraining. ESI Section 4 retains the original prompts, source references and case-specific inventory limits, including ambiguities in the frozen inputs.

The five-model comparison included Qwen3.6-27B and Qwen3.8-27B alongside GPT-4o, Claude Sonnet 4.6 and Claude Opus 4.6. This spans locally served 27B models and commercial model families, allowing the architecture effect to be examined separately from choosing a particular generator. Each model was tested in both architectures for three repeats of each case, giving 90 outcomes. Three separate Qwen, OpenAI and Claude evaluator calls assessed each normalized final design using the same 14 criteria, covering chemical fidelity, feed chemistry, numerical and topology consistency, inventory, physical plausibility, operating procedures and uncertainty. The rubric rewards the delivered design rather than the presence of agents or a long discussion. Applicable integer ratings from 0 to 4 were averaged with equal judge and criterion weights and divided by four; critical flags were retained separately. Tables S7–S8 define the rubric, and Table S9 specifies the complementary module-ablation screen.

The comparison holds task information constant, not computation: FlowPilot can retrieve evidence, call tools and revise candidates, whereas one-shot generation uses one model call. It therefore tests the utility of the complete design architecture, not whether agent dialogue alone causes an improvement at equal token cost. For each model and architecture, the three case scores were averaged within each repeat; the reported mean and sample standard deviation summarize those three repeat-level values. Generator and architecture labels were removed from evaluator packets, but judging remained an LLM-based assessment, with shared model families and potentially recognizable output styles. The exact inputs,

evaluator configuration, applicability rules and repeat structure are retained in ESI Section 4 and Methods.




Figure 4. *Ablation benchmarking* ***and cost efficiency.*** ***(a)*** *Architecture comparison under shared inputs and fixed evaluation.* ***(b)*** *Benchmark scores and (c) raw judge critical flags: mean and sample SD across three repeats, each containing three chemistry cases. The six-model display includes the archived GPT-5.4 generator comparison; this additional model is not included in the five-model aggregates in Tables S10–S11. (d) Selected Qwen3.8-27B ablations: mean and between-case SD with one generation per case-condition (all 15 conditions: Table S9). (e) Mean FlowPilot score divided by mean generation cost under the recorded price schedule, excluding judging and deployment. Critical flags are judge findings, not independently confirmed physical errors. ESI Section 4 provides evaluation details.*

FlowPilot increased the mean score for each of the five generators (Figure 4b; Table S10). Across this cohort, the architecture means were 0.917 for FlowPilot and 0.794 for one-shot generation. The gain was largest for GPT-4o (+0.226), followed by Qwen3.8-27B (+0.168) and Qwen3.6-27B (+0.139); Claude Sonnet 4.6 and Opus 4.6 showed smaller gains of +0.034 and +0.049. The one-shot means spanned 0.684–0.890, whereas FlowPilot means occupied the narrower range of 0.904–0.932. This pattern suggests that the design architecture was particularly useful when direct generation left more requirements unresolved. The two 27B models within FlowPilot also exceeded the commercial one-shot means in this cohort, supporting the practical value of workflow structure without establishing that a smaller model is intrinsically more capable. The smaller Claude gains are equally informative: stronger direct outputs leave less room for improvement. Figure 4 additionally retains an archived GPT-5.4 comparison, which is not pooled into the five-model summaries.

The critical-flag analysis asks whether the higher average scores correspond to fewer consequential defects in the proposed process (Figure 4c; Table S11). Judges recorded 98 judge-level critical flags across 45 one-shot outcomes and 4 across 45 FlowPilot outcomes; 18 and 43 outcomes, respectively, had no flag. Panel c groups these findings by generator: each point is the mean total across the three chemistries within a repeat, not a measured failure frequency. The large reductions for the Qwen models and GPT-4o are consistent with the larger score gains in panel b, whereas the Claude one-shot designs already contained fewer flagged defects. This makes the reduction more informative than a score increase alone, but does not convert the assessment into a prediction of laboratory success.

The underlying examples illustrate why these defects matter chemically and operationally. A one-shot hydrogenolysis procedure placed a vented gas–liquid separator before its only pressure-defining BPR while describing pressurized reaction, leaving the proposed gas contact and pressure boundary incompatible as written. Another mixed an empty-bed time with a different reported residence-time value, obscuring the exposure assigned to the substrate. FlowPilot was not defect-free: one CuAAC output placed Cu/C in the liquid preparation despite specifying a packed catalyst bed, a contradiction that changes how the catalyst is contacted and retained. Moreover, one judge incorrectly treated equal-reference sccm and mL min−1 values as differing by a factor of 1,000. The archived counts retain that false positive, and multiple flags can refer to one underlying defect. They are therefore reported as judge findings, not as independently confirmed physical errors or safety probabilities.

The case-specific analysis helps locate the improvement (Figure S6). Hydrogenolysis showed the largest mean gain for both Qwen models and for Opus 4.6, consistent with the demands of coordinating gas delivery, catalyst contact and pressure control. At criterion level, the displayed gains in executable

topology were positive for every model–case mean, whereas transformation-fidelity changes were small in comparison (Figure S7). This pattern points to process integration, not simply recognition of the named reaction, as an important source of the observed benefit. Not every criterion improved, and the run-level flag map retains the remaining failures (Figure S8). Resource use must also be considered: Figure S9 reports tokens, runtime and generation cost, while Figure 4e relates score to cost under the archived price schedule. The Qwen configurations offered higher score-per-generation-cost ratios under that schedule; this is a deployment-relevant trade-off, not a measurement of local hardware costs or experimental productivity. Table S12 defines the numerical closure checks underlying the engineering assessment.

To examine the role of coordinated review, we separately tested 15 Qwen3.8-27B configurations over the same three cases (Figure 4d; Table S9). The selected conditions in panel d compare the full pipeline with one-shot generation, removal of the council and removal of individual domain reviewers. Removing the council reduced the mean score from 0.928 to 0.670, below the 0.743 one-shot result in this screen. In this screen, the initial sequence of agent calls without council review did not recover the quality of the complete configuration. This is consistent with a benefit from reviewing whether chemical and engineering choices form a coherent process, although one generation per case cannot isolate that mechanism from generation variability. The full condition table is retained because the displayed subset alone does not describe every architecture tested.

The domain removals help interpret that result. Without the Chemistry reviewer, the mean was 0.902; without Fluidics, Safety or Kinetics it was 0.913, 0.915 or 0.924, respectively. These reviewers examine coupled decisions such as whether a supported catalyst remains in the intended phase, whether gas and liquid feeds support the stated contact time, and whether thermal and pressure assumptions are compatible with the solvent and hardware. Their overlapping responsibilities allow another reviewer or a deterministic check to catch some omissions, so the smaller changes do not establish that a removed specialty is unimportant. Conversely, one-pass review (0.932) and omission of preselection refinement (0.935) slightly exceeded the complete configuration. The result favors coordinated cross-domain checking, not an assumption that more discussion always improves the design. Each condition was generated once per chemistry; the bars show between-case variation, not replicate uncertainty, and the screen cannot resolve a causal ranking of individual agents.

These assessments also need to remain useful to the researcher making an experimental decision. The interface retains the original protocol and answered follow-up questions (Figure S10), and the categorized inventory and constraints (Figure S11; Table S13). The audit examples include pressure-control and residence-time inconsistencies in one-shot designs, a catalyst-placement defect in a FlowPilot output, and

an evaluator false positive (Table S14). This connection between design, evidence and review provides the starting point for testing the proposed process in the laboratory.

Connected design extends beyond reaction conditions to subsequent material handling, as illustrated by continuous isoxazole synthesis coupled to inline solvent separation and recovery.[56] An earlier FlowPilot computational dry run examined aldehyde α-bromination followed by an inline quench, connecting a reaction step to downstream reagent deactivation (ESI Section 6.4; Figure S12). This archived illustration is retained as a pre-experimental design example, including its unresolved mixing warnings, rather than as an additional laboratory validation. The two studies below instead examine actual implementation of connected reaction sequences.

We next examined two connected-stage reactions that were separate from the architecture-benchmark cases. The purpose was to assess how the design workflow accommodates chemical sequence, equipment and researcher priorities when preparing an experiment, and what becomes apparent only after implementation. For each chemistry, three standardized response sets retained the same batch protocol and laboratory inventory while varying the design brief. Set 1 prioritized integrated final yield without unnecessarily long residence times; Set 2 emphasized high conversion with the shortest reasonably justified starting times; and Set 3 gave greater emphasis to throughput, compactness and overall operating balance. These were related design priorities, not three different reactions or replicate experiments. The fixed-ID responses are compared in Tables S15–S16, and all six archived proposed topologies are reproduced in Figures S13–S18 (ESI Section 7). Some sets converged to the same implemented conditions, giving two distinct reported operating points for each chemistry. The following analysis connects those conditions to chemical outcomes, while distinguishing the initial proposal from changes made during implementation.


Staged oxygen delivery in photoredox Giese addition and oxidation

The first case couples photoredox carbon–carbon bond formation to selective oxidation of the resulting sulfide (Figure 5). Photoinduced electron transfer generates an alpha-thiomethyl radical from an alpha-silyl sulfide; addition to acrylonitrile forms the sulfide intermediate, which is then oxidized to sulfoxide 4a.[57] The batch procedure separates these transformations in time, with 4 h under argon followed by 6 h exposed to air. The connected flow design instead separates the oxygen-free and oxygen-fed environments spatially. All three response sets therefore required oxygen introduction only at the second-stage inlet and at least two equivalents relative to the substrate. The process-design question was how to combine sufficient upstream sulfide formation with downstream oxygen delivery, irradiation and gas–liquid operation, not simply how far the batch time could be shortened.

We implemented this arrangement using a 2 or 5 mL PFA coil in a Vapourtec UV-150 module followed by a separately illuminated 20 mL FEP coil, both at 25 ± 1 °C. The reactor–light pairing preserved the compatibility of the first-stage module while allowing the second coil to use its own irradiation source. A 2.0 mL sample loop introduced substrate 1a (0.100 M), acrylonitrile (0.200 M) and iridium photocatalyst (0.500 mM) into the carrier stream at 0.020 mL min−1. The first-stage nominal liquid times were consequently 100 and 250 min. Pure oxygen entered at the interstage mixer at a controller setting of 0.090 mL min−1. Under the proposal's STP convention (273.15 K, 1 atm), this corresponds to 0.00402 mmol min−1 of oxygen, or 2.01 equivalents against the nominal substrate feed. The displayed second-stage index of 181.82 min uses inlet-reference gas volume, 20/(0.020 + 0.090); it is not the residence time at reactor pressure. ESI Section 8 distinguishes these nominal calculations from the experimental gas-reference and sample-collection metadata.


Implementation revealed an additional constraint that stoichiometry alone did not capture. An initial trial with pure oxygen at 0.43 mL min−1 and liquid at 0.020 mL min−1 showed gas backflow toward the first reactor. We specified pure oxygen in the revised design inputs and reduced the gas setting to 0.090 mL min−1; the gas choice was researcher-directed, not an autonomous discovery by the model. The proposal included a gas-line check valve, although that component alone does not establish protection of the upstream liquid branch. With a 7 bar cartridge BPR and recorded system pressures of 5.1–5.6 bar, the implemented 2 mL first-stage configuration, reported jointly for Sets 1/3, gave 97% yield, whereas the 5 mL configuration associated with Set 2 gave 98%. These are NMR yields, compared contextually with the published flow yield of 90%.[57] Both operating points supported the connected transformation; the one-percentage-point difference does not resolve a residence-time benefit without replicates. Table S17 and Figures S19–S20 document the conditions, irradiation and apparatus. The case demonstrates why spatial reaction design, quantitative gas delivery and observations from the assembled apparatus must be considered together.

a Two-stage photoredox sequence



Acrylonitrile (2 equiv), Ir photocatalyst (0.5 mol%); EtOH / pH 9 buffer (5:1).

b Connected configuration implemented at KHU




25 ± 1 °C | 2 mL sample loop | O_2 introduced only after R1

c Operating points and yield

KHU set(s)	R1 time min	R2 time* min	Pressure bar
1 / 3	100	181.8	5.1–5.4
2	250	181.8	5.2–5.6

Yield (%)



*R2 is an inlet/STP time index, not operating-pressure residence time.

Figure 5. *Photoredox Giese addition/oxidation from chemistry to laboratory implementation. (a) Precursor 1a is converted through sulfide 3a to sulfoxide 4a. (b) Connected equipment arrangement; oxygen is introduced after R1. Feed A contains 0.100 M 1a, 0.200 M acrylonitrile and 0.500 mM iridium photocatalyst. The process schematic is not a piping or safety-certification diagram. (c) Implemented operating points and yield, with the literature flow reference from Park et al.[57] All plotted yields are determined by ^{1}H NMR; grouped Sets 1/3 are one supplied result entry, not independent repeats. R1 time is V/Qliquid. The R2 value is the nominal inlet/STP index V/(Qliquid + Qgas,STP), not residence time under operating pressure. The MFC reference state requires confirmation. Literature and present experiments used different conditions.*


Coupled feed and residence-time design for telescoped amidation

The second case tests a different form of stage coupling: formation and downstream consumption of a reactive intermediate (Figure 6). 3-Methyl-4-nitrobenzoic acid is activated by 2,2′-dipyridyldithiocarbonate (DPDTC) in the presence of DMAP to form a 2-pyridyl thioester; benzylamine then undergoes aminolysis to give the amide.[58] The batch procedure uses two 30 min periods at 95 °C, separated by cooling and amine addition. For continuous operation, FlowPilot must distinguish a necessary chemical sequence from a batch-handling operation: benzylamine must enter after activation, whereas cooling need not be reproduced automatically if direct transfer can be implemented. The three response sets emphasized integrated yield, conversion-focused timing and throughput, respectively, while preserving this chemistry and the intended feed stoichiometry (ESI Section 7).

We implemented separate activation and amine feeds using two channels of the same Vapourtec E-series system, with direct interstage mixing and no intermediate isolation. Feed A contained acid (0.500 M), DPDTC (0.525 M) and DMAP (0.0500 M) in 2-MeTHF; Feed B contained benzylamine (2.10 M). For Set 1, liquid rates of 0.160 and 0.0400 mL min−1 delivered nominal acid and amine molar flows of 0.0800 and 0.0840 mmol min−1, preserving 1.05 equivalents of amine. Two 5 mL ETFE coils gave nominal times of 31.25 and 25.00 min, because the downstream coil receives both liquid feeds. This distinction is central to the design: specifying two reactor times without updating the downstream material balance would not preserve the proposed stoichiometry and exposure. The implementation used a 2.0 mL sample loop for Feed A, a 95 °C water bath for both coils and a 7 bar cartridge BPR; recorded pressure for Set 1 was 5.2–5.3 bar.


Set 1 gave 86% yield. Sets 2/3 shared a second implemented configuration: a 10 mL first coil and a 5 mL second coil, with feed rates of 0.280 and 0.0700 mL min−1, stage times of 35.71 and 14.29 min, and 68% yield. Both outcomes and the 98% literature batch reference are NMR yields.[58] The second configuration increased nominal substrate delivery from 0.0800 to 0.140 mmol min−1 and reduced total nominal time from 56.25 to 50.00 min, but redistributed exposure toward the activation stage and away from amidation. The lower yield at this operating point, despite its longer nominal first-stage time, shows that neither upstream exposure nor total nominal time alone explains the outcome. The observations motivate further examination of the downstream exposure and intermediate composition, but do not identify a rate-limiting step because several variables changed together. Table S18 and Figure S21 report the conditions and apparatus; Tables S19–S20 connect the proposals to implementation changes and component molar feeds. Together with the photochemical case, this experiment shows the role of FlowPilot in formulating testable, connected process choices whose chemical performance remains subject to measurement.

a Telescoped activation and amidation



DPDTC (1.05 equiv), DMAP (10 mol%), benzylamine (1.05 equiv); 2-MeTHF.

b Connected configuration implemented at KHU




Two E-series pump channels | 2 mL sample loop | No intermediate isolation

c Operating points and yield

KHU set(s)	R1 time min	R2 time min	Pressure bar
1	31.25	25.00	5.2–5.3
2 / 3	35.71	14.29	5.5–5.8

Yield (%)



Stage times use V_1/Q_A and $V_2/(Q_A + Q_B)$, respectively.

Figure 6. *DPDTC-mediated amidation from reaction sequence to connected operation. (a) Acid 1b is activated to a 2-pyridyl thioester and undergoes aminolysis to amide 3b. (b) Two heated ETFE coils receive acid/DPDTC/DMAP in Feed A (0.500/0.525/0.0500 M) and benzylamine in Feed B (2.10 M), added between the stages. (c) Implemented operating points and yield, with the literature batch reference from Saunders et al.[58] All plotted yields are determined by ^{1}H NMR. Sets 2/3 share one supplied result entry. Stage times use V1/QA and V2/(QA + QB); recorded pressures are distinct from the 7 bar BPR cartridge rating. The literature reference is contextual rather than a matched flow-control experiment.*

DISCUSSION

The central contribution of FlowPilot is to make the connected flow process, rather than an isolated reaction condition, the object of agentic design. A researcher can begin with a conventional procedure and a laboratory inventory, express a design priority, and inspect alternative configurations in terms of chemistry, quantitative operation and realizable equipment. This complements microreactor assistants, synthesis-development platforms and process-simulation agents by organizing their related capabilities around a laboratory-specific design task.[46-51,59-60] Linking these steps allows a proposed operating point to be examined together with its chemical rationale and hardware requirements, rather than as a detached recommendation.

The benchmark helps explain why this organization matters. The same generator produced higher mean scores within FlowPilot for all five models, and improvements extended to topology, material balance and inventory rather than being confined to chemical nomenclature. In the module screen, simply separating the initial workflow into stages without council review performed poorly, whereas coordinated review recovered much of the design quality. At the same time, simpler council settings occasionally matched or exceeded the complete configuration. These findings argue for selective, accountable review of coupled decisions rather than maximizing agent count or discussion length. They also identify a practical opportunity for locally served models: the tested 27B generators delivered competitive assessed designs when supported by the architecture, although additional computation is part of that benefit.

The experiments address a different question from the benchmark: what happens when a proposed configuration becomes an apparatus and the complete reaction sequence is tested? For Giese addition/oxidation, separating oxygen exposure spatially enabled the connected chemistry, but the backflow observation exposed a pressure-interaction problem not settled by gas-equivalent arithmetic. For amidation, feed stoichiometry and stage allocation were coupled, and the higher nominal substrate feed gave lower yield despite longer upstream exposure. The response sets thus provided alternative starting priorities rather than a guarantee of distinct or improved experimental outcomes. The sample-loop implementations establish product formation at the reported conditions; they should not be interpreted as measurements of sustained production or as a controlled comparison of all three objectives.

A useful design assistant must consequently retain both the rationale for a proposal and the evidence that later challenges it. FlowPilot's saved inputs, stage calculations, equipment assignments and council records support this relationship between researcher and model, while the remaining design defects and evaluator false positive show why neither model confidence nor a benchmark score should substitute for

scientific judgment. Experimental observations can be returned with the conditions actually used, so that subsequent proposals respond to measured process behavior rather than repeated assumptions. Coupling this record to Bayesian optimization or language-guided experimental priors offers a route to more systematic prospective refinement.[30-34,61] The next test of that workflow is whether it reduces experimental effort across additional chemistries and inventories, not merely whether it produces a more persuasive initial answer.

CONCLUSION

FlowPilot provides an agentic design environment in which researchers can develop continuous-flow processes from reaction-level information and the equipment available in their laboratory. Standardized interaction defines the problem; literature and handbook knowledge inform the alternatives; and council review with engineering calculations connects chemical intent to feeds, stage conditions and a realizable process configuration. The shared design record makes these decisions inspectable and provides continuity between a proposal and the next experimental cycle.

Across the five-model architecture comparison, the mean benchmark score increased from 0.794 for one-shot generation to 0.917 for FlowPilot, with fewer judge-reported critical flags. The internal screen supports the role of coordinated review while showing that additional refinement is not uniformly beneficial. Laboratory implementation then demonstrated the connected Giese addition/oxidation and amidation sequences at 97–98% and 68–86% NMR yield, respectively. The gas-flow observations and yield differences between operating points reveal the importance of testing the complete process, beyond checking the consistency of its description.

These results position FlowPilot as a partner in researcher-led process development: it organizes the design decisions that must agree, exposes assumptions for review and retains measured outcomes for further refinement. Its value is not to replace experimentation with a generated protocol, but to connect chemical knowledge, engineering design and laboratory implementation within one accountable workflow.

METHODS

Standardized inputs and study organization

The standardized workflow begins with a batch protocol and a structured intake package recording the objective, chemistry identity, experimental history, laboratory inventory, operating limits, and chemist

hypotheses. Deterministic protocol triggers activate questions from a versioned bank of stable identifiers, and confirmed package state determines which remain pending. The LLM extracts and interprets answers but cannot introduce new identifiers or override readiness. Information such as historical evidence can be explicitly marked unavailable; conditional gas, irradiation and stage questions follow the resolution rules in Table S3. The confirmed package is frozen for the run, retaining the answers and their provenance. Measured observations, protocol facts, and hypotheses are stored separately. Hard safety and equipment constraints remain mandatory even when earlier measurements were obtained under different conditions. Computational comparisons used archived case packages rather than newly generated conversations, keeping the supplied chemistry and constraints constant between architectures. The intake contract and question rules are given in ESI Section 2 and Tables S2–S3. Benchmark campaigns and subsequent laboratory-design runs were treated as distinct software/configuration records; the dated development history is summarized in the companion version-history record.

Literature corpus and plan-aware retrieval

The literature resource comprised 464 classified flow-chemistry records annotated with available reaction, reactor, material, operating-condition, yield, and inlet-stream information. Missing metadata were retained as missing rather than filled from model inference. A complementary handbook-derived store contained 2,537 engineering rules with topic, severity, source, and applicability information.[3-4,21] Relevant rules supplied context to chemistry interpretation; only checks implemented in the calculation and validation routines acted as deterministic constraints. Field completeness and rule coverage are reported in Table S4.

For operational retrieval, the chemistry plan supplies reaction class, mechanism, catalyst, solvent, phase regime, and operating conditions. The search begins with paired batch-flow records under mechanism and phase filters, relaxes filters when fewer than three candidates remain, and expands to the full corpus when no paired result remains. The final score combines semantic and field similarity with weights of 0.60 and 0.40. The operational field components and weights are listed in Table S5. In the architecture benchmark, the designated source record was excluded before final retrieval selection; this restriction does not establish absence from model pretraining.

The retrospective figure analyses used stored corpus embeddings and inverse Euclidean-distance similarity, $1/(1 + d)$, rather than newly generated query embeddings. The rank analysis reranked the 20 nearest non-self records for 80 queries using photocatalyst, solvent, and wavelength terms weighted 0.30, 0.20, and 0.20; temperature and concentration were not included in that offline score. A separate family analysis sampled up to 15 queries per recorded family and measured the fraction of matching-family

records in each top-five result set. Its 56 queries and script-specific similarity functions are documented in ESI Section 3.2 and Table S6. These analyses measure metadata alignment, not the full live retrieval policy or independent chemical correctness.

Engineering calculations and stage accounting

The engineering layer recalculated quantities dependent on proposed operating choices. Component molar delivery was obtained from concentration and liquid volumetric flow, and each stage received the cumulative flow of the streams introduced at or upstream of that stage. For a nominal liquid-filled reactor, the stage time was calculated as reactor volume divided by local liquid flow. An interstage feed therefore changed the downstream material balance and time calculation without changing the upstream flow. Packed-bed empty volume, estimated liquid holdup, and catalyst-contact time were distinguished where applicable. Stage totals were formed only from times reported on compatible bases.

Gas equivalents were calculated from the reactive-gas molar flow divided by the limiting-reactant molar flow, including gas composition and the stated reference temperature and pressure. The proposal STP convention was 273.15 K and 1 atm. Where required by a benchmark contract, in-channel gas volume was derived by ideal-gas scaling using absolute operating pressure and temperature. The inlet-reference index V/(Qliquid + Qgas,STP) was kept separate from pressure-corrected nominal time and from measured residence time. Ideal-gas correction alone does not determine liquid holdup or residence-time distribution; a no-slip estimate additionally neglects phase slip, gas dissolution or consumption, and axial pressure variation. Pressure-loss and thermal screening used the selected geometry, phase assumptions, and available material properties; estimated heat-transfer or reaction-enthalpy inputs were identified as assumptions. The implemented quantities, multiphase conventions, and heat-transfer screening are detailed in ESI Section 5 and Table S12.

Candidate generation and council review

The downstream Designer generated alternative geometries and operating choices from the chemistry plan, retrieved analogies, engineering calculations, and inventory constraints. The Chemistry, Kinetics, Fluidics, and Safety specialists reviewed chemical compatibility, reaction-time plausibility, transport and hardware feasibility, and hazards, respectively. The Skeptic examined assumptions and contradictions, and the Orchestrator selected among the reviewed candidates. Agent verdicts and proposed revisions were stored with candidate identifiers. Changes to independent variables triggered deterministic recalculation before a candidate could be compared or published. Candidate and revision budgets followed the configuration recorded for each campaign rather than being inferred from the final output. Rejected

alternatives and revision history were retained alongside the selected candidate. The component responsibilities are specified in ESI Section 2.1, the ablation configurations in Table S9, and an archived discussion example in ESI Section 6.4.

Inventory realization and result publication

Inventory profiles were entered through categorized equipment forms, imported as structured JSON, or normalized from laboratory documents into typed records with stable identifiers. Available quantities, system membership, material, reactor volume and diameter, pump range and setting increment, pressure and temperature limits, and compatible light modules were recorded where supplied. The form fields share the pipeline's equipment schema, and edited profiles require validation before export or design use. Realization assigned required operations to available items and checked the declared capability and connectivity constraints. Calculations were repeated when equipment selection changed a dependent quantity. An unresolved essential requirement was retained as a diagnostic requirement, not silently replaced with invented hardware (Figure S11; Table S13).

The final design contract reconciled the selected proposal, stage table, stream table, equipment allocation, and topology. GUI numerical views and the executable process diagram were derived from that record; earlier calculations and council exchanges remained separately available for inspection. Timestamped run folders stored the input package, result, final contract, topology, equipment allocation, and available diagram artifacts. Experimental feedback was linked to the conditions actually tested before being supplied to a later design cycle. ESI Sections 2.4–2.5 and 6 document the GUI and saved artifacts, with the machine-readable feedback and provenance records retained in the companion archive. Exact computational replay additionally requires the model, decoding settings, dependencies, and software revision recorded for the campaign.

Matched architecture comparison and LLM judging

The primary comparison used CuAAC, photochemical oxidation, and hydrogenolysis case packages with the same protocol, objective, inventory, and final-output contract for both architectures. One-shot generation received this information in a single call; FlowPilot distributed it across its interpretation, calculation, review, and realization stages. Qwen3.6-27B, Qwen3.8-27B, GPT-4o, Claude Sonnet 4.6, and Claude Opus 4.6 were each used with both architectures for three generation repeats per case, giving 90 outcomes at the recorded generation temperature of 0.2. The archived GPT-5.4 generator results additionally displayed in Figure 4b–c were not included in these five-model aggregates or Tables S10–S11. ESI Section 4 describes the case prompts, inventory limits and model records; the accompanying

frozen-input files retain the exact JSON and complete design-input strings. The comparison concerns delivered design quality under matched task information, not equal token or computation budgets.

For judging, final designs were normalized into candidate packets with generator and architecture labels removed. Separate Qwen, OpenAI, and Claude judge calls received the candidate, common input context, reference facts, deterministic verification evidence, and the fixed 14-criterion rubric. The archived judge configuration used Qwen3.6-27B, GPT-5.4, and Claude Sonnet 4.6 at temperature 0.0; these evaluator calls were separate from candidate generation. Each applicable criterion received an integer rating from 0 to 4. Ratings were averaged across judges for each criterion, then across applicable criteria, and divided by four to give a score from 0 to 1. All judges and applicable criteria had equal weight. Gas bookkeeping and multistage closure could be excluded only when their applicability conditions were false; missing required information was scored rather than treated as inapplicable. Critical flags were counted separately from the numerical score. Deterministic evidence did not confer an architecture-specific bonus, and identity masking did not guarantee that output style concealed the architecture. Some evaluator model families also served as generators; separate calls therefore do not establish statistical independence or remove possible model-family preferences. Scoring anchors, criterion definitions, and applicability rules are specified in Tables S7–S8.

Ablation experiments and statistical reporting

For each generator and architecture, the three case scores were averaged within each repeat. Reported architecture error bars are the sample standard deviation of these three repeat-level means, not the dispersion of all nine individual outcomes. Critical-flag counts were summed across the three cases within a repeat before calculating their mean and sample standard deviation. The aggregate values in Tables S10–S11 use only the five-model cohort. Generation cost was estimated from recorded token usage and the archived model-specific price schedule, excluding evaluator calls and deployment costs. Figure 4e uses mean score divided by mean generation cost; the case-specific ESI plots instead summarize per-outcome score-to-cost ratios (Figure S9). The comparisons are descriptive; no statistical-significance claim or population-wide generalization is made from three repeats and three selected chemistries.

The internal ablation screen fixed the generator to Qwen3.8-27B and tested 15 conditions over the same three cases, producing 45 outcomes with one generation per condition-case pair. The conditions removed or modified council components, revision stages, selection, or candidate budgets. Disabled specialists received no substitute score, and active council weights were renormalized. The resulting standard deviations describe between-case variation, not repeatability; all conditions are reported in Table S9. No experimental yield uncertainty was inferred from these computational repeats.

Laboratory implementation and chemical analysis

We implemented the two connected-stage cases using a Vapourtec E-series system with sample-loop injection. For the Giese addition/oxidation sequence, a PFA coil in a 450 nm UV-150 module was followed by a separately illuminated FEP coil. The first stage was designed to remain oxygen-free, although the exact feed-degassing procedure was not specified in the supplied laboratory methods. Pure oxygen was introduced through an MFC at the interstage mixer, and both reactors were maintained at 25 ± 1 °C. For DPDTC-mediated amidation, the acid/DPDTC/DMAP solution and benzylamine solution were delivered by separate channels, with amine addition between two ETFE coils maintained at 95 °C. Reported concentrations and molar feeds describe the nominal sample solution, not a measured concentration profile throughout the dispersed injection. Both setups used a 7 bar cartridge BPR; recorded system pressure was reported separately from the cartridge rating. Actual concentrations, molar feeds, operating points, and proposal-to-implementation differences are tabulated in ESI Section 8 and Tables S17–S20.

NMR yields were reported using 1,3-benzodioxole as the internal standard. Isolated products were characterized by 1H and 13C NMR spectroscopy and low-resolution mass spectrometry. Shared response-set entries in the supplied laboratory record were treated as grouped operating points, not independent replicates, and no experimental standard deviation was assigned without individual measurements. ESI Section 8 contains the feed preparation, work-up, irradiation specifications, apparatus photographs, and characterization records; Figures S22–S25 reproduce the product spectra. MFC reference-state confirmation, collection windows, and quantitative-NMR calculation records are identified there as outstanding metadata rather than filled by inference.

AUTHOR INFORMATION

Corresponding Authors

*Boyoung Y. Park, E-mail: boyoungy.park@khu.ac.kr; *Gwang-Noh Ahn, E-mail: gnahn@krict.re.kr

Author Contributions

A.M. and M.P. contributed equally to this work. The complete contributor-role statement and approval of the final author list will be confirmed by all authors before submission.

Availability of data and code

Source code is publicly accessible at https://github.com/armtfgh/flowpilot. Benchmark scripts and the data-access index are available at https://github.com/armtfgh/flowpilot/tree/master/ablation_test and https://github.com/armtfgh/flowpilot/tree/master/ablation_results, respectively. The latter is currently an index, not the complete outcome archive. The ESI contains the reported numerical summaries, experimental procedures, and characterization spectra. As of 29 September 2026, the repository is public but has no tagged manuscript release; the complete benchmark archive, raw experimental analytical files, and a persistent data DOI have not yet been deposited. These release items remain to be completed before submission.

ACKNOWLEDGMENT

This work was supported by the Strategic Research Program ("Accelerated Scale-up of Advanced Materials via Autonomous Experimental Systems", DK2685-01) of the National Research Council of Science & Technology (NST), funded by the Ministry of Science and ICT (MSIT) of the Republic of Korea, and by the Research Program of the Korea Research Institute of Chemical Technology (KRICT) (KK2651-10 and BSK26-118). This work was also supported by the National Research Foundation of Korea (NRF) grant funded by the Korea government (MSIT) (RS-2026-25594673).

ABBREVIATIONS

BPR, back-pressure regulator; CuAAC, copper(I)-catalyzed azide–alkyne cycloaddition; DPDTC, 2,2′-dipyridyldithiocarbonate; DMAP, 4-(dimethylamino)pyridine; Da, Damköhler number; ETFE, ethylene tetrafluoroethylene; FEP, fluorinated ethylene propylene; IF, intensification factor; LLM, large language model; LRMS, low-resolution mass spectrometry; MFC, mass flow controller; 2-MeTHF, 2-methyltetrahydrofuran; NMR, nuclear magnetic resonance; Pe, Péclet number; PFA, perfluoroalkoxy; PFD, process flow diagram; PTFE, polytetrafluoroethylene; RAG, retrieval-augmented generation; Re, Reynolds number; STP, standard temperature and pressure (273.15 K and 1 atm for the proposal calculations); STY, space-time yield.

REFERENCES

(1) Rossetti, I.; Compagnoni, M. Chemical Reaction Engineering, Process Design and Scale-up Issues at the Frontier of Synthesis: Flow Chemistry. *Chem. Eng. J.* 2016, *296*, 56–70. https://doi.org/10.1016/j.cej.2016.02.119.

(2) Feng, K.; Zhu, Y.-Y.; Gu, S.; Long, J.; Wang, H.-F. Typical Cases of Continuous Flow Chemistry in Pharmaceutical Synthesis in 2023-2024. *Asian J. Org. Chem.* 2025, *14*, e202500132. https://doi.org/10.1002/ajoc.202500132.

(3) Capaldo, L.; Wen, Z.; Noël, T. A Field Guide to Flow Chemistry for Synthetic Organic Chemists. *Chem. Sci.* 2023, *14* (16), 4230–4247. https://doi.org/10.1039/D3SC00992K.

(4) Plutschack, M. B.; Pieber, B.; Gilmore, K.; Seeberger, P. H. The Hitchhiker's Guide to Flow Chemistry. *Chem. Rev.* 2017, *117* (18), 11796–11893. https://doi.org/10.1021/acs.chemrev.7b00183.

(5) Cambié, D.; Bottecchia, C.; Straathof, N.; Hessel, V.; Noël, T. Applications of Continuous-Flow Photochemistry in Organic Synthesis, Material Science, and Water Treatment. *Chem. Rev.* 2016, *116* (17), 10276–10341. https://doi.org/10.1021/acs.chemrev.5b00707.

(6) Padoin, N.; Matiazzo, T.; Riella, H.; Soares, C. A Perspective on the Past, the Present, and the Future of Computational Fluid Dynamics (CFD) in Flow Chemistry. *J. Flow Chem.* 2024, *14*, 239–256. https://doi.org/10.1007/s41981-024-00313-4.

(7) Movsisyan, M.; Delbeke, E.; Berton, J.; Battilocchio, C.; Ley, S.; Stevens, C. Taming Hazardous Chemistry by Continuous Flow Technology. *Chem. Soc. Rev.* 2016, *45* (18), 4892–4928. https://doi.org/10.1039/c5cs00902b.

(8) Yasukawa, T.; Kobayashi, S. Translation of Batch to Continuous Flow in Photoredox Reactions. *ACS Cent. Sci.* 2021, 7 (7), 1099–1101. https://doi.org/10.1021/acscentsci.1c00711.

(9) Noël, T.; Cao, Y.; Laudadio, G. The Fundamentals Behind the Use of Flow Reactors in Electrochemistry. *Acc. Chem. Res.* 2019, *52*, 2858–2869. https://doi.org/10.1021/acs.accounts.9b00412.

(10) Gemoets, H.; Su, Y.; Shang, M.; Hessel, V.; Luque, R.; Noël, T. Liquid Phase Oxidation Chemistry in Continuous-Flow Microreactors. *Chem. Soc. Rev.* 2016, *45* (1), 83–117. https://doi.org/10.1039/c5cs00447k.

(11) Wegner, J.; Ceylan, S.; Kirschning, A. Flow Chemistry – A Key Enabling Technology for (Multistep) Organic Synthesis. *Adv. Synth. Catal.* 2012, *354*, 17–57. https://doi.org/10.1002/adsc.201100584.

(12) Plouffe, P.; Macchi, A.; Roberge, D. From Batch to Continuous Chemical Synthesis—A Toolbox Approach. *Org. Process Res. Dev.* 2014, *18*, 1286–1294. https://doi.org/10.1021/op5001918.

(13) Ingham, R. J.; Battilocchio, C.; Fitzpatrick, D. E.; Sliwinski, E.; Hawkins, J. M.; Ley, S. V. A Systems Approach Towards an Intelligent and Self-Controlling Platform for Integrated Continuous Reaction Sequences. *Angew. Chem. Int. Ed.* 2015, *54* (1), 144–148. https://doi.org/10.1002/anie.201409356.

(14) Adamo, A.; Beingessner, R. L.; Behnam, M.; Chen, J.; Jamison, T. F.; Jensen, K. F.; Monbaliu, J.-C. M.; Myerson, A. S.; Revalor, E. M.; Snead, D. R.; Stelzer, T.; Weeranoppanant, N.; Wong, S. Y.; Zhang, P. On-Demand Continuous-Flow Production of Pharmaceuticals in a Compact, Reconfigurable System. *Science* 2016, *352* (6281), 61–67. https://doi.org/10.1126/science.aaf1337.

(15) Holtze, C.; Boehling, R. Batch or Flow Chemistry? – A Current Industrial Opinion on Process Selection. *Curr. Opin. Chem. Eng.* 2022, *36*, 100798. https://doi.org/10.1016/j.coche.2022.100798.

(16) Glasnov, T. N.; Kappe, C. O. The Microwave-to-Flow Paradigm: Translating High-Temperature Batch Microwave Chemistry to Scalable Continuous-Flow Processes. *Chem. Eur. J.* 2011, *17* (43), 11956–11968. https://doi.org/10.1002/chem.201102065.

(17) Zhang, J.; Wang, K.; Teixeira, A.; Jensen, K.; Luo, G. Design and Scaling Up of Microchemical Systems: A Review. *Annu. Rev. Chem. Biomol. Eng.* 2017, *8*, 285–305. https://doi.org/10.1146/annurev-chembioeng-060816-101443.

(18) An, H.; Li, A.; Sasmito, A. P.; Kurnia, J. C.; Jangam, S. V.; Mujumdar, A. S. Computational Fluid Dynamics (CFD) Analysis of Micro-Reactor Performance: Effect of Various Configurations. *Chem. Eng. Sci.* 2012, *75*, 85–95. https://doi.org/10.1016/j.ces.2012.03.004.

(19) Ripken, R. M.; Wood, J. A.; Schlautmann, S.; Günther, A.; Gardeniers, H. J. G. E.; Le Gac, S. Towards Controlled Bubble Nucleation in Microreactors for Enhanced Mass Transport. *React. Chem. Eng.* 2021, *6* (10), 1869–1877. https://doi.org/10.1039/D1RE00092F.

(20) Mielke, E.; Plouffe, P.; Koushik, N.; Eyholzer, M.; Gottsponer, M.; Kockmann, N.; Macchi, A.; Roberge, D. M. Local and Overall Heat Transfer of Exothermic Reactions in Microreactor Systems. *React. Chem. Eng.* 2017, *2* (5), 763–775. https://doi.org/10.1039/C7RE00085E.

(21) Guidi, M.; Seeberger, P. H.; Gilmore, K. How to Approach Flow Chemistry. *Chem. Soc. Rev.* 2020, *49* (24), 8910–8932. https://doi.org/10.1039/C9CS00832B.

(22) Mallia, C. J.; Baxendale, I. R. The Use of Gases in Flow Synthesis. *Org. Process Res. Dev.* 2016, *20* (2), 327–360. https://doi.org/10.1021/acs.oprd.5b00222.

(23) Chauhan, R.; Rana, A.; Mottafegh, A.; Kim, D. P.; Singh, A. K. Manual to Auto-Optimization Platform of Multistep Apixaban Synthesis. *Organic Process Research & Development* 2025, *29* (3), 881-888. https://doi.org/10.1021/acs.oprd.4c00535.

(24) Aand, D.; Rana, A.; Mottafegh, A.; Kim, D. P.; Singh, A. K. Autonomous closed-loop photochemical reaction optimization for the synthesis of various angiotensin II receptor blocker molecules. *Reaction Chemistry & Engineering* 2024, *9* (9), 2427-2435. https://doi.org/10.1039/D4RE00138A.

(25) Tu, Z.; Choure, S.; Fong, M. H.; Roh, J.; Levin, I.; Yu, K.; Joung, J.; Morgan, N.; Li, S.-C.; Sun, X.; Lin, H.; Murnin, M.; Liles, J.; Struble, T.; Fortunato, M.; Liu, M.; Green, W.; Jensen, K.; Coley, C. ASKCOS: Open-Source, Data-Driven Synthesis Planning. *Acc. Chem. Res.* 2025, *58* (11), 1764–1775. https://doi.org/10.1021/acs.accounts.5c00155.

(26) Coley, C.; Green, W.; Jensen, K. Machine Learning in Computer-Aided Synthesis Planning. *Acc. Chem. Res.* 2018, *51* (5), 1281–1289. https://doi.org/10.1021/acs.accounts.8b00087.

(27) Hartog, P.; Westerlund, A.; Tetko, I.; Genheden, S. Investigations into the Efficiency of Computer-Aided Synthesis Planning. *J. Chem. Inf. Model.* 2025, *65* (4), 1771–1781. https://doi.org/10.1021/acs.jcim.4c01821.

(28) Haydary, J. *Chemical Process Design and Simulation*; Wiley: **2018**. https://doi.org/10.1002/9781119311478.

(29) Reynoso-Donzelli, S.; Ricardez-Sandoval, L. A Reinforcement Learning Approach with Masked Agents for Chemical Process Flowsheet Design. *AIChE J.* 2025, *71* (1), e18584. https://doi.org/10.1002/aic.18584.

(30) Mottafegh, A.; Joo, J.-U.; Na, G.-S.; Sharma, V.; Kim, D.-P. AI-Assisted Autonomous Manufacturing of Tailored Drug-Loaded Nanoparticles by Multi-Step Continuous-Flow Platform. *Chem. Eng. J.* 2024, *500*, 157454. https://doi.org/10.1016/j.cej.2024.157454.

(31) Dunlap, J.; Ethier, J.; Putnam-Neeb, A.; Iyer, S.; Luo, S.-X. L.; Feng, H.; Torres, J. G.; Doyle, A.; Swager, T.; Vaia, R.; Mirau, P.; Crouse, C.; Baldwin, L. Continuous Flow Synthesis of Pyridinium Salts Accelerated by Multi-Objective Bayesian Optimization with Active Learning. *Chem. Sci.* 2023, *14*, 8061–8069. https://doi.org/10.1039/d3sc01303k.

(32) Ahn, G.-N.; Kang, J.-H.; Lee, H.-J.; Park, B. E.; Kwon, M.; Na, G.-S.; Kim, H.; Seo, D.-H.; Kim, D.-P. Exploring Ultrafast Flow Chemistry by Autonomous Self-Optimizing Platform. *Chem. Eng. J.* 2023, *453*, 139707. https://doi.org/10.1016/j.cej.2022.139707.

(33) Mottafegh, A.; Ahn, G.-N.; Kim, D.-P. Meta Optimization Based on Real-Time Benchmarking of Multiple Surrogate Models for Autonomous Flow Synthesis. *Lab. Chip* 2023, *23* (6), 1613–1621. https://doi.org/10.1039/D2LC00938B.

(34) Jorayev, P.; Soritz, S.; Sung, S.; Jeraal, M.; Russo, D.; Barthelme, A.; Toussaint, F.; Gaunt, M.; Lapkin, A. Machine Learning-Driven Optimization of Continuous-Flow Photoredox Amine Synthesis. *Org. Process Res. Dev.* 2025, *29*, 1411–1422. https://doi.org/10.1021/acs.oprd.4c00533.

(35) Coley, C. W.; Thomas III, D. A.; Lummiss, J. A. M.; Jaworski, J. N.; Breen, C. P.; Schultz, V.; Hart, T.; Fishman, J. S.; Rogers, L.; Gao, H.; Hicklin, R. W.; Plehiers, P. P.; Byington, J.; Piotti, J. S.; Green, W. H.; Hart, A. J.; Jamison, T. F.; Jensen, K. F. A Robotic Platform for Flow Synthesis of Organic Compounds Informed by AI Planning. *Science* 2019, *365* (6453), eaax1566. https://doi.org/10.1126/science.aax1566.

(36) Pilon, S.; Savino, E.; Bayley, O. M.; Vanzella, M.; Claros, M.; Siasiaridis, P.; Liu, J.; Lukas, F.; Damian, M.; Tseliou, V.; Intini, N.; Slattery, A.; SanJosé-Orduna, J.; den Hartog, T.; Peters, R. A. H.; Gargano, A. F. G.; Mutti, F. G.; Noël, T. A flexible and affordable self-driving laboratory for automated reaction optimization. *Nature Synthesis* 2026, advance online publication. https://doi.org/10.1038/s44160-026-01053-0.

(37) Chauhan, R.; Mottafegh, A.; Rana, A.; Singh, A. K. UV-visible Auto-Reactometry enabled parallel screening for accelerating chemical synthesis development with LLM. *Chemical Engineering Journal* 2026, *533*, 174829. https://doi.org/10.1016/j.cej.2026.174829.

(38) M. Bran, A.; Cox, S.; Schilter, O.; Baldassari, C.; White, A. D.; Schwaller, P. Augmenting Large Language Models with Chemistry Tools. *Nat. Mach. Intell.* 2024, *6* (5), 525–535. https://doi.org/10.1038/s42256-024-00832-8.

(39) Boiko, D. A.; MacKnight, R.; Kline, B.; Gomes, G. Autonomous Chemical Research with Large Language Models. *Nature* 2023, *624* (7992), 570–578. https://doi.org/10.1038/s41586-023-06792-0.

(40) Zou, Y.; Cheng, A. H.; Aldossary, A.; Bai, J.; Leong, S. X.; Campos-Gonzalez-Angulo, J. A.; Choi, C.; Ser, C. T.; Tom, G.; Wang, A.; Zhang, Z.; Yakavets, I.; Hao, H.; Crebolder, C.; Bernales, V.; Aspuru-Guzik, A. El Agente: An Autonomous Agent for Quantum Chemistry. *Matter* 2025, *8* (7), 102263. https://doi.org/10.1016/j.matt.2025.102263.

(41) Gottweis, J.; Weng, W.-H.; Daryin, A.; Tu, T.; Sirkovic, P.; Myaskovsky, A.; Glowaty, G.; Weissenberger, F.; Orlandi, A.; Popovici, D.; Palepu, A.; Rong, K.; Tanno, R.; Saab, K.; Zhang, F.; Blum, J.; Carroll, A.; Kulkarni, K.; Tomašev, N.; Zverinski, D.; Rendulic, I.; Vedadi, E.; Hasler, F.; Rimanic, L.; Boia, M.; Budiselic, I.; Feinstein, B.; Bellaiche, M.; Sheffer, T.; Freyberg, J.; Ratcliff, J.; Bertolli, O.; Chou, K.; Hassidim, A.; Gokturk, B.; Vahdat, A.; Guan, Y.; Dhillon, V.; Vaishnav, E. D.; Lee, B.; Costa, T. R. D.; Penadés, J. R.; Peltz, G.; Matias, Y.; Manyika, J.; Hassabis, D.; Xu, Y.; Kohli, P.; Pawlosky, A.; Karthikesalingam, A.; Natarajan, V. Accelerating scientific discovery with Co-Scientist. *Nature* 2026, *655* (8122), 487-496. https://doi.org/10.1038/s41586-026-10644-y.

(42) Miao, J.; Davis, J. R.; Zhang, Y.; Pritchard, J. K.; Zou, J. Reimagining research papers as interactive and reliable AI agents. *Nature* 2026, advance online publication. https://doi.org/10.1038/s41586-026-11044-y.

(43) Pagel, S.; Jirasek, M.; Cronin, L. Verification and execution of the scientific literature via chemputation augmented by large language models. *Communications Chemistry* 2026, *9* (1), 191. https://doi.org/10.1038/s42004-026-01993-w.

(44) Panapitiya, G.; Saldanha, E.; Job, H.; Hess, O. AutoLabs: cognitive multi-agent systems with self-correction for autonomous chemical experimentation. *Scientific Reports* 2026, *16* (1), 19554. https://doi.org/10.1038/s41598-026-45593-z.

(45) Hsu, B.; Setty, P. V.; Butler, R. M.; Lewis, R.; Stone, C.; Weinberg, R.; Brettin, T.; Stevens, R.; Foster, I.; Ramanathan, A. PRISM: protocol refinement through intelligent simulation modeling. *Digital Discovery* 2026, *5* (6), 2613-2628. https://doi.org/10.1039/D6DD00004E.

(46) Pan, Y.; Xiao, Q.; Zhao, F.; Li, Z.; Liu, J.; Ullah, S.; Lim, K. H.; Huang, T.; Yu, Z.; Li, C.; Zhang, D.; Xue, Q.; Chen, Q.; Kawi, S.; Wang, Y.; Luo, G. Chat-microreactor: A large-language-model-based assistant for designing continuous flow systems. *Chemical Engineering Science* 2025, *311*, 121567. https://doi.org/10.1016/j.ces.2025.121567.

(47) Wang, Q.; Wang, Y.; Gong, X. An LLM-Based Intelligent Agent and Its Application in Making the Lanolin Saponification Process Greener. *Pharmaceuticals* 2026, *19* (2), 264. https://doi.org/10.3390/ph19020264.

(48) Ruan, Y.; Lu, C.; Xu, N.; He, Y.; Chen, Y.; Zhang, J.; Xuan, J.; Pan, J.; Fang, Q.; Gao, H.; Shen, X.; Ye, N.; Zhang, Q.; Mo, Y. An automatic end-to-end chemical synthesis development platform powered by large language models. *Nature Communications* 2024, *15* (1), 10160. https://doi.org/10.1038/s41467-024-54457-x.

(49) Tian, X.; Du, W.; Yang, S.; Hu, H.; Xin, H.; Qu, S.; Ye, K. From Text to Simulation: A Multi-Agent LLM Workflow for Automated Chemical Process Design. *Proceedings of the AAAI Conference on Artificial Intelligence* 2026, *40* (35), 29705-29713. https://doi.org/10.1609/aaai.v40i35.40215.

(50) Yang, Y.; Li, R.; Ma, J.; Zhang, K.; Liu, Q.; Han, J.; Bu, Y.; Zhou, J.; Lian, D.; Li, X.; Chen, E. CeProAgents: A Hierarchical Agents System for Automated Chemical Process Development. *arXiv* 2026, 2603.01654v1. Preprint. https://arxiv.org/abs/2603.01654v1.

(51) Zhang, T. Harness as an Asset: Enforcing Determinism via the Convergent AI Agent Framework (CAAF). *arXiv* 2026, 2604.17025v3. Preprint. https://arxiv.org/abs/2604.17025v3.

(52) Bai, J.; Aldossary, A.; Swanick, T.; Müller, M.; Kang, Y.; Choi, C.; Yoshikawa, N.; Zhang, Z.; Lee, J. W.; Ko, T. W.; Yin, A.; Vakili, M. G.; Crebolder, C.; Bernales, V.; Aspuru-Guzik, A. El Agente Gráfico: A Semantic Execution Runtime for Scientific Agents. *arXiv* 2026, 2602.17902v2. Preprint. https://arxiv.org/abs/2602.17902v2.

(53) Müller, M.; Bai, J.; Gottstein, W.; Mandal, A.; Nazeri, M.; Savino, E.; Fang, Y.; Das, S.; Carrillo, S. P. G.; Kang, Y.; Pérez-Sánchez, J. B.; Pilon, S.; Fitzner, M.; Noël, T.; Gu, F.; Bernales, V.; Aspuru-Guzik, A. La Agente Óptima: Towards Agentic Self-Driving Laboratories. *arXiv* 2026, 2609.04564v1. Preprint. https://arxiv.org/abs/2609.04564v1.

(54) Mirza, A.; Alampara, N.; Kunchapu, S.; Ríos-García, M.; Emoekabu, B.; Krishnan, A.; Gupta, T.; Schilling-Wilhelmi, M.; Okereke, M.; Aneesh, A.; Asgari, M.; Eberhardt, J.; Elahi, A. M.; Elbeheiry, H. M.; Gil, M. V.; Glaubitz, C.; Greiner, M.; Holick, C. T.; Hoffmann, T.; Ibrahim, A.; Klepsch, L. C.; Köster, Y.; Kreth, F. A.; Meyer, J.; Miret, S.; Peschel, J. M.; Ringleb, M.; Roesner, N. C.; Schreiber, J.; Schubert, U. S.; Stafast, L. M.; Wonanke, A. D. D.; Pieler, M.; Schwaller, P.; Jablonka, K. M. A framework for evaluating the chemical knowledge and reasoning abilities of large language models against the expertise of chemists. *Nature Chemistry* 2025, *17* (7), 1027-1034. https://doi.org/10.1038/s41557-025-01815-x.

(55) Ranković, B.; Griffiths, R.-R.; Schwaller, P. Large language models as uncertainty-calibrated optimizers for experimental discovery. *Nature Machine Intelligence* 2026, *8* (9), 1466-1477. https://doi.org/10.1038/s42256-026-01283-z.

(56) Ahn, G.-N.; Shin, J.-A.; Lee, S. Sustainable Continuous Synthesis of 3,5-Disubstituted Isoxazoles: Development of an Integrated Reaction–Separation–Recovery System for Deep Eutectic Solvents. *ACS Sustainable Chem. Eng.* 2025, *13*, 6589–6597. https://doi.org/10.1021/acssuschemeng.5c00580.

(57) Park, J.; Kim, S. H.; Cho, J.-Y.; Atriardi, S. R.; Kim, J.-Y.; Mardhiyah, H.; Park, B. Y.; Woo, S. K. Batch and Flow Synthesis of Sulfides and Sulfoxides Using Green Solvents and Oxidant through Visible-Light Photocatalysis. *Green Chem.* 2025, *27*, 3284–3292. https://doi.org/10.1039/d4gc05769d.

(58) Saunders, J. M.; Oceguera Nava, E.; Li, J.; Wong, M. J.; Freiberg, K. M.; Lipshutz, B. H. Flow-to-Flow Technology: Amide Formation in the Absence of Traditional Coupling Reagents Using DPDTC. *ACS Sustainable Chem. Eng.* 2025, *13*, 6646–6655. https://doi.org/10.1021/acssuschemeng.5c00914.

(59) Zeng, T.; Badrinarayanan, S.; Ock, J.; Lai, C.-K.; Barati Farimani, A. LLM-Guided Chemical Process Optimization with a Multi-Agent Approach. *Mach. Learn. Sci. Technol.* 2025, *6* (4), 045067. https://doi.org/10.1088/2632-2153/ae2382.

(60) Kim, S.; Choi, J.; Jang, K.; Park, J.; Bernales, V.; Aspuru-Guzik, A.; Jung, Y. Materealize: A Multi-Agent Deliberation System for End-to-End Material Design and Synthesis. arXiv 2026, 2601.15743v1. Preprint. https://doi.org/10.48550/arXiv.2601.15743.

(61) Mottafegh, A.; Ahn, G.-N. Adaptive human-in-the-loop optimization using language-guided priors for chemical experiments. *Journal of Chemical Information and Modeling* 2026, *66* (15), 8833-8847. https://doi.org/10.1021/acs.jcim.6c00976.