

Shahjalal University of Science and Technology

Department of Computer Science and Engineering

CSE 400



Fake News Detection in Social Media Using Machine Learning

Students

ARNAB SEN SHARMA
Reg. No.: 2013331017
4th year, 1st Semester

MARUF AHMED MRIDUL
Reg. No.: 2013331015
4th year, 1st Semester

Department of Computer Science and Engineering

Supervisor

MD SAIFUL ISLAM
Assistant Professor
Department of Computer Science and Engineering

18th March, 2018

Fake News Detection in Social Media Using Machine Learning



A Thesis submitted to the Department of Computer Science and Engineering, Shahjalal University of Science and Technology in partial fulfillment of the requirements for the degree of Bachelor of Science in Computer Science and Engineering.

Students

ARNAB SEN SHARMA
Reg. No.: 2013331017
4th year, 1st Semester

MARUF AHMED MRIDUL
Reg. No.: 2013331015
4th year, 1st Semester

Department of Computer Science and Engineering

Supervisor

MD SAIFUL ISLAM
Assistant Professor
Department of Computer Science and Engineering

18th March, 2018

Chapter 3

Data Collection and Preprocessing

3.1 Data Collection

We have not actually collected any dataset ourselves. For experimenting what we have learned so far we have used an open dataset available on GitHub. The dataset is available at [17]. This dataset contains 6335 news articles labeled either 'FAKE' or 'REAL'. These news articles were collected during the time of presidential election of USA,2016. We are really grateful to **GeorgeM-Intire**[18] for such wonderful dataset, which really helped us get started. We used this dataset for training and testing our model.

	title	text	label
Unnamed: 0			
8476	You Can Smell Hillary's Fear	Daniel Greenfield, a Shillman Journalism Fello...	FAKE
10294	Watch The Exact Moment Paul Ryan Committed Pol...	Google Pinterest Digg LinkedIn Reddit Stumbleu...	FAKE
3608	Kerry to go to Paris in gesture of sympathy	U.S. Secretary of State John F. Kerry said Mon...	REAL
10142	Bernie supporters on Twitter erupt in anger ag...	— Kaydee King (@KaydeeKing) November 9, 2016 T...	FAKE
875	The Battle of New York: Why This Primary Matters	It's primary day in New York and front-runners...	REAL

(a)

	title	text	label
Unnamed: 0			
4490	State Department says it can't find emails fro...	The State Department told the Republican Natio...	REAL
8062	The 'P' in PBS Should Stand for 'Plutocratic' ...	The 'P' in PBS Should Stand for 'Plutocratic' ...	FAKE
8622	Anti-Trump Protesters Are Tools of the Oligarc...	Anti-Trump Protesters Are Tools of the Oligar...	FAKE
4021	In Ethiopia, Obama seeks progress on peace, se...	ADDIS ABABA, Ethiopia —President Obama convene...	REAL
4330	Jeb Bush Is Suddenly Attacking Trump. Here's W...	Jeb Bush Is Suddenly Attacking Trump. Here's W...	REAL

(b)

Figure 3.3: An Overview of the Dataset

4.3 Feature Extraction

For now we have used the most common word embedding technique TF-IDF. We used *TfidfVectorizer* of sklearn for this technique. We set `max_df = 0.6` to ignore the word which appear in more than 60% of the datasets. For now we use only article text as our dataset and discard all other information like source of the news.

4.4 Models and Evaluation

We have implemented several models using sklearn. We split our dataset in two parts using sklearn's `test_train_split` such that two third of the dataset was used as training data and rest one third was used as primary evaluation dataset. We have implemented Naive Bayes Tree , SVM , Passive Aggressive Classifier and Random Forest Classifier.

4.4.1 Naive Bayes classifier

We used Multinomial naive Bayes as our naive Bayes classifier. We trained this classifier using our training data and evaluated the classifier with our primary evaluation data which we got by splitting our dataset. This classifier gave us the evaluation score of 84.1%. Below is shown the confusion matrix on the classifiers performance on our primary evaluation dataset.




Figure 4.3: Confusion Matrix of Naive Bayes Classifier

Multinomial Naive Bayes has a parameter α which acts as a additive smoothing parameter. Tuning this α parameter we were able to achieve upto 86.861% accuracy. Below is shown different

accuracy rates against different α values which we were able to achieve for this dataset.

Alpha: 0.00 Accuracy: 0.84422
Alpha: 0.10 Accuracy: 0.86861
Alpha: 0.20 Accuracy: 0.86000
Alpha: 0.30 Accuracy: 0.85761
Alpha: 0.40 Accuracy: 0.85331
Alpha: 0.50 Accuracy: 0.84901
Alpha: 0.60 Accuracy: 0.84757
Alpha: 0.70 Accuracy: 0.84422
Alpha: 0.80 Accuracy: 0.83801
Alpha: 0.90 Accuracy: 0.83227
Alpha: 1.00 Accuracy: 0.82748
Alpha: 1.10 Accuracy: 0.82509
Alpha: 1.20 Accuracy: 0.82414
Alpha: 1.30 Accuracy: 0.82127
Alpha: 1.40 Accuracy: 0.81935




Figure 4.4: Different accuracy rates against different α values

4.4.2 SVM

Now we tried our luck with SVM in the hope of getting a better result. This model took almost 20 minutes to build, almost 10 times the time needed to build the naive Bayes model. But we were very surprised at first to see that during testing all of the news were classified as 'FAKE' and thus achieving a very poor accuracy rate 48.2%.




Figure 4.7: Confusion Matrix of SVM(no parameter tuning) on evaluation dataset

Then we tuned the value of the parameter C, which is the penalty parameter for error term with default value of 1.0. We set it's value to 1000.0 and now the SVM was working better giving us the accuracy of 81.2%. Below is given the confusion matrix.




Figure 4.10: Confusion Matrix of SVM(probability = True , C = 1000.0) on evaluation dataset

We could not get a better result using SVM and the building process of this model is very time




Figure 4.11: Different accuracy rates against different number of trees

Using Random Forest Classifier we got our highest accuracy rate of 88.2%, when we set number of trees to 26. Below is the confusion tree shown for this task.




Figure 4.14: Confusion Matrix of Random Forest Classifier($n_{\text{estimators}} = 26$, criterion = 'entropy') on evaluation dataset

4.4.4 Passive Aggressive Classifier

We actually acquired our highest accuracy rate Passive Aggressive Classifier. After some parameter tuning we got the accuracy rate of 91.2% after setting number of maximum iteration to 50 and random state to 17. Below is given the confusion matrix.




Figure 4.17: Confusion Matrix of Passive Aggressive Classifier(max_iter=50 , random_state = 17) on evaluation dataset.

4.4.5 XGBoost

XGBoost is combination of gradient boosted decision trees. This algorithm is very fast and provides high performance. We got a fair accuracy rate of 81.2% using naive bayes classifier and 88.2% using Random Forest Classifier. So, now we tried XGBoost in our dataset. Using XGBoost we got the accuracy rate of 88.9%. The confusion matrix is given below.




Figure 4.20: Confusion Matrix of XGBoost model on evaluation dataset

Accuracy Graph -




Figure 4.21: Accuracies for different classifiers




Figure 4.24: Confusion Matrix of Passive Aggressive Classifier for Word2Vec approach on evaluation dataset.

The XGBoost worked a bit better, giving us the accuracy rate of 82.5%. Below is the confusion matrix.




Figure 4.27: Confusion Matrix of XGBoost model for Word2Vec approach on evaluation dataset.

We thought Word2Vec mean multiplied with TF-IDF would give us a better result, but unfortunately it didn't.

4.8 Doc2Vec approach

Now we tried our luck with the Doc2Vec model of *gensim*. This Doc2Vec model takes a article or sentence or document and returns a vector. This would be ideal for us. But using this approach we could not get a satisfactory result. Using Doc2Vec vector as a feature Passive Aggressive model would give us a F1-score of 65.5% and XGBoost would give us an F1-score of 64.6% on evaluation dataset. Below is given the confusion matrices.




Figure 4.30: Confusion Matrix of Passive Aggressive Classifier for Doc2Vec approach on evaluation dataset.




Figure 4.33: Confusion Matrix of XGBoost model for Doc2Vec approach on evaluation dataset.

5.4 At a Glance




Figure 5.1: Work-flow of the Proposed Methodology