DIFF at the pivot: transplant progress or transplant the task

Source and destination prompts show exactly where the cached activation is taken from and inserted.

(a) Query transfer

Same instruction · different completed conditions

SOURCE · vowel filtering completed

Keep words that are palindromes and start with a vowel.

```
def func(words: list[str]):
    res = [w for w in words
           if w[0].lower() in "aeiou"]

    return [w for w in res if
```

↑ Prompt ends at the boxed token.

Cache Q at if

↓

Patch Q at if

Selected goal heads

DESTINATION · palindrome filtering completed

Keep words that are palindromes and start with a vowel.

```
def func(words: list[str]):
    res = [w for w in words
           if w == w[::-1]]

    return [w for w in res if
```

↑ Prompt ends at the boxed token.

GOALSCOPE · SUMMARIZED FROM SLIDE 3

Source: palindrome Destination: vowel

Patched destination: palindrome

PATCHED CONTINUATION · SLIDE 3 EXCERPT

```
word == word[::-1] and word.lower() == word.lower()[::-1]]
```

Reported continuation retained, including its repeated palindrome test.

(b) Key/value transfer

Different instructions · shared sorting progress

SOURCE · Python

Return True if the shortest word starts with a vowel.

```
def func(words: list[str]):
    res = sorted(words, key=len)


    return
```

Shared progress: words sorted by length.

Cache task K,V

↓

Patch task K,V

Shaded spans only

DESTINATION · C++

Return True if the longest word is a palindrome.

```
auto func(std::vector<std::string> words){
    std::stable_sort(words.begin(), words.end(),
        /* ascending word-length comparator */);
    return
```

Shared progress: words sorted by length.

GOALSCOPE · SUMMARIZED FROM SLIDE 5

Source: vowel Destination: palindrome

Patched destination: vowel

PATCHED CONTINUATION · SLIDE 5 EXCERPT

```
!words.empty() &&
std::string("aeiouAEIOU").find(words.front()[0])
    != std::string::npos;
```

Q carries which work is done; task K,V supplies what is required. The resulting read selects the next subgoal.

Source: goal-diff.pdf, slides 3 and 5. Prompt excerpts are shortened; readouts are summarized; output excerpts preserve the reported expressions.

Query arrow marks the prefill sites; the slide also reports repeated decode patching. K,V replaces the destination task span, not its code prefix.