Two interventions, one destination prompt

Change the progress query or the task keys/values to change which condition the model implements next.

$G_{src_q} = G_{dst}$; $P_{src_q} \neq P_{dst}$

$G_{src_kv} \neq G_{dst}$; $P_{src_kv} = P_{dst}$

p_{src_q} QUERY DONOR

$G = \{T_1, T_2\}$ $P = \{T_2\}$

Keep words satisfying both conditions:

T_1: the word is a palindrome
T_2: the word starts with a vowel

```
def func(words: list[str]):
    res = [w for w in words
           if w[0] in "aeiou"]

    return [w for w in res if
```

π: final token of the prompt

p_{dst} SHARED DESTINATION

$G = \{T_1, T_2\}$ $P = \{T_1\}$

Keep words satisfying both conditions:

T_1: the word is a palindrome
T_2: the word starts with a vowel

```
def func(words: list[str]):
    res = [w for w in words
           if w == w[::-1]]

    return [w for w in res if
```

π: final token of the prompt

p_{src_kv} TASK DONOR

$G = \{T_1, T_3\}$ $P = \{T_1\}$

Keep words satisfying both conditions:

T_1: the word is a palindrome
T_3: the word has >1 unique characters

```
def func(words: list[str]):
    res = [w for w in words
           if w == w[::-1]]

    return [w for w in res if
```

π: final token of the prompt

$q_{dst} \leftarrow q_{src_q}$

$(K,V)_{dst} \leftarrow (K,V)_{src_kv}$

Read the same destination under three conditions

Clean run

$M(p_{dst})$

T_2 vowel-initial

`w[0] in "aeiou"]`

Query-patched run

$M(p_{dst})$ $[q_{dst} \leftarrow q_{src_q}]$

T_1 palindrome

`w == w[::-1]]`

K/V-patched run

$M(p_{dst})$ $[(K,V)_{dst} \leftarrow (K,V)_{src_kv}]$

T_3 >1 unique characters

`len(set(w)) > 1]`

Schematic continuations · Each patch is applied separately to the same p_dst; the destination text is never replaced.

G: task set; P: completed work; π: pivot. Nonempty lowercase words assumed. Arrows identify activation sites; patch settings belong in the caption.