INTENT BEFORE ACTION: DECODABLE AND STEERABLE SUB-GOAL REPRESENTATIONS IN LLMS

Anonymous authors
Paper under double-blind review

ABSTRACT

When an LLM writes code to satisfy a multi-step specification, does it know *what it intends to do next* before it starts writing? We show that code LLMs encode a compact representation of their next instrumental sub-goal before emitting its implementation, and that this representation is decodable and portable. Using activation patching across programming languages, we localize this encoding to a set of attention heads, which we call the *goal heads*. We introduce GOALSCOPE, a lightweight probe that uses what these heads write to the residual stream to verbalize the upcoming sub-task in natural language. We demonstrate that the encoding is abstract: it can be extracted from one context and reapplied to trigger the same sub-goal in a different programming language. These heads also mediate the model's own implementation: preserving their access to task information largely preserves performance, while restricting that access in a broader set of goal heads sharply impairs it. We replicate the readout and transfer findings across model families and sizes, and explore the same heads' readouts in code without explicitly enumerated sub-tasks and in non-code settings. Our results provide concrete, testable evidence that LLMs encode abstract representations of intermediate goals before realizing them in tokens.

1 INTRODUCTION

arnab: I am using terms like "sub-goal", "intention", ... interchangeably in the intro. We need to come to a consensus on what term to use.

Consider a programmer asked to implement *merge sort*, a task that decomposes into several sub-tasks: *split the array*, *sort the two halves*, and *merge the sorted halves*. Before writing the loop that combines the two sorted arrays, the programmer already has a coherent goal: *"merge the two halves."* We ask whether large language models (LLMs) write code the same way: when an LLM emits a long span of tokens to satisfy a multi-step specification, does it hold an explicit representation of the *next* instrumental sub-goal before it begins its implementation?

We study the *instrumental* level of this hierarchy: the *broader goal* (implement merge sort) decomposes into *instrumental sub-goals* (merge the two sorted arrays), each of which admits many *implementations* (such as using a *for* loop or a *while* loop). Our question concerns a representation of *which sub-goal the model is about to pursue*, and whether that representation can be separated from how it is realized in code.

Although LLMs are trained to predict one token at a time, a growing body of work shows that they *look ahead*: they encode information about tokens they have not yet emitted (Pal et al., 2023) and plan toward constraints several tokens in the future (Lindsey et al., 2025). We ask what the plan for the *next step* looks like as a concrete internal object, and whether that object is one we can read and move between contexts.

We investigate this question through activation patching on code tasks with multiple sub-goals. Our main experiments use `Qwen2.5-Coder-32B-Instruct`, with replications across model families and sizes. Our analysis yields three key findings.

The next sub-goal is encoded before implementation, and is verbalizable (Section 3). We localize the encoding of the LM's next sub-goal to a compact set of attention heads, which we call the *goal heads*. We introduce GOALSCOPE, a lightweight probe built on these heads that verbalizes the upcoming sub-goal directly from the LM's internal activations. Before the model writes the

implementation, we can extract what the heads write to the residual stream and use it to generate a faithful description of the operation it is about to perform.

The encoding is abstract and portable (Section 3.2). Transplanting the encoding steers a fresh code context to pursue the source sub-goal. A goal extracted from Python can trigger the same operation in C++, and vice versa. This portability provides evidence that the heads carry a representation of the operation that generalizes across its surface realizations. We also explore whether the same heads can verbalize sub-goals in code whose component steps are not explicitly listed, and inferred relations in non-code few-shot tasks (Section 6).

Goal heads mediate the model's implementation of the sub-goal (Sections 4 and 5). A small set of heads suffices for effective readout, and a broader set is causally important for carrying out the operation. When we restrict other upper-layer heads' access to the upcoming task and code span, preserving goal-head access largely preserves implementation performance. Conversely, restricting the broader goal-head set to the attention sink sharply reduces performance, while restricting random heads has little effect. The heads attend to relevant task descriptions, and changing their query or key/value states can redirect the sub-goal pursued. Using their value and output projections, we also introduce **OVReader** to trace where the upcoming sub-goal becomes readable in intermediate residual states.

Our results provide concrete, testable evidence that code LLMs represent and pursue intermediate goals: a compact, portable, causally manipulable encoding of *intent* that precedes action.

arnab: Teaser figure: the readout + one steering example, framed as "intent before action".

2 Task and Intervention Setup

2.1 Language models and head contributions

An autoregressive transformer M maps a token prefix $x = (x_1, \ldots, x_n)$ to a distribution over its next token. Write h_t^ℓ for the residual state at layer ℓ and position t. Suppressing normalization and positional encoding, a head's contribution to the residual stream is

$$a_t^{\ell j} = \left(\sum_{i \le t} \mathrm{Attn}(q_t, K)_i v_i \right) W_O^{\ell j}, \qquad \mathrm{Attn}(q_t, K) = \mathrm{softmax}\left(\frac{q_t K^\top}{\sqrt{d_{\mathrm{head}}}} \right). \tag{1}$$

Here queries, keys, and values are learned projections of the normalized residual states; queries and keys additionally receive the model's positional transformation. In grouped-query attention, multiple query heads share a key/value head. We denote an individual head by $[\ell, j]$ and call $a_t^{\ell j}$ its *head contribution*: what the head writes to the residual stream after the output projection.

2.2 Sequential subgoal implementation

A prompt specifies an ordered sequence $G = (g_1, \ldots, g_K)$ of operations on the same input and asks the model to implement them sequentially. For example, a program may be asked to compute the number of digits in an integer and then check whether it is even. We supply the implementation of the first operation and stop at the assignment prefix for the second:

```
def func(n: int):
  a = len(str(abs(n)))
  b =
```

At the final =, the model has yet to write the evenness check. We call this next sub-goal g_k the *frontier*. This setup lets us identify the upcoming assignment and compare its implementation with a readout captured before it is written.

Our main evaluation contains 253 specifications over integers, strings, lists of integers, and lists of strings. Each prompt lists two to four operations, which we refer to as predicates, including Boolean tests, counts, and other transformations. We inspect five positions around the frontier: the end of the preceding line, indentation, the variable name, the assignment operator, and the first implementation token. The first four are pre-implementation capture positions, which we call *pivots*; the fifth provides a comparison after implementation has begun. We use the assignment operator as the principal pivot for the ablation experiments. The corpus supplies 1,265 observations per evaluation mode, with

five repeated measurements per specification. The data distribution, complete example prompt, and tokenization are in Appendices A and C.1.

We use *progress* to denote the completed sub-goals. Under execution in the specified order, these are the prefix $(g_1, \ldots, g_{k-1})$. Later experiments vary the task order and completed work to examine how they influence the next sub-goal.

2.3 Interventions and generation

Activation patching replaces selected activations in a destination run with activations cached from a source run (Vig et al., 2020; Mueller et al., 2026). We write $M(p)[a_t^{\ell j} \leftarrow a_{\text{src}}^{\ell j}]$ for a forward pass on prompt p with a source head contribution substituted at position t.

We use head-output replacement to localize the *goal heads*. For the main GoalScope readout, we sum their source contributions into a single vector and add it to the residual stream of a separate probe run. We also transfer queries and task-span keys and values to examine how goal-head attention selects and accesses task information (Section 5). For each intervention, we specify both the positions patched during prefill and whether the patch is repeated during subsequent decoding.

3 The Next Sub-Goal Is Encoded Before Implementation

Can we read what the model is about to do before it writes the implementation? We first locate attention heads that carry a portable representation of a code operation. We then use their contributions at the pivot to describe the upcoming sub-goal and to trigger its implementation in a new context.

3.1 Localizing goal heads

We locate the *goal heads* using activation patching on a simpler, single-predicate task. A source and a destination prompt request different predicates on the same datatype, written in different programming languages. Both prompts end where the next token distinguishes the requested implementations. We cache the source head contributions and learn a sparse mask $m^{\ell j}$ jointly over attention heads. In the destination run, the mask controls which contributions are replaced:

$$a_{-1}^{\ell j} \leftarrow m^{\ell j} a_{\text{src}}^{\ell j} + (1 - m^{\ell j}) a_{-1}^{\ell j}. \tag{2}$$

The mask is optimized to promote a token that would begin implementing the *source predicate in the destination language*. We choose this target to differ from the source's next token, so the localization objective rewards transfer across different token realizations. We call the selected set H the *goal heads*. Our main selection contains 122 heads in layers 28–55 of the 64-layer model. The mask-learning procedure and head-set construction are described in Appendix B. We next test the selected heads on full readout continuations.

3.2 GoalScope and implementation transfer

GoalScope is a lightweight probe that verbalizes the sub-goal encoded at a single token position. Building on Patchscope (Ghandeharioun et al., 2024), we cache what the selected heads write to the residual stream at the source pivot and sum these contributions into one vector. A separate run of the same model receives a fixed prompt asking what operation it is performing. We inject the cached vector into this probe's residual stream and generate a natural-language description. The source task reaches the probe through the injected activations; its instructions and code are not supplied as text.

Our main configuration adds the vector at layers 35–45, scaled to 0.1 times the local residual norm. We reuse the same source vector at the probe's last prompt position and every subsequent decoding step, generating the readout greedily. Appendix C gives the exact prompt, normalization, and replacement variant.

Faithfulness. We ask whether the verbalization faithfully describes a nontrivial part of what the model implements in its next assignment. The controlled frontier identifies this assignment, allowing us to compare the readout with the model's generated code.

Implementation transfer. We inject the same encoding into a code stub in another programming language and ask whether it triggers a nontrivial part of the source operation. For example, an encod-




Figure 1: Selected-head readouts across capture positions on the OVReader evaluation corpus (64 examples per datatype). The first implementation token is shown as a comparison, separately from pre-implementation positions. The plotted "causality" metric is implementation transfer with trivial-readout sanitization. This corpus is distinct from the locked 253-specification corpus used for the pooled rates in the text.

ing captured from Python is used to steer a C++ continuation. This tests whether the representation can guide a new implementation of the operation. We refer to this metric as *implementation transfer*; saved evaluation plots label it "causality." We test the heads' role in the model's original generation separately in Section 4.

For both measures, an oracle compares the readout with the extracted implementation of the source frontier assignment. A positive judgment credits nontrivial agreement, including partial implementations; it does not certify executable correctness. Transfer scoring also rejects trivial sign/zero continuations that can arise as defaults of the probe stub. Exact oracle prompts are in Appendix D.

3.3 Readout across capture positions

At the assignment operator, before the first implementation token, the 122-head readout achieves 97.2% faithfulness and 95.7% implementation transfer on the 253-specification corpus (Figure 2). The model thus carries a readable and portable representation of the upcoming operation at this pivot.

Readout quality varies with the capture position. It is strongest near the assignment operator and first implementation token, and weaker at the end of the previous line. Pooled over all five positions, including the first implementation token, the scores are 87.9% faithfulness and 79.2% implementation transfer. Figure 1 shows the positional pattern on the separate OVReader evaluation corpus; Appendix M.1 reports the head-budget results at the remaining positions on the 253-specification corpus.

These two readouts expose complementary properties of the encoding: a natural-language description reveals its semantic content, while cross-language transfer shows that it can guide a different realization of the operation. We next examine how compactly the encoding can be read and how the heads contribute to the model's own implementation.

4 Goal Heads Carry and Mediate the Sub-Goal

How many heads are needed to read the sub-goal, and how important are these heads for carrying it out? We study both questions: first by varying the number of heads used for readout, then by restricting their access to task information during the model's own code generation.

4.1 Small head sets support effective readout

Twenty-five selected heads, approximately 0.98% of the model's 2,560 query heads, achieve 93.7% readout faithfulness and 90.5% implementation transfer at the assignment pivot. The 122-head reference achieves 97.2% and 95.7%, respectively (Figure 2). Much of the sub-goal's semantic content can therefore be recovered from a small fraction of the attention heads.

Larger selections do not improve performance monotonically. The selections differ in membership and are not strictly nested, so the curves compare available head sets rather than isolate head count




Figure 2: Readout versus head budget at the assignment-operator pivot, before implementation (253 matched specifications; norm-relative additive injection, $\alpha = .1$). Lines show available head selections; stars mark the separately selected 122-head reference. Selections are not strictly nested, so connecting points guides comparison rather than isolating an effect of head count alone. Other capture positions appear in Appendix M.1.

Condition	122 heads	250 heads
Clean baseline	.925	.925
Spare goal-head access	.806	.913
Spare random-head access	.091	.095
Restrict goal heads to sink	.854	.158
Restrict random heads to sink	.925	.921

Table 1: Frontier implementation success under span restriction and sink-attention interventions ($n = 253$). "Spare" preserves selected heads' access to the blocked task/code span in layers 20 and above. "Restrict" limits the selected heads to attention at position zero.

alone. Results at the other capture positions appear in Appendix M.1. Comparisons with full-attention and residual-stream readouts are in Appendix M.

4.2 Goal heads mediate implementation

We next ask whether the model relies on the *goal heads* to implement the next sub-goal. On the same 253 specifications, we intervene at the assignment pivot and continue the intervention during decoding. We compare the original generation with interventions on the 122-head core, a broader 250-head set, and random-head controls.

Sufficiency of goal-head access. We preserve the selected heads' access to the upcoming task and code span while blocking that access for other heads in layers 20 and above. The blocked span begins just before the frontier description and ends at the final prompt token. Lower layers, MLPs, and attention to positions outside this span continue to operate. This tests whether goal-head access can sustain implementation when other upper-layer heads lose access to the same information. The control preserves access for a comparable number of random heads; exact spans and sampling pools are in Appendix N.

Necessity of goal-head access. In the complementary experiment, we restrict the selected heads to attend only to position zero, the attention sink, while other heads operate normally. The selected heads still contribute the sink value but lose access to the task and code tokens. We compare with applying the same restriction to an equal-size random set, drawn from the depth pool and disjoint from the goal heads.

Preserving access for the 250 goal heads retains 91.3% implementation success, close to the 92.5% clean baseline; preserving random-head access retains only 9.5% (Table 1). Conversely, restricting

the 250 goal heads to the sink reduces success to 15.8%, while the random control remains at 92.1%. The broader goal-head set therefore plays a causal role in mediating the model's implementation of the sub-goal.

The 122-head core shows a smaller effect: restricting it leaves success at 85.4%. Taken together with the readout curves, this reveals a distinction between the heads needed to expose the sub-goal and the broader set whose access is important for execution. These sufficiency and necessity tests concern access under the specified interventions; the heads operate within the rest of the network.

5 How Goal Heads Access the Upcoming Sub-Goal

What information do the *goal heads* use to guide the next operation? We examine where the heads attend, how changing their queries or task-span keys and values affects the continuation, and where the sub-goal can be read from the residual stream.

5.1 Attention to relevant task descriptions

The *goal heads* often look back to the task they are about to implement. At a frontier position, their collective value-weighted attention concentrates on tokens in the prompt describing the upcoming predicate. This resembles the gaze behavior observed during generation in other settings (Gandikota & Bau, 2026). These qualitative attention patterns suggest a connection between the task descriptions and the goal encoding. We test that connection causally by changing the information available through the heads' keys and values.

5.2 Changing task information redirects implementation

Consider a source prompt with tasks (A, B, C) and a destination with tasks (A, B, D), both with A and B already implemented. The next requested sub-goal is C in the source and D in the destination. We cache the keys and values of the source task tokens and transplant them into the destination's goal-head attention. The destination prompt still requests D; the patched heads now access the source task information. We ask whether this change makes the model implement C.

At the assignment pivot, the 250-head intervention produces source-directed continuations in approximately 99% of cases across four datatypes and four language directions. Here, *source-directed* includes the oracle's labels for the source goal alone or both source and destination goals. A separate GoalScope readout identifies the source goal exclusively in approximately 96% of cases. Transfer also works across programming languages, producing a destination-language realization of the source operation. These results show that the task information accessed through goal-head keys and values can redirect the model's next sub-goal. Configurations and scoring details are in Appendix N.1.

The patch is routed to the selected query heads, accounting for shared KV heads, and remains active across prefill and decoding. Earlier patched outputs can therefore influence later destination states and queries. The result establishes adaptation to changed task information; locating the progress representation requires additional controls over these interactions.

5.3 Queries carry information about the next sub-goal

We next cache the source queries at the pivot and transplant them into the destination's goal heads. In the multi-predicate setup, this produces approximately 94% source-directed continuations across the four language directions (Appendix N.1). Query states thus carry information that can steer the choice of sub-goal. To examine whether this information concerns completed work or the upcoming operation, we use a task-order contrast in which the two predict different continuations.

The source orders tasks (A, B, C, D) and has completed (A, B), making C its next task. The destination orders tasks (A, B, D, C) and has completed only A. If the transferred state specifies only the completed prefix (A, B), the destination order would make D the next task. A state that carries the source's upcoming sub-goal would instead favor C. The observed query transfer favors C.

This qualitative contrast supports the presence of goal-specific information in the query. A systematic evaluation that independently varies progress, task order, and target identity is needed to determine how broadly this interpretation holds and how progress information also contributes.




Figure 3: OVReader at the assignment pivot: readout quality across source layers, compared with the selected heads' actual output readout. The evaluation uses 64 examples per datatype. The plotted "causality" metric is implementation transfer with trivial-readout sanitization. This pre-implementation position is separated from the first implementation token; other positions appear in Appendix O.

5.4 Reading intermediate residual states with OVReader

At what depth does the upcoming sub-goal become readable? We introduce **OVReader**, which uses the goal heads' value and output projections to read intermediate residual states. For a residual state at the pivot, we apply each selected head's projections, normalize the transformed vectors, and aggregate them. The resulting direction steers the GoalScope probe. This gives us a readout built from the model's own weights, with no additional decoder training (Appendix O).

At the assignment operator, OVReader can recover the sub-goal around layer 40, with readout quality approaching that of the selected heads' actual outputs (Figure 3). Across the five capture positions, performance generally peaks around layers 48–52 and declines toward the final layer; earlier token positions show different emergence profiles. The upcoming sub-goal is therefore accessible in intermediate residual states before implementation begins. These depths overlap the selected-head range of layers 28–55. The curves locate where the readout is effective; determining where the sub-goal is first selected requires further causal interventions.

The experiments identify complementary parts of the mechanism: task-span keys and values provide information that can redirect the operation, queries can favor a particular sub-goal, and the goal heads' projections make that sub-goal readable from intermediate residual states. Understanding how these components combine completed work with the task specification remains an open question.

6 Beyond Explicitly Specified Code Tasks

Do the heads localized on code also carry an operation that the model infers from examples? Our controlled code tasks name each sub-goal in the prompt. We now examine a few-shot setting where the intended relation is conveyed through demonstrations.

Few-shot relation tasks. Following the function-vector setting (Todd et al., 2024), we provide input–output pairs demonstrating a relation, followed by a new input. We retain the 122 heads localized on code and adapt the probe question to ask for the hidden rule in a short phrase. For example, an antonym prompt contains the following pairs:

```
Q: enter  A: exit
Q: feasible  A: infeasible
. . .
Q: mercy  A:
```

The model answers "cruelty" and continues generating question–answer pairs. At the newline following "cruelty," GoalScope reads *"Identifying antonyms."* At the answer-prefix token `A` before a later answer, "slow," it again reads *"Identifying antonyms."* The probe is given neither the name of the relation nor the demonstrations as text. The code-localized head contributions carry enough information to describe the inferred operation.

These are qualitative readouts during the continuing sequence, with the first captured after the initial answer and the second before a later answer. Nearby positions also produce vague or incorrect descriptions. Appendix L gives the full demonstration list, exact probe wording, token indices, and contrasting readouts. The example shows that the code-localized heads can expose an inferred non-code relation; a quantitative evaluation across relations and positions remains to be completed.

Code without enumerated sub-goals. Free-form code poses a related question: can the readout describe a step that the model chooses while solving a broader programming request? Here, evaluation must identify a meaningful operation in the model's continuation, which may be a local statement or a larger enclosing computation. This extension requires qualitative examples and an explicit choice of sub-goal granularity.

We report replications within other model families and sizes in Appendix J. Further exploratory non-code settings are discussed in Appendix L.

7 Related Work

Planning and look-ahead in LMs. Prior work shows that autoregressive LMs encode information about future tokens (Pal et al., 2023) and plan toward constraints in later output (Lindsey et al., 2025). We study the upcoming computation at the level of an instrumental sub-goal. Our experiments ask whether its representation can be read before implementation and transferred to guide the same operation in a new context.

claude: Add citations: future-lens / prompt-injection look-ahead, poetry-planning (Anthropic biology), chess/maze planning, emergent world models.

Portable task representations and function abstractions. Function vectors are compact representations of demonstrated input–output tasks, carried by a small set of attention heads and transferable to new contexts (Todd et al., 2024). Concept-induction heads carry word representations that mediate translation across languages (Feucht et al., 2025). Filter heads encode predicates in their query states and reapply them across collections, formats, languages, and tasks (Sen Sharma et al., 2026). Our work examines a related abstraction during multi-step generation: the particular sub-goal the model is about to implement. We localize its encoding in head contributions, verbalize its content, and test its portability across programming languages.

Verbalizing internal representations. Patchscope uses a language model to express information extracted from its hidden states (Ghandeharioun et al., 2024). GoalScope applies this approach to the contributions of causally localized attention heads at a single source position. The cached signal is reused throughout probe generation to obtain a multi-token description or code implementation. OVReader extends this readout to intermediate residual states using the selected heads' value and output projections.

claude: Add: logit lens, tuned lens, SelfIE, function-vector readouts; contrast what GoalScope reads (head-output, multi-token) vs. residual-stream single-token lenses.

High-level interpretability of goal-directed behavior. The high-level interpretability agenda studies model behavior through abstractions that can be investigated without a complete account of every underlying computation (Greenblatt, 2024). We use an instrumental sub-goal as such an abstraction. Cross-language transfer tests whether its encoding can guide different implementations, while restrictions on goal-head attention test its role in the model's own generation.

claude: Cite causal abstraction / DAS (Geiger et al.), high-level causal mediation; position our cross-language transfer as the abstraction test.

8 Discussion

We find that code LLMs carry a compact representation of their upcoming sub-goal before writing its implementation. The representation can be extracted from attention-head contributions, verbalized in natural language, and transplanted to trigger the same operation in another programming language. The heads also mediate the model's own implementation: preserving their access to task information largely preserves performance, and restricting a broader set sharply reduces it. These findings connect an interpretable description of what the model is about to do with an internal representation that can influence its behavior.

An abstraction of the upcoming operation. The portability of the encoding suggests a separation between the identity of a sub-goal and its realization in code. An operation extracted from Python can guide a C++ implementation, even though the two require different tokens. Natural-language verbalization provides a complementary way to inspect this semantic content. Our evidence concerns

the upcoming operation near the start of its implementation; it leaves open how much of a longer plan is represented and how its details are chosen. Verbalizability also does not establish that the representation's native format is natural language.

From goal representation to goal selection. The intervention results identify several parts of goal-directed computation. Queries carry information that can favor a particular sub-goal; task-span keys and values supply information to which the model can adapt; and the heads' projections expose the upcoming operation in intermediate residual states. The ablations further distinguish a small set sufficient for readout from a broader set important for implementation. These observations constrain the mechanism, while leaving open how the model combines completed work with the specification to select its next step. Independently varying progress, task order, and target identity offers a way to investigate that computation. The current interventions establish causal involvement under specific access restrictions, rather than a unique bottleneck or an isolated goal-selection circuit.

Scope and limitations. Our principal quantitative setting uses explicit task specifications and a known frontier. The oracle measures nontrivial semantic agreement and can credit partial implementations, so success rates should be interpreted separately from executable program correctness. Capture positions are repeated observations of the same specifications, and head-budget comparisons use selections that are not strictly nested. Replications use each model's own heads and activations; differences between models combine checkpoint, head-selection, and generation effects. The few-shot example is qualitative, and evaluating free-form code requires further examples and decisions about sub-goal granularity. These settings are promising tests of how far the code-localized representation generalizes.

GOALSCOPE provides a concrete tool for examining what a model is about to do as generation proceeds. Further work can use these readouts to study how sub-goals change, when an intended operation fails to be implemented, and how the model decides to move on to the next step. Our exploratory boundary-signal interventions (Appendix F) provide a complementary starting point for the last question.

ETHICS

REPRODUCIBILITY

ACKNOWLEDGEMENTS

REFERENCES

Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, et al. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 1(1):12, 2021.

Sheridan Feucht, Eric Todd, Byron C Wallace, and David Bau. The dual-route model of induction. In *Conference on Language Models (COLM)*, 2025. URL https://openreview.net/forum?id=bNTrKqqnG9.

Rohit Gandikota and David Bau. Gaze heads: How vlms look at what they describe. *arXiv preprint arXiv:2606.14703*, 2026.

Asma Ghandeharioun, Avi Caciularu, Adam Pearce, Lucas Dixon, and Mor Geva. Patchscopes: A unifying framework for inspecting hidden representations of language models. In *International Conference on Machine Learning (ICML)*, 2024.

Ryan Greenblatt. High-level interpretability: how LLMs make decisions in pursuit of goals, 2024. Interview remarks; high-level, intervention-style interpretability of goal-directed behavior.

Jack Lindsey, Wes Gurnee, Emmanuel Ameisen, Brian Chen, Adam Pearce, Nicholas L. Turner, Craig Citro, Joshua Batson, et al. On the biology of a large language model. *Transformer Circuits Thread*, 2025. URL https://transformer-circuits.pub/2025/attribution-graphs/biology.html.

Aaron Mueller, Jannik Brinkmann, Millicent Li, Samuel Marks, Koyena Pal, Nikhil Prakash, Can Rager, Aruna Sankaranarayanan, Arnab Sen Sharma, Jiuding Sun, et al. The quest for the right mediator: Surveying mechanistic interpretability for nlp through the lens of causal mediation analysis. *Computational Linguistics*, 52(1):331–378, 2026.

Koyena Pal, Jiuding Sun, Andrew Yuan, Byron C. Wallace, and David Bau. Future lens: Anticipating subsequent tokens from a single hidden state. In *Conference on Computational Natural Language Learning (CoNLL)*, 2023.

Arnab Sen Sharma, Giordano Rogers, Natalie Shapira, and David Bau. LLMs process lists with general filter heads. In *International Conference on Learning Representations (ICLR)*, 2026. URL https://filter.baulab.info/. arXiv:2510.26784.

Eric Todd, Millicent L. Li, Arnab Sen Sharma, Aaron Mueller, Byron C. Wallace, and David Bau. Function vectors in large language models. In *International Conference on Learning Representations (ICLR)*, 2024.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Yaron Singer, and Stuart Shieber. Investigating gender bias in language models using causal mediation analysis. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 12388–12401. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/92650b2e92217715fe312e6fa7b90d82-Paper.pdf.

A Evaluation Corpus and Exact Prompt

A.1 Locked prefill-to-frontier corpus

The main GoalScope evaluation uses `data/goalscope_eval.json`, generated with seed 123 from the QTASKS predicate bank. It contains 253 Python specifications. Each specifies two, three, or four predicates and prefills one or more completed predicates before the frontier assignment. The function and intermediate-variable naming conventions are fixed; the exact example below uses `func` and successive letter variables. Sampling balances the frontier predicate within each datatype, rather than making the four datatype counts identical. The number of completed predicates is between one and three and always less than the total number of predicates.

Datatype	Specs	Frontiers	Repeats	$T = 2$	$T = 3$	$T = 4$	Records/mode
int	65	13	5	26	15	24	325
list[int]	60	12	5	23	25	12	300
str	64	16	4	26	21	17	320
list[str]	64	16	4	17	21	26	320
Total	253	57	—	92	82	79	1265

Table 2: Distribution of the locked evaluation corpus. T is the number of predicates in the specification; repeats count distinct prefill contexts per frontier. Frontier identities are counted within datatype. Each specification contributes five capture positions per evaluation mode.

Datatype	1 completed	2 completed	3 completed
int	38	18	9
list[int]	36	19	5
str	43	16	5
list[str]	34	20	10
Total	151	73	29

Table 3: Number of completed predicates in the prefilled context. These counts are specification-level, not token-position-level.

The frontier bank excludes the integer predicates `is_negative`, `is_positive`, and `sign`, and the integer-list predicates `all_positive`, `contains_zero`, `count_negative`, and `count_positive`. This exclusion applies to measured frontier targets; it does not forbid such predicates in completed context. The following lists give every retained frontier ID; each occurs the number of times specified in Table 2.

int (5 contexts per frontier). `absolute_value`, `count_set_bits`, `digit_count`, `digit_sum`, `is_even`, `is_multiple_of_3`, `is_odd`, `is_palindrome`, `is_perfect_square`, `is_power_of_two`, `is_prime`, `is_two_digit`, `last_digit`.

list[int] (5 contexts per frontier). `count_even`, `count_odd`, `distinct_count`, `has_duplicate`, `has_even`, `is_sorted`, `max_val`, `mean_int`, `min_val`, `product_all`, `total_sum`, `value_range`.

str (4 contexts per frontier). `all_lowercase`, `count_digits`, `count_letters`, `count_lowercase`, `count_spaces`, `count_uppercase`, `first_is_letter`, `has_digit`, `has_space`, `is_alnum`, `is_palindrome`, `last_char`, `length`, `starts_upper`, `vowel_count`, `word_count`.

list[str] (4 contexts per frontier). `all_unique_lengths`, `any_empty`, `count_all_lowercase`, `count_capitalized`, `count_ends_consonant`, `count_long`, `count_short`, `count_starts_vowel`, `count_with_digit`, `distinct_count`, `has_palindrome`, `longest_word_length`, `shortest_word_length`, `total_length`, `total_uppercase_letters`, `total_vowels`.

A.2 Exact source prompt and capture positions

The following is the complete saved prompt for `int_python_000` in the Qwen2.5-Coder-32B evaluation, including chat delimiters and the assistant prefill. The input ends immediately after the final `=` without an added newline. In the prompt illustrations, `\n` marks an actual newline; unmarked wrapping only fits the text to the box. The accompanying text files preserve the exact bytes.

```
<|im_start|>system\n
You are a helpful assistant proficient in programming. Always wrap your code inside
<code></code> blocks. Just the code, no need to comment or explain.<|im_end|>\n
<|im_start|>user\n
Write a Python program that implements a function `func` which, given an integer `n`,
computes in sequential order:\n
(1) the number of digits\n
(2) whether the number is even\n
<|im_end|>\n
<|im_start|>assistant\n
<code>\n
def func(n: int):\n
    a = len(str(abs(n)))\n
    b =
```

The first predicate, digit count, is already implemented; the frontier is evenness. The saved capture indices are 102 (previous-line end), 103 (indentation), 104 (variable), 105 (assignment operator), and 106 (first implementation token). They are indices in this model's tokenization, not universal character offsets. The saved clean continuation is:

```
 (n % 2 == 0)\n
    return a, b\n
</code>
```

The gold implementation span used by the judge is `b = (n % 2 == 0)`. More generally, the runner extracts the actual generated frontier assignment as `impl_span`; it does not use the natural-language predicate description as the oracle's CODE field. This tests agreement with the generated operation and must be distinguished from clean correctness against the requested predicate. The controlled frontier identifies the assignment directly, without an oracle segmentation call.

Five capture positions yield 1,265 records per mode and model, with repeated observations of the same 253 specifications. Rates pool records unless a position or datatype is explicitly selected. This corpus is separate from the 64-per-datatype OVReader sampling and the source/destination-pair corpora used for Q/KV transfer; their counts should not be combined.

B Localizing Attention Heads

Localization uses contrastive single-predicate prompts and learns a mask jointly over attention heads. The target is a token appropriate for the source predicate in the destination language, chosen to differ from the source continuation token. Applying the learned mask selects head activations for replacement. Subsequent readout uses the selected heads' projected contributions; the localization next-token objective and the multi-token evaluation are distinct.

The core Qwen2.5-Coder-32B selection has 122 heads in layers 28–55, from a thresholded mask within the candidate layer band. The broader set used in ablations contains 250 heads and includes earlier and later layers. The small-set readout sweep uses available selections from training snapshots and mask sweeps; these are not strictly nested prefixes of one ranking. Counts alone therefore do not determine head membership or the intervention's depth distribution.

Draft completion item: consolidate localization training splits, mask optimization settings, selection-file hashes, and per-model selection provenance into a final configuration table.

C GoalScope

C.1 Capture positions

The evaluation indexes the final four prompt tokens around a prefilled frontier assignment and the first generated implementation token: previous-line end, indentation, variable, assignment operator, and first implementation. Position names refer to the actual tokenized boundary; they are not interchangeable with an entire source line. The first implementation token is not a pre-implementation pivot. A cached state at a given position has no causal access to subsequent tokens, even when those tokens are displayed for context.

C.2 Aggregation and probe generation

At source position t, the main readout aggregates projected head contributions $g_t = \sum_{(\ell,j)\in H} a_t^{\ell j}$. At probe layer ℓ and current position s, norm-relative additive injection uses

$$r_{\ell,s} \leftarrow r_{\ell,s} + \alpha \|r_{\ell,s}\| \frac{g_t}{\|g_t\|}. \tag{3}$$

The main configuration uses $\alpha = .1$, layers 35–45 inclusive, and repeated injection during greedy probe generation. This coefficient is a fraction of the probe's local residual norm and is not interchangeable with an unnormalized additive coefficient. The source vector is fixed for the whole readout.

The default verbalization prompt is:

> System: You are a helpful assistant proficient in programming.
> User: What are you doing at this line of the code. Keep your answer as brief as possible.
> Assistant:

The probe receives no source code as text. Implementation transfer uses a code-stub probe instead and measures nontrivial agreement with the source subgoal. A distinct replacement variant substitutes selected heads' pre-output-projection activations in their corresponding layers, rather than aggregating them into a single direction; this is the variant used in the cross-model table. Its layer sites come from the head set, not the additive injection band.

C.3 Evaluation

An oracle judges whether the generated description or implementation matches a nontrivial part of the extracted frontier code. The full system rubrics, user-message templates, and saved examples are in Appendix D. Reported implementation-transfer results apply trivial-readout sanitization to avoid crediting a probe's default sign/zero comparisons. These judgments do not certify execution correctness. Clean continuation agreement, probe readout agreement, and intervention-induced changes are separate measurements. Corpus size and capture-position pooling are stated with each result.

D Exact Oracle Prompts and Scoring

The evaluation calls `claude-sonnet-4-6` with a system rubric and a user message, a maximum response budget of 512 tokens, and caching enabled. The complete system prompts below are extracted verbatim from the runner. Their MD5-prefix rubric identifiers, `78bfd5f4` (faithfulness) and `9c106246` (causality), match the saved configurations used here. The code's mode name *causality* denotes the implementation-transfer metric in the main text. Spelling, punctuation, and lenient scoring language are preserved as used, rather than edited for exposition.

As in Appendix A, `\n` marks actual newlines in the illustrated prompts; soft wrapping is unmarked.

D.1 FAITHFULNESS: SYSTEM MESSAGE

```
You are grading a lightweight interpretability probe (a patchscope). The DESCRIPTION
below was read out of a model's hidden state at a SINGLE token while the model was
writing one line of Python CODE that checks some property of its input. Because it is
squeezed out of one token under a steering/patching setup, the description is usually
NOISY: it may be wrapped in chat scaffolding (like 'Sure, but first let us ...'),
contain code fences or half-written code, be cut off mid-sentence, or repeat and loop.
Look PAST all of that surface noise and grade only the SUBSTANCE.\n
\n
The question: does the description surface ANYTHING genuinely relevant to what the CODE
is doing — any relevant operation, quantity, sub-step, or property of the input? Pulling
even a small correct fragment out of a single token is a SUCCESS, so grade as leniently
as possible — EXCEPT that a read-out which has collapsed into a degenerate repeating
loop is NOT a success, no matter what tokens the loop contains (see HEAVY_LOOP).\n
\n
Decide in this order — check MALFORMED and HEAVY_LOOP FIRST, and only then YES / NO /
NO_INFO:\n
\n
  MALFORMED  - the description is contentless: empty, pure punctuation or garbage, or
  repetition that carries NO relevant meaning.\n
  HEAVY_LOOP - the description is DOMINATED by a short repeating cycle: a unit of
  roughly five words/tokens or fewer that repeats over and over (e.g. 'value >= value
  >= value >= ...', 'len len len len', 'sum sum ( sum % sum == 0' on repeat, 'x % x == x
  % 0' on repeat). Once you collapse the repetition, little or no coherent description
  is left. Assign HEAVY_LOOP EVEN IF the looped fragment contains a relevant operator,
  name, or token — a stuck loop is not a faithful read-out. This takes PRECEDENCE over
  YES.\n
  YES        - the description contains SOME intelligible content genuinely relevant to
  what the code does, however partial, imprecise, or garbled — and it is NOT merely a
  short repeating loop.\n
  NO         - the description is coherent and about a specific thing, but that thing is
  COMPLETELY UNRELATED to what the code does. No conceptual sub-parts have been
  identified correctly.\n
  NO_INFO    - the description is coherent but too generic to indicate any specific
  aspect of the code (e.g. just 'doing a computation on the number').\n
\n
The following do NOT count against the description (still YES, provided it is not a
HEAVY_LOOP):\n
  - Wrong specifics: a wrong constant, threshold, bound, modulus, operator, or
  comparison. If the code computes some quantity and compares it to a value, naming the
  quantity alone is enough and the exact value can be wrong or missing. Example: the
  code implements `average temperature > 30`; a read-out about `computing the average
  temperature` is YES even though the `> 30` part is wrong or absent.\n
  - Wrong implementation nuance: naming a different mechanism for the same idea.
  Example: the read-out says `sorting with bubble sort` while the code calls .sort() or
  uses quicksort -> still YES.\n
  - Partial coverage: naming just one relevant ingredient of a multi-part check
  counts.\n
\n
Grade on meaning, not on shared keywords. Output only YES, NO, NO_INFO, MALFORMED, or
HEAVY_LOOP.\n
Put your final answer inside <verdict>{ans}</verdict> tags, with no other text or
explanation, to facilitate automated parsing.
```

User-message template. Braced fields below denote runtime substitutions, not literal strings sent to the oracle. `impl_span` is the extracted Python frontier assignment; `readout.strip()` removes leading and trailing whitespace from the generated probe readout.

```
Code: {impl_span}\n
Description: {readout.strip()}\n
Answer:
```

Exact instantiated example. This user message is copied from the saved assignment-pivot record for `int_python_000` in the 122-head norm-relative additive run.

```
Code: b = (n % 2 == 0)\n
Description: I'm checking if the number is even by using the modulus operator (`%`). If
`number % 2 == 0`, it's even.\n
Answer:
```

D.2 Causality / implementation transfer: system message

```
You are grading a lightweight interpretability probe (a patchscope). The DESCRIPTION
below was read out of a model's hidden state at a SINGLE token while the model was
writing one line of Python CODE that checks some property of its input. The read-out
method is a steering setup on a informationless C++ function stub. Because it is
squeezed out of one token, the description is usually NOISY: it may be half-written
code, be cut off mid-generation, be syntactically incorrect, or repeat and loop. Look
PAST all of that surface noise and grade only the SUBSTANCE.\n
\n
The question: does the C++ completion surface **ANYTHING GENUINELY RELEVANT** to what
the CODE is doing — any relevant operation, quantity, sub-step, or property of the
input? Pulling even a small correct fragment should be considered a SUCCESS, so grade
leniently — EXCEPT that a completion which has collapsed into a degenerate repeating
loop is NOT a success, no matter what tokens the loop contains (see HEAVY_LOOP).\n
\n
Decide in this order — check MALFORMED and HEAVY_LOOP FIRST, and only then YES / NO /
NO_INFO:\n
\n
  MALFORMED  - the completion is contentless: empty, pure punctuation or garbage, or
  repetition that carries NO relevant meaning.\n
  HEAVY_LOOP - the completion is DOMINATED by a short repeating cycle: a unit of
  roughly five words/tokens or fewer that repeats over and over (e.g. 'value >= value
  >= value >= ...', '(value(value(value...', 'sum sum ( sum % sum == 0' on repeat,
  'value == sum sum sum value ==' on repeat). Once you collapse the repetition, little
  or no coherent content is left. Assign HEAVY_LOOP EVEN IF the looped fragment
  contains a relevant operator, name, or token — a stuck loop is not a successful
  transfer. This takes PRECEDENCE over YES.\n
  YES        - the completion contains SOME intelligible content genuinely relevant to
  what the code does, however partial, imprecise, or garbled — and it is NOT merely a
  short repeating loop.\n
  NO         - the completion is coherent and about a specific thing, but that thing is
  COMPLETELY UNRELATED to what the code does. No conceptual sub-parts have been
  identified correctly.\n
  NO_INFO    - the completion is coherent but too generic to indicate any specific
  aspect of the code (e.g. just 'doing a computation on the number').\n
\n
The following do NOT count against the completion (still YES, provided it is not a
HEAVY_LOOP):\n
  - Wrong specifics: a wrong constant, threshold, bound, modulus, operator, or
  comparison. If the code computes some quantity and compares it to a value, naming the
  quantity alone is enough and the exact value can be wrong or missing. Example: the
  code implements `count(word, "b") > 5`; a c++ completion that counts the number of a
  `substr` in the `word` should be judged YES, even if the substr != b and/or the
  threshold is wrong.\n
  - Partial coverage: naming just one relevant ingredient of a multi-part check counts.
  For `count(word, "b") > 5`, a c++ completion that only counts the number of `substr`
  in the `word` is still YES, even if it doesn't check the threshold.\n
  - Different implementation nuance: different implementation strategies for the same
  idea. Example: the python code implements nth fibonacci recursively; a c++ completion
  implements it iteratively. Still YES, because the underlying property is the same.\n
\n
```

```
Finally, grade on meaning, not on shared keywords. Output only YES, NO, NO_INFO,
MALFORMED, or HEAVY_LOOP.\n
Put your final answer inside <verdict>{ans}</verdict> tags, with no other text or
explanation, to facilitate automated parsing.
```

User-message template. The C++ `readout` includes the fixed assistant prefill `bool check(auto value){` concatenated with the generated continuation before grading.

```
Python (gold): {impl_span}\n
C++ (read-out): {readout.strip()}\n
Answer:
```

Exact instantiated example. The following is the saved user message for the same specification and assignment pivot in the implementation-transfer run.

```
Python (gold): b = (n % 2 == 0)\n
C++ (read-out): bool check(auto value){ return (value % 2 == 0); }\n
Answer:
```

D.3 Generation prompt for the implementation probe

This is the role-separated probe instruction and assistant prefill, before the model-specific chat template is applied. It is distinct from the judging prompts above.

```
System:\n
You are a helpful assistant proficient in programming.\n
\n
User:\n
You are implementing a simple C++ function that checks for a condition. Just write the
function body, without any comments or explanations. Assume all the necessary headers
are already included.\n
\n
Assistant (prefill):\n
bool check(auto value){
```

D.4 Verdict parsing and deterministic exclusions

The parser first looks for a verdict inside `<verdict>` tags and otherwise uses the last recognized bare verdict. Unrecognized responses become `UNPARSED`. The reported hard-YES rate counts only `YES` in the numerator and all records in the denominator; `NO`, `NO_INFO`, `MALFORMED`, `HEAVY_LOOP`, and `UNPARSED` are not successes. These rubrics explicitly permit partial content and wrong constants or thresholds. Consequently, their rates are not exact predicate accuracy or executable-program accuracy.

Before calling the oracle, empty readouts become `MALFORMED`. In the causality mode, a deterministic sanitizer assigns `NO` to continuations containing only the generic function scaffolding and sign/zero comparisons. The implementation removes the recognized scaffolding words, logical/comparison operators, standalone zero literals, and punctuation; a readout is trivial if nothing remains. Genuine arithmetic or bitwise operations and nonzero constants survive this test. Such short-circuited records have no oracle user message. This readout exclusion is distinct from the frontier exclusions in Appendix A.

E Gaze Mechanism

E.1 Setup

E.2 Evaluation

The goal heads look back to what they are implementing.

The LM implements where the goal heads look back to.

E.3 Gaze heads vs Concept-Copier heads

F Boundary Signals: Moving On and Staying

This supporting line of experiments asks whether signals associated with ending a subgoal can influence when the model advances, independently of the semantic identity read by GoalScope. Prompts permit a predicate to occupy one or several lines, with repeated lines beginning with the current predicate's variable. At a line boundary, the next variable therefore indicates whether the model stays with that predicate or moves to the next one.

Source/destination contrasts are constructed so the source's next variable, the destination's native next variable, and the desired counterfactual variable differ. Head-output patching is optimized to promote the counterfactual continuation, reducing direct copying of a source variable as an explanation. Transfers from completed to incomplete steps can induce moving on; reverse transfers can induce staying or repetition. Variable renaming, cross-language examples, and reversed instruction order probe the reach of this signal.

These observations motivate a distinction between subgoal identity and transitions between subgoals. A next-variable change alone does not show correct implementation of the next predicate, and repeated output under a stay intervention requires separate interpretation. Full continuation scoring and tests of changes to goal readouts are needed before claiming a complete causal dissociation. Boundary experiments are therefore supporting material rather than a premise of the main subgoal-representation account.

G Checking for Functional Dissociation

G.1 Goal heads vs Impulse heads

H Role of MLPs

arnab: TODO: path patching experiments: patch + freeze MLPs with dest values. Measure intervention effects.

I Generalization across Programming Styles and Languages

J Generalization Across Model Families and Sizes

We repeat localization and evaluation within five models: Qwen2.5-Coder at 14B and 32B parameters, Qwen2.5-32B-Instruct, and OLMo-3.1-32B instruction and SFT variants. Each model uses its own selected heads and its own probe generation. This tests replication of readable and transferable task information, not activation transplantation between models.

J.1 Matched evaluation and head selection

All ten runs use the same 253 specification identifiers and five capture positions, yielding 1,265 records per model and mode. Rates below are recomputed from saved records. The intervention is head replacement with source coefficient 1 and steering throughout decoding; the probe generation budget is 64 tokens. Replacement operates at the selected heads' own layers and ignores the additive steer-band setting. Thus the results are not directly interchangeable with the main norm-relative additive scores.

The Qwen sets contain 122, 88, and 108 heads, respectively. The OLMo comparison uses 93 instruction-model heads and 91 SFT-model heads from the candidate band 10–36, using the exported threshold selections rather than the older 130/79-head pair. Their counts are approximately matched, not identical. Head membership and its layer distribution remain model-specific. Full model identifiers and selection names are listed below for reproducibility.

`Qwen/Qwen2.5-Coder-32B-Instruct`
Selection: `goal`.

Model	Heads	Selected layer range	Faithfulness	Transfer
Qwen Coder 32B	122	28–55	0.823	0.783
Qwen Coder 14B	88	18–47	0.598	0.401
Qwen Instruct 32B	108	29–55	0.308	0.540
OLMo Instruct 32B (+RL)	93	11–35	0.495	0.689
OLMo Instruct 32B (SFT)	91	11–34	0.595	0.533

Table 4: Within-model replication on the locked corpus, pooled over capture positions. Head sets are model-specific. A selected layer range gives its endpoints, not a claim that every layer is represented.

`Qwen/Qwen2.5-Coder-14B-Instruct`
Selection: `goal`.

`Qwen/Qwen2.5-32B-Instruct`
Selection: `goal`.

`allenai/Olmo-3.1-32B-Instruct`
Selection: `json:goal__lam20_thr1.0_band10-36`.

`allenai/Olmo-3.1-32B-Instruct-SFT`
Selection: `json:goal__lam20_thr0.6_band10-36`.

J.2 Results by capture position




Figure 4: Readout faithfulness and implementation transfer within each model across capture positions (253 records per point). The first implementation token is separated from the four earlier positions. The common scale exposes differences in timing and metric, which pooled rates can obscure.

Model	Metric	Prev. end	Indent	Variable	Assignment	First impl.
Qwen Coder 32B	Faith.	0.439	0.885	0.885	0.945	0.960
Qwen Coder 32B	Transfer	0.300	0.858	0.838	0.945	0.972
Qwen Coder 14B	Faith.	0.154	0.474	0.557	0.889	0.917
Qwen Coder 14B	Transfer	0.028	0.198	0.206	0.791	0.783
Qwen Instruct 32B	Faith.	0.000	0.245	0.071	0.636	0.589
Qwen Instruct 32B	Transfer	0.040	0.601	0.217	0.905	0.937
OLMo Instruct 32B (+RL)	Faith.	0.020	0.648	0.257	0.814	0.735
OLMo Instruct 32B (+RL)	Transfer	0.158	0.881	0.526	0.921	0.957
OLMo Instruct 32B (SFT)	Faith.	0.055	0.668	0.466	0.925	0.862
OLMo Instruct 32B (SFT)	Transfer	0.036	0.628	0.324	0.818	0.858

Table 5: Exact per-position rates for the model comparison in Figure 4.

J.3 Interpretation

The Coder-32B configuration scores above Coder-14B on both pooled metrics; it also outperforms the generic Qwen-32B instruction configuration on these code tasks. For OLMo, the instruction model has higher implementation-transfer scores, while the SFT model has higher readout faithfulness. Replication therefore does not imply identical performance or a single ordering of models across metrics.

These comparisons vary checkpoints, head sets, and potentially source-generation competence together. They support the presence of the phenomenon across families and sizes, but do not isolate causal effects of scale, code training, or RL. Capturing at equivalent named boundaries also need not mean identical tokenization across models. The approximate OLMo budget matching reduces one disparity without controlling every difference. All scores use the partial-content oracle rubric in Appendix D, rather than execution-based program correctness.

K Generalization to Unspecified Settings

L Generalization to Non-Code Settings

L.1 Few-shot antonym example

The saved exploratory run in `19_goalscope_out_of_domain.ipynb` uses six demonstrations: enter/exit, feasible/infeasible, manned/unmanned, fuzzy/smooth, arise/settle, and far/near. The prompt ends at `Q: mercy` followed by `A:`. Its continuation starts with "cruelty" and then generates further question–answer pairs. The code-localized 122-head set supplies norm-relative additive readouts with $\alpha = .1$, injection layers 35–45, and repeated steering during readout generation.

The probe uses the system instruction "You are a helpful assistant." and the user instruction "You are answering a series of questions that all follow the same hidden rule. In one short phrase, what task are you performing?" This is a domain-adapted probe, not the original code-oriented prompt. Saved token indices refer to the notebook's tokenized prompt plus continuation.

Position	Source token	Readout
57	newline after cruelty	Identifying antonyms.
60	light	Identifying patterns.
70	A before slow	Identifying antonyms.
71	colon before slow	Decoding or interpreting slower actions.

Table 6: Selected qualitative readouts from one saved antonym run, including a vague description and a mismatch. These are not a quantitative evaluation sample.

L.2 Other exploratory domains

Recipe, travel, and narrative prompts use adapted verbalization questions. These settings require separate decisions about the granularity and correctness of the next step; they are not included in the code results or claimed as a validated general-purpose planning readout. A systematic evaluation remains to be completed.

M Readout Sources and Head Budgets

Selected contributions provide a substantially more effective injection direction than the tested full-attention and raw-residual aggregates. Equal relative norm controls overall perturbation magnitude, but does not ensure that a shared injection strength or aggregation rule is optimal for every source. OVReader provides a separate test of information extracted from the residual.

Injected source	Faithfulness	Implementation transfer
122-head aggregate	.879	.792
Attention output, L40–50	.343	.334
Residual, L25–56	.031	.020
Residual, L40–50	.009	.006

Table 7: Source comparison under norm-relative injection at $\alpha = .1$ on the locked corpus, pooled over five positions. Poor raw-residual injection is a result about this readout configuration, not proof that the residual lacks subgoal information.




Figure 5: Head-budget curves for the remaining four capture positions, using the same 253 specifications and configurations as Figure 2. Stars indicate the 122-head reference; blue solid lines show readout faithfulness and orange dashed lines implementation transfer. The first implementation token is a comparison position, not evidence of encoding before implementation. The common vertical scale makes differences across positions visible.

M.1 Head-budget results at other capture positions

We recompute each rate as the fraction of saved oracle verdicts equal to YES, including all 253 records per position in its denominator. The same specification identifiers occur at every head budget in both evaluation modes. Each position is a repeated measurement of those specifications. All runs use norm-relative additive injection at $\alpha = .1$, layers 35–45, and steering throughout probe decoding. The head selections differ in construction and are not strictly nested; the 122-head reference is displayed separately from the connected sweep.

N Details of Causal and Context Interventions

The native ablation evaluation uses 253 frontier assignments. Both intervention types begin at the final prompt token and continue at subsequent query positions during decoding; earlier query rows remain unmodified. For span restriction, the blocked key interval begins one token before the frontier description and extends through the prompt's final assignment token. Heads in layers 20–63 outside the spared set are blocked from that interval. For sink restriction, selected heads attend only to key

position zero. The latter produces the sink value contribution and is not mathematically identical to zeroing a head.

The 122-head core and 250-head set differ in both membership and depth coverage. Random controls sample from the corresponding depth pool, not a matched count at each individual layer. For a set containing heads below layer 20, those heads are outside the span-restriction band. Thus total selected count and number of spared heads inside that band must be distinguished. The experiments test these specified interventions, not arbitrary removal of the entire complement or isolation of the selected heads from the rest of the network.

N.1 Task and query transfer

Task-span KV transfer uses per-query-head output routing to avoid transferring to every query head sharing a KV head. Task spans are padded to equal length and source keys are re-rotated to destination positions; equal lengths do not imply identical absolute starts. The KV patch is active across prefill positions and decoding. Query transfer patches the specified pivot tokens and reuses the source pivot query during the steering window (32 forward passes in the evaluation CLI, including prefill). The reported transfer configurations also amplify selected OV contributions with coefficient 2; this differs from the GoalScope probe's coefficient 0.1.

The principal multi-predicate 250-head runs report approximately 94% source-directed generation for query transfer ($n = 2048$) and 99% for KV transfer at the assignment pivot ($n = 512$), spanning four datatypes and four language directions. The latter uses no non-goal-head ablation. These rates count source-or-both oracle labels and do not imply perfect program correctness. GoalScope's patched source readout is a separate outcome. Q-filter examples exhibit readout/behavior disagreement; aggregate readout success should not be treated as a substitute for implementation success.

The qualitative task-order example in the main text follows the saved figure with unequal source/destination progress. It should not be described as an identical-progress experiment. Broader conclusions about query content require a systematic crossed design. We make no claim that these interventions demonstrate a particular set-subtraction operation.

O OVReader

For a residual state after source layer L, OVReader applies each selected head's value map and output map, including its pre-attention normalization gain. It unit-normalizes each transformed vector and averages them. This operator is based on model weights, but is not a single linear projection because of the per-head normalization. The aggregate steers a separate GoalScope probe with norm-relative coefficient .15; the selected-head-output comparison uses .1.

The evaluation samples 64 examples per datatype, with five capture positions and layer sweeps through the final layer. At the assignment operator, readout can approach the head-output reference around L40; pooled curves generally peak near L48–52. A decline at the final layer indicates reduced accessibility through this particular transformation and probe, not absence of all subgoal information. Implementation-transfer scores were rejudged with a trivial-output sanitizer; existing records should not be described as a freshly resampled corpus excluding all trivial target predicates.