D / A shared readout for clean and DIFF-patched computations

Hold the destination prompt fixed. Change the source computation, then extract its selected-head signal.

SHARED DESTINATION

Tasks: T_1 = palindrome; T_2 = vowel-initial

```
ys = [s for s in xs if s == s[::-1]]
zs =      ← extract at the final "=" token t
```

DONOR SETUPS

Q donor: same {T_1, T_2}; completed {T_2}.

KV donor: {T_1, T_3}; completed {T_1}.

T_3 = more than one distinct character.

(a) COMPUTATION INSPECTED	(b) EXTRACT	(c) FIXED PROBE	(d) READOUT
Clean destination Original destination forward	Selected head sum g_t^{clean}	Same prompt + model $r \leftarrow r + \alpha \lVert r \rVert \hat{g}_t$	**Keep vowel-initial strings.**
Query-patched destination Transplant donor Q at selected heads	Selected head sum $g_t^{Q\ \text{patch}}$	Same prompt + model $r \leftarrow r + \alpha \lVert r \rVert \hat{g}_t$	**Filter palindromes.**
KV-patched destination Transplant donor task-span K,V	Selected head sum $g_t^{KV\ \text{patch}}$	Same prompt + model $r \leftarrow r + \alpha \lVert r \rVert \hat{g}_t$	**Keep strings with >1 distinct character.**

The DIFF transplant occurs in the computation being inspected. GoalScope is a separate activation-to-text intervention.

Rows show predicted readouts for the illustrative setup, not measured transfer results or behavioral continuations.

SCHEMATIC EXAMPLES · Verbalizations are illustrative, not recorded outputs. | Additive norm-relative GoalScope.