

Global irrigation water demands biased by unreliable irrigation efficiencies

R code

Arnald Puy

Contents

1	Read in data	3
2	The model	7
2.1	Function to create sample matrix	7
2.2	Define distributions	8
2.3	Uncertainty in the proportion of large-scale irrigated areas	10
2.4	Function to create sample matrix and transform to appropriate distributions	10
2.5	Run the model	11
2.6	Define settings	12
2.7	Run model	12
2.8	Extract model output	13
3	Uncertainty analysis	21
3.1	Retrieve data from ISIMIP	31
4	Sensitivity analysis	37

```

# Function to read in all required packages in one go:
loadPackages <- function(x) {
  for(i in x) {
    if(!require(i, character.only = TRUE)) {
      install.packages(i, dependencies = TRUE)
      library(i, character.only = TRUE)
    }
  }
}

# Load the packages
loadPackages(c("data.table", "tidyverse", "sensobol", "wesanderson",
              "cowplot", "parallel", "foreach", "doParallel",
              "countrycode", "gggridges", "scales", "overlapping",
              "sp", "rworldmap", "ncdf4"))

# Create custom theme
theme_AP <- function() {
  theme_bw() +
    theme(panel.grid.major = element_blank(),
          panel.grid.minor = element_blank(),
          legend.background = element_rect(fill = "transparent",
                                            color = NA),
          legend.key = element_rect(fill = "transparent",
                                     color = NA),
          legend.position = "top",
          strip.background = element_rect(fill = "white"),
          plot.margin = margin(t = 0, r = 0.3, b = 0, l = 0.3, unit = "cm"))
}

# Set checkpoint

dir.create(".checkpoint")
library("checkpoint")

checkpoint("2021-08-02",
          R.version = "4.0.3",
          checkpointLocation = getwd())

```

1 Read in data

```
# READ IN DATA -----

# Rohwer data
rohwer <- fread("rohwer_data_all.csv")
rohwer[rohwer == ""] <- NA
rohwer <- rohwer[, Large_fraction:= Large_fraction / 100]

# Jager data
jager <- fread("jager_data.csv")
jager.list <- split(jager, jager$Country)

# Bos data
bos <- fread("bos_data.csv")
bos <- bos[, Scale := ifelse(Irrigated_area < 10000, "<10.000 ha", ">10.000 ha")]

# Solley data (USA)
usa.dt <- fread("usa_efficiency.csv")
usa.dt <- usa.dt[, Efficiency:= consumptive.use / total.withdrawal]

# FAO 1997 data (Irrigation potential in Africa)
fao_dt <- fread("fao_1997.csv")
fao_dt <- fao_dt[, Efficiency:= Efficiency / 100]

# Create data set with E_a values as defined by Rohwer
bos.rohwer.ea <- data.table("Irrigation" = c("Surface", "Sprinkler"),
                           "Value" = c(0.6, 0.7),
                           "variable" = "E[a]")

# Create data set with E_c values as defined by Rohwer
bos.rohwer.ec <- data.table("Irrigation" = c("Surface", "Sprinkler"),
                           "Value" = c(0.8, 0.95),
                           "variable" = "E[c]")

bos.rohwer.all <- rbind(bos.rohwer.ec, bos.rohwer.ea)

# As a function of scale
bos.rohwer.mf.ec <- data.table("Scale" = c("<10.000 ha", ">10.000 ha"),
                              "Value" = c(0.85, 0.59),
                              "variable" = "E[c]")

bos.rohwer.mf.ed <- data.table("Scale" = c("<10.000 ha", ">10.000 ha"),
                              "Value" = c(0.81, 0.72),
                              "variable" = "E[d]")

bos.rohwer.mf.all <- rbind(bos.rohwer.mf.ec, bos.rohwer.mf.ed)
```

```

# PLOT -----

bos2 <- copy(bos)
bos2 <- setnames(bos2, c("E_a", "E_c", "E_d"), c("E[a]", "E[c]", "E[d]"))

# Field and conveyance efficiency -----

a <- bos2 %>%
  melt(., measure.vars = c("E[a]", "E[c]")) %>%
  ggplot(., aes(value, fill = Irrigation, color = Irrigation)) +
  geom_histogram(position = "identity", alpha = 0.4, bins = 15) +
  facet_wrap(~variable, labeller = label_parsed) +
  scale_x_continuous(breaks = pretty_breaks(n = 3)) +
  geom_vline(data = bos.rohwer.all, aes(xintercept = Value,
                                       color = Irrigation,
                                       group = variable),
            lty = 2,
            size = 1) +
  labs(x = "", y = "Counts") +
  theme_AP()

# As a function of scale -----

b <- melt(bos2, measure.vars = c("E[c]", "E[a]", "E[d]")) %>%
  na.omit() %>%
  ggplot(., aes(value, fill = Scale, color = Scale)) +
  geom_histogram(bins = 15, position = "identity", alpha = 0.6) +
  labs(x = "Irrigation efficiency", y = "Counts") +
  facet_wrap(~ variable, labeller = label_parsed) +
  geom_vline(data = bos.rohwer.mf.all, aes(xintercept = Value,
                                       color = Scale,
                                       group = variable),
            lty = 2,
            size = 1) +
  scale_x_continuous(breaks = pretty_breaks(n = 3)) +
  scale_color_manual(values = wes_palette(2, name = "Chevalier1"),
                    name = "Scale",
                    labels = c("<10.000 ha", ">10.000 ha")) +
  scale_fill_manual(values = wes_palette(2, name = "Chevalier1"),
                   name = "Scale",
                   labels = c("<10.000 ha", ">10.000 ha")) +
  theme_AP()


bottom <- plot_grid(a, b, ncol = 1, labels = c("c", "d"))

## Warning: Removed 74 rows containing non-finite values (stat_bin).


```

bottom

c



d



PLOT USA AND AFRICA -----

```
c1 <- ggplot(usa.dt, aes(Efficiency)) +
  geom_histogram() +
  scale_x_continuous(breaks = pretty_breaks(n = 3)) +
  geom_vline(xintercept = 0.6, lty = 2) +
  labs(x = "", y = "Counts") +
  theme_AP()

d1 <- ggplot(fao.dt, aes(Efficiency)) +
  geom_histogram() +
  scale_x_continuous(breaks = pretty_breaks(n = 3)) +
  labs(x = "", y = "") +
  theme_AP()


top <- cowplot::plot_grid(c1, d1, ncol = 2, labels = "auto")
```

`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.

Warning: Removed 3 rows containing non-finite values (stat_bin).


`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.

top



PLOT MERGED

```
plot_grid(top, bottom, ncol = 1, rel_heights = c(0.3, 0.7))
```



2 The model

2.1 Function to create sample matrix

```
# CREATE FUNCTION TO DESIGN SAMPLE MATRIX -----

params_algo <- list(
  "Surface" = c("Ea_surf", "Ec_surf", "m", "r_L", "X1", "X2"),
  "Sprinkler" = c("Ea_sprinkler", "Ec_sprinkler", "m"),
  "Micro" = c("Ea_micro", "Ec_micro", "m"),
  "Mixed" = c("Ea_surf", "Ea_sprinkler", "Ec_surf", "Ec_sprinkler", "m", "r_L", "X1", "X2"),
  "Jager" = c("Ea_surf", "Ea_sprinkler", "Ec_surf", "Ec_sprinkler",
              "Ea_micro", "Ec_micro", "m", "r_L", "X1", "X2")
)

params_fun <- function(IFT) {
  out <- params_algo[[IFT]]
  return(out)
}
```

```

sample_matrix_fun <- function(IFT) {
  params <- params_fun(IFT = IFT)
  mat <- sensobol::sobol_matrices(N = N, params = params)
  out <- list(params, mat)
  names(out) <- c("parameters", "matrix")
  return(out)
}

```

2.2 Define distributions

```

# DEFINE TRUNCATED DISTRIBUTIONS -----

# EA SURFACE -----

Ea.surface <- bos[Irrigation == "Surface"][, .(min = min(E_a, na.rm = TRUE),
                                                    max = max(E_a, na.rm = TRUE))]

shape <- 3.502469
scale <- 0.5444373
minimum <- Ea.surface$min
maximum <- Ea.surface$max
weibull_dist <- sapply(c(minimum, maximum), function(x)
  pweibull(x, shape = shape, scale = scale))

# EC SURFACE -----

Ec.surface <- bos[Irrigation == "Surface"][, .(min = min(E_c, na.rm = TRUE),
                                                    max = max(E_c, na.rm = TRUE))]

shape1 <- 5.759496
shape2 <- 1.403552
minimum.beta <- Ec.surface$min
maximum.beta <- Ec.surface$max
beta_dist <- sapply(c(minimum.beta, maximum.beta), function(x)
  pbeta(x, shape1 = shape1, shape2 = shape2))

# EA SPRINKLER -----

Ea.sprinkler <- bos[Irrigation == "Sprinkler"][, .(min = min(E_a, na.rm = TRUE),
                                                    max = max(E_a, na.rm = TRUE))]

shape.spr <- 6.9913711
scale.spr <- 0.7451178
minimum.spr <- Ea.sprinkler$min
maximum.spr <- Ea.sprinkler$max
weibull_dist_spr <- sapply(c(minimum.spr, maximum.spr), function(x)
  pweibull(x, shape = shape.spr, scale = scale.spr))

# MANAGEMENT FACTOR (m) -----

```



```

shape1.m <- 5.759496
shape2.m <- 1.403552
minimum.m <- 0.65
maximum.m <- 1
beta_dist.m <- sapply(c(minimum.m, maximum.m), function(x)
  pbeta(x, shape1 = shape1.m, shape2 = shape2.m))

# FUNCTION TO TRANSFORM TO APPROPRIATE DISTRIBUTIONS -----

distributions_fun <- list(

  # SURFACE IRRIGATION
  # -----

  "Ea_surf" = function(x) {

    out <- qunif(x, weibull_dist[[1]], weibull_dist[[2]])
    out <- qweibull(out, shape, scale)
  },

  "Ec_surf" = function(x) {

    out <- qunif(x, beta_dist[[1]], beta_dist[[2]])
    out <- qbeta(out, shape1, shape2)
  },

  # SPRINKLER IRRIGATION
  # -----

  "Ea_sprinkler" = function(x) {

    out <- qunif(x, weibull_dist_spr[[1]], weibull_dist_spr[[2]])
    out <- qweibull(out, shape.spr, scale.spr)
  },

  "Ec_sprinkler" = function(x) qunif(x, 0.64, 0.96),

  # MICRO (DRIP) IRRIGATION
  # -----

  "Ea_micro" = function(x) out <- qunif(x, 0.75, 0.95),
  "Ec_micro" = function(x) out <- qunif(x, 0.9, 0.95),

  # PROPORTION LARGE
  # -----

  "Proportion_large" = function(x) x,

```

```

# MANAGEMENT FACTOR
# -----

"m" = function(x) {
  out <- qunif(x, beta_dist.m[[1]], beta_dist.m[[2]])
  out <- qbeta(out, shape1.m, shape2.m)
},

# REDUCTION IN MANAGEMENT FACTOR DUE TO LARGE-SCALE
# -----
"r_L" = function(x) qunif(x, 0, 0.5),

# IRRIGATED AREA DATASET
# -----

"X1" = function(x) floor(x * (4 - 1 + 1)) + 1,

# THRESHOLD FOR LARGE-SCALE IRRIGATED AREAS
# -----

"X2" = function(x) floor(x * (5 - 1 + 1)) + 1
)

```

2.3 Uncertainty in the proportion of large-scale irrigated areas

```

# DEFINE THE UNCERTAINTY IN THE LARGE FRACTION AT THE COUNTRY LEVEL -----

rohwer.frac <- rohwer[, .(Country, Large_fraction)]
rohwer.frac[, `:=` (min = Large_fraction, max = Large_fraction + 0.1)]

countries.list <- split(rohwer.frac, seq(nrow(rohwer.frac)))
names(countries.list) <- rohwer$Country

n.rows <- nrow(rohwer)
triggers.dt <- rohwer[rep(seq_len(n.rows), 4 * 5)][, .(Country, IFT)] %>%
  .[, X1:= rep(1:4, each = n.rows, times = 5)] %>%
  .[, X2:= rep(1:5, each = n.rows, times = 4)] %>%
  .[, Proportion_large:= runif(n.rows * 4 * 5)] %>%
  .[, index:= paste(Country, X1, X2, sep = ".")]

triggers.dt <- setkey(triggers.dt, index)

```

2.4 Function to create sample matrix and transform to appropriate distributions

```

# FULL ALGORITHM TO CREATE SAMPLE MATRIX -----

```

```

full_sample_matrix <- function(IFT, Country) {
  tmp <- sample_matrix_fun(IFT = IFT)
  mat <- tmp[["matrix"]]
  temp <- colnames(mat)
  mat <- sapply(seq_along(temp), function(x) distributions_fun[[temp[x]]](mat[, x]))
  colnames(mat) <- temp
  countries.frac <- countries.list[[Country]]
  out <- list(tmp$parameters, mat)
  names(out) <- c("parameters", "matrix")
  return(out)
}

```

2.5 Run the model

```

# FULL MODEL -----

full_model <- function(IFT, Country, sample.size, R) {

  country.differences <- setdiff(rohwer$Country, jager$Country)
  tmp <- full_sample_matrix(IFT = IFT, Country = Country)
  mat <- tmp$matrix

  if(IFT == "Surface" | IFT == "Mixed" | IFT == "Jager") {
    X1 <- mat[, "X1"]
    X2 <- mat[, "X2"]
    index <- paste(Country, X1, X2, sep = ".")
    Proportion_large <- triggers.dt[index][, Proportion_large]
  }

  if(IFT == "Surface") {

    Mf <- mat[, "m"] - mat[, "r_L"] * Proportion_large
    y <- mat[, "Ea_surf"] * mat[, "Ec_surf"] * Mf

  } else if(IFT == "Sprinkler") {

    Mf <- mat[, "m"]
    y <- mat[, "Ea_sprinkler"] * mat[, "Ec_sprinkler"] * Mf

  } else if(IFT == "Mixed") {

    Mf.surf <- mat[, "m"] - mat[, "r_L"] * Proportion_large
    y.surf <- mat[, "Ea_surf"] * mat[, "Ec_surf"] * Mf.surf

    Mf.sprink <- mat[, "m"]
    y.sprink <- mat[, "Ea_sprinkler"] * mat[, "Ec_sprinkler"] * Mf.sprink
  }
}

```

```

y <- 0.5 * y.surf + mat[, "r_L"] * y.sprink

} else if(IFT == "Micro") {

  Mf <- mat[, "m"]
  y <- mat[, "Ea_micro"] * mat[, "Ec_micro"] * Mf

} else if(IFT == "Jager") {

  if(Country %in% country.differences == TRUE) {
    next
  }

  Mf.surf <- mat[, "m"] - mat[, "r_L"] * Proportion_large
  y.surf <- mat[, "Ea_surf"] * mat[, "Ec_surf"] * Mf.surf

  Mf.spr <- mat[, "m"]
  y.spr <- mat[, "Ea_sprinkler"] * mat[, "Ec_sprinkler"] * Mf.spr

  Mf.micro <- mat[, "m"]
  y.micro <- mat[, "Ea_micro"] * mat[, "Ec_micro"] * Mf.micro

  y <- jager.list[[Country]]$Surface_fraction * y.surf +
    jager.list[[Country]]$Sprinkler_fraction * y.spr +
    jager.list[[Country]]$Drip_fraction * y.micro

}

ind <- sobol_indices(N = sample.size, Y = y, params = tmp$parameters,
                    boot = TRUE, R = R)
out <- list(y, ind)
names(out) <- c("output", "indices")
return(out)
}

```

2.6 Define settings

```
# DEFINE SETTINGS -----
```

```

N <- 2^14
R <- 10^2

```

2.7 Run model

```
# RUN MODEL -----
```

```
new.rohwer <- rohwer[Country %in% jager$Country][, IFT:= "Jager"]
```

```
all.dt <- list(rohwer, new.rohwer)

y <- list()
for(j in 1:length(all.dt)) {
  y[[j]] <- mclapply(1:nrow(all.dt[[j]]), function(x)
    full_model(IFT = all.dt[[j]][[x, "IFT"]],
               Country = all.dt[[j]][[x, "Country"]],
               sample.size = N,
               R = R),
    mc.cores = detectCores() * 0.75)
}
```

2.8 Extract model output

```
# EXTRACT MODEL OUTPUT -----

names(y) <- c("Rohwer et al. 2007", "Jägermeyr et al. 2015")

output <- tmp <- list()
for(i in names(y)) {
  output[[i]] <- lapply(y[[i]], function(x) x[["output"]][1:(2 * N)])

  if(i == "Rohwer et al. 2007") {

    names(output[[i]]) <- rohwer$Country

  } else if(i == "Jägermeyr et al. 2015") {

    names(output[[i]]) <- new.rohwer$Country

  }
  tmp[[i]] <- lapply(output[[i]], data.table) %>%
    rbindlist(., idcol = "Country")

  if(i == "Rohwer et al. 2007") {

    tmp[[i]] <- merge(tmp[[i]], rohwer[, .(Country, IFT)], all.x = TRUE) %>%
      .[, IFT:= factor(IFT, levels = c("Surface", "Sprinkler", "Micro", "Mixed"))]

  } else if(i == "Jägermeyr et al. 2015") {

    tmp[[i]] <- tmp[[i]][, IFT:= "Jager"]

  }

  tmp[[i]] <- tmp[[i]][, Continent:= countrycode(tmp[[i]][, Country],
                                                  origin = "country.name"),
```

```

                                destination = "continent")]]
}

## Warning in countrycode_convert(sourcevar = sourcevar, origin = origin, destination = dest,
## Warning in countrycode_convert(sourcevar = sourcevar, origin = origin, destination = dest,
uncertainty.dt <- rbindlist(tmp, idcol = "Approach")
uncertainty.dt <- uncertainty.dt[, Study:= ifelse(IFT == "Jager",
                                                "The proportion of IFTs is known",
                                                "The proportion of IFTs is not known")]

# EXPORT UNCERTAINTY IN IRRIGATION EFFICIENCY -----

fwrite(uncertainty.dt, "uncertainty.dt.csv")

# COMPUTE RANGES -----

calc <- uncertainty.dt[, .(min = min(V1), max = max(V1)), .(Continent, Country)] %>%
  .[, .(range = max - min), .(Continent, Country)] %>%
  .[order(range)]

print(calc, n = Inf)

```

```

##      Continent      Country      range
##  1:      Asia      Cyprus 0.4679420
##  2:      Asia United Arab Emirates 0.4900561
##  3:      Asia      Israel 0.4944147
##  4:      Asia      Jordan 0.5149145
##  5:     Europe      Austria 0.6014893
##  6:     Europe      Belgium 0.6014893
##  7:      <NA>    Byelarus 0.6014893
##  8:     Europe      Denmark 0.6014893
##  9:     Europe      Finland 0.6014893
## 10:     Europe      Germany 0.6014893
## 11:     Europe      Greece 0.6014893
## 12:     Europe      Hungary 0.6014893
## 13:     Europe      Latvia 0.6014893
## 14:     Europe      Lithuania 0.6014893
## 15:     Europe      Luxembourg 0.6014893
## 16:     Africa      Malawi 0.6014893
## 17:     Europe      Slovakia 0.6014893
## 18:     Europe      Sweden 0.6014893
## 19:     Europe      Switzerland 0.6014893
## 20:     Europe      Ukraine 0.6147176
## 21:     Europe      Czech Republic 0.6477047
## 22:     Europe      Russia 0.6622102
## 23:     Europe      Croatia 0.6645827
## 24:     Europe      United Kingdom 0.6680857

```


## 25:	Europe	Romania	0.6684038
## 26:	Africa	Swaziland	0.6796764
## 27:	Americas	Cuba	0.6796800
## 28:	Africa	Benin	0.6838233
## 29:	Americas	United States	0.6859862
## 30:	Asia	Brunei	0.6879111
## 31:	Asia	Lebanon	0.6892404
## 32:	Europe	Netherlands	0.6896682
## 33:	Asia	Saudi Arabia	0.6898575
## 34:	Asia	Kazakhstan	0.6920644
## 35:	Africa	Mozambique	0.6939102
## 36:	Americas	Brazil	0.6959479
## 37:	Europe	France	0.6976147
## 38:	Africa	Zambia	0.6985666
## 39:	Africa	Zimbabwe	0.6985699
## 40:	Africa	Namibia	0.7002246
## 41:	Africa	South Africa	0.7025134
## 42:	Africa	Tunisia	0.7025813
## 43:	Asia	Qatar	0.7036842
## 44:	Asia	Kuwait	0.7046397
## 45:	Americas	Canada	0.7077460
## 46:	Africa	Ivory Coast	0.7091386
## 47:	Europe	Italy	0.7108935
## 48:	Africa	Burkina Faso	0.7115694
## 49:	Europe	Bulgaria	0.7147026
## 50:	Africa	Algeria	0.7182193
## 51:	Europe	Spain	0.7190056
## 52:	Americas	French Guiana	0.7191150
## 53:	Oceania	Australia	0.7218235
## 54:	Africa	Lesotho	0.7226186
## 55:	Asia	Japan	0.7247774
## 56:	Americas	Uruguay	0.7264713
## 57:	Asia	Iraq	0.7277116
## 58:	Asia	Azerbaijan	0.7284226
## 59:	Africa	Libya	0.7299519
## 60:	Africa	Zaire	0.7306228
## 61:	Africa	Botswana	0.7322712
## 62:	Africa	Gabon	0.7325094
## 63:	Americas	Paraguay	0.7327599
## 64:	Asia	Turkey	0.7330840
## 65:	Africa	Uganda	0.7335162
## 66:	Americas	Jamaica	0.7340006
## 67:	Asia	Burma	0.7344695
## 68:	Americas	Guatemala	0.7352743
## 69:	Africa	Tanzania	0.7353794
## 70:	Oceania	Papua New Guinea	0.7357704
## 71:	Asia	Nepal	0.7364300
## 72:	Africa	Congo	0.7364368

## 73:	Americas	Ecuador	0.7379232
## 74:	Africa	Kenya	0.7381012
## 75:	Americas	Haiti	0.7389654
## 76:	Africa	Chad	0.7398257
## 77:	Africa	Central African Republic	0.7406275
## 78:	Americas	Colombia	0.7406412
## 79:	Africa	Gambia	0.7410900
## 80:	Americas	Puerto Rico	0.7411452
## 81:	Africa	Western Sahara	0.7412732
## 82:	Europe	Portugal	0.7424699
## 83:	Americas	El Salvador	0.7424882
## 84:	Asia	India	0.7430188
## 85:	Africa	Cameroon	0.7430382
## 86:	Asia	Turkmenistan	0.7431978
## 87:	Africa	Egypt	0.7434191
## 88:	Asia	Syria	0.7437367
## 89:	Africa	Madagascar	0.7453378
## 90:	Americas	Costa Rica	0.7460634
## 91:	Asia	Yemen	0.7464134
## 92:	Africa	Equatorial Guinea	0.7472551
## 93:	Europe	Serbia	0.7476467
## 94:	Africa	Liberia	0.7479554
## 95:	Americas	Bolivia	0.7480052
## 96:	Africa	Somalia	0.7480674
## 97:	Asia	Laos	0.7481253
## 98:	Africa	Ethiopia	0.7482251
## 99:	Africa	Rwanda	0.7482431
## 100:	Asia	Kyrgyzstan	0.7484823
## 101:	Asia	Bhutan	0.7487014
## 102:	Europe	Norway	0.7488203
## 103:	Europe	Poland	0.7495878
## 104:	Africa	Mali	0.7501681
## 105:	Asia	Sri Lanka	0.7502131
## 106:	Asia	Mongolia	0.7502820
## 107:	Americas	Trinidad	0.7505246
## 108:	Africa	Guinea-Bissau	0.7507230
## 109:	Africa	Guinea	0.7508012
## 110:	Asia	China	0.7508179
## 111:	Africa	Mauritania	0.7508221
## 112:	Asia	Indonesia	0.7509219
## 113:	Asia	Armenia	0.7511245
## 114:	Europe	Bosnia and Herzegovina	0.7513991
## 115:	Africa	Morocco	0.7514743
## 116:	Asia	Iran	0.7514788
## 117:	Americas	Suriname	0.7515058
## 118:	Americas	Peru	0.7516554
## 119:	Americas	Argentina	0.7521091
## 120:	Americas	Chile	0.7522434

## 121:	Africa	Sierra Leone	0.7525826
## 122:	Africa	Niger	0.7526578
## 123:	Africa	Angola	0.7530253
## 124:	Africa	Burundi	0.7531444
## 125:	Americas	Belize	0.7533846
## 126:	Asia	South Korea	0.7544530
## 127:	Americas	Mexico	0.7544977
## 128:	Asia	Malaysia	0.7545882
## 129:	Africa	Djibouti	0.7546681
## 130:	Americas	Honduras	0.7550064
## 131:	Africa	Togo	0.7550732
## 132:	Africa	Eritrea	0.7555949
## 133:	Europe	Moldova	0.7563886
## 134:	Asia	Cambodia	0.7569788
## 135:	Africa	Senegal	0.7574388
## 136:	Europe	Macedonia	0.7578519
## 137:	Africa	Nigeria	0.7589399
## 138:	Africa	Sudan	0.7593515
## 139:	Asia	Thailand	0.7607690
## 140:	Asia	Pakistan	0.7615949
## 141:	Americas	Nicaragua	0.7622110
## 142:	Asia	Vietnam	0.7641254
## 143:	Americas	Venezuela	0.7645259
## 144:	Americas	Dominican Republic	0.7645690
## 145:	Europe	Albania	0.7647019
## 146:	Asia	Uzbekistan	0.7672137
## 147:	Asia	Tajikistan	0.7680949
## 148:	Asia	Georgia	0.7709388
## 149:	Asia	Bangladesh	0.7714909
## 150:	Americas	Guyana	0.7752999
## 151:	Asia	Philippines	0.7759418
## 152:	Americas	Panama	0.7774470
## 153:	Europe	Slovenia	0.7784899
## 154:	Asia	North Korea	0.7820092
## 155:	Africa	Ghana	0.7850875
## 156:	Asia	Afghanistan	0.7865884
## 157:	Asia	Oman	0.7878713
## 158:	Oceania	New Zealand	0.7892427
##	Continent	Country	range

```
ggplot(calc, aes(range)) +
  geom_histogram() +
  labs(x = "Range", y = "N. of countries") +
  theme_AP()
```

```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```




```
# COMPARE RANGES -----

ranges_empirical <- uncertainty.dt[, .(higher = max(V1), lower = min(V1)), IFT] %>%
  .[, Study:= "This study"]%>%
  .[!IFT == "Jager"]

ranges_efficiencies <- fread("ranges_efficiencies.csv")

rbind(ranges_empirical, ranges_efficiencies)[, mean.value:= (higher + lower) / 2] %>%
  .[, Study:= factor(Study, levels = c("This study",
    "Brouwer et al. 1989",
    "Rogers et al. 1997",
    "Clemmens and Molden 2007",
    "Rohwer et al. 2007",
    "Van Halsema and Vincent 2012"))] %>%

na.omit() %>%
ggplot(., aes(mean.value, Study, color = ifelse(Study == "This study", "red", "black"))) +
  geom_point() +
  scale_x_continuous(breaks = pretty_breaks(n = 3)) +
  geom_errorbar(aes(xmin = lower, xmax = higher)) +
  scale_color_identity() +
  facet_wrap(~IFT, ncol = 4) +
  labs(x = "Irrigation efficiency", y = "") +
  theme_AP()
```



```

# CHECK OVERLAP -----

dd <- uncertainty.dt[!Continent == "Oceania"][Study == "The proportion of IFTs is not known"] %>%
  split(., .$Continent, drop = TRUE)

overlap.dt <- lapply(dd, function(x) split(x, x$IFT, drop = TRUE)) %>%
  lapply(., function(x) lapply(x, function(y) y[, V1])) %>%
  lapply(., function(x) overlap(x)$OV)

overlap.dt

## $Africa
## Surface-Sprinkler      Surface-Mixed      Sprinkler-Mixed
##           0.2341197           0.7482128           0.1513037
##
## $Americas
## Surface-Mixed
##           0.7622839
##
## $Asia
## Surface-Micro Surface-Mixed      Micro-Mixed
##           0.04502982           0.72015229           0.01232303
##
## $Europe
## Surface-Sprinkler      Surface-Mixed      Sprinkler-Mixed
##           0.2404475           0.7435392           0.1536190

ff <- uncertainty.dt[!Continent == "Oceania"] %>%
  .[Country %in% intersect(rohwer[, Country], jager[, Country])] %>%
  split(., .$Country, drop = TRUE) %>%
  lapply(., function(x) split(x, x$Approach, drop = TRUE)) %>%
  lapply(., function(x) lapply(x, function(y) y[, V1])) %>%
  lapply(., function(x) overlap(x)$OV) %>%
  lapply(., data.table) %>%
  rbindlist(., idcol = "Country") %>%
  .[, Continent:= countrycode(., Country,
                             origin = "country.name",
                             destination = "continent")]

list_continents <- list(c("Africa", "Asia"), c("Americas", "Europe"))

# PLOT OVERLAP -----

dd <- list()
for(i in 1:length(list_continents)) {
  dd[[i]] <- ff[Continent %in% list_continents[[i]]] %>%
    ggplot(., aes(reorder(Country, V1), V1)) +
    geom_point() +

```

```

scale_color_discrete(name = "GM") +
labs(y = "Overlap", x = "") +
facet_wrap(~Continent, scales = "free_y") +
coord_flip() +
theme_AP()
}

```

```
dd
```

```
## [[1]]
```



```
##
```

```
## [[2]]
```



3 Uncertainty analysis

```
# PLOT UNCERTAINTY -----

gg <- list()
for (i in 1:length(list_continents)) {
  gg[[i]] <- ggplot(uncertainty.dt[Continent %in% list_continents[[i]]],
    aes(x = V1, y = fct_reorder(Country, V1), fill = Study)) +
  geom_density_ridges(scale = 2, alpha = 0.3) +
  labs(x = "Irrigation efficiency", y = "") +
  facet_wrap(~Continent, scales = "free") +
  scale_x_continuous(breaks = pretty_breaks(n = 3),
```

```
      limits = c(0, 1)) +  
scale_fill_manual(values = wes_palette("Chevalier1")) +  
theme_AP() +  
theme(legend.position = "top") +  
guides(fill = guide_legend(nrow = 2, byrow = TRUE))  
}
```


MERGE PLOTS -----

```
gg
```

```
## [[1]]
```

```
## Picking joint bandwidth of 0.0117
```

```
## Picking joint bandwidth of 0.0118
```




##

[[2]]

Picking joint bandwidth of 0.012

Picking joint bandwidth of 0.0108



PLOT UNCERTAINTY IN EACH IRRIGATION TECHNOLOGY -----

```
gg <- list()

for(i in 1:length(list_continents)) {
  gg[[i]] <- uncertainty.dt[Approach == "Rohwer et al. 2007"][Continent %in% list_continents[i]]
  ggplot(., aes(x = V1, y = fct_reorder(Country, V1), fill = IFT)) +
    geom_density_ridges(scale = 2, alpha = 0.3) +
    labs(x = "Irrigation efficiency", y = "") +
    facet_wrap(~Continent, scales = "free") +
    scale_x_continuous(breaks = pretty_breaks(n = 3),
                      limits = c(0, 1)) +
    theme_AP() +

```



```

    theme(legend.position = "top")
  if(i == 1) {
    gg[[i]] <- gg[[i]] +
      scale_fill_manual(values = c("#899DA4", "#C93312", "#DC863B", "#FAEFD1"),
                        labels = c("Surface", "Sprinkler", "Micro", "Mixed"),
                        name = "Irrigation")
  } else if(i == 2) {
    gg[[i]] <- gg[[i]] +
      scale_fill_manual(values = c("#899DA4", "#C93312", "#FAEFD1"),
                        labels = c("Surface", "Sprinkler", "Mixed"),
                        name = "Irrigation")
  }
}


gg

```

```
## [[1]]
```

```
## Picking joint bandwidth of 0.012
```

```
## Picking joint bandwidth of 0.012
```




##

[[2]]

Picking joint bandwidth of 0.0126

Picking joint bandwidth of 0.0113



```
# PLOT ROHWER ET AL.'S IRRIGATION EFFICIENCY VALUES -----

rohwer[, Continent:= countrycode(rohwer[, Country], origin = "country.name",
                                destination = "continent")]

## Warning in countrycode_convert(sourcevar = sourcevar, origin = origin, destination = dest,
dd <- list()
for (i in 1:length(list_continents)) {
  dd[[i]] <- ggplot(rohwer[Continent %in% list_continents[[i]]],
                    aes(x = Ep, y = fct_reorder(Country, Ep), color = IFT)) +
    geom_point() +
    labs(x = "Irrigation efficiency", y = "") +
    scale_x_continuous(breaks = pretty_breaks(n = 3),
```

```


    limits = c(0, 1)) +
  facet_wrap(~Continent, scales = "free") +
  scale_color_discrete(name = "Irrigation") +
  theme_AP()
}

```

```
dd
```


```
## [[1]]
```

```
## Warning: Removed 1 rows containing missing values (geom_point).
```



```
##
```

```
## [[2]]
```




```
# CALCULATE THE UNCERTAINTY IN THE RANGES -----

selection_continents <- c("Africa", "Asia", "Americas", "Europe")

factor_unc <- uncertainty.dt[, .(min = min(V1), max = max(V1)), .(Continent, Country)] %>%
  .[Continent %in% selection_continents] %>%
  .[, factor:= max / min]

ggplot(factor_unc, aes(factor)) +
  geom_histogram() +
  facet_wrap(~Continent, ncol = 4) +
  labs(x = "Factor", y = "N. of countries") +
  theme_AP()

## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```



*# Number of countries whose irrigation water withdrawals fluctuate a factor of x
due to uncertainty in irrigation efficiency*

```
factor_unc %>%
  .[, factor:= floor(max / min)] %>%
  .[, .(number.countries = .N), factor] %>%
  .[order(factor)] %>%
  print()
```

```
##      factor number.countries
## 1:      2              4
## 2:      3             15
## 3:      4              1
## 4:      5              4
## 5:      8              1
## 6:     12              1
## 7:     17             10
## 8:     18             18
## 9:     20              1
## 10:    24              6
## 11:    25              4
## 12:    26              8
## 13:    27             11
## 14:    28             14
## 15:    29             10
## 16:    30              5
## 17:    31              8
## 18:    32              6
## 19:    33              4
## 20:    34              3
## 21:    35              5
## 22:    36              1
## 23:    38              1
## 24:    39              3
## 25:    40              2
## 26:    41              1
## 27:    42              1
## 28:    47              1
## 29:    51              1
## 30:    52              3
```

```
## 31:      53      1
##      factor number.countries
```

3.1 Retrieve data from ISIMIP

```
# FUNCTIONS TO EXTRACT DATA FROM .NC FILES -----

coords2country = function(points) {
  countriesSP <- rworldmap::getMap(resolution = 'low')
  pointsSP = sp::SpatialPoints(points, proj4string=CRS(proj4string(countriesSP)))
  indices = sp::over(pointsSP, countriesSP)
  indices$ADMIN
}

# Function to load and extract data from .nc files from ISIMIP
open_nc_files <- function(file, dname, selected.years, vec) {
  ncin <- nc_open(file)
  # get longitude, latitude, time
  lon <- ncvar_get(ncin, "lon")
  lat <- ncvar_get(ncin, "lat")
  # Get variable
  tmp_array <- ncvar_get(ncin, dname)
  m <- lapply(selected.years, function(x) vec[[x]])

  out <- lapply(m, function(x) {
    tmp_slice <- lapply(x, function(y) tmp_array[, , y])
    # create dataframe -- reshape data
    # matrix (nlon*nlat rows by 2 cols) of lons and lats
    lonlat <- as.matrix(expand.grid(lon,lat))
    # vector of `tmp` values
    tmp_vec <- lapply(tmp_slice, function(x) as.vector(x))
    # create dataframe and add names
    tmp_df01 <- lapply(tmp_vec, function(x) data.frame(cbind(lonlat, x)))
    names(tmp_df01) <- x
    da <- lapply(tmp_df01, data.table) %>%
      rbindlist(., idcol = "month") %>%
      na.omit()
    # Convert coordinates to country
    Country <- coords2country(da[1:nrow(da), 2:3])
    df <- cbind(Country, da)
    setDT(df)
    out <- na.omit(df)[, .(Water.Withdrawn = sum(x)), Country]
    out[, Water.Withdrawn:= Water.Withdrawn * 10000]
    out[, Continent:= countrycode(out[, Country],
                                   origin = "country.name",
                                   destination = "continent")] %>%
    .[, Code:= countrycode(out[, Country],
```

```

        origin = "country.name",
        destination = "un")] %>%
    .[, Country:= countrycode(out[, Code],
        origin = "un",
        destination = "country.name")] %>%
    .[!Continent == "Oceania"]
    setcolorder(out, c("Country", "Continent", "Code", "Water.Withdrawn"))
  })
  return(out)
}

# READ IN NC FILES -----

# Define settings
vecs <- 1:((2010 - 1970) * 12)
vec <- split(vecs, ceiling(seq_along(vecs) / 12))
names(vec) <- 1971:2010
selected.years <- "2010"
dname <- "pirrww"

files <- list("h08_wfdei_nobc_hist_varsoc_co2_pirrww_global_monthly_1971_2010.nc",
  "pcr-globwb_wfdei_nobc_hist_varsoc_co2_pirrww_global_monthly_1971_2010.nc",
  "lpjml_wfdei_nobc_hist_varsoc_co2_pirrww_global_monthly_1971_2010.nc",
  "watergap2_wfdei_nobc_hist_varsoc_co2_pirrww_global_monthly_1971_2010.nc")

names.isimip <- c("H08", "PCR-GLOBWB", "LPJmL", "WaterGap")

isimip.dt <- mclapply(files, function(x)
  open_nc_files(file = x, dname = dname, selected.years = selected.years, vec = vec),
  mc.cores = detectCores() * 0.75)

# EXTRACT CORRECTIVE COEFFICIENTS FOR IRRIGATION EFFICIENCY FOR LPJML -----

ncin <- nc_open("irrigation_project_efficiencies.nc")
lon <- ncvar_get(ncin, "lon")
lat <- ncvar_get(ncin, "lat")
tmp_array <- ncvar_get(ncin)
lonlat <- as.matrix(expand.grid(lon,lat))
da <- na.omit(cbind(lonlat, as.vector(tmp_array))) %>%
  data.frame() %>%
  na.omit()
Country <- coords2country(da[1:nrow(da), 1:2])
lpjml_efficiencies <- cbind(Country, da) %>%
  na.omit() %>%
  data.table() %>%
  .[, .(Ep = mean(V3)), Country]

```



```

# ARRANGE NC FILES -----

names(isimip.dt) <- names.isimip

isimip.dt <- lapply(isimip.dt, function(x) rbindlist(x)) %>%
  rbindlist(., idcol = "Model") %>%
  na.omit() %>%
  # To correct for duplicate country in Cyprus
  .[, .(Water.Withdrawn = mean(Water.Withdrawn)), .(Model, Country, Continent, Code)]

lpjml_harmonized <- merge(isimip.dt[Model == "LPJmL"], lpjml_efficiencies, all.x = TRUE) %>%
  .[, Water.Withdrawn:= Water.Withdrawn * Ep] %>%
  .[, Ep:= NULL]

isimip.dt <- rbind(isimip.dt[!Model == "LPJmL"], lpjml_harmonized)

fwrite(isimip.dt, "isimip.dt")

# MERGE UNCERTAINTY IN EP WITH ISIMIP DATA -----

efficiency.dt <- copy(uncertainty.dt) %>%
  setnames(., "V1", "Ep")

ghm.dt <- dcast(isimip.dt, Country + Continent + Code ~ Model, value.var = "Water.Withdrawn")
full.dt <- merge(efficiency.dt, ghm.dt, by = c("Country", "Continent"), all.x = TRUE) %>%
  .[, (names.isimip):= lapply(.SD, function(x) x / Ep), .SDcols = names.isimip]
tmp.dt <- melt(full.dt, measure.vars = names.isimip, variable.name = "Model",
  value.name = "IWW_corrected")
ghm.large <- melt(ghm.dt, measure.vars = names.isimip, variable.name = "Model",
  value.name = "IWW")
gm.uncertainty <- tmp.dt[, .(min = min(IWW_corrected), max = max(IWW_corrected)),
  .(Country, Continent, Model)]
gm.dt <- merge(ghm.large, gm.uncertainty)

# PLOT UNCERTAINTY IN EP WITH ISIMIP DATA -----

countries_list <- c("Egypt", "Sudan", "South Africa", "Morocco", "Madagascar",
  "United States", "Mexico", "Brazil", "Chile", "Peru",
  "India", "China", "Pakistan", "Iran", "Indonesia",
  "Italy", "Spain", "France", "Ukraine", "Romania")

gm.dt[Country %in% countries_list] %>%
  ggplot(., aes(reorder(Country, IWW), IWW, color = Model)) +
  geom_point(position = position_dodge(0.7)) +
  geom_errorbar(aes(ymin = min,
    ymax = max),
    position = position_dodge(0.7)) +
  scale_y_log10(breaks = trans_breaks("log10", function(x) 10 ^ (2 * x)),

```


```

    labels = trans_format("log10", math_format(10 ^ .x))) +
    scale_color_discrete(name = "GM") +
    labs(y = expression(paste("Irrigation water withdrawal ", " ", "(" , 10^9, m^3/year, " ", ")")),
         x = "") +
    facet_wrap(~Continent, scales = "free_y") +
    coord_flip() +
    theme_AP()

```

Warning: Removed 1 rows containing missing values (geom_point).

GM H08 PCR-GLOBWB LPJmL WaterGap



PLOT RANGES OF STRUCTURAL UNCERTAINTY AND RANGES OF

STRUCTURAL UNCERTAINTY + UNCERTAINTY IN IRRIGATION EFFICIENCY -----

```

range.gm <- gm.dt %>%
  .[, .(min = min(IWW, na.rm = TRUE), max = max(IWW, na.rm = TRUE)), .(Country, Continent)] %>%
  .[, Approach:= "WaterGap, LPJmL, H08, PCR-GLOBWB"]

range.study <- gm.dt %>%
  .[, .(min = min(min, na.rm = TRUE), max = max(max, na.rm = TRUE)), .(Country, Continent)] %>%
  .[, Approach:= "WaterGap, LPJmL, H08, PCR-GLOBWB \n + uncertainty in irrigation efficiency"]


rbind(range.gm, range.study) %>%
  .[Country %in% countries_list] %>%
  .[, mean:= (min + max) / 2] %>%
  ggplot(. , aes(reorder(Country, mean), mean, color = Approach)) +
  geom_errorbar(aes(ymin = min,
                    ymax = max),

```

```

    position = position_dodge(0.7)) +
scale_y_log10(breaks = trans_breaks("log10", function(x) 10 ^ (2 * x)),
    labels = trans_format("log10", math_format(10 ^ .x))) +
scale_color_manual(name = "GM", values = wes_palette("Royal1")) +
labs(y = expression(paste("Irrigation water withdrawal ", " ", "(", 10^9, m^3/year, " ", ")"),
    x = "")) +
facet_wrap(~Continent, scales = "free_y") +
coord_flip() +
theme_AP() +
guides(color = guide_legend(nrow = 2, byrow = TRUE))

```



```

# PLOT RANGES OF STRUCTURAL UNCERTAINTY AND RANGES OF

```

```

# STRUCTURAL UNCERTAINTY + UNCERTAINTY IN IRRIGATION EFFICIENCY (COMPLETE) -----

```

```

dd <- list()
for (i in 1:length(list_continents)) {
  dd[[i]] <- rbind(range.gm, range.study) %>%
    .[, mean:= (min + max) / 2] %>%
    .[Continent %in% list_continents[[i]]] %>%
  ggplot(., aes(reorder(Country, mean), mean, color = Approach)) +
  geom_errorbar(aes(ymin = min,
    ymax = max),
    position = position_dodge(0.7)) +
  scale_y_log10(breaks = trans_breaks("log10", function(x) 10 ^ (2 * x)),
    labels = trans_format("log10", math_format(10 ^ .x))) +
  scale_color_manual(name = "GM", values = wes_palette("Royal1")) +
  labs(y = expression(paste("Irrigation water withdrawal ", " ", "(", 10^9, m^3/year, " ", ")"),
    x = "")) +
  facet_wrap(~Continent, scales = "free_y") +

```

```

coord_flip() +
theme_AP() +
guides(color = guide_legend(nrow = 2, byrow = TRUE))
}

```


```
dd
```

```
## [[1]]
```

```
## Warning: Transformation introduced infinite values in continuous y-axis
```


```
## Warning: Transformation introduced infinite values in continuous y-axis
```

```
## Warning: Transformation introduced infinite values in continuous y-axis
```



```
##
## [[2]]

## Warning: Transformation introduced infinite values in continuous y-axis
```



```
# PRINT RANGES -----
# print(range.study, n = Inf)
```

4 Sensitivity analysis

```
# SAMPLE MATRIX DISTRIBUTIONS -----
# Define labels
```


```
label_facets <- c("Ea_surf" = "$E_{a_{su}}$",
                  "Ec_surf" = "$E_{c_{su}}$",
                  "Ea_sprinkler" = "$E_{a_{sp}}$",
                  "Ec_sprinkler" = "$E_{c_{sp}}$",
                  "Ea_micro" = "$E_{a_{mi}}$",
                  "Ec_micro" = "$E_{c_{mi}}$",
                  "Proportion_large" = "$f_L$",
                  "m" = "$m$",
                  "r_L" = "$r_L$")

mat <- data.table(full_sample_matrix(IFT = "Jager", Country = "Spain")$matrix)
mat <- mat[, Proportion_large:= NULL]
```

```
## Warning in `[.data.table`(mat, , `:=`(Proportion_large, NULL))`: Column
## 'Proportion_large' does not exist to remove
```

```
melt(mat, measure.vars = colnames(mat)) %>%
  ggplot(., aes(value)) +
  geom_histogram() +
  labs(x = "Value", y = "Counts") +
  scale_x_continuous(breaks = pretty_breaks(n = 3)) +
  facet_wrap(~variable) +
  theme_AP()
```

```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```



```
# EXTRACT SOBOLO' INDICES -----
```

```
ind <- lapply(y$`Rohwer et al. 2007`, function(x) x[["indices"]])$results)
names(ind) <- rohwer$Country
ind <- rbindlist(ind, idcol = "Country")
```



```

jager.tmp <- lapply(y[["Jägermeyr et al. 2015"]], function(x) x$indices$results)
names(jager.tmp) <- new.rohwer$Country

jager.ind <- rbindlist(jager.tmp, idcol = "Country") %>%
  .[, Continent:= countrycode(., Country),
    origin = "country.name",
    destination = "continent")] %>%
  .[, parameters:= ifelse(parameters == "Ea_surf", "E[a[su]]",
    ifelse(parameters == "Ec_surf", "E[c[su]]",
    ifelse(parameters == "Ea_sprinkler", "E[a[sp]]",
    ifelse(parameters == "Ec_sprinkler", "E[c[sp]]",
    ifelse(parameters == "Ea_micro", "E[a[mi]]",
    ifelse(parameters == "Ec_micro", "E[c[mi]]",
    ifelse(parameters == "Proportion_l

## Warning in countrycode_convert(sourcevar = sourcevar, origin = origin, destination = dest,
Continent_vector <- c("Africa", "Americas", "Asia", "Europe")


lapply(Continent_vector, function(x)
  ggplot(jager.ind[Continent == x], aes(parameters, original, fill = sensitivity), color = bla
  geom_bar(stat = "identity", position = position_dodge(0.6), color = "black") +
  scale_fill_discrete(name = "Sensitivity", labels = c("Si", "Ti")) +
  labs(x = "", y = "Sobol' indices") +
  scale_x_discrete(labels = ggplot2:::parse_safe) +
  coord_flip() +
  scale_y_continuous(breaks = pretty_breaks(n = 3)) +
  facet_wrap(~Country) +
  theme_AP() +
  theme(strip.text.x = element_text(size = 6),
    axis.text.x = element_text(size = 6)) +
  ggtitle(x)
)

## [[1]]

```



Africa

Sensitivity ■ Si ■ Ti



[[2]]


Americas



[[3]]

Asia

Sensitivity ■ Si ■ Ti



[[4]]

Europe

Sensitivity ■ Si ■ Ti

