

Document Markup Language (DML) Specification 1.0

Abstract

This specification defines the Document Markup Language (DML), a markup language for books, articles, notes and other types of documents. DML is normatively available as a [RELAX NG](#) (Appendix A, pg. 22) schema with additional [Schematron](#) (Appendix A, pg. 22) assertions.

Conventions

The keywords *must*, *must not*, *required*, *shall*, *shall not*, *should*, *should not*, *recommended*, *may*, and *optional*, when emphasized, are to be interpreted as described in [IETF RFC 2119](#) (Appendix A, pg. 23).

- A `monospaced` font is used for code, elements, attributes, tags and value literals.
- An *italic monospaced* font is used for variables.

Element:

When an element (node with type `element`) is mentioned in the text, it is always preceded by a slash (/) and it optionally has an associated `attribute` (pg. 1) as a predicate. [Element EBNF definition](#) (pg. 2).

Notation for the `/section` element

```
/section  
/section[@role]
```

Attribute:

When an attribute (node with type `attribute`) is mentioned in the text, it is always preceded by an at-sign (@) and it optionally has an associated value. [Attribute EBNF definition](#) (pg. 2).

```
@role
@role="chapter"
```

When a tag is mentioned in the text, it is always preceded by a less-than symbol (<) and it is followed by a greater-than symbol (>). [Tag EBNF definition](#) (pg. 2).

Notation for the start tag `<section ...>`

```
<section role="chapter" ...>
```

*
Zero or more times.

EBNF^[1] definitions

- Element ::= '/' Name ('[' Attribute ']')*
- Attribute ::= '@' Name ('=' ' "' Value '"')?
- Tag ::= '<' Name (S
Name '=' ' "' Value '"')* S? '...' ? ' / '? '>'
- Name ::= ([A-Za-z] + ':')? [A-Za-z_] [A-Za-z0-9_-.]*
- Value ::= [^<>"']+
- S ::= (#x20 | #x9 | #xD | #xA)+

Document Markup Language (DML) Specification 1.0

Status of this document

This is a *draft* and it may change at any time based on comments and on its development process.

Table of Contents

1. Elements.....	4
1.1. The <code>/abbr</code> element.....	5
1.2. The <code>/cell</code> element.....	5
1.3. The <code>/citation</code> element.....	6
1.4. The <code>/dml</code> element.....	6
1.5. The <code>/em</code> element.....	7
1.6. The <code>/example</code> element.....	7
1.7. The <code>/figure</code> element.....	8
1.8. The <code>/group</code> element.....	9
1.9. The <code>/item</code> element.....	9
1.10. The <code>/list</code> element.....	10
1.11. The <code>/metadata</code> element.....	13
1.12. The <code>/note</code> element.....	13
1.13. The <code>/object</code> element.....	14
1.14. The <code>/p</code> element.....	15
1.15. The <code>/quote</code> element.....	16
1.16. The <code>/section</code> element.....	17
1.17. The <code>/span</code> element.....	18
1.18. The <code>/sub</code> element.....	18
1.19. The <code>/summary</code> element.....	18
1.20. The <code>/sup</code> element.....	18
1.21. The <code>/table</code> element.....	18
1.22. The <code>/title</code> element.....	19
2. Core attributes.....	19
2.1. The <code>@xml:id</code> attribute.....	19
2.2. The <code>@xml:lang</code> attribute.....	19
2.3. The <code>@class</code> attribute.....	19
2.4. The <code>@href</code> attribute.....	20
2.5. The <code>@status</code> attribute.....	20
3. Metadata attributes.....	20
3.1. The <code>@about</code> attribute.....	20
3.2. The <code>@content</code> attribute.....	20
3.3. The <code>@datatype</code> attribute.....	21
3.4. The <code>@typeof</code> attribute.....	21
3.5. The <code>@property</code> attribute.....	21
3.6. The <code>@resource</code> attribute.....	21
4. Flow.....	21
4.1. Block.....	21
4.2. Table.....	21
4.3. Inline.....	22
5. Relationship with RDFa.....	22
6. Namespace.....	22
7. Schema.....	22
Appendix A — Resources.....	22

1. Elements

(Draft) Add /listing for program listing? in cdm!

1.1. The `/abbr` element

The `/abbr` element represents an abbreviation or acronym.

Status

Released

Flow

Inline (Section 4.3, pg. 22)

Children

```
( $inline[not( /abbr )] | text() )+
```

Attributes

```
( $core.attrs* | $meta.attrs* )
```

Parents

```
( $block | $inline[not( /abbr )] )
```

The `@content` attribute (Section 3.2, pg. 20) may be used to provide an expansion of the abbreviation.

The `@about` attribute (Section 3.1, pg. 20) may be used to provide a resource which contains the expanded form.

`@content` and `@about` attributes are mutually exclusive.

Example 1.1-1: `/abbr` element with inline expansion

```
<p>Example of <abbr content="Document Markup Language">DML</abbr>'s /abbr  
element.</p>
```

Example 1.1-2: `/abbr` element with remote expansion

```
<p>Example of <abbr about="http://example.org/glossary#dml">DML</abbr>'s /abbr  
element.</p>
```

(Draft)

1.2. The `/cell` element

...?

1.3. The `/citation` element

The `/citation` element represents a citation reference of a quotation block.

Status

Released

Flow

[Block](#) (Section 4.1, pg. 21)

Children

```
( $inline | text() )+
```

Attributes

```
( $core.attrs* | $meta.attrs* )
```

Parents

```
( /quote )
```

1.4. The `/dml` element

The `/dml` element is the root element for a DML document.

Status

Released

Flow

[Block](#) (Section 4.1, pg. 21)

Children

```
( /title, $block[not( /title | /citation )]+ )  
(: this expression is more accurated but necessary? :)  
(  
  /title,  
  $block[not( /title | /citation | preceding-sibling::/section )]+,  
  /section*
```

)

Attributes

(\$core.attrs*)

(Draft) TODO: examples

1.5. The `/em` element

The `/em` element represents an emphasized text.

Status

Released

Flow

[Inline](#) (Section 4.3, pg. 22)

Children

(\$inline | text())+

Attributes

(\$core.attrs* | \$meta.attrs* | @role?)

Parents

(\$block | \$inline)

The `@role` attribute *may* be used to provide strong emphasized text with `strong` value.

Example 1.5-1: Usage of `/em` element

```
<p>
  <em>Lorem ipsum</em> dolor sit amet, consectetur adipisicing elit, sed do <em
    role="strong">eiusmod tempor incididunt ut labore</em> et dolore magna aliqua.
</p>
```

1.6. The `/example` element

The `/example` element represents an example.

Status

Released

Flow

[Block](#) (Section 4.1, pg. 21)

Children

```
( /title?, $block[not( /example | /citation )]+ )
```

Attributes

```
( $core.attrs* | $meta.attrs* )
```

Parents

```
( /dml | /note | /section )
```

Example 1.6-1: Usage of `/example` element

```
<example xml:id="example-identifier">
  <title>Title of the Lorem Ipsum example</title>
  <p>Lorem ipsum dolor sit amet...</p>
</example>
```

1.7. The `/figure` element

The `/figure` element is a figure container; it usually contains an illustration or something to be shown graphically.

Status

Released

Flow

[Block](#) (Section 4.1, pg. 21)

Children

```
( /title?, $block[not( /example | /figure | /citation | /quote )]+ )
```

Attributes

```
( $core.attrs* | $meta.attrs* )
```

Parents

```
( /dml | /example | /note | /section )
```


Example 1.7-1: Usage of `/figure` element

```
<figure xml:id="figure-identifier">
  <title>It shown an illustration throught a figure element</title>
  <object src="path/to/illustration"/>
</figure>
```

1.8. The `/group` element

The `/group` element is a generic table cell container.

Status

Released

Flow

[Table](#) (Section 4.2, pg. 21)

Children

(`/group+` | `/title+` | (`/title?`, `/cell+`))

Attributes

(`$core.attrs*` | `$meta.attrs*` | `@role?`)

Parents

(`/group` | `/table`)

The `@role` attribute *may* be used to provide a form to refine the `/group` element meaning. Allowed values are:

`header`

A header table group. Table header *must* be the first child of a `/table` element.

`footer`

A footer table group. Table footer *must* be child of a `/table` element.

1.9. The `/item` element

The `/item` element represents a list item container.

Status

Released

Flow

[Block](#) (Section 4.1, pg. 21)

Children

```
(  
  ( /title*, $block[not( /item | /title | /citation )]+ ) |  
  ( $inline | text() )+  
)
```

Attributes

```
( $core.attrs* | $meta.attrs* | @role? )
```

Parents

```
( /list )
```

(Draft) The functionality of `/item[@role="footer"]` is too specific for DML? maybe yes. Reevaluate.

The `@role` attribute *may* be used to provide a form to refine the `/item` element when is the last child of a `/list[@role="leaded"]` element. The only possible value is `footer`.

1.10. The `/list` element

The `/list` element represents a list of items.

Status

Released

Flow

[Block](#) (Section 4.1, pg. 21)

Children

```
( /title?, /item+ )
```

Attributes

```
( $core.attrs* | $meta.attrs* | @role? )
```

Parents

```
( /dml | $block[$block[not( self::/list )]] )
```

The `@role` attribute *may* be used to provide a form to refine the `/list` element meaning. Allowed values are:

`ordered`

A list which items order is relevant.

`lead`

(Review) A list with enforced relation between item title and item content. Like price list.

Example 1.10-1: Simple list

```
<list>
  <item>sugar</item>
  <item>salt</item>
  <item>pepper</item>
</list>
```

Example 1.10-2: Ordered list

```
<list role="ordered">
  <item>first</item>
  <item>second</item>
  <item>third</item>
</list>
```

Example 1.10-3: List with title

```
<list>
  <title>List title</title>
  <item>first</item>
  <item>second</item>
  <item>third</item>
</list>
```

Example 1.10-4: Definition list

```
<list>
  <item>
    <title>Dweeb</title>
    <p>Young excitable person who may mature into a Nerd or Geek.</p>
  </item>
  <item>
    <title>Hacker</title>
    <p>A clever programmer.</p>
  </item>
  <item>
    <title>Nerd</title>
    <p>Technically bright but socially inept person.</p>
  </item>
</list>
```

Example 1.10-5: Definition list with multiple terms and definitions

```
<list>
  <item>
    <title>Center</title>
    <title>Centre</title>
    <list>
      <item>A point equidistant from all points on the surface of a
        sphere.</item>
      <item>In some field sports, the player who holds the middle position on
        the field, court, or forward line.</item>
    </list>
  </item>
  <item>
    <title>Color</title>
    <title>Colour</title>
    <p>The property possessed by an object of producing different sensations on
      the eye.</p>
  </item>
</list>
```

Example 1.10-6: Leaded list

```
<list role="leaded">
  <item>
    <title>Sugar</title>
    <p>1 €/u.</p>
  </item>
  <item>
    <title>Salt</title>
    <p>1 €/u.</p>
  </item>
  <item>
    <title>Pepper</title>
    <p>2 €/u.</p>
  </item>
</list>
```

(Draft)

1.11. The `/metadata` element

...?

1.12. The `/note` element

The `/note` element represents a generic document note or annotation. It *may* be used as a root element in [\(Review\) DML islands](#) in non-DML documents.

Status

Draft

Flow

[Block](#) (Section 4.1, pg. 21)

Children

```
(
  ( /title?, $block[not( /title | /note | /citation )]+ ) |
  ( $inline | text() )+
)
```

Attributes

```
( $core.attrs* | $meta.attrs* | @role? )
```

Parents

```
( /dml | $block[$block[not( self::/note )]] )
```

The `@role` attribute may be used to provide a form to refine the `/note` element meaning. Allowed values are:

`tip`

A suggestion, tip or trick.

`warning`

An admonition note.

`sidebar`

A note that is isolated from the main narrative flow.

(Draft) `/section[@role="aside"]` or `/note[@role="aside"]` or `@role="sidebar"` ...?

footnote

A footnote. Footnotes in paged medias usually occur at the end of the page which cite it.

(Draft) TODO: examples

1.13. The `/object` element

The `/object` element represents a generic embedded media object like images, videos, audio and other types of multimedia files.

Status

Draft

Flow

When its parent is an inline element or a block element that only allows inline elements its flow is [inline](#) (Section 4.3, pg. 22), otherwise its flow is [block](#) (Section 4.1, pg. 21).

Children

```
( $block* | ( $inline | text() )* )
```

Attributes

```
( $core.attrs* | $meta.attrs* | @src | @type? )
```

Parents

```
( /dml | $block | $inline )
```

The `@src` attribute *must* be used to provide the URI (`xs:anyURI`) of the resource.

The `@type` attribute *may* be used to provide the mime type of the resource.

The children of the `/object` element *must* be used to provide an alternative content if the resource provided by `@src` fails to load.

The alternative content *must* be *inline* or *block* in accordance of the flow of its `/object` parent.

Example 1.13-1: Usage of block flow `/object` element.

```
<figure xml:id="fig-markup-trends">
  <title>Usage of markup language in %</title>
  <object src="markup-trends.svg" type="application/svg+xml">
    <list role="leaded">
      <item>
        <title>HTML</title>
        <p>98%</p>
      </item>
      <item>
        <title>DocBook</title>
        <p>1%</p>
      </item>
      <item>
        <title>Other</title>
        <p>1%</p>
      </item>
    </list>
  </object>
</figure>
```

Example 1.13-2: Usage of inline flow `/object` element.

```
<p>
  Press the <object src="accept-call-button-icon.svg"><em>accept
  call</em></object> button to allow an incoming call.
</p>
```

1.14. The `/p` element

The `/p` element represents a generic block of text usually a paragraph.

Status

Released

Flow

[Block](#) (Section 4.1, pg. 21)

Children

(`$inline` | `text()`)+

Attributes

(`$core.attrs*` | `$meta.attrs*`)

Parents

```
( /dml | $block[$block] )
```

1.15. The `/quote` element

The `/quote` element represents a generic quotation container.

Status

Draft

Flow

When its parent is an inline element or a block element that only allows inline elements its flow is `inline` (Section 4.3, pg. 22), otherwise its flow is `block` (Section 4.1, pg. 21).

Children

```
( $block[not( /quote | /citation )]+ /citation | ( $inline | text() )+ )
```

Attributes

```
( $core.attrs* | $meta.attrs* | @citation? )
```

Parents

```
( /dml | $block[not( /quote | /citation )] | $inline[not( /quote )] )
```

The `@citation` attribute *must* be used to provide the URI (`xs:anyURI`) of the resource cited when the flow of `/quote` element is *inline*, otherwise *must not* be used.

(Draft)

Example 1.15-1: Usage of block flow `/quote` element.

```
<section>
  ( ... )
  <quote>
    <p>Lorem ipsum</p>
    <citation>??? <span href="http://some.resource">???</span> ??? </citation>
  </quote>
  ( ... )
</section>
```


(Draft)

Example 1.15-2: Usage of inline flow `/quote` element.

```
<p>
  ??? <quote citation="http://some.resource">cite</quote> ???
</p>
```

1.16. The `/section` element

The `/section` element represents a generic document section.

Status

Draft

Flow

Block (Section 4.1, pg. 21)

Children

```
( /title, $block[not( /title | /citation )]+ )
```

Attributes

```
( $core.attrs* | $meta.attrs* | @role? )
```

Parents

```
( /dml | /note | /object[parent::$block] | /quote[parent::$block] | /section )
```

The `@role` attribute *may* be used to provide a form to refine the `/section` element meaning. Allowed values are:

`abstract`

A summary or statement of the contents of a document.

`part`

A part of a book. Parts usually group related chapters in a book.

`chapter`

(Review) A main division of a book.

`appendix`

An appendix in a document. Appendixes usually occur at the end of a document.

(Draft) `header`

(Draft) description ...?

(Draft) footer

(Draft) description ...?

(Draft) toc

(Draft) description ...?

license

(Draft) description ...?

(Draft) TODO: examples

(Draft)

1.17. The `/span` element

...?

(Draft)

1.18. The `/sub` element

...?

(Draft)

1.19. The `/summary` element

...?

(Draft)

1.20. The `/sup` element

...?

(Draft)

1.21. The `/table` element

...?

(Draft)

1.22. The `/title` element

...?

2. Core attributes

```
$score.attrs ::= ( @xml:id | @xml:lang | @xml:base | @dir | @class | @href |  
@status )
```

These attributes *must not* be repeated.

- `@xml:id`
- `@xml:lang`
- (Draft) `@xml:base`
- (Draft) `@dir`
- `@class`
- `@href`
- `@status`

(Draft)

2.1. The `@xml:id` attribute

...?

(Draft)

2.2. The `@xml:lang` attribute

...?

(Draft)

2.3. The `@class` attribute

...?

(Draft)

2.4. The `@href` attribute

...?

(Draft)

2.5. The `@status` attribute

...?

3. Metadata attributes

- `@about?`
- `@content?`
- `@datatype?`
- `@typeof?`
- `@property?`
- `@resource?`

(Draft)

3.1. The `@about` attribute

...?

(Draft)

3.2. The `@content` attribute

...?

(Draft)

3.3. The `@datatype` attribute

...?

(Draft)

3.4. The `@typeof` attribute

...?

(Draft)

3.5. The `@property` attribute

...?

(Draft)

3.6. The `@resource` attribute

...?

(Draft)

4. Flow

4.1. Block

4.2. Table

<http://www.w3.org/TR/CSS21/tables.html>

4.3. Inline

(Draft)

5. Relationship with RDFa

...?

(Draft)

6. Namespace

<http://purl.oclc.org/NET/dml/1.0>

(Draft)

7. Schema

RELAX NG and Schematron references

Appendix A — Resources

RELAX NG

- ISO/IEC 19757-2:2008: [Information technology — Document Schema Definition Language \(DSDL\) — Part 2: Regular-grammar-based validation — RELAX NG](http://standards.iso.org/ittf/PubliclyAvailableStandards/c052348_ISO_IEC_19757-2_2008(E).zip) ([http://standards.iso.org/ittf/PubliclyAvailableStandards/c052348_ISO_IEC_19757-2_2008\(E\).zip](http://standards.iso.org/ittf/PubliclyAvailableStandards/c052348_ISO_IEC_19757-2_2008(E).zip)). ISO/IEC. 2008.
- [RELAX NG Home page](http://www.relaxng.org/) (<http://www.relaxng.org/>)

Schematron

- ISO/IEC 19757-3:2006: [Information technology — Document Schema Definition Language \(DSDL\) — Part 3: Rule-based validation — Schematron](http://standards.iso.org/ittf/PubliclyAvailableStandards/c040833_ISO_IEC_19757-3_2006(E).zip) ([http://standards.iso.org/ittf/PubliclyAvailableStandards/c040833_ISO_IEC_19757-3_2006\(E\).zip](http://standards.iso.org/ittf/PubliclyAvailableStandards/c040833_ISO_IEC_19757-3_2006(E).zip)). ISO/IEC. 2006.
- [Schematron Home page](http://www.schematron.com) (<http://www.schematron.com>)

IETF (Internet Engineering Task Force)

- [RFC 2119: Key words for use in RFCs to Indicate Requirement Levels](http://www.apps.ietf.org/rfc/rfc2119.html) (<http://www.apps.ietf.org/rfc/rfc2119.html>). S. Bradner. 1997.
- [RFC 4646: Tags for the Identification of Languages](http://www.apps.ietf.org/rfc/rfc4646.html) (<http://www.apps.ietf.org/rfc/rfc4646.html>). A. Phillips, Ed., M. Davis. 2006.

RDFa

- [RDFa in XHTML: Syntax and Processing](http://www.w3.org/TR/2008/REC-rdfa-syntax-20081014/) (<http://www.w3.org/TR/2008/REC-rdfa-syntax-20081014/>). B. Adida, M. Birbeck, S. McCarron, S. Pemberton. 2008.
- [RDFa Primer](http://www.w3.org/TR/2008/NOTE-xhtml-rdfa-primer-20081014/) (<http://www.w3.org/TR/2008/NOTE-xhtml-rdfa-primer-20081014/>). B. Adida, M. Birbeck. 2008.

Dublin Core Metadata Initiative

- [Dublin Core Metadata Initiative Home page](http://dublincore.org/). (<http://dublincore.org/>)
- [Expressing Dublin Core metadata using HTML/XHTML meta and link elements](http://dublincore.org/documents/2008/08/04/dc-html/) (<http://dublincore.org/documents/2008/08/04/dc-html/>). P. Jhonston, A. Powell. 2008.