

rosumo



Description

"rosumo" is a driver to use the [Jumping Sumo](#) robot, built by Parrot, in [ROS](#). It relies on [ARDroneSDK3](#), the official Parrot SDK. It is written in C++.

Supported hardware

The library was developed for the original Parrot Jumping Sumo, as shown in the picture. However, it should work seamlessly with the newer versions (Jumping Race Drones and Jumping Night Drones).

Supported firmware: v1.99.0. The list and changelog of firmwares is available [here](#).

Licence

LGPL v3 (GNU Lesser General Public License version 3). See LICENCE.

ROS driver node

To launch the Sumo driver:

```
1 $ roslaunch rosumo rosumo.launch
```

Node parameters

- `camera_calibration_filename` [std::string, default: ""]

If not empty, the path to the calibration file of the camera. For instance, `$(find rosumo)/data/sumo_camera_parameters.yaml`

- `camera_calibration_camname` [std::string, default: "camname"]

Name of the camera in the calibration file of the camera. For instance, `$(find rosumo)/data/sumo_camera_parameters.yaml`

Subscriptions

- `cmd_vel` [geometry_msgs::Twist, (m/s, rad/s)]

The instantaneous speed order. Send it every 10 Hz to obtain continuous motion.

- `anim` [std_msgs::String]

Play one of the predefined animations, among `metronome`, `ondulation`, `slalom`, `slowshake`, `spin`, `spinJump`, `spinToPosture`, `spiral`, `tap`.

- `set_posture [std_msgs::String]`

Play one of the predefined postures, among `standing`, `kicker`, `jumper`.

- `sharp_turn [std_msgs::Float32, radians]`

Make a on-the-spot turn. Positive angles generate CCW turns.

- `high_jump [std_msgs::Empty]`

Perform a high jump (about 80 cm high).

- `long_jump [std_msgs::Empty]`

Perform a long jump (about 80 cm long).

Publications

- `camera/image_raw [sensor_msgs::Image]`

The 640x480 raw image, encoded as `bgr8`. The framerate is roughly 15 fps. The image comes from the MJPEG video stream of the robot. If there is no subscriber to the topic, the streaming is stopped from the robot, which saves battery.

- `camera/camera_info [sensor_msgs::CameraInfo]`

The `camera_info` read from a calibration file.

- `battery_percentage [std_msgs::Int16, 0~100]`

The percentage of remaining battery.

- `posture [std_msgs::String]`

The current predefined posture among `unknown`, `standing`, `kicker`, `jumper`.

- `link_quality [std_msgs::Int16, 0~5]`

Quality of the Wifi connection, between 0 (very bad) and 5 (very good).

- `alert [std_msgs::String]`

The alerts emitted by the robot. Current they only concern the battery level, among `unknown`, `none`, `low_battery`, `critical_battery`

- `outdoor [std_msgs::Int16]`

TODO

Keyboard remote control

To launch remote control of the Sumo thanks to keyboard:

```
1 $ roslaunch rosumo joy_teleop.launch
```

It is based on the [turtlebot_teleop](#) package.

Joystick remote control

To launch remote control of the Sumo thanks to a USB joystick:

```
1 $ roslaunch rosumo joy_teleop.launch
```

It is based on the [joy](#) package.

Wiimote remote control

To launch remote control of the Sumo thanks to a Nintendo Wiimote, you need two launchers, one for the Wiimote driver, the other for the teleop node.

```
1 $ roslaunch rosumo wiimote_node.launch
2 $ roslaunch rosumo wiimote_teleop.launch
```

It is based on the [wiimote](#) package.

Installation

You first need to install the official SDK (ARDrone3) by Parrot. A summary of the instructions comes below.

Dependencies

```
1 Ubuntu 14.04:
2 $ sudo apt-get install phablet-tools autoconf libavahi-client-dev libavcodec-
3 dev libavformat-dev libswscale-dev
4 Ubuntu 16.04:
5 $ sudo apt install repo autoconf libavahi-client-dev libavcodec-dev libavfor-
6 mat-dev libswscale-dev
```

FFMPEG for Trusty: you need the latest version of ffmpeg. Use the [official PPA](#):

```
1 $ sudo add-apt-repository ppa:mc3man/trusty-media
2 $ sudo apt-get update
3 $ sudo apt-get dist-upgrade
```

Download ARDroneSDK3

Following [the instructions](#):

```
1 $ repo init -u https://github.com/Parrot-Developers/arsdk_manifests.git
2 $ repo sync --force-sync
```

Build ARDroneSDK3

```
1 $ ./build.sh -p arsdk-native -t build-sdk -j
```

Build ARDroneSDK3 samples (optional)

```
1 $ git clone https://github.com/Parrot-Developers/Samples.git
```

New version - build.sh-based

```
1 $ ./build.sh -p arsdk-native -t build-sample
```

Old version - Makefile-based

Change the lines in the Makefile:

```
1 $ cd Samples/Unix/JumpingSumoPiloting
2 $ geany Makefile
3 SDK_DIR=/home/arnaud/sumo/out/Unix-base/staging/usr
4 CFLAGS=-I$(IDIR) -I $(SDK_DIR)/include/
5 LDIR = $(SDK_DIR)/lib/
6 <check the different -L flags>
7 <add json to libs>
```

```
1 $ make
2 $ LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/home/arnaud/sumo/out/Unix-base/staging/usr/lib ./JumpingSumoPiloting
3 $ sudo sh -c 'LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/home/arnaud/sumo/out/Unix-base/staging/usr/lib ./JumpingSumoPiloting '
```

Build rosumo with Catkin

```
1 $ catkin_make --only-pkg-with-deps rosumo
```

To specify the path to the ARDroneSDK3 'usr' folder:

```
1 $ catkin_make --only-pkg-with-deps rosumo -DARDRONESDK3_PATH=~/.out/Unix-base/staging/usr
```

Camera calibration

Following the instructions of camera_calibration [wiki page](#) and [tutorial](#) :

```
1 $ rosrun camera_calibration cameracalibrator.py --size 8x10 --square 0.0298 image:=/rosumol/rgb camera:=/camera
```