

**CSS
IS
AWESOME!**

Igor Laborie

Expert Java & Web, < **Monkey Patch** /> <<http://www.monkeypatch.io/>>

 @ilaborie <<https://twitter.com/ilaborie>>

 igor@monkeypatch.io <<mailto:igor@monkeypatch.io>>

 *Je ne suis pas un designer*

“ When designing computer systems, one is often faced with a choice between using a more or less powerful language for publishing information, for expressing constraints, or for solving some problem. This finding explores tradeoffs relating the choice of language to reusability of information. The "Rule of Least Power" suggests choosing the least powerful language suitable for a given purpose.

1. Texte
2. HTML (sémantique) & CSS (layout, style, animations simples)
3. SVG (formes et animations complexes)
4. JavaScripts

⚠️... mais il y a toujours de bonnes raisons pour ne pas suivre ces règles

- Selectors
- Box model
- Float
- Media Query
- Transitions
- Gradients
- Responsive Design
- Media
- Variables
- Colors
- Shapes
- ...

I. Utiliser un pré-processeur ?

II. Unités

III. Flexbox et Grid

IV. Pseudo éléments

V. Animations

VI. Pseudo classes d'état

VII. HTML

VIII. Compatibilité des navigateurs

IX. Conclusion

Utiliser un
pré-processeur ?

Bordure des boutons

#7

```
button {  
  background: lightblue;  
  border: medium solid purple;  
}  
button.danger { /*  
  background: salmon;  
  color: rebeccapurple; */  
}
```


Alors utilise-t-on un pré-processeurs ?

#8

Oui, mais privilégiez:

- le CSS
- les post-processeurs
-  `currentColor` <<https://css-tricks.com/currentcolor/>>
-  `background-origin`
<<https://developer.mozilla.org/fr/docs/Web/CSS/background-origin>>
- **w3c** CSS Variables (aka Custom Properties)
<<https://www.w3.org/TR/css-variables/>>
- **w3c** CSS Color Module Level 4 <<https://www.w3.org/TR/css-color-4/>>

Unités



 CommitStrip <<http://www.commitstrip.com/fr/2016/10/10/a-story-about-css-units/>>


px, cm, pt, ... longueurs absolues (mesure physique)

em, rem fonction de la `font-size`

ex, ch hauteur d'un x, largeur d'un 0

vh, vw (100vh, 100vw) = (hauteur, largeur) du
viewport


vmin, vmax $\min(1vh, 1vw)$, $\max(1vh, 1vw)$




```
<body>
  <header>Header</header>
  <div>
    <nav>Menu</nav>
    <main>Content</main>
    <aside>Side</aside>
  </div>
  <footer>Footer</footer>
</body>
```

-  Unités <<https://developer.mozilla.org/fr/docs/Web/CSS/length>>
- **w3c** Truc et astuces <<https://www.w3.org/Style/Examples/007/units.fr.html>>
-  calc <<https://developer.mozilla.org/fr/docs/Web/CSS/calc>>

Flexbox et Grid



```
<body>
  <header>Header</header>
  <div>
    <nav>Menu</nav>
    <main>Content</main>
    <aside>Side</aside>
  </div>
  <footer>Footer</footer>
</body>
```

```
<body>
  <header>Header</header>
  <div>
    <nav>Menu</nav>
    <main>Content</main>
    <aside>Side</aside>
  </div>
  <footer>Footer</footer>
</body>
```

Flexbox

- 🎬 Flexbox, et le CSS redevient fun ! (Hubert SABLONNIÈRE) <https://www.youtube.com/watch?v=5F_ngjHDcjQ>
- 📐 Solved by Flexbox <<https://philipwalton.github.io/solved-by-flexbox/>>
- 🐸 Flexbox Froggy <<https://flexboxfroggy.com/>>

Grid

- # Grid by examples <<https://gridbyexample.com/>>
- 🎬 CSS Grid Changes Everything (About Web Layouts) by Morten Rand-Hendriksen <https://www.youtube.com/watch?v=txZq7Laz7_4>
- 🥕 Grid Garden <<http://cssgridgarden.com/>>

Pseudo éléments

Le dinner d'un philosophe

#19

```
.table {  
  color: gray;  
  font-size: 5em;  
  /*content: ' ';*/  
}
```

Triangle avec des bordures

#20


```
div.top, div.right, div.bottom, div.left {  
  border: 1em solid transparent;  
  display: inline-block;  
  box-shadow: 0 0 0 .1em transparent;  
}  
  
div.top { border-top-color: transparent; }  
div.right { border-right-color: transparent; }  
div.bottom { border-bottom-color: transparent; }  
div.left { border-left-color: transparent; }
```

```
.popover {  
  position: relative;  
  background: teal;  
}  
  
/* .popover::before {  
  position: absolute;  
  z-index: 0;  
  content: '';  
  top: 0em; left: 0em;  
  border: 1em solid red;  
  border-top-color: red;  
}*/
```

[w3c <https://www.w3.org/TR/CSS22/generate.html#before-after-content>](https://www.w3.org/TR/CSS22/generate.html#before-after-content)

- mais aussi `::first-letter`, `::first-line`,
`::selection`, `::backdrop`
-  [An Ultimate Guide To CSS Pseudo-Classes And Pseudo-Elements](https://www.smashingmagazine.com/2016/05/an-ultimate-guide-to-css-pseudo-classes-and-pseudo-elements) [guide-to-css-pseudo-classes-and-pseudo-elements](https://www.smashingmagazine.com/2016/05/an-ultimate-guide-to-css-pseudo-classes-and-pseudo-elements)

⚠ `::before` et `::after` ne marchent pas sur `input`, `img`, `iframe` (pas encore spécifié)

- Table et assiette de  [CSS Diner](https://flukeout.github.io/) [<https://flukeout.github.io/>](https://flukeout.github.io/)
-  [Dîner des philosophes](#)

Animations


```
.loader {
  display : inline-block;
  white-space : normal;
  height: 1em;
  line-height : 1.5;
  overflow: auto;
  box-shadow : 0 0 0 .05em red;
}

.loader::before {
  display : inline-table;
  /*content: '0\| 1\| 2\| 3\| 4\| 5\| 6\| 7\| 8\| 9';*/
  /*content: ':\| :\| :\| :\| .\| .\| .\| .\| :\| :\|';*/
  /*animation: spin 5s infinite;*/
}

@keyframes spin {
  to { transform : translateY(-15em); }
}
```

```
.editable svg path {  
  stroke: purple;  
  stroke-width: .1em;  
  fill: none;  
  /*stroke-dasharray: 0;*/  
  /*stroke-dashoffset: 0;*/  
  /*animation: draw 4s linear;*/  
}  
  
@keyframes draw {  
  to { stroke-dashoffset: 0; }  
}
```

-  Utiliser les animations CSS

https://developer.mozilla.org/fr/docs/Web/CSS/Animations_CSS/Utiliser_les_animations_CSS

- ➡ Text Spinner <http://tawian.io/text-spinners/>

- ➡ CSS only loader <https://www.pexels.com/blog/css-only-loaders/>

-  Animate.css <https://daneden.github.io/animate.css/>

-  How SVG Line Animation Works [https://css-tricks.com/svg-line-](https://css-tricks.com/svg-line-animation-works/)

[animation-works/](https://css-tricks.com/svg-line-animation-works/)

-  `<progress>`

<https://developer.mozilla.org/fr/docs/Web/HTML/Element/Progress>

Pseudo classes d'état

Input Text

Mandatory

➡ hover me <#usage_des_info_bulles>

- :hover
- :focus
- :visited
- :checked
- :valid
- :invalid
- :empty
- :target
- ...

```
.like input[type=checkbox] + label {  
  box-shadow: 0 0 0 1px red;  
}  
.like input[type=checkbox] + label::before {  
  content: '';  
}  
.like input[type=checkbox] + label::before {  
  content: '';  
}  
.like fieldset input[type=checkbox] { opacity: 1; }
```

```
.switch + label {  
  display: block;  
  position: relative;  
  padding: .1em;  
  width: 2em;  
  height: 1em;  
  background-color: #ccc;  
  border-radius: 1em;  
  border: medium solid #444;  
  transition: 0.4s;  
}  
  
.switch:checked + label {  
  background-color: green;  
}
```

```
.switch + label::before {  
  display: block;  
  position: absolute;  
  content: '';  
  top: 0.1em;  
  left: 0.1em;  
  height: 1em;  
  width: 1em;  
  background-color: #fff;  
  border-radius: 50%;  
  transition: all 0.25s;  
}  
  
.switch:checked + label::before {  
  transform: translateX(1em);  
}
```



```
.panel input[type=checkbox] {  
    /* hide me */  
}
```

Principe pour les onglets

#33

```
<div class="tabs">
  <input type="radio" name="tab" id="home" checked>
  <input type="radio" name="tab" id="projects">
  <input type="radio" name="tab" id="about">
  <nav>
    <label for="home">Home</label>
    <label for="projects">Projects</label>
    <label for="about">About</label>
  </nav>
  <div data-for="home">Home page</div>
  <div data-for="projects">Projects page</div>
  <div data-for="about">About page</div>
</div>
```


HTML

```
<details>
  <summary>Des détails</summary>
  <p>Plus d'infos
    à propos des détails.</p>
</details>
```

```
details {
  border: medium solid currentcolor;
  border-radius: .25em;
  width: 100%;
}

details summary {
  background: #888; color: #eee;
}
```

```
.editable dialog {  
  border: medium solid rgba(0, 0, 0, 0.3);  
  border-radius: .125em;  
  padding: .125rem;  
  box-shadow: .25em .25em .125em rgba(0, 0, 0, 0.42);  
}  
  
/* .editable dialog::backdrop {  
  position: fixed;  
  top: 0; right: 0; bottom: 0; left: 0;  
  background-color: rgba(0, 0, 0, 0.8);  
} */
```

-  Collapsible Panel Polyfill <<https://github.com/chemerisuk/better-details-polyfill/>>
-  Dialog Polyfill <<https://github.com/GoogleChrome/dialog-polyfill/>>

Compatibilité des navigateurs

➡ **caniuse** <<http://caniuse.com>>

➡ **The CSS3 / CSS4 Test** <<http://css3test.com>>

IE 7+, Firefox, Chrome

Pseudo classes (CSS3
selectors 93)

IE 8+, Firefox, Chrome

::before, ::after 98

IE 9+, Firefox, Chrome

currentColor 98

background-origin 98

box-shadow 98

calc 97

vh, vw, ... 97

IE 10+, Firefox, Chrome

flexbox 98

Conclusion

1. Utilisez du CSS pour simplifier le code
2. Utilisez intelligemment les pre/post-processeurs
3. HTML, SVG are Awesome !
4. JavaScript, TypeScript could be Awesome !

1. Revue de code
2. DRY
3. Clean Code
4. Single Responsibility Principle
5. ...

-  les slides en HTML <<https://ilaborie.github.io/slides/devfest-tls.html#cssIsAwesome>>
-  les slides en PDF <<https://ilaborie.github.io/slides/devfest-tls.pdf>>
-  le code <<https://github.com/ilaborie/slides>>
-  Making Of
<http://www.monkeypatch.io/2017/05/02/MakingOf_CSS_is_Awesome.html>

- (Ctrl|⌘) + Shift + i



- ➡ CSS Secret by Lea Verou <[https://www.amazon.fr/CSS-Secrets-](https://www.amazon.fr/CSS-Secrets-Lea-Verou/dp/1449372635)

[Lea-Verou/dp/1449372635](https://www.amazon.fr/CSS-Secrets-Lea-Verou/dp/1449372635)>

- 🦊 CSS sur MDN <<https://developer.mozilla.org/fr/docs/Web/CSS>>

- ➡ CodePen <<https://codepen.io/>> , ➡ JSFiddle <<https://jsfiddle.net/>> , ➡

[Dabblet](http://dabblet.com/) <<http://dabblet.com/>> ,...

- ✨ CSS Tricks <<https://css-tricks.com/>> , 📖 Smashing Magazine

<<https://www.smashingmagazine.com/>>

- 🚧 CSS Flags <<https://pixelastic.github.io/css-flags/>>

CSS
is
Awesome!

