

Capella and Arcadia Functions-Structure-Interfaces

INPUTS FOR SYSML V2 WG – JUNE 20TH, 2017


Stéphane Bonnet

In charge of Thales Corporate MBSE Coaching & Community
Capella Design Authority

stephane.bonnet@thalesgroup.com




The big picture




The example illustrated in the following slide is an adaptation of the example used by the SysML v2 Working Group. It is not the most accurate description of a real Camera design.


Exchanges between functions are actually computed based on the exchanges existing between child leaf functions (which are not displayed on this diagram)



High-level functions

Arcadia method: In a completed design, all exchanges are ONLY between leaf functions. There is no delegation mechanism between parent and children functions







Leaf functions allocated to structure elements


The level 1 functions can be visualized on the Camera component even though there is no real allocation relationship in the model between the parent functions and the Camera component (this is the meaning of the *Italic labels of functions*). These functions can be visualized because all their children functions are actually allocated to sub components of Camera ((this is the meaning of the dashed borders of functions)

Graphical, computed simplified view





Data model



Data model

A « communication mechanism » can optionally be set on every Exchange Item

Exchange Item
Editing of the properties of an object Exchange Item

Base Description Extensions Management

Name : Shooting settings
Summary :

☐ Is abstract
☐ Is Final

Super : <undefined>


Exchange Mechanism :
☐ UNSET ☐ EVENT ☐ FLOW ☐ OPERATION ☒ SHARED_DATA

Exchange Item Elements :
mode: SHOOTING MODE
style: SHOOTING STYLE


Realized Exchange Items : <undefined>

Finish Cancel

Allocation of Exchange Items to Functional Exchanges



Component exchanges
can be automatically
initialized/deduced by
Capella based on
functional exchanges




Allocation of
functional
exchanges to
component
exchanges


Interfaces can be automatically
initialized by Capella, based on
previous allocations.
Dedicated model validation rules
detect gaps in interfaces between
structural elements and functions

Interfaces between components


related, in any way, in whole or in
- © Thales 2015 All rights reserved.




Different kinds of sequence diagrams



Function-based scenario, label of sequence messages if the name of functional exchanges




Function-based scenario, label of sequence messages if the name of allocated Exchange Item (can be a subset)







Interface scenario, no reference to functions anymore

Step by step model building



The labels of FunctionalExchanges can be replaced by the names of the allocated ExchangeItems



Limitations – Way forward

... or why we are interested in the current SysML v2 work on interfaces

- The interface provide/require concept is not natural for most system engineers. It is too SW-oriented. We like the idea of having components participating in interfaces and playing roles instead.
- We need to describe interfaces with protocols (using mechanisms like sequence diagrams, state machines, etc.).



Open Source Solution for Model-Based Systems Engineering



Download:
<http://polarsys.org/capella/download.html>