

EECS442 Final Project Presentation

License Plate Recognition

Jiongsheng Cai, Jingyao Hu, Yucheng Yin

Group Lamborghini, University of Michigan College of Engineering

December 7, 2017

Prepared for EECS 442 Computer Vision
Fall 2017

Introduction: License Plate recognition



- **Application**

- Check plate registration status by police forces
- Electronic toll collection
- Parking lot fee collection

- **Example vehicle image**



Method summary



CNN
prediction

819KXH75



Method – Plate Localization and Extraction

- **Edge detection to remove unnecessary information**

- ☐ Apply two kernels horizontally and vertically
- ☐ Filter pixels by defining a threshold

- **Calculate histogram to extract the plate**


- ☐ Calculate column-wise and row-wise difference
- ☐ Calculate horizontal and vertical histogram by defining a threshold
- ☐ Traverse histogram to get pairs of starting points and ending points
- ☐ Choose start and end points with largest difference (length)

Method – Character Segmentation

- **Calculate the column weight(sum) to do horizontal segmentation**
 - ❑ Large color difference(black and white) between character and the space in the middle of the two characters
- **Calculate the row weight(sum) to do vertical segmentation**
 - ❑ Set the top and bottom boundaries for each character
- **Use the character feature to further remove the noise**
 - ❑ The ratio of row to column sits in a specific range (0.5 – 2.0)
 - ❑ The ratio of the sum of character matrix to its (row * column) is greater than some threshold value(> 0.1)

Method – Character Recognition

- EMNIST – an extension of MNIST dataset
- trained on 131,600 characters, 47 balanced class
- 87.33% accuracy on EMNIST test data



Results – Good example

Original Images



After Extraction

819KXH75

After Segmentation

8 1 9 K
X H 7 5

Recognition Result

819KXH75









DU 748-BH

D U 7 4
8 B H

0U748BH

Results – Bad Example

Original Images	After Edge Detection	After Extraction	Recognition Result
			<div data-bbox="1954 621 2372 719">N/A</div>
			<div data-bbox="1959 1113 2377 1212">N/A</div>

Discussion and Improvements

- Rotation and illumination invariant for extraction
- Remove noise for extraction and segmentation
- Improve accuracy for CNN recognition (R-CNN, better models)

Conclusion

- Implement a typical algorithm for license plate recognition
- Good results for extraction and segmentation
- Accuracy for recognition need to be improved

For any questions or concerns, feel free to contact:

yyucheng@umich.edu