

Heaps, Binary Heaps and Heapsort

Subhabrata Samajder



IIIT, Delhi
Summer Semester,
20th June, 2022

Heapsort

Heapsort

- Like Merge-sort it's worst case time complexity is $\mathcal{O}(n \log n)$.
- Like Quick-sort it is an **in place** algorithm.
 - # of elements stored outside the input array at any time: $\mathcal{O}(1)$.
- Combines the better attributes of the two sorting algorithms.


Heapsort (Cont.)

- Introduces a different algorithm design technique:
 - the use of a data structure to manage information during the execution of the algorithm.
 - This data structure is called a **heap**.
- Apart from heapsort it also makes an **efficient priority queue**.
- The term **heap** was originally coined in the context of heapsort.
- But it has since come to refer to as **garbage-collection storage** provided by programming languages like **Lisp** and **Java**.
- **But heap data structure is not garbage-collected storage!**

Heaps

Heap

A **Min-Heap** is a (rooted) tree data structure where the value stored in a node **less than or equal to** the value stored in each of its children.



Heap (Cont.)

- The lowest/highest priority element is always stored at the **root**.
- It is **not** a sorted structure.
- It can be regarded as being partially ordered.
- It is useful when it is necessary to repeatedly remove the object with the lowest/highest priority.

Query Operations:

- $\text{FIND-MIN}(H)$: Report the smallest key stored in the heap.

Modifying Operations:

- $\text{CREATEHEAP}(H)$: Create an empty heap H .
- $\text{INSERT}(x, H)$: Insert a new key with value x into the heap H .
- $\text{EXTRACT-MIN}(H)$: Delete the smallest key from H .
- $\text{DECREASE-KEY}(p, \Delta, H)$: Decrease the value of the key p by amount Δ .
- $\text{MERGE}(H_1, H_2)$: Merge two heaps H_1 and H_2 .

Variants

- 2-3 heap
- B-heap
- Beap
- Binary heap
- Binomial heap
- Brodal queue
- d -ary heap
- Fibonacci heap
- K-D Heap
- Leaf heap
- Leftist heap
- Pairing heap
- Radix heap
- Randomized meldable heap
- Skew heap
- Soft heap
- Ternary heap
- Treap
- Weak heap

Variants

- 2-3 heap
- B-heap
- Beap
- Binary heap
- Binomial heap
- Brodal queue
- d -ary heap
- Fibonacci heap
- K-D Heap
- Leaf heap
- Leftist heap
- Pairing heap
- Radix heap
- Randomized meldable heap
- Skew heap
- Soft heap
- Ternary heap
- Treap
- Weak heap

Complete Binary Tree


Can we implement a binary tree using an array?

Complete Binary Tree

Can we implement a binary tree using an array?


Yes, in some special cases.

A Complete Binary Tree




A complete binary of 12 nodes.

A Complete Binary Tree




Can you see a relationship between **label of a node** and **labels of its children**?

A Complete Binary Tree



- The label of the **leftmost node** at level $i = 2^i - 1$.
- The label of a **node** v at level i occurring at k^{th} place from **left** $= 2^i + k - 2$.
- The label of the **left** child of v is $= 2 \cdot (2^i + (k - 2)) + 1$.
- The label of the **right** child of v is $= 2 \cdot (2^i + (k - 2)) + 2$.


A Complete Binary Tree



- Let v be a node with label j .
- Label of **left child**(v) = $2j + 1$.
- Label of **right child**(v) = $2j + 2$.
- Label of **parent**(v) = $\lfloor (j - 1) / 2 \rfloor$.

A Complete Binary Tree and An Array


Can we implement a complete binary tree using an array?



A Complete Binary Tree and An Array



Can we implement a complete binary tree using an array? Yes!

Advantage: It is the most compact representation.




A Complete Binary Tree and An Array

Can we implement a complete binary tree using an array?




A Complete Binary Tree and An Array

Can we implement a complete binary tree using an array?




A Complete Binary Tree and An Array

Can we implement a complete binary tree using an array?




A Complete Binary Tree and An Array

Can we implement a complete binary tree using an array?




A Complete Binary Tree and An Array

Can we implement a complete binary tree using an array?




A Complete Binary Tree and An Array

Can we implement a complete binary tree using an array?



A Complete Binary Tree and An Array



Can we implement a complete binary tree using an array?



Binary Heap

Binary (Min) Heap

Definition: It is a **complete binary tree** satisfying the **heap property** at each node.




Implementation of a Binary Heap

H[] : An **array** of size n used for storing the binary heap.

size : A **variable** for the total number of keys **currently** in the heap.


FIND-MIN(H)



H :

| | | | | | | | | | | | | | | | |
|---|----|---|----|----|----|----|----|----|----|----|----|----|----|----|----|
| 4 | 14 | 9 | 17 | 23 | 21 | 29 | 91 | 37 | 25 | 88 | 33 | | | | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |

FIND-MIN(H)



H :


| | | | | | | | | | | | | | | | |
|---|----|---|----|----|----|----|----|----|----|----|----|----|----|----|----|
| 4 | 14 | 9 | 17 | 23 | 21 | 29 | 91 | 37 | 25 | 88 | 33 | | | | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |

Return $H[0]$

EXTRACT-MIN(H)

Goal: Deletes the smallest key from H .


Challenge: Preserve the complete binary tree structure as well as the heap property!



EXTRACT-MIN(H)

Goal: Deletes the smallest key from H .

Challenge: Preserve the complete binary tree structure as well as the heap property!




• $swap(H[0], H[size - 1])$.

EXTRACT-MIN(H)

Goal: Deletes the smallest key from H .

Challenge: Preserve the complete binary tree structure as well as the heap property!




- $\text{swap}(H[0], H[\text{size} - 1])$.
- $\text{size} = \text{size} - 1$.

EXTRACT-MIN(H)

Goal: Deletes the smallest key from H .

Challenge: Preserve the complete binary tree structure as well as the heap property!




- $swap(H[0], H[size - 1])$.
- $size = size - 1$.
- While $x > key[left[x]]$ or $x > key[right[x]]$, then
 - $swap(x, \min\{left[x], right[x]\})$.

EXTRACT-MIN(H)

Goal: Deletes the smallest key from H .

Challenge: Preserve the complete binary tree structure as well as the heap property!




- $swap(H[0], H[size - 1])$.
- $size = size - 1$.
- While $x > key[left[x]]$ or $x > key[right[x]]$, then
 - $swap(x, \min\{left[x], right[x]\})$.

EXTRACT-MIN(H)

Goal: Deletes the smallest key from H .


Challenge: Preserve the complete binary tree structure as well as the heap property!



- $swap(H[0], H[size - 1])$.
- $size = size - 1$.
- While $x > key[left[x]]$ or $x > key[right[x]]$, then
 - $swap(x, \min\{left[x], right[x]\})$.
- Complexity: # swaps = $\mathcal{O}(\# \text{ levels in binary heap}) = \mathcal{O}(\log n)$ (show it!).

INSERT(x, H)

Let $x = 11$.




$H :$

| | | | | | | | | | | | | | | | | | | | | | | |
|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 9 | 14 | 21 | 17 | 23 | 33 | 29 | 71 | 37 | 25 | 88 | 41 | 52 | 32 | 76 | 98 | 85 | 47 | 57 | | | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | | 31 |

INSERT(x, H)

Let $x = 11$.




$H :$

| | | | | | | | | | | | | | | | | | | | | | | |
|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 9 | 14 | 21 | 17 | 23 | 33 | 29 | 71 | 37 | 25 | 88 | 41 | 52 | 32 | 76 | 98 | 85 | 47 | 57 | 11 | | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | ... | 31 |

- $H[size] = x$.
- $size = size + 1$

INSERT(x, H)


Let $x = 11$.



- $H[\text{size}] = x$.
- $\text{size} = \text{size} + 1$
- While $\text{parent}[x] > x$, then
 - $\text{swap}(x, \text{parent}[x])$.

INSERT(x, H)


Let $x = 11$.



- $H[\text{size}] = x$.
- $\text{size} = \text{size} + 1$
- While $\text{parent}[x] > x$, then
 - $\text{swap}(x, \text{parent}[x])$.

INSERT(x, H)

Let $x = 11$.



- $H[\text{size}] = x$.
- $\text{size} = \text{size} + 1$
- While $\text{parent}[x] > x$, then
 - swap($x, \text{parent}[x]$).

INSERT(x, H) (Cont.)

Begin

$i \leftarrow \text{size}(H);$

$H[\text{size}] \leftarrow x;$

$\text{size}(H) \leftarrow \text{size}(H) + 1;$

while ($i > 0$ and $H[i] < H[\lfloor (i-1)/2 \rfloor]$)

$\text{swap}(H[i], H[\lfloor (i-1)/2 \rfloor]);$

$i \leftarrow \lfloor (i-1)/2 \rfloor;$

End

Complexity?

INSERT(x, H) (Cont.)

Begin

$i \leftarrow \text{size}(H);$

$H[\text{size}] \leftarrow x;$

$\text{size}(H) \leftarrow \text{size}(H) + 1;$

while ($i > 0$ and $H[i] < H[\lfloor (i-1)/2 \rfloor]$)

$\text{swap}(H[i], H[\lfloor (i-1)/2 \rfloor]);$

$i \leftarrow \lfloor (i-1)/2 \rfloor;$

End

Complexity: $\mathcal{O}(\log n)$.

The Remaining Operations on Binary Heap

- **DECREASE-KEY(p, Δ, H):** Decrease the value of the key p by amount Δ .
 - Similar to **INSERT(x, H)**.
 - Do it as an exercise!
 - **Complexity?**
- **MERGE(H_1, H_2):** Merge two heaps H_1 and H_2 .

The Remaining Operations on Binary Heap

- **DECREASE-KEY(p, Δ, H):** Decrease the value of the key p by amount Δ .
 - Similar to **INSERT(x, H)**.
 - Do it as an exercise!
 - **Complexity:** $\mathcal{O}(n)$.
 - **Note:** Searching for p takes $\mathcal{O}(n)$
 - Can you do it in $\mathcal{O}(\log n)$?
- **MERGE(H_1, H_2):** Merge two heaps H_1 and H_2 .

The Remaining Operations on Binary Heap

- **DECREASE-KEY(p, Δ, H):** Decrease the value of the key p by amount Δ .
 - Similar to **INSERT(x, H)**.
 - Do it as an exercise!
 - **Complexity:** $\mathcal{O}(n)$.
 - Needs some additional information called **MAP**!
 - **MAP:** Stores the index corresponding to each key.
- **MERGE(H_1, H_2):** Merge two heaps H_1 and H_2 .

The Remaining Operations on Binary Heap

- **DECREASE-KEY(p, Δ, H):** Decrease the value of the key p by amount Δ .
 - Similar to **INSERT(x, H)**.
 - Do it as an exercise!
 - **Complexity:** $\mathcal{O}(n)$.
 - Needs some additional information called **MAP**!
 - **MAP:** Stores the index corresponding to each key.
- **MERGE(H_1, H_2):** Merge two heaps H_1 and H_2 .
 - **Complexity?**

The Remaining Operations on Binary Heap

- **DECREASE-KEY**(p, Δ, H): Decrease the value of the key p by amount Δ .
 - Similar to **INSERT**(x, H).
 - Do it as an exercise!
 - **Complexity:** $\mathcal{O}(n)$.
 - Needs some additional information called **MAP**!
 - **MAP:** Stores the index corresponding to each key.
- **MERGE**(H_1, H_2): Merge two heaps H_1 and H_2 .
 - **Complexity:** $\mathcal{O}(n \log n)$
 - Can you do it in $\mathcal{O}(n)$?

Building a Binary heap

Building a Binary Heap Incrementally


Problem: Given elements $\{x_0, \dots, x_{n-1}\}$, build a binary heap H storing them.

Building a Binary Heap Incrementally

Problem: Given elements $\{x_0, \dots, x_{n-1}\}$, build a binary heap H storing them.

Trivial Solution: Build the Binary heap **incrementally**.

```
CREATEHEAP( $H$ ):  
  for  $i = 0$  to  $n - 1$   
    INSERT( $x_i, H$ );
```



H :

| | | | | | | | | | | | | | | | | | | | | | | |
|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 9 | 11 | 21 | 17 | 14 | 33 | 29 | 71 | 37 | 23 | 88 | 41 | 52 | 32 | 76 | 98 | 85 | 47 | 57 | 25 | | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | | 31 |

Time Complexity

- Consider a **complete binary tree** of height h with k leaf nodes in the last level.
- The total number of nodes $n = (2^h - 1) + k$.
- Therefore, number of leaf nodes is equal to

$$\begin{aligned} k + (2^{h-1} - \lceil k/2 \rceil) &= 2^{h-1} + \lfloor k/2 \rfloor \\ &= \left\lceil \frac{1}{2} \{2^h + k - 1\} \right\rceil = \lceil n/2 \rceil \end{aligned}$$

Time Complexity

- Consider a **complete binary tree** of height h with k leaf nodes in the last level.
- The total number of nodes $n = (2^h - 1) + k$.
- Therefore, number of leaf nodes is equal to

$$\begin{aligned} k + (2^{h-1} - \lceil k/2 \rceil) &= 2^{h-1} + \lfloor k/2 \rfloor \\ &= \left\lceil \frac{1}{2} \{2^h + k - 1\} \right\rceil = \lceil n/2 \rceil \end{aligned}$$

- Time complexity for inserting a **leaf node** $= \mathcal{O}(\log n)$
- Time complexity for building a heap **incrementally** is $\mathcal{O}(n \log n)$.

Time Complexity

- Consider a **complete binary tree** of height h with k leaf nodes in the last level.
- The total number of nodes $n = (2^h - 1) + k$.
- Therefore, number of leaf nodes is equal to

$$\begin{aligned}k + (2^{h-1} - \lceil k/2 \rceil) &= 2^{h-1} + \lfloor k/2 \rfloor \\&= \left\lceil \frac{1}{2} \{2^h + k - 1\} \right\rceil = \lceil n/2 \rceil\end{aligned}$$

- Time complexity for inserting a **leaf node** $= \mathcal{O}(\log n)$
- Time complexity for building a heap **incrementally** is $\mathcal{O}(n \log n)$.

A Binary Heap can be build in $\mathcal{O}(n)$ time.

Time Complexity

- Consider a **complete binary tree** of height h with k leaf nodes in the last level.
- The total number of nodes $n = (2^h - 1) + k$.
- Therefore, number of leaf nodes is equal to


$$\begin{aligned}k + (2^{h-1} - \lceil k/2 \rceil) &= 2^{h-1} + \lfloor k/2 \rfloor \\&= \left\lceil \frac{1}{2} \{2^h + k - 1\} \right\rceil = \lceil n/2 \rceil\end{aligned}$$

- Time complexity for inserting a **leaf node** $= \mathcal{O}(\log n)$
- Time complexity for building a heap **incrementally** is $\mathcal{O}(n \log n)$.

A Binary Heap can be build in $\mathcal{O}(n)$ time.


Conclusion: $\mathcal{O}(n)$ algorithm \Rightarrow each leaf nodes must take $\mathcal{O}(1)$.

An Alternate Approach




- **Heap Property:** Every **node** stores values **smaller** than its **children**.

An Alternate Approach




- **Heap Property:** Every **node** stores values **smaller** than its **children**.
- **Note:** Only need to ensure this property at each node.

An Alternate Approach




- **Heap Property:** Every node stores values smaller than its children.
- **Note:** Only need to ensure this property at each node.
- **Question:** In any complete binary tree, how many nodes satisfy the heap property?

An Alternate Approach




- **Heap Property:** Every **node** stores values **smaller** than its **children**.
- **Note:** Only need to ensure this property at each node.
- **Question:** In any **complete binary tree**, how many nodes satisfy the heap property?
All the leaf nodes surely does!

An Alternate Approach




- **Heap Property:** Every **node** stores values **smaller** than its **children**.
- **Note:** Only need to ensure this property at each node.
- **Question:** In any **complete binary tree**, how many nodes satisfy the heap property?
All the leaf nodes surely does!
- **Question:** Does this suggest a **new approach** to build binary heap?

An Alternate Approach



- **Heap Property:** Every **node** stores values **smaller** than its **children**.
- **Note:** Only need to ensure this property at each node.
- **Question:** In any **complete binary tree**, how many nodes satisfy the heap property?
All the leaf nodes surely does!
- **Question:** Does this suggest a **new approach** to build binary heap?

An Alternate Approach



Bottom up
approach




$H :$

| | | | | | | | | | | | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 98 | 14 | 33 | 37 | 11 | 52 | 32 | 85 | 17 | 25 | 88 | 41 | 21 | 29 | 76 | 47 | 75 | 9 | 57 | 23 | | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | | 31 |


- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.

An Alternate Approach



- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.

An Alternate Approach



Bottom up
approach




$H :$

| | | | | | | | | | | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 98 | 14 | 33 | 37 | 11 | 52 | 32 | 85 | 17 | 23 | 88 | 41 | 21 | 29 | 76 | 47 | 75 | 9 | 57 | 25 | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 31 |


- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.

An Alternate Approach



- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.

An Alternate Approach



Bottom up
approach




H :

| | | | | | | | | | | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|---|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 98 | 14 | 33 | 37 | 11 | 52 | 32 | 85 | 9 | 23 | 88 | 41 | 21 | 29 | 76 | 47 | 75 | 17 | 57 | 25 | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 31 |


- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.

An Alternate Approach




- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.

An Alternate Approach



- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.

An Alternate Approach




H :

| | | | | | | | | | | | | | | | | | | | | | |
|----|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 98 | 9 | 21 | 14 | 11 | 33 | 29 | 47 | 17 | 23 | 88 | 41 | 52 | 32 | 76 | 85 | 75 | 37 | 57 | 25 | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 31 |

- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.

An Alternate Approach




$H :$

| | | | | | | | | | | | | | | | | | | | | | |
|----|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 98 | 9 | 21 | 14 | 11 | 33 | 29 | 47 | 17 | 23 | 88 | 41 | 52 | 32 | 76 | 85 | 75 | 37 | 57 | 25 | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 31 |

- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.

An Alternate Approach



H :

| | | | | | | | | | | | | | | | | | | | | | | |
|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|
| 9 | 11 | 21 | 14 | 23 | 33 | 29 | 47 | 17 | 25 | 88 | 41 | 52 | 32 | 76 | 85 | 75 | 37 | 57 | 98 | | ... | |
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 31 |

- Copy the given n elements $\{x_0, \dots, x_{n-1}\}$ into an array H .
- The heap property holds for all the leaf nodes.
- Leaving all the leaf nodes, process the elements in the **decreasing order of their index** and set the heap property for each of them.
- Let v be a node corresponding to index i in H .
- The process of restoring heap property at i called **HEAPIFY**(i, H).

HEAPIFY(i, H)

For node i , compare its value with those of its children

- If it is greater than any of its children
 - Swap it with smallest child
 - and move down ...
- Else stop.

HEAPIFY(i, H)

Begin

$n \leftarrow \text{size}(H) - 1;$

Flag \leftarrow true;

while ($i \leq \lfloor (n - 1)/2 \rfloor$ and Flag = true)

 min $\leftarrow i;$

 if ($H[i] > H[2i + 1]$)

 min $\leftarrow 2i + 1;$

 if ($2i + 2 \leq n$ and $H[\text{min}] > H[2i + 2]$)

 min $\leftarrow 2i + 2;$

 if (min $\neq i$)

 swap($H[i], H[\text{min}]$);

$i \leftarrow \text{min};$

 else

 Flag \leftarrow false;

End

Complexity

- How many nodes of height h can there be in a complete binary tree of n nodes?

Complexity

- How many nodes of height h can there be in a complete binary tree of n nodes?
- **Note:** Each sub-tree is also a complete binary tree.
 - A sub-tree of height h has **at least** 2^h nodes.
 - **No** two sub-tree of height h have **any element in common**.

Complexity

- How many nodes of height h can there be in a complete binary tree of n nodes?
- **Note:** Each sub-tree is also a complete binary tree.
 - A sub-tree of height h has **at least** 2^h nodes.
 - **No** two sub-tree of height h have **any element in common**.
- \therefore the # nodes of height h is bounded above by $\frac{n}{2^h}$.
- Hence, time complexity of building a heap is given by

$$\begin{aligned}\sum_{h=1}^{\log n} \frac{n}{2^h} \cdot \mathcal{O}(h) &\leq cn \sum_{h=1}^{\log n} \frac{h}{2^h} < cn \sum_{h=1}^{\infty} \frac{h}{2^h} \\ &= cn \cdot \frac{(1/2)}{(1 - 1/2)^2} \quad [\because \sum_{i=1}^{\infty} ix^i = \frac{x}{(1-x)^2} \text{ for } |x| < 1] \\ &= 2cn = \mathcal{O}(n).\end{aligned}$$

Heapsort

Heapsort

- Build heap H on the given n elements.
- **While** (H is not empty)
 $x \leftarrow \text{EXTRACT-MIN}(H)$;
 print x ;
- **Complexity:** $\mathcal{O}(n \log n)$.

Homework:

- Implement a BINARY-MAX-HEAP in C.
- Use it to sort numbers in an decreasing order.
- For a given n ,
 - Take (fixed) m many random inputs of size n each.
 - Compute the average time take by your Heapsort program.
- Repeat the above process for $n = 4, 5, \dots, 1000$.
- Plot the values in a graph where x -axis is n and y -axis denotes the average time taken for each n .

Thank You for your kind attention!

Books and Other Materials Consulted

- ① *Introduction to Algorithms* by [Thomas H Cormen](#), [Charles E Leiserson](#), [Ronald L Rivest](#), [Clifford Stein](#).
- ② Taken from [Prof. Surendar Baswana](#) (CSE, IIT Kanpur) [lecture slides](#).
- ③ Taken from [Prof. Surendar Baswana](#) (CSE, IIT Kanpur) [lecture slides](#).

Questions!!