

Recursion and Recurrences

Subhabrata Samajder



IIIT, Delhi
Summer Semester,
2nd May, 2022

Recursion: A Recap

Recursion

Definition

A “function” is said to be **recursive** if it calls itself, either directly or indirectly.

Recursion

Definition

A “function” is said to be **recursive** if it calls itself, either directly or indirectly.

- In its simplest form, the idea of recursion is straight-forward.

Recursion

Definition

A “function” is said to be **recursive** if it calls itself, either directly or indirectly.

- In its simplest form, the idea of recursion is straight-forward.

Example:

```
#include <stdio.h>

int main(void) {
    printf(“ The universe is never ending! ”);
    main();
    return 0; }
```

Recursion

Definition

A “function” is said to be **recursive** if it calls itself, either directly or indirectly.

- In its simplest form, the idea of recursion is straight-forward.

Example:

```
int sum(int n) {  
    if (n <= 1)  
        return n;  
    else  
        return (n + sum(n - 1)); }
```

Example: `sum(4)`

Example: `sum(4)`

Function call	Value returned		
<code>sum(1)</code>	1		
<code>sum(2)</code>	$2 + \text{sum}(1)$	or	$2 + 1$
<code>sum(3)</code>	$3 + \text{sum}(2)$	or	$3 + 2 + 1$
<code>sum(4)</code>	$4 + \text{sum}(3)$	or	$4 + 3 + 2 + 1$

- The base case is considered,

Example: `sum(4)`

Function call	Value returned		
<code>sum(1)</code>	1		
<code>sum(2)</code>	$2 + \text{sum}(1)$	or	$2 + 1$
<code>sum(3)</code>	$3 + \text{sum}(2)$	or	$3 + 2 + 1$
<code>sum(4)</code>	$4 + \text{sum}(3)$	or	$4 + 3 + 2 + 1$

- The base case is considered,
- then working out from the base case, the other cases are considered.

Simple recursive routines follow a standard pattern!

Simple recursive routines follow a standard pattern!

- The problem is broken into sub-problem(s).

Recursion (Cont.)

Simple recursive routines follow a standard pattern!

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).

Recursion (Cont.)

Simple recursive routines follow a standard pattern!

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.

Recursion (Cont.)

Simple recursive routines follow a standard pattern!

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.
- Then there is a general recursive case in which one of the variables, often an integer, is passed as an argument in such a way as to ultimately lead to the base case.

Recursion (Cont.)

Simple recursive routines follow a standard pattern!

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.
- Then there is a general recursive case in which one of the variables, often an integer, is passed as an argument in such a way as to ultimately lead to the base case.

Example: `sum()`

Recursion (Cont.)

Simple recursive routines follow a standard pattern!

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.
- Then there is a general recursive case in which one of the variables, often an integer, is passed as an argument in such a way as to ultimately lead to the base case.

Example: `sum()`

- $\text{sum}(n) = n + (n - 1) + \cdots + 1 = n + \text{sum}(n - 1).$

Recursion (Cont.)

Simple recursive routines follow a standard pattern!

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.
- Then there is a general recursive case in which one of the variables, often an integer, is passed as an argument in such a way as to ultimately lead to the base case.

Example: `sum()`

- $\text{sum}(n) = n + (n - 1) + \dots + 1 = n + \text{sum}(n - 1).$
- The variable n is reduced by 1 each time until
- the base case with $n = 1$ is reached.

Examples: Factorial

$$0! = 1, \quad n! = n(n-1) \cdots 3 \cdot 2 \cdot 1 \quad \text{for } n > 0$$

or equivalently,

$$0! = 1, \quad n! = n \cdot ((n-1)!) \quad \text{for } n > 0$$

Examples: Factorial

$$0! = 1, \quad n! = n(n-1) \cdots 3 \cdot 2 \cdot 1 \quad \text{for } n > 0$$

or equivalently,

$$0! = 1, \quad n! = n \cdot ((n-1)!) \quad \text{for } n > 0$$

For example: $5! = 5 \cdot 4 \cdot 3 \cdot 2 \cdot 1 = 120$.

Examples: Factorial

$$0! = 1, \quad n! = n(n-1) \cdots 3 \cdot 2 \cdot 1 \quad \text{for } n > 0$$

or equivalently,

$$0! = 1, \quad n! = n \cdot ((n-1)!) \quad \text{for } n > 0$$

For example: $5! = 5 \cdot 4 \cdot 3 \cdot 2 \cdot 1 = 120$.

- **Base Case:** $0! = 1$ and $1! = 1$.

Examples: Factorial

$$0! = 1, \quad n! = n(n-1) \cdots 3 \cdot 2 \cdot 1 \quad \text{for } n > 0$$

or equivalently,

$$0! = 1, \quad n! = n \cdot ((n-1)!) \quad \text{for } n > 0$$

For example: $5! = 5 \cdot 4 \cdot 3 \cdot 2 \cdot 1 = 120$.

- **Base Case:** $0! = 1$ and $1! = 1$.
- **Recursive Case:** $n! = n \cdot (n-1)!$.

Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

Note:

- Works properly within the limits of [integer precision](#).

Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

Note:

- Works properly within the limits of **integer precision**.
- Factorial function grows very rapidly!

Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

Note:

- Works properly within the limits of **integer precision**.
- Factorial function grows very rapidly!
- **RecFactorial(n)** runs only a few values of n (upto $n = 12!!$).

Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

Note:

- Works properly within the limits of **integer precision**.
- Factorial function grows very rapidly!
- **RecFactorial(n)** runs only a few values of n (upto $n = 12!!$).
- For $n > 12$, incorrect values are returned.

Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

Note:

- Works properly within the limits of **integer precision**.
- Factorial function grows very rapidly!
- **RecFactorial(n)** runs only a few values of n (upto $n = 12!!$).
- For $n > 12$, incorrect values are returned.
- **This type of programming error is common!!**

Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

Take Away: Functions that are logically correct can return incorrect values if the logical operations in the body of the function are beyond the integer precision available to the system!!

Factorial: Iterative Version

Note:

- As in `sum()`, `RecFactorial()` activates n **nested copies** of the function before returning level by level to the original call.

Factorial: Iterative Version

Note:

- As in `sum()`, `RecFactorial()` activates n **nested copies** of the function before returning level by level to the original call.
- Thus n **function calls** are used for this computation.
- This is **“costly”**!!

Factorial: Iterative Version

Note:

- As in `sum()`, `RecFactorial()` activates n **nested copies** of the function before returning level by level to the original call.
- Thus n **function calls** are used for this computation.
- This is **“costly”**!!

“What to do?”

Factorial: Iterative Version

Note:

- As in `sum()`, `RecFactorial()` activates n **nested copies** of the function before returning level by level to the original call.
- Thus n **function calls** are used for this computation.
- This is **“costly”**!!

“What to do?”

Way out: Rewrite them as **iterative functions**.

Factorial: Iterative Version

Note:

- As in `sum()`, `RecFactorial()` activates n **nested copies** of the function before returning level by level to the original call.
- Thus n **function calls** are used for this computation.
- This is **“costly”**!!

“What to do?”

Way out: Rewrite them as **iterative functions**.

```
int IterFactorial (int n) {      /* iterative version */  
    int product = 1;  
  
    for ( ; n > 1; -n)  
        product *= n;  
    return product; }
```

Factorial: Iterative Version

Note:

- As in `sum()`, `RecFactorial()` activates n **nested copies** of the function before returning level by level to the original call.
- Thus n **function calls** are used for this computation.
- This is **“costly”**!!

“What to do?”

Way out: Rewrite them as **iterative functions**.

```
int IterFactorial (int n) {      /* iterative version */
    int product = 1;
    for ( ; n > 1; -n)
        product *= n;
    return product; }
```

IterFactorial(n): Takes only 1 function call.

Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

“Then why bother?”

Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

“Then why bother?”

- Recursion is more elegant.

Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

“Then why bother?”

- Recursion is more elegant.
- Requires fewer variables to make the same calculation.

Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

“Then why bother?”

- Recursion is more elegant.
- Requires fewer variables to make the same calculation.
- Takes care of its bookkeeping by stacking arguments and variables for each invocation.

Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

“Then why bother?”

- Recursion is more elegant.
- Requires fewer variables to make the same calculation.
- Takes care of its bookkeeping by stacking arguments and variables for each invocation.
- *This stacking of arguments, while invisible to the user, is still costly in time and space.*

Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

“Then why bother?”

- Recursion is more elegant.
- Requires fewer variables to make the same calculation.
- Takes care of its bookkeeping by stacking arguments and variables for each invocation.
- *This stacking of arguments, while invisible to the user, is still costly in time and space.*
- On some machines a simple recursive call with one integer argument can require eight 32-bit words on the stack.

Fibonacci Sequence

Fibonacci sequence is defined recursively as

$$f_1 = 1, \quad f_2 = 1, \quad f_{i+1} = f_i + f_{i-1} \quad \text{for } i = 1, 2, \dots$$

Every element ($i \geq 3$) is the sum of it's previous two elements.

The sequence begins as 1, 1, 2, 3, 5, ...

Fibonacci Sequence

Consider the following sequence:

$$2/1 = 2.0 \quad (\text{bigger})$$

$$3/2 = 1.5 \quad (\text{smaller})$$

$$5/3 = 1.67 \quad (\text{bigger})$$

$$8/5 = 1.6 \quad (\text{smaller})$$

$$13/8 = 1.625 \quad (\text{bigger})$$

$$21/13 = 1.615 \quad (\text{smaller})$$

$$34/21 = 1.619 \quad (\text{bigger})$$

$$55/34 = 1.618 \quad (\text{smaller})$$

$$89/55 = 1.618$$

Fibonacci Sequence

Consider the following sequence:

$$2/1 = 2.0 \quad (\text{bigger})$$

$$3/2 = 1.5 \quad (\text{smaller})$$

$$5/3 = 1.67 \quad (\text{bigger})$$

$$8/5 = 1.6 \quad (\text{smaller})$$

$$13/8 = 1.625 \quad (\text{bigger})$$

$$21/13 = 1.615 \quad (\text{smaller})$$

$$34/21 = 1.619 \quad (\text{bigger})$$

$$55/34 = 1.618 \quad (\text{smaller})$$

$$89/55 = 1.618$$



Note:

- This sequence seem to be converging!
- It converges to the *golden ratio*.

Golden Ratio

$$\varphi = \frac{1 + \sqrt{5}}{2} \approx 1.6180339887498948482$$

- It is a special number.
- Couple of ways to visually understand it are with
a *line segment* *Golden rectangles*



- It is an *irrational number* that is a root of the quadratic equation


$$x^2 - x - 1 = 0$$

Golden Ratio

- Reciprocal of φ or φ^{-1} :
 - $f_n/f_{n+1} \rightarrow 0.618$ as $n \rightarrow \infty$.
 - This is the reciprocal of φ : $1/1.618 = 0.618$.
 - It is highly unusual for the decimal representation of the fractional part of a number and its reciprocal to be **exactly the same**.
 - This only adds to the mystique of the Golden Ratio and leads us to ask: What makes it so special?

Golden Ratio

- **Some examples:**



The ancient temple in Greece fits almost precisely into a golden rectangle.

Golden Ratio

- **Some examples:**



1 : 1.618

Butterflies.

Recursive Fibonacci Sequence: Function Calls

```
int RecFibonacci (int n) {  
    if (n <= 1)  
        return n;  
    else  
        return (RecFibonacci(n - 1) + RecFibonacci(n - 2)); }
```

Recursive Fibonacci Sequence: Function Calls

Value of n	Value of $\text{RecFibonacci}(n)$	Number of function calls required to recursively compute $\text{RecFibonacci}(n)$
0	0	1
1	1	1
2	1	3
.....		
23	28657	92735
24	46368	150049
.....		
42	267914296	866988873
43	433494437	1402817465

Requires a large number of function calls even for moderate values of n .

Recursion: Summary

- It is seductive to use recursion.
- But one must be careful about run-time limitations and inefficiencies.

Recursion: Summary

- It is seductive to use recursion.
- But one must be careful about run-time limitations and inefficiencies.
- It is sometimes necessary to recode to an equivalent iterative method.

Recursion: Summary

- It is seductive to use recursion.
- But one must be careful about run-time limitations and inefficiencies.
- It is sometimes necessary to recode to an equivalent iterative method.
- Some programmers feel that because the use of recursion is inefficient, it should not be used.

Recursion: Summary

- It is seductive to use recursion.
- But one must be careful about run-time limitations and inefficiencies.
- It is sometimes necessary to recode to an equivalent iterative method.
- Some programmers feel that because the use of recursion is inefficient, it should not be used.
- The inefficiencies, however, are often of little consequence - as in the case of the quicksort algorithm.

Recursion: Summary


- It is seductive to use recursion.
- But one must be careful about run-time limitations and inefficiencies.
- It is sometimes necessary to recode to an equivalent iterative method.
- Some programmers feel that because the use of recursion is inefficient, it should not be used.
- The inefficiencies, however, are often of little consequence - as in the case of the quicksort algorithm.
- For many applications, recursive code is easier to write, understand, maintain.

Recursion: Summary

- It is seductive to use recursion.
- But one must be careful about run-time limitations and inefficiencies.
- It is sometimes necessary to recode to an equivalent iterative method.
- Some programmers feel that because the use of recursion is inefficient, it should not be used.
- The inefficiencies, however, are often of little consequence - as in the case of the quicksort algorithm.
- For many applications, recursive code is easier to write, understand, maintain.
- These reasons often prescribe its use.


Towers of Hanoi

Towers of Hanoi: Problem Statement




- There are three towers.
- n disks of decreasing radius are placed on the 1st tower.
- Move all of the disks from the 1st tower to the 3rd tower.
- **Condition:** At no moment of time can a larger disk be placed on top of smaller disks.
- The remaining tower can be used to temporarily hold disks.

Towers of Hanoi: Solution for $n = 3$



Towers of Hanoi: Solution for $n = 3$


Step 1: Move disks a to tower 3.



Towers of Hanoi: Solution for $n = 3$

Step 1: Move disks a to tower 3.

Step 2: Move disks b to tower 2.




Towers of Hanoi: Solution for $n = 3$

Step 1: Move disks a to tower 3.

Step 2: Move disks b to tower 2.

Step 3: Move disks a to tower 2.




Towers of Hanoi: Solution for $n = 3$

Step 1: Move disks a to tower 3.

Step 2: Move disks b to tower 2.

Step 3: Move disks a to tower 2.

Step 4: Move disks c to tower 3.



Towers of Hanoi: Solution for $n = 3$


Step 1: Move disks a to tower 3.

Step 2: Move disks b to tower 2.

Step 3: Move disks a to tower 2.

Step 4: Move disks c to tower 3.

Step 5: Move disks a to tower 1.



Towers of Hanoi: Solution for $n = 3$

Step 1: Move disks a to tower 3.


Step 2: Move disks b to tower 2.

Step 3: Move disks a to tower 2.

Step 4: Move disks c to tower 3.

Step 5: Move disks a to tower 1.

Step 6: Move disks b to tower 3.



Towers of Hanoi: Solution for $n = 3$

Step 1: Move disks a to tower 3.

Step 2: Move disks b to tower 2.


Step 3: Move disks a to tower 2.

Step 4: Move disks c to tower 3.


Step 5: Move disks a to tower 1.

Step 6: Move disks b to tower 3.

Step 7: Move disks a to tower 3.



Towers of Hanoi: Solution for $n = 3$



Homework:

- Write a recursive algorithm that solves the Towers of Hanoi problem for n disks.
- Implement your algorithm in C.

Recurrences

Definition

A **recurrence relation** is an equation that expresses each element of a sequence $\{a_n\}_{n=0}^{\infty}$ as a function of the preceding ones, i.e.,

$$a_n = \psi(a_0, a_1, \dots, a_{n-1}).$$

Why Recurrences?

Why Recurrences?

- Computing time/space complexity \equiv a counting problem.

Why Recurrences?

- Computing time/space complexity \equiv a counting problem.
- \therefore a sequence.

Why Recurrences?

- Computing time/space complexity \equiv a counting problem.
- \therefore a sequence.
- **Recursive algorithms:** It is **not** easy to compute the number of instructions by looking at code.

Why Recurrences?

- Computing time/space complexity \equiv a counting problem.
- \therefore a sequence.
- **Recursive algorithms:** It is **not** easy to compute the number of instructions by looking at code.
 - The number of instructions in one instance of function call depends on the number of instructions executed when recursive calls are made.

Why Recurrences?

- Computing time/space complexity \equiv a counting problem.
- \therefore a sequence.
- **Recursive algorithms:** It is **not** easy to compute the number of instructions by looking at code.
 - The number of instructions in one instance of function call depends on the number of instructions executed when recursive calls are made.
 - In such cases it is easier for us to express it as some *recurrence relation* of the times/space complexity.

Why Recurrences?

- Computing time/space complexity \equiv a counting problem.
- \therefore a sequence.
- **Recursive algorithms:** It is **not** easy to compute the number of instructions by looking at code.
 - The number of instructions in one instance of function call depends on the number of instructions executed when recursive calls are made.
 - In such cases it is easier for us to express it as some *recurrence relation* of the times/space complexity.
- Appears frequently in the analysis of algorithms.

Questions?

- 1 How to form recurrence relation for a counting problem?

Questions?

- 1 How to form recurrence relation for a counting problem? Easy!!

Questions?

- ① How to form recurrence relation for a counting problem? Easy!!
- ② How to solve such relations?

Questions?

- ① How to form recurrence relation for a counting problem? Easy!!
- ② How to solve such relations?

- We briefly discuss few useful technique for solving recurrences.
- Present general solutions of **two classes** of recurrences that are among the **most common** recurrences involved in analyzing algorithms.

Intelligent Guesses

- Guessing a solution may seem like a nonscientific method!
- But, keeping our pride aside, it works very well for a wide class of recurrence relations.
- It works even better when we are *not* trying to find the *exact solution*, but only an *upper bound*.
- **Why guess?** Proving a certain bound is valid is *easier* than deriving that bound.

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

- Can compute the value of the function for every n .

Example:

$$F(3) = F(2) + F(1) = 2, \quad F(4) = F(3) + F(2) = 3, \dots$$

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

- Can compute the value of the function for every n .

Example:

$$F(3) = F(2) + F(1) = 2, \quad F(4) = F(3) + F(2) = 3, \dots$$

- **Note:** By definition we need $n - 2$ steps to compute $F(n)$.

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

- Can compute the value of the function for every n .

Example:

$$F(3) = F(2) + F(1) = 2, \quad F(4) = F(3) + F(2) = 3, \dots$$

- **Note:** By definition we need $n - 2$ steps to compute $F(n)$.
- Would be more convenient to have an **explicit (or closed-form) expression** for $F(n)$.
 - It would enable us to compute $F(n)$ quickly.
 - We can also compare $F(n)$ with other known functions.

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

- $F(n)$ is the sum of two previous values.

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

- $F(n)$ is the sum of two previous values.
- **Possible guess:** $F(n)$ is doubled every time, i.e., $F(n) \approx 2^n$.

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

- $F(n)$ is the sum of two previous values.
- **Possible guess:** $F(n)$ is doubled every time, i.e., $F(n) \approx 2^n$.
- Let $F(n) = ca^n$, then we get

$$ca^n = ca^{n-1} + ca^{n-2} \Rightarrow a^2 = a + 1 \quad (\text{Characteristic equation}).$$

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

- $F(n)$ is the sum of two previous values.
- **Possible guess:** $F(n)$ is doubled every time, i.e., $F(n) \approx 2^n$.
- Let $F(n) = ca^n$, then we get

$$ca^n = ca^{n-1} + ca^{n-2} \Rightarrow a^2 = a + 1 \quad (\text{Characteristic equation}).$$

- **Solving:** $a_1 = (1 + \sqrt{5})/2 (> 0)$ and $a_2 = (1 - \sqrt{5})/2 (< 0)$.

Fibonacci Sequence

$$F(n) = F(n-1) + F(n-2), \quad F(1) = 1, F(2) = 1.$$

- $F(n)$ is the sum of two previous values.
- **Possible guess:** $F(n)$ is doubled every time, i.e., $F(n) \approx 2^n$.
- Let $F(n) = ca^n$, then we get

$$ca^n = ca^{n-1} + ca^{n-2} \Rightarrow a^2 = a + 1 \quad (\text{Characteristic equation}).$$

- **Solving:** $a_1 = (1 + \sqrt{5})/2 (> 0)$ and $a_2 = (1 - \sqrt{5})/2 (< 0)$.
- $\therefore F(n) = \mathcal{O}((a_1)^n)$.
 - Find a constant c such that $c(a_1)^n \geq F(1)$ and $F(2)$.

Fibonacci Sequence: Exact Solution

- Need to consider the initial values more carefully.

Fibonacci Sequence: Exact Solution

- Need to consider the initial values more carefully.
- **General Solution:** $c_1(a_1)^n + c_2(a_2)^n$.

Fibonacci Sequence: Exact Solution

- Need to consider the initial values more carefully.
- **General Solution:** $c_1(a_1)^n + c_2(a_2)^n$.
- Find c_1 and c_2 , s. t., $F(1) = 1$ and $F(2) = 1$.

Fibonacci Sequence: Exact Solution

- Need to consider the initial values more carefully.
- **General Solution:** $c_1(a_1)^n + c_2(a_2)^n$.
- Find c_1 and c_2 , s. t., $F(1) = 1$ and $F(2) = 1$.
- **Solving:** $c_1 = 1/\sqrt{5}$, and $c_2 = -1/\sqrt{5}$.

Fibonacci Sequence: Exact Solution

- Need to consider the initial values more carefully.
- **General Solution:** $c_1(a_1)^n + c_2(a_2)^n$.
- Find c_1 and c_2 , s. t., $F(1) = 1$ and $F(2) = 1$.
- **Solving:** $c_1 = 1/\sqrt{5}$, and $c_2 = -1/\sqrt{5}$.
- **Exact solution:**

$$F(n) = \frac{1}{\sqrt{5}} \left[\frac{1 + \sqrt{5}}{2} \right]^n - \frac{1}{\sqrt{5}} \left[\frac{1 - \sqrt{5}}{2} \right]^n.$$

Fibonacci Sequence: Exact Solution

- Need to consider the initial values more carefully.
- **General Solution:** $c_1(a_1)^n + c_2(a_2)^n$.
- Find c_1 and c_2 , s. t., $F(1) = 1$ and $F(2) = 1$.
- **Solving:** $c_1 = 1/\sqrt{5}$, and $c_2 = -1/\sqrt{5}$.
- **Exact solution:**

$$F(n) = \frac{1}{\sqrt{5}} \left[\frac{1 + \sqrt{5}}{2} \right]^n - \frac{1}{\sqrt{5}} \left[\frac{1 - \sqrt{5}}{2} \right]^n.$$

Note: This idea, can be used to solve recurrences of the form

$$F(n) = b_1 F(n-1) + b_2 F(n-2) + \cdots + b_k F(n-k) \quad (k \text{ constant}).$$

Books Consulted

- ① *Introduction to Algorithms: A Creative Approach* by Udi Manber.
- ② *Introduction to Algorithms* by Thomas H Cormen, Charles E Leiserson, Ronald L Rivest, Clifford Stein.

Thank You for your kind attention!