

# Introduction to Algorithms (Cont.) and Big-oh Notation

Subhabrata Samajder



IIIT, Delhi  
Summer Semester,  
28<sup>th</sup> April, 2022

# Searching Problem

- **I/P:** A list  $L$  of integer values and another value  $v$ .
- **Question:** Does  $v \in L$ ?
- **O/P:** 'index of  $s$ ' if  $v \in L$ ; else it returns 'FLAG'.

# Linear Search

```
LinearSearch( $L[1, \dots, n]$ ,  $s$ ):  
  for  $i = 1$  to  $n$   
    if ( $L[i] = s$ )  
      return  $i$ ;  
  endfor;  
  return FLAG.
```

# Linear Search

```
LinearSearch( $L[1, \dots, n]$ ,  $s$ ):  
  for  $i = 1$  to  $n$   
    if ( $L[i] = s$ )  
      return  $i$ ;  
  endfor;  
  return FLAG.
```

- **Basic operation:** Comparison of the type ' $L[i] = s$ '

# Linear Search

```
LinearSearch( $L[1, \dots, n], s$ ):  
  for  $i = 1$  to  $n$   
    if ( $L[i] = s$ )  
      return  $i$ ;  
  endfor;  
  return FLAG.
```

- **Basic operation:** Comparison of the type ' $L[i] = s$ '
  - Depends on the size of integers  $L[i]$ 's and  $s$ .
  - **Assumption:** The sizes of  $L[i]$ 's and  $s$  are constant.
  - Then, the time taken for each comparison is a *constant*.

# Linear Search

```
LinearSearch( $L[1, \dots, n], s$ ):  
  for  $i = 1$  to  $n$   
    if ( $L[i] = s$ )  
      return  $i$ ;  
  endfor;  
  return FLAG.
```

- **Basic operation:** Comparison of the type ' $L[i] = s$ '
  - Depends on the size of integers  $L[i]$ 's and  $s$ .
  - **Assumption:** The sizes of  $L[i]$ 's and  $s$  are constant.
  - Then, the time taken for each comparison is a *constant*.
- **Size of input:**  $|L|$ .

# Linear Search

LinearSearch( $L[1, \dots, n], s$ ):

  for  $i = 1$  to  $n$

    if ( $L[i] = s$ )

      return  $i$ ;

  endfor;

  return FLAG.

- **Basic operation:** Comparison of the type ' $L[i] = s$ '
  - Depends on the size of integers  $L[i]$ 's and  $s$ .
  - **Assumption:** The sizes of  $L[i]$ 's and  $s$  are constant.
  - Then, the time taken for each comparison is a *constant*.
- **Size of input:**  $|L|$ .
- **Time complexity:** Number of comparisons of the type

' $L[i] = s$ '.

- # other operations  $\propto$  # comparisons.

# Linear Search

```
LinearSearch( $L[1, \dots, n], s$ ):  
  for  $i = 1$  to  $n$   
    if ( $L[i] = s$ )  
      return  $i$ ;  
  endfor;  
  return FLAG.
```

- **Unsuccessful search:**  $n$  comparisons.



# Linear Search

```
LinearSearch( $L[1, \dots, n], s$ ):  
  for  $i = 1$  to  $n$   
    if ( $L[i] = s$ )  
      return  $i$ ;  
  endfor;  
  return FLAG.
```

- **Unsuccessful search:**  $n$  comparisons.
- **Successful search:** Between 1 to  $n$  comparisons.

# Linear Search

```
LinearSearch( $L[1, \dots, n], s$ ):  
  for  $i = 1$  to  $n$   
    if ( $L[i] = s$ )  
      return  $i$ ;  
  endfor;  
  return FLAG.
```

- **Unsuccessful search:**  $n$  comparisons.
- **Successful search:** Between 1 to  $n$  comparisons.
- **Worst-case complexity:**  $n$  comparisons.

# Linear Search

```
LinearSearch( $L[1, \dots, n], s$ ):  
  for  $i = 1$  to  $n$   
    if ( $L[i] = s$ )  
      return  $i$ ;  
  endfor;  
  return FLAG.
```

- **Unsuccessful search:**  $n$  comparisons.
- **Successful search:** Between 1 to  $n$  comparisons.
- **Worst-case complexity:**  $n$  comparisons.
- $\therefore \#$  steps in the worst case =  $c_1 n$ , for some constant  $c_1$ .

## Average-case complexity:

- Fix  $n$  integers.

## Average-case complexity:

- Fix  $n$  integers.
- Two cases may arise:
  - **Successful search:**  $s \in L[1]$ .
    - Call this event succ.
    - Assign  $1/n$  (uniform) probability to each of these cases.
    - That is,  $\Pr[T(n) = i | \text{succ}] = \frac{1}{n}, \forall i = 1, 2, \dots, n$ .

## Average-case complexity:

- Fix  $n$  integers.
- Two cases may arise:
  - **Successful search:**  $s \in L[1]$ .
    - Call this event succ.
    - Assign  $1/n$  (uniform) probability to each of these cases.
    - That is,  $\Pr[T(n) = i | \text{succ}] = \frac{1}{n}, \forall i = 1, 2, \dots, n$ .
  - **Unsuccessful search:**  $s \notin L$ .
    - Call this event unsucc.
    - In this case  $\Pr[T(n) = n | \text{unsucc}] = 1$ .

## Average-case complexity:

- Fix  $n$  integers.
- Two cases may arise:
  - **Successful search:**  $s \in L[1]$ .
    - Call this event succ.
    - Assign  $1/n$  (uniform) probability to each of these cases.
    - That is,  $\Pr[T(n) = i | \text{succ}] = \frac{1}{n}, \forall i = 1, 2, \dots, n.$
  - **Unsuccessful search:**  $s \notin L.$ 
    - Call this event unsucc.
    - In this case  $\Pr[T(n) = n | \text{unsucc}] = 1.$
- Assume that  $\Pr[\text{succ}] = \Pr[\text{unsucc}] = \frac{1}{2}.$

# Linear Search

## Average-case complexity:

- Fix  $n$  integers.
- Two cases may arise:
  - **Successful search:**  $s \in L[1]$ .
    - Call this event succ.
    - Assign  $1/n$  (uniform) probability to each of these cases.
    - That is,  $\Pr[T(n) = i | \text{succ}] = \frac{1}{n}, \forall i = 1, 2, \dots, n$ .
  - **Unsuccessful search:**  $s \notin L$ .
    - Call this event unsucc.
    - In this case  $\Pr[T(n) = n | \text{unsucc}] = 1$ .
- Assume that  $\Pr[\text{succ}] = \Pr[\text{unsucc}] = \frac{1}{2}$ .

Then,

$$\begin{aligned} E[T(n)] &= E[T(n) | \text{succ}] \cdot \Pr[\text{succ}] + E[T(n) | \text{unsucc}] \cdot \Pr[\text{unsucc}] \\ &= \frac{1}{2} \left( \sum_{i=1}^n i \cdot \frac{1}{n} + n \cdot 1 \right) = \frac{3n+1}{4}. \end{aligned}$$



# Linear Search

**Assume:**  $L$  is sorted in ascending order.

**Assume:**  $L$  is sorted in ascending order.

- **Note:** LinearSearch cannot take advantage of this information.

**Assume:**  $L$  is sorted in ascending order.

- **Note:** LinearSearch cannot take advantage of this information.
- **Question:** Can we do better?

# Binary Search




Figure: Binary Search (Courtesy: Wikipedia)

# Binary Search (Cont.)

Binary\_Search( $L, n, s$ )

**I/P:**  $L$  (a sorted array in the range 1 to  $n$ ), and  $z$  (the search key).

**O/P:** *Position* (an index  $i$  such that  $L[i] = s$ , or 0 if no such index exist).

Begin

$Position := \text{Find}(s, 1, n);$

End

# Binary Search (Cont.)

Binary\_Search( $L, n, s$ )

**I/P:**  $L$  (a sorted array in the range 1 to  $n$ ), and  $z$  (the search key).

**O/P:** *Position* (an index  $i$  such that  $L[i] = s$ , or 0 if no such index exist).

Begin

*Position* := Find( $s, 1, n$ );

End

*function* Find( $s, Left, Right$ ) : integer

Begin

If ( $Left = Right$ )

If ( $L[Left] = s$ )

return  $Left$ ;

else

return 0;

else

$Middle := \lceil 1/2(Left + Right) \rceil$ ;

If ( $s < L[Middle]$ )

return Find( $s, Left, Middle - 1$ );

else

return Find( $s, Middle, Right$ );

End

# Binary Search (Cont.)

Binary\_Search( $L, n, s$ )

**I/P:**  $L$  (a sorted array in the range 1 to  $n$ ), and  $z$  (the search key).

**O/P:** *Position* (an index  $i$  such that  $L[i] = s$ , or 0 if no such index exist).

Begin

$Position := \text{Find}(s, 1, n);$

End

*function* Find( $s, Left, Right$ ) : integer

Begin

If ( $Left = Right$ )

  If ( $L[Left] = s$ )

    return  $Left$ ;

  else

    return 0;

  else

$Middle := \lceil 1/2(Left + Right) \rceil;$

    If ( $s < L[Middle]$ )

      return Find( $s, Left, Middle - 1$ );

    else

      return Find( $s, Middle, Right$ );

End

**Homework:** Implement BinarySearch in C.

## Binary Search (Cont.)

- After one search the size of the search space is reduced by *half*, i.e., becomes  $n/2$ .



## Binary Search (Cont.)

- After one search the size of the search space is reduced by *half*, i.e., becomes  $n/2$ .
- After each subsequent search the list size becomes  $\frac{n}{2^2}, \frac{n}{2^3}, \dots$
- **Successful search:**  $k$  comparisons, where

$$\frac{n}{2^k} = 1 \quad \Rightarrow \quad k = \lceil \log_2 n \rceil.$$

## Binary Search (Cont.)

- After one search the size of the search space is reduced by *half*, i.e., becomes  $n/2$ .
- After each subsequent search the list size becomes  $\frac{n}{2^2}, \frac{n}{2^3}, \dots$

- **Successful search:**  $k$  comparisons, where

$$\frac{n}{2^k} = 1 \Rightarrow k = \lceil \log_2 n \rceil.$$

- **Unsuccessful search:**  $\lceil \log_2 n \rceil$  comparisons.

## Binary Search (Cont.)

- After one search the size of the search space is reduced by *half*, i.e., becomes  $n/2$ .
- After each subsequent search the list size becomes  $\frac{n}{2^2}, \frac{n}{2^3}, \dots$
- **Successful search:**  $k$  comparisons, where

$$\frac{n}{2^k} = 1 \quad \Rightarrow \quad k = \lceil \log_2 n \rceil.$$

- **Unsuccessful search:**  $\lceil \log_2 n \rceil$  comparisons.
- **Worst-case time complexity:**  $\lceil \log_2 n \rceil$  comparisons.

## Binary Search (Cont.)

- After one search the size of the search space is reduced by *half*, i.e., becomes  $n/2$ .
- After each subsequent search the list size becomes  $\frac{n}{2^2}, \frac{n}{2^3}, \dots$
- **Successful search:**  $k$  comparisons, where

$$\frac{n}{2^k} = 1 \Rightarrow k = \lceil \log_2 n \rceil.$$

- **Unsuccessful search:**  $\lceil \log_2 n \rceil$  comparisons.
- **Worst-case time complexity:**  $\lceil \log_2 n \rceil$  comparisons.
- **Average-case time complexity:**  $\lceil \log_2 n \rceil$  comparisons.

## Binary Search (Cont.)

- After one search the size of the search space is reduced by *half*, i.e., becomes  $n/2$ .
- After each subsequent search the list size becomes  $\frac{n}{2^2}, \frac{n}{2^3}, \dots$
- **Successful search:**  $k$  comparisons, where

$$\frac{n}{2^k} = 1 \Rightarrow k = \lceil \log_2 n \rceil.$$

- **Unsuccessful search:**  $\lceil \log_2 n \rceil$  comparisons.
- **Worst-case time complexity:**  $\lceil \log_2 n \rceil$  comparisons.
- $\therefore$  # steps in the worst case =  $c_2 \times \lceil \log_2 n \rceil$ ,  $c_2 = \text{constant}$ .

## Binary Search (Cont.)

- After one search the size of the search space is reduced by *half*, i.e., becomes  $n/2$ .
- After each subsequent search the list size becomes  $\frac{n}{2^2}, \frac{n}{2^3}, \dots$
- **Successful search:**  $k$  comparisons, where

$$\frac{n}{2^k} = 1 \Rightarrow k = \lceil \log_2 n \rceil.$$

- **Unsuccessful search:**  $\lceil \log_2 n \rceil$  comparisons.
- **Worst-case time complexity:**  $\lceil \log_2 n \rceil$  comparisons.
- $\therefore$  # steps in the worst case =  $c_2 \times \lceil \log_2 n \rceil$ ,  $c_2 = \text{constant}$ .
- Clearly, BinarySearch is “better” than LinearSearch.

## Binary Search (Cont.)

- After one search the size of the search space is reduced by *half*, i.e., becomes  $n/2$ .
- After each subsequent search the list size becomes  $\frac{n}{2^2}, \frac{n}{2^3}, \dots$
- **Successful search:**  $k$  comparisons, where

$$\frac{n}{2^k} = 1 \Rightarrow k = \lceil \log_2 n \rceil.$$

- **Unsuccessful search:**  $\lceil \log_2 n \rceil$  comparisons.
- **Worst-case time complexity:**  $\lceil \log_2 n \rceil$  comparisons.
- $\therefore$  # steps in the worst case =  $c_2 \times \lceil \log_2 n \rceil$ ,  $c_2 = \text{constant}$ .
- Clearly, BinarySearch is “better” than LinearSearch.
- **Question:** Which is the “best” possible algorithm for a given ‘problem’?

# Comparing Algorithms

Consider a problem  $\Pi$ .

- Any algorithm which solves  $\Pi$  will take as input an instance of the problem and return the correct answer.



# Comparing Algorithms

Consider a problem  $\Pi$ .

- Any algorithm which solves  $\Pi$  will take as input an instance of the problem and return the correct answer.
- Two algorithms for the same problem can be compared by comparing their time complexities.
- More generally, one can ask for the best possible algorithm to solve  $\Pi$  or to show that  $\Pi$  cannot be solved efficiently.

# Comparing Algorithms

Consider a problem  $\Pi$ .

- Any algorithm which solves  $\Pi$  will take as input an instance of the problem and return the correct answer.
- Two algorithms for the same problem can be compared by comparing their time complexities.
- More generally, one can ask for the best possible algorithm to solve  $\Pi$  or to show that  $\Pi$  cannot be solved efficiently.
- Answering such questions form the motivation for the rich area of [algorithm design and analysis \(ADA\)](#).

# Asymptotic Notation

- **Measure of performance:** Worst-case complexity.

- **Measure of performance:** Worst-case complexity.
  - LinearSearch:  $t(n) = c_1 n$ .
  - BinarySearch:  $t(n) = c_2 \times \lceil \log_2 n \rceil$ .

- **Measure of performance:** Worst-case complexity.
  - LinearSearch:  $t(n) = c_1 n$ .
  - BinarySearch:  $t(n) = c_2 \times \lceil \log_2 n \rceil$ .
  - **Note:** The constants  $c_1$  and  $c_2$  depends upon many things including implementation details.

# Asymptotic Notation

- **Measure of performance:** Worst-case complexity.
  - LinearSearch:  $t(n) = c_1 n$ .
  - BinarySearch:  $t(n) = c_2 \times \lceil \log_2 n \rceil$ .
  - **Note:** The constants  $c_1$  and  $c_2$  depends upon many things including implementation details.
  - Would be **convenient** to have a method which does not involve these constants.

# Big-oh Notation




Figure: Binary Search (Courtesy: Wikipedia)

## Big-oh Notation (Cont.)

### Definition ( $\mathcal{O}$ -notation)

Let  $g$  and  $f$  be functions from the set of natural numbers to itself. The function  $f$  is said to be  $\mathcal{O}(g)$  (**read big-oh of  $g$** ), if there is a constant  $c$  and a natural  $n_0$  such that

$$f(n) \leq cg(n) \text{ for all } n > n_0.$$



# Big-oh Notation (Cont.)

## Definition ( $\mathcal{O}$ -notation)

Let  $g$  and  $f$  be functions from the set of natural numbers to itself. The function  $f$  is said to be  $\mathcal{O}(g)$  (**read big-oh of  $g$** ), if there is a constant  $c$  and a natural  $n_0$  such that

$$f(n) \leq cg(n) \text{ for all } n > n_0.$$

- LinearSearch =  $\mathcal{O}(n)$  (both cases)
- BinarySearch =  $\mathcal{O}(\log n)$  (both cases)
  - **Homework:** Derive the average-case complexity of BinarySearch with early termination.

# Big-oh Notation (Cont.)

## Definition ( $\mathcal{O}$ -notation)

Let  $g$  and  $f$  be functions from the set of natural numbers to itself. The function  $f$  is said to be  $\mathcal{O}(g)$  (**read big-oh of  $g$** ), if there is a constant  $c$  and a natural  $n_0$  such that

$$f(n) \leq cg(n) \text{ for all } n > n_0.$$

- $\text{LinearSearch} = \mathcal{O}(n)$  (both cases)
- $\text{BinarySearch} = \mathcal{O}(\log n)$  (both cases)
  - **Homework:** Derive the average-case complexity of  $\text{BinarySearch}$  with early termination.
- **Caveat:**
  - 1 We lose a lot of details.
  - 2 Details can be important in actual practice.

## Big-oh Notation (Cont.)

**Note:**  $\mathcal{O}(g)$  is a set!

## Big-oh Notation (Cont.)

**Note:**  $\mathcal{O}(g)$  is a set!

**Abuse of notation:** We write  $f = \mathcal{O}(g)$  to mean  $f \in \mathcal{O}(g)$ .

## Big-oh Notation (Cont.)

**Note:**  $\mathcal{O}(g)$  is a set!

**Abuse of notation:** We write  $f = \mathcal{O}(g)$  to mean  $f \in \mathcal{O}(g)$ .

**Examples:**

- $5n^2 + 15 = \mathcal{O}(n^2)$  [ $\because 5n^2 + 15 \leq 6n^2$  for  $n > 4$ ].

## Big-oh Notation (Cont.)

**Note:**  $\mathcal{O}(g)$  is a set!

**Abuse of notation:** We write  $f = \mathcal{O}(g)$  to mean  $f \in \mathcal{O}(g)$ .

**Examples:**

- $5n^2 + 15 = \mathcal{O}(n^2)$  [ $\because 5n^2 + 15 \leq 6n^2$  for  $n > 4$ ].
- $5n^2 + 15 = \mathcal{O}(n^3)$  [ $\because 5n^2 + 15 \leq n^3$  for all  $n > 6$ ].

# Big-oh Notation (Cont.)

**Note:**  $\mathcal{O}(g)$  is a set!

**Abuse of notation:** We write  $f = \mathcal{O}(g)$  to mean  $f \in \mathcal{O}(g)$ .

**Examples:**

- $5n^2 + 15 = \mathcal{O}(n^2)$  [ $\because 5n^2 + 15 \leq 6n^2$  for  $n > 4$ ].
- $5n^2 + 15 = \mathcal{O}(n^3)$  [ $\because 5n^2 + 15 \leq n^3$  for all  $n > 6$ ].
- $\mathcal{O}(1)$  denote a constant.

## Big-oh Notation (Cont.)

**Note:**  $\mathcal{O}(g)$  is a set!

**Abuse of notation:** We write  $f = \mathcal{O}(g)$  to mean  $f \in \mathcal{O}(g)$ .

### Examples:

- $5n^2 + 15 = \mathcal{O}(n^2)$  [ $\because 5n^2 + 15 \leq 6n^2$  for  $n > 4$ ].
- $5n^2 + 15 = \mathcal{O}(n^3)$  [ $\because 5n^2 + 15 \leq n^3$  for all  $n > 6$ ].
- $\mathcal{O}(1)$  denote a constant.
- One can include constants within the  $\mathcal{O}$  notation.
- But there is no reason to do it.
- We therefore write  $\mathcal{O}(n)$  instead of  $\mathcal{O}(5n + 4)$ .



# Poly-time vs. Exponential Algorithm

## Poly-time:

- $\mathcal{O}(n^c)$ .
- Identified with *efficient* algorithms.

# Poly-time vs. Exponential Algorithm

## Poly-time:

- $\mathcal{O}(n^c)$ .
- Identified with *efficient* algorithms.

## Exponential-time:

- $\mathcal{O}(2^n)$ .
- Identified with *inefficient* algorithms.

# Poly-time vs. Exponential Algorithm

## Poly-time:

- $\mathcal{O}(n^c)$ .
- Identified with *efficient* algorithms.

## Exponential-time:

- $\mathcal{O}(2^n)$ .
- Identified with *inefficient* algorithms.

For any given problem, it is of interest to be able to design a polynomial time algorithm to solve it.

# Some Results

**Monotonically growing function:** If  $n_1 > n_2 \Rightarrow f(n_1) \geq f(n_2)$ .

## Some Results

**Monotonically growing function:** If  $n_1 > n_2 \Rightarrow f(n_1) \geq f(n_2)$ .

### Theorem

*For all constants  $c > 0$  and  $a > 1$ , and for all monotonically growing functions  $f(n)$ ,*

$$(f(n))^c = \mathcal{O}(a^{f(n)}).$$

*In other words, an exponential function grows faster than does a polynomial function.*

# Some Results

**Monotonically growing function:** If  $n_1 > n_2 \Rightarrow f(n_1) \geq f(n_2)$ .

## Theorem

*For all constants  $c > 0$  and  $a > 1$ , and for all monotonically growing functions  $f(n)$ ,*

$$(f(n))^c = \mathcal{O}(a^{f(n)}).$$

*In other words, an exponential function grows faster than does a polynomial function.*

**Proof:** Home Work!

# Some Results

**Monotonically growing function:** If  $n_1 > n_2 \Rightarrow f(n_1) \geq f(n_2)$ .

## Theorem

*For all constants  $c > 0$  and  $a > 1$ , and for all monotonically growing functions  $f(n)$ ,*

$$(f(n))^c = \mathcal{O}(a^{f(n)}).$$

*In other words, an exponential function grows faster than does a polynomial function.*

**Proof:** Home Work!

## Corollaries:

- Putting  $f(n) = n$ , we get  $n^c = \mathcal{O}(a^n)$ .
- Putting  $f(n) = \log_a n$ , we get  $(\log_a n)^c = \mathcal{O}(a^{\log_a n}) = \mathcal{O}(n)$ .

## Some Results (Cont.)

### Lemma

- ① If  $f(n) = \mathcal{O}(s(n))$  and  $g(n) = \mathcal{O}(r(n))$  then

$$f(n) + g(n) = \mathcal{O}(s(n) + r(n)).$$

- ② If  $f(n) = \mathcal{O}(s(n))$  and  $g(n) = \mathcal{O}(r(n))$  then

$$f(n).g(n) = \mathcal{O}(s(n).r(n)).$$



## Some Results (Cont.)

### Lemma

- ① If  $f(n) = \mathcal{O}(s(n))$  and  $g(n) = \mathcal{O}(r(n))$  then

$$f(n) + g(n) = \mathcal{O}(s(n) + r(n)).$$

- ② If  $f(n) = \mathcal{O}(s(n))$  and  $g(n) = \mathcal{O}(r(n))$  then

$$f(n).g(n) = \mathcal{O}(s(n).r(n)).$$

**Proof:** Home Work!

## Some Results (Cont.)

### Note:

- It is not possible to *subtract* or *divide*.

## Some Results (Cont.)

### Note:

- It is not possible to *subtract* or *divide*.
- That is, it is **not true** in general that  $f(n) = \mathcal{O}(s(n))$  and  $g(n) = \mathcal{O}(r(n))$  imply that

$$f(n) - g(n) = \mathcal{O}(s(n) - r(n))$$

or that

$$f(n)/g(n) = \mathcal{O}(s(n)/r(n)).$$

## Some Results (Cont.)

### Note:

- It is not possible to *subtract* or *divide*.
- That is, it is **not true** in general that  $f(n) = \mathcal{O}(s(n))$  and  $g(n) = \mathcal{O}(r(n))$  imply that

$$f(n) - g(n) = \mathcal{O}(s(n) - r(n))$$

or that

$$f(n)/g(n) = \mathcal{O}(s(n)/r(n)).$$

(Show it!)

# Better Processors vs. Efficient Algorithms

running times	$time_1$ 1000 steps/sec	$time_2$ 2000 steps/sec	$time_3$ 4000 steps/sec	$time_4$ 8000 steps/sec
$\log_2 n$	0.010	0.005	0.003	0.001
$n$	1	0.5	0.25	0.125
$n \log_2 n$	10	5	2.5	1.25
$n^{1.25}$	32	16	8	4
$n^2$	1,000	500	250	125
$n^3$	1,000,000	500,000	250,000	125,000
$1.1^n$	$10^{39}$	$10^{39}$	$10^{38}$	$10^{38}$

**Table:** Running times (in seconds) under different assumptions ( $n = 1000$ ).

## Other Asymptotic Notations

## Definition

If there exist constants  $c$  and  $N$ , such that for all  $n > N$  the number of steps  $T(n)$  required to solve the problem for input size  $n$  is at least  $cg(n)$ , i.e.,

$$T(n) \geq cg(n),$$

then we say that  $T(n) = \Omega(g(n))$ .

## Definition

If there exist constants  $c$  and  $N$ , such that for all  $n > N$  the number of steps  $T(n)$  required to solve the problem for input size  $n$  is at least  $cg(n)$ , i.e.,

$$T(n) \geq cg(n),$$

then we say that  $T(n) = \Omega(g(n))$ .

- **Example:**  $n^2 = \Omega(n^2 - 100)$ ,  $n = \Omega(n^{0.9})$ .



## Definition

If there exist constants  $c$  and  $N$ , such that for all  $n > N$  the number of steps  $T(n)$  required to solve the problem for input size  $n$  is at least  $cg(n)$ , i.e.,

$$T(n) \geq cg(n),$$

then we say that  $T(n) = \Omega(g(n))$ .

- **Example:**  $n^2 = \Omega(n^2 - 100)$ ,  $n = \Omega(n^{0.9})$ .
- The  $\Omega$  notation thus correspond to the “ $\geq$ ” relation.

# $\Theta$ Notation

## Definition

If a certain function  $f(n)$  satisfies both  $f(n) = \mathcal{O}(g(n))$  and  $f(n) = \Omega(g(n))$ , then we say that  $f(n) = \Theta(g(n))$ .

- **Example:**  $5n \log_2 n - 10 = \Theta(n \log n)$ .

## Definition

If a certain function  $f(n)$  satisfies both  $f(n) = \mathcal{O}(g(n))$  and  $f(n) = \Omega(g(n))$ , then we say that  $f(n) = \Theta(g(n))$ .

- **Example:**  $5n \log_2 n - 10 = \Theta(n \log n)$ .
- The constants used to prove the  $\mathcal{O}$  part and the  $\Omega$  part need not be the same.

# Small-oh or Little-oh Notation

- The  $\mathcal{O}$ ,  $\Omega$  and  $\Theta$  correspond (loosely) to “ $\leq$ ”, “ $\geq$ ”, and “ $=$ ”.
- Sometimes we need notation corresponding to “ $<$ ” and “ $>$ ”.

## Definition

We say that  $f(n) = o(g(n))$  (pronounced “ $f(n)$  is little oh of  $g(n)$ ”) if

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0.$$

# Small-oh or Little-oh Notation

- The  $\mathcal{O}$ ,  $\Omega$  and  $\Theta$  correspond (loosely) to “ $\leq$ ”, “ $\geq$ ”, and “ $=$ ”.
- Sometimes we need notation corresponding to “ $<$ ” and “ $>$ ”.

## Definition

We say that  $f(n) = o(g(n))$  (pronounced “ $f(n)$  is little oh of  $g(n)$ ”) if

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0.$$

**Example:**  $n/\log_2 n = o(n)$ , but  $n/10 \neq o(n)$ .

### Definition

Similarly, we say that  $f(n) = \omega(g(n))$  (small omega) if

$$g(n) = o(f(n)).$$

In other words,  $f(n) = \omega(g(n))$  means that for any positive constant  $c$ , there exists a constant  $N$ , such that

$$0 \leq cg(n) < f(n)$$

for all  $n \geq N$ . The value of  $N$  must not depend on  $n$ , but may depend on  $c$ .

- ① Chapter 2 of *A Course on Cooperative Game Theory* by Satya R. Chakravarty, Palash Sarkar and Manipushpak Mitra.
- ② *Introduction to Algorithms: A Creative Approach* by Udi Manber.

Thank You for your kind attention!