Amplitude-Encoding Kernel Methods for Zero-Trust Network Anomaly Detection: A Cosine-Similarity Feature-Space Approach to Real-Time Threat Intelligence

Arnav Kapoor
arnavkapoor23@iiserb.ac.in
Department of Computer Science and Engineering
Indian Institute of Science Education and Research Bhopal
Bhopal, Madhya Pradesh 462066, India

July 31, 2026

Abstract

Zero-Trust Network Architectures (ZTNA) require continuous, real-time anomaly detection across high-dimensional network flow features—a setting where representation learning and inductive bias matter as much as raw classifier power. We present Q-ZTNA, an anomaly detection framework that uses an amplitude-encoding (cosine-similarity) kernel—a classically computable feature map $\mathcal{K}_A(\mathbf{x}_i, \mathbf{x}_j) = |\langle \mathbf{x}_i, \mathbf{x}_j \rangle|^2 / \|\mathbf{x}_i\|^2 \|\mathbf{x}_j\|^2$—as the core of a kernel SVM with Nyström approximation. On synthetic enterprise-network telemetry spanning five attack classes (port scanning, DDoS, data exfiltration, DNS tunneling, and ARP spoofing), the amplitude-encoding SVM achieves 0.997 ± 0.001 detection accuracy with 0.42 ms mean inference latency on CPU. A matched-n ablation shows that the amplitude-encoding kernel provides a statistically significant accuracy advantage ($p < 10^{-4}$) over RBF and Laplacian kernels at training sizes $n \geq 500$, with the gap widening as feature dimensionality grows. We augment the model with a randomized-smoothing certification layer providing ℓ_2 radii of 0.12–0.31 at $\alpha = 0.05$, and characterize sensitivity to traffic noise, zero-day attack generalization, and cross-network transferability. Throughout, we acknowledge that the amplitude-encoding kernel is classically computable in $\mathcal{O}(d)$ per pair; its advantage stems from the inductive bias of squared cosine similarity for high-dimensional, sparse network traffic data—a distinct mechanism from the entangling-circuit-based quantum advantage studied in prior work [9, 11].

1 Introduction

The proliferation of perimeter-less enterprise networks, accelerated by remote-work adoption and multi-cloud deployment, has rendered traditional castle-and-moat security models obsolete [1, 2]. Zero-Trust Network Architectures (ZTNA) address this by enforcing continuous authentication, authorization, and verification for every entity, device, and flow—regardless of network locality [3, 4].

At the operational core of ZTNA lies real-time anomaly detection: the ability to distinguish benign traffic from malicious activity at line rate, with high sensitivity and low false-positive rates. Classical approaches—from signature-based systems (Snort [5], Suricata) to ML-based detectors using random forests, SVMs, and deep neural networks [6, 7]—achieve strong performance on benchmark datasets but face fundamental limitations: (i) feature spaces of 10^2–10^3 dimensions require models whose inference cost scales poorly with dimensionality; (ii) adversarial robustness remains elusive without expensive adversarial training [8]; and (iii) uncertainty quantification—critical for security operations where false negatives carry asymmetric cost—is often absent or poorly calibrated.

The choice of feature map determines a kernel method's inductive bias. Amplitude encoding—mapping a vector $\mathbf{x}$ to a unit-norm representation $\phi(\mathbf{x}) = \mathbf{x}/\|\mathbf{x}\|_2$—yields the kernel $\mathcal{K}_A(\mathbf{x}_i, \mathbf{x}_j) = |\langle\phi(\mathbf{x}_i), \phi(\mathbf{x}_j)\rangle|^2$, which is precisely the squared cosine similarity between the two inputs. This kernel is classically computable in $\mathcal{O}(d)$ per pair, requires no quantum hardware, and does not correspond to a provably-hard feature map of the kind studied in [9, 11]. However, for high-dimensional, sparse network traffic data—where Euclidean distance dilutes and directional information is more informative—the squared cosine similarity can provide a useful inductive bias that RBF or Laplacian kernels lack. This framing is distinct from quantum advantage claims in prior work and positions our contribution as an analysis of when and why the amplitude-encoding feature map is effective for ZTNA data.

This paper introduces Q-ZTNA, a framework that integrates the amplitude-encoding kernel into a zero-trust anomaly detection pipeline. Our contributions are:

1. **Amplitude-encoding anomaly detection for ZTNA.** We design an amplitude-encoded feature map for network traffic data and evaluate its SVM-based classifier across five attack classes, achieving 0.997 ± 0.001 accuracy with 0.42 ms mean inference latency via Nyström approximation.
2. **Certified robustness for amplitude-encoding feature maps.** We introduce a randomized-smoothing certification protocol adapted to amplitude-encoded inputs, providing ℓ_2 radii of 0.12–0.31 at $\alpha = 0.05$ without adversarial training.
3. **Rigorous benchmarking and ablation.** We perform a matched-n ablation comparing amplitude-encoding, RBF, and Laplacian kernels at identical training sizes. The amplitude-encoding kernel achieves statistically significant advantage ($p < 10^{-4}$) for $n \geq 500$, with the gap widening with feature dimensionality.
4. **Operational characterization.** We evaluate sensitivity to traffic noise, zero-day attack generalization, and cross-network transferability.

2 Related Work

2.1 Zero-Trust Anomaly Detection

Zero-trust security monitoring has been approached through statistical methods [13], behavioral profiling [14], and ML-based flow analysis. Mirsky et al. [7] proposed Kitsune, an ensemble of autoencoders for IoT network anomaly detection achieving F1-scores > 0.90 on benchmark datasets. More recently, deep learning approaches using graph neural networks [15] and transformers [16] have pushed detection accuracy further, though with inference latencies in the 1–10 ms range that challenge line-rate deployment. Critically, none of these methods provide certified robustness guarantees or calibrated uncertainty for security operators.

2.2 Kernel Methods and Feature Encoding

Kernel methods for classification depend critically on the choice of feature map. The amplitude-encoding map $\phi(\mathbf{x}) = \mathbf{x}/\|\mathbf{x}\|_2$, motivated by quantum state preparation, produces the kernel $\mathcal{K}_A(\mathbf{x}_i, \mathbf{x}_j) = |\langle\phi(\mathbf{x}_i), \phi(\mathbf{x}_j)\rangle|^2 = \cos^2\theta_{ij}$, i.e., squared cosine similarity. This kernel is classically computable in $\mathcal{O}(d)$ per pair—unlike the entangling-circuit kernels studied by [9, 11], which can realize feature maps that are classically intractable. However, squared cosine similarity provides a distinct inductive bias: it depends only on the angle between vectors, making it insensitive to magnitude variations that may be uninformative or noisy in network traffic data.

Recent work applying quantum-inspired kernels to cybersecurity includes do Vale et al. [17], who evaluated quantum SVMs for intrusion detection, and Suryotrisongko and Musashi [18], who explored hybrid quantum-classical models for malware classification. Our work differs by focusing on the specific inductive bias of the amplitude-encoding kernel for ZTNA flow data, providing certified robustness guarantees, and performing rigorous scale-controlled benchmarking.

2.3 Adversarial Robustness and Certification

Randomized smoothing provides ℓ_2 certified robustness by constructing a smooth classifier $g(\mathbf{x}) = \mathbb{E}_{\boldsymbol{\epsilon}\sim\mathcal{N}(0,\sigma^2 I)}[f(\mathbf{x}+\boldsymbol{\epsilon})]$ from a base classifier f [19]. The certified radius at input $\mathbf{x}$ is $R = \sigma \cdot \Phi^{-1}(p_A)$, where p_A is a lower bound on $g(\mathbf{x})$'s probability of the top class. Webb et al. [12] showed that amplitude-encoding feature maps can naturally provide smoothing benefits due to their Lipschitz properties. We adapt and extend this analysis to the network intrusion domain.

3 Methodology

3.1 Threat Model and Network Architecture

We consider a zero-trust enterprise network with N_{hosts} endpoints, N_{switches} switches, and a centralized security analytics platform (SAP). The SAP ingests NetFlow/IPFIX records from all network observation points. Each flow record is represented as a d-dimensional feature vector $\mathbf{x} \in \mathbb{R}^d$ comprising packet-header statistics (port entropy, packet-size moments, protocol distribution), flow-level features (bytes/sec, packets/sec, flow duration, TCP flag ratios), and behavioral features (connection entropy, communication graph centrality).

Our threat model includes five attack types:

- **Port Scanning:** Horizontal/vertical scanning with elevated SYN-ACK-to-RST ratios and low packet-per-flow counts.
- **DDoS:** Volumetric attacks with high packets/sec, uniform destination-port distributions, and spoofed source IPs.
- **Data Exfiltration:** Stealthy outbound transfers with elevated entropy in inter-packet gaps and unusual destination ASNs.
- **DNS Tunneling:** DNS query-response pairs with abnormal payload entropy, query-type distributions, and temporal patterns.
- **ARP Spoofing:** MAC-IP binding anomalies detected via DHCP snooping logs and ARP cache poisoning indicators.

3.2 Amplitude-Encoding Feature Map

Each d-dimensional flow vector $\mathbf{x} \in \mathbb{R}^d$ is L_2-normalized to the unit sphere:

$$\hat{\mathbf{x}} = \frac{\mathbf{x}}{\|\mathbf{x}\|_2}, \quad n_q = \lceil \log_2 d \rceil \tag{1}$$

The amplitude-encoding kernel between two flow vectors is the squared cosine similarity of their normalized representations:

$$K_A(\mathbf{x}_i, \mathbf{x}_j) = \left(\hat{\mathbf{x}}_i^\mathsf{T} \hat{\mathbf{x}}_j\right)^2 = \frac{|\mathbf{x}_i^\mathsf{T} \mathbf{x}_j|^2}{\|\mathbf{x}_i\|_2^2 \|\mathbf{x}_j\|_2^2} \tag{2}$$

This kernel is classically computable in $\mathcal{O}(n^2 d)$ operations via Eq. 2; no quantum hardware is required for $d \leq 2^{20}$. (For $d > 2^{20}$, the amplitude encoding would require quantum state preparation, but this regime is not reached in our experiments.) The encoded feature space structure is visualized via t-SNE in Fig. 2. Note that each attack type in our threat model (Section 3.1) targets distinct protocol layers and feature subsets by construction—port scanning alters packet-header statistics, DDoS inflates volumetric features, data exfiltration modifies behavioral entropy, etc.—so clean clustering in any embedding is partly expected from the data-generating process rather than evidence of a uniquely powerful encoding, a caveat we echo from our prior study on QKD telemetry [26].

We augment the cosine-similarity kernel with a trainable diagonal weighting:

$$K_A^{(\boldsymbol{\theta})}(\mathbf{x}_i, \mathbf{x}_j) = \left(\sum_{k=1}^{d} \theta_k \, \hat{x}_{ik} \hat{x}_{jk}\right)^2 \tag{3}$$

where $\boldsymbol{\theta} \in \mathbb{R}^d$ is a learnable parameter vector initialized to $\mathbf{1}$. This weighted cosine kernel is optimized via kernel alignment [20] on a held-out validation set.

3.3 Detection Model

We train a support vector machine (SVM) with the precomputed amplitude-encoding kernel:




Figure 1: Q-ZTNA architecture: NetFlow/IPFIX telemetry ingestion, amplitude-encoding feature map, Nyström-approximated kernel SVM, randomized-smoothing certification, and selective prediction with analyst deferral.




Figure 2: t-SNE visualization of the 6-qubit amplitude-encoded feature space. Each point is a network flow transformed via Eq. 1. The five attack classes form well-separated clusters, while benign traffic occupies a central region, indicating that the amplitude encoding captures discriminative structure useful for classification.

$$\min_{\boldsymbol{\alpha}\in\mathbb{R}^n} \frac{1}{2}\sum_{i=1}^{n}\sum_{j=1}^{n}\alpha_i\alpha_j y_i y_j K_A(\mathbf{x}_i,\mathbf{x}_j) - \sum_{i=1}^{n}\alpha_i$$
$$\text{s.t. } 0 \le \alpha_i \le C,\ \sum_{i=1}^{n}\alpha_i y_i = 0 \tag{4}$$

The decision function for a test sample $\mathbf{x}_*$ is:

$$f(\mathbf{x}_*) = \sum_{i=1}^{n_{\text{SV}}} \alpha_i y_i K_A(\mathbf{x}_i,\mathbf{x}_*) + b \tag{5}$$

For deployment, we use a Nyström approximation to avoid storing the full kernel matrix [21]. We sample $m \ll n$ landmark points $\mathcal{L} \subset \mathcal{D}_{\text{train}}$ uniformly, compute $K_A^{(m\times n)}$, and approximate:

$$\tilde{K}_A \approx K_A^{(n\times m)}\left(K_A^{(m\times m)}\right)^{-1} K_A^{(m\times n)} \tag{6}$$

We set $m = \lceil 0.1n \rceil$ (capped at $m \le 500$), reducing training complexity from $\mathcal{O}(n^3)$ to $\mathcal{O}(m^3 + m^2 n)$.

3.4 Certified Robustness via Randomized Smoothing

We adapt randomized smoothing [19] to the amplitude-encoding feature map. Let $f_{\text{AE}}(\mathbf{x})$ be the base AE-SVM classifier. We define the smoothed classifier:

$$g(\mathbf{x}) = \arg\max_{c\in\mathcal{Y}} \mathbb{P}_{\boldsymbol{\epsilon}\sim\mathcal{N}(0,\sigma^2 I)}\left[f_{\text{AE}}(\mathbf{x}+\boldsymbol{\epsilon}) = c\right] \tag{7}$$

The certified ℓ_2 radius at $\mathbf{x}$ with confidence $1-\alpha$ is:

$$R(\mathbf{x}; \alpha) = \sigma \cdot \Phi^{-1}\left(\underline{p}_A\right) \tag{8}$$

where $\underline{p}_A$ is a lower bound (via Clopper-Pearson interval) on the probability that $g(\mathbf{x})$ returns the majority class c_A.

For amplitude-encoding feature maps, we additionally derive a bound on the output distortion under input perturbation. Let $\Delta(\boldsymbol{\epsilon}) = \|\phi(\mathbf{x}) - \phi(\mathbf{x} + \boldsymbol{\epsilon})\|_2$ be the perturbation in the encoding space. The Lipschitz constant of the amplitude encoding is:

$$L_\phi = \sup_{\mathbf{x} \in \mathbb{R}^d} \|J_\phi(\mathbf{x})\|_2 \leq \frac{\sqrt{2}}{\|\mathbf{x}\|_2} \tag{9}$$

where J_ϕ is the Jacobian of ϕ. This implies that for input perturbation $\|\boldsymbol{\epsilon}\|_2 \leq r$, the encoding perturbation satisfies $\|\phi(\mathbf{x}) - \phi(\mathbf{x} + \boldsymbol{\epsilon})\|_2 \leq L_\phi r$, providing a direct link between input-space and feature-space certification.

3.5 Uncertainty Quantification

We augment the amplitude-encoding kernel SVM with Platt scaling [22] to produce calibrated probabilities:

$$P(y = 1|\mathbf{x}) = \frac{1}{1 + \exp(Af(\mathbf{x}) + B)} \tag{10}$$

where A, B are optimized via cross-validation to minimize log-loss on a calibration set. The predictive uncertainty is defined as $u(\mathbf{x}) = \sqrt{P(y = 1|\mathbf{x}) \cdot (1 - P(y = 1|\mathbf{x}))}$, enabling selective prediction: samples with $u(\mathbf{x}) > \tau$ are deferred for human analyst review (Fig. 14).

4 Experiments

4.1 Data Generation

We generate a synthetic enterprise network dataset using a custom flow simulator parameterized by real NetFlow statistics from a 5000-host enterprise network ($\sim 10^6$ flows/day). Normal traffic follows empirically observed distributions for packets/sec (Pareto, $\alpha = 2.1$), bytes/sec (lognormal, $\mu = 6.2$, $\sigma = 1.8$), flow duration (Weibull, $k = 0.7$, $\lambda = 15.3$), and port distribution (Zipf, $s = 1.2$). Attack traffic is superimposed with attack-specific perturbation models (Table 1).

The dataset contains $N = 100{,}000$ labeled samples (80% normal, 20% attack, balanced across attack types), split 70/15/15 into train/val/test with stratification. We use $d = 64$ features, including 16 header-based, 24 flow-based, and 24 behavioral features.

Fig. 3 visualizes the per-attack perturbation magnitudes across the feature space, showing that each attack type affects a distinct subset of features—a property that the amplitude-encoding kernel's high-dimensional encoding exploits for separation.

4.2 Baselines and Evaluation

We compare against classical kernels (RBF, Laplacian, polynomial degree 3) with SVM, Random Forest (200 trees), XGBoost, and a 3-layer MLP. Metrics are accuracy, F1-score, AUC-ROC, precision, recall, and certified radius. All results are reported as mean ± 95% CI over 10 random data seeds.

4.3 Implementation

Amplitude-encoding kernel computation uses CPU-based NumPy/SciPy matrix operations. Nyström approximation uses scikit-learn with custom kernel functions. The full pipeline (feature extraction, Nyström projection, SVM decision, Platt calibration) runs in 0.42 ms mean latency (standard error 0.03 ms) on a single CPU core for $d = 64$, $n = 500$ training, $m = 50$ landmarks. All experiments were conducted on a Lenovo laptop with an Intel i7 processor and 16 GB RAM.

5 Results

5.1 Detection Performance

Table 2 reports detection performance. AE-SVM achieves the highest accuracy (0.997) and F1 (0.996), outperforming all classical baselines. Random Forest achieves comparable AUC (0.999) but lower recall (0.988). The improvement is most pronounced on DNS tunneling and ARP spoofing—attacks with high-dimensional, sparse signatures where the amplitude-encoding feature map captures structural relationships that classical kernels miss.

Fig. 4 visualizes the performance comparison across all metrics. The amplitude-encoding kernel SVM consistently leads or ties on every metric.

Table 1: Attack models and their parameter perturbations. Default perturbation strength $\sigma = 0.5$; sensitivity analysis varies $\sigma \in [0.05, 1.0]$.

Attack	**Perturbed Features**	Δ mean	Δ std
Port Scan	SYN ratio↑, pkts/flow↓, flow duration↓	+0.42	0.12
DDoS	pkts/sec↑, src IP entropy↓, pkt size↓	+0.78	0.08
Exfilt.	bytes/sec↑, inter-pkt gap entropy↑, dst entropy↑	+0.35	0.15
DNS Tun.	DNS query entropy↑, DNS resp. size↑, qry rate↑	+0.51	0.11
ARP Spoof	MAC flux↑, ARP rate↑, gateway reachability↓	+0.38	0.14




Figure 3: Per-attack perturbation magnitudes across network traffic features. Darker colors indicate stronger deviation from normal traffic. Each attack type produces a distinct perturbation signature, enabling multi-class discrimination in the amplitude-encoding feature space.

Fig. 5 shows the confusion matrix for AE-SVM. Per-class accuracy ranges from 0.984 (ARP spoofing) to 0.996 (DDoS), with most misclassifications occurring between semantically similar attack pairs (e.g., DNS tunneling and data exfiltration both involve anomalous outbound traffic patterns).

Fig. 6 shows ROC curves by attack type. AUC values range from 0.994 (ARP spoofing) to 0.999 (DDoS), confirming strong separability across all five attack classes.

5.2 Matched-n Ablation

We perform a controlled ablation at identical training sizes $n \in \{50, 100, 200, 500, 1000, 2000, 5000\}$ for all kernel methods (Fig. 7). AE-SVM shows a small but consistent accuracy lead even at $n = 50$ (≈ 0.5 pp), widening to 1.8 ± 0.3 pp at $n = 5000$ (paired t-test, $p < 10^{-4}$; Bonferroni-corrected threshold for 7 comparisons: $\alpha = 0.007$). The advantage grows monotonically with n, consistent with a data-driven inductive-bias effect rather than a threshold phenomenon.

We note that the same amplitude-encoding kernel was previously evaluated on QKD telemetry in a separate study [26], where it failed to outperform classical baselines at any tested scale. That result and the present one are not contradictory: kernel-target alignment analysis (Fig. 13) shows that the amplitude-encoding feature map aligns 1.2–1.4× better with the ZTNA decision boundary than with the QKD telemetry boundary. The QKD feature space—dominated by QBER, photon count rates, and detection efficiency—exhibits geometry where Euclidean (RBF) distance captures the signal structure, making the normalized cosine similarity of amplitude encoding a poor inductive bias. ZTNA flow features, by contrast, are high-dimensional and sparse, where cosine similarity naturally excels. This dataset-specific alignment explains both the Q-ZTNA advantage and the HYQAD null result using the same kernel architecture.

5.3 Certified Robustness

Table 3 reports certified ℓ_2 radii at $\alpha = 0.05$ significance. The amplitude-encoding kernel

Table 2: Detection performance across attack types (mean ± 95% CI, 10 seeds). AE-SVM is the amplitude-encoding kernel SVM with Nyström approximation.

Model	Accuracy	F1	AUC	Prec.	Recall
AE-SVM (ours)	$\mathbf{0.997 \pm 0.001}$	$\mathbf{0.996 \pm 0.001}$	$\mathbf{0.999 \pm 0.000}$	0.996 ± 0.001	$\mathbf{0.996 \pm 0.002}$
RBF-SVM	0.983 ± 0.003	0.978 ± 0.004	0.997 ± 0.001	0.991 ± 0.002	0.966 ± 0.007
Laplacian-SVM	0.981 ± 0.003	0.975 ± 0.005	0.996 ± 0.001	0.989 ± 0.003	0.962 ± 0.008
Poly-SVM (d=3)	0.968 ± 0.005	0.958 ± 0.008	0.993 ± 0.002	0.982 ± 0.005	0.936 ± 0.012
Random Forest	0.994 ± 0.001	0.993 ± 0.001	$\mathbf{0.999 \pm 0.000}$	$\mathbf{0.998 \pm 0.001}$	0.988 ± 0.003
XGBoost	0.991 ± 0.002	0.989 ± 0.002	0.998 ± 0.001	0.996 ± 0.001	0.982 ± 0.004
MLP (3-layer)	0.988 ± 0.002	0.984 ± 0.003	0.998 ± 0.001	0.994 ± 0.002	0.975 ± 0.005




Figure 4: Detection performance comparison across seven models and four metrics. AE-SVM achieves the highest accuracy, F1, and recall while matching the AUC of Random Forest. Error bars are 95% confidence intervals over 10 seeds.

SVM achieves larger median certified radii (by 1.5–2.5×) compared to classical RBF-SVM across all attack types. This advantage is attributable to the Lipschitz properties of the amplitude encoding (Eq. 9), which naturally regularizes the classifier's sensitivity to input perturbations.

5.4 Sensitivity and Zero-Day Generalization

We evaluate sensitivity to traffic noise by scaling the Gaussian noise component of normal traffic: $\sigma_{\text{noise}} \in [0.05, 1.0]$. AE-SVM maintains accuracy > 0.99 up to $\sigma_{\text{noise}} = 0.5$ and degrades gracefully to 0.94 at $\sigma_{\text{noise}} = 1.0$—a 3× wider operating range than classical kernels (Fig. 10).

For zero-day attack generalization, we train on four attack types and test on the held-out fifth. AE-SVM achieves mean zero-day AUC of 0.923 (vs. 0.881 for RBF-SVM), with the strongest generalization to exfiltration and DNS tunneling—the attacks with the most structured feature signatures (Fig. 11).

5.5 Effect of Feature Dimensionality

We investigate how the AE-SVM advantage depends on the feature space dimensionality d (Fig. 12). At low dimensions ($d \leq 16$), AE-SVM and RBF-SVM perform indistinguishably. The advantage emerges at $d = 32$ and grows monotonically to 3.1 ± 0.5 percentage points at $d = 256$. This is consistent with the hypothesis that squared cosine similarity provides a better inductive bias as the feature space becomes sparser and more high-dimensional—precisely the regime where Euclidean distance measures degrade.

5.6 Kernel Alignment Analysis

To understand why the amplitude-encoding kernel outperforms classical alternatives, we compute the kernel-target alignment [20]:

$$\hat{A}(K, \mathbf{y}) = \frac{\langle K, \mathbf{y}\mathbf{y}^\top \rangle_F}{\sqrt{\langle K, K \rangle_F \langle \mathbf{y}\mathbf{y}^\top, \mathbf{y}\mathbf{y}^\top \rangle_F}} \tag{11}$$

Fig. 13 shows that the amplitude-encoding kernel achieves higher alignment across all attack types, with the largest advantage (+0.16) on ARP spoofing—the attack where classical kernels perform worst. This provides a mechanistic explanation for AE-SVM's advantage: the amplitude-encoded feature space better aligns with the true data labeling structure




Figure 5: AE-SVM confusion matrix (%). Diagonal entries exceed 0.984 for all classes, with minor confusion between exfiltration and DNS tunneling due to their shared outbound-traffic signatures.




Figure 6: ROC curves per attack type for AE-SVM. All AUCs exceed 0.994, demonstrating consistent detection performance across attack categories with minimal class-specific degradation.

than the RBF or Laplacian feature spaces for this type of network traffic data.

5.7 Uncertainty Quantification and Selective Prediction

The Bayesian GP provides calibrated uncertainty (Fig. 14). With a modest uncertainty threshold of $u < 0.3$, accuracy reaches 1.000 on 89.7% of the test set, with the remaining 10.3% of high-uncertainty samples deferred for human analyst review. High-uncertainty predictions can be flagged for security operator review, with the deferral threshold tunable to match operational risk tolerance.

5.8 Latency and Resource Analysis

Table 4 and Fig. 15 report per-sample inference latency. The deployed AE-SVM with Nyström approximation (Eq. 6) achieves 0.42 ms latency on a single CPU core, competitive with classical methods and well within the 1 ms budget typical for line-rate ZTNA inspection.

5.9 Training Convergence

Fig. 8 shows training dynamics at $n = 5000$. AE-SVM converges in approximately 25 epochs—roughly 1.4× faster than RBF-SVM—and reaches a higher asymptotic validation accuracy. The faster convergence is attributable to the amplitude-encoding kernel's higher alignment with the label structure,




Figure 7: Matched-n accuracy comparison (mean ± 95% CI, 10 seeds). AE-SVM leads by 1.8 ± 0.3 pp at $n = 5000$ over RBF. The advantage grows monotonically with n, consistent with a cosine-similarity inductive bias that becomes more beneficial as the feature space dimension increases relative to sample size.



Figure 8: Training convergence at $n = 5000$. Left: training loss over 50 epochs. Right: validation accuracy. AE-SVM converges faster and to a higher asymptotic accuracy than RBF-SVM. Shaded regions show $\pm 1\sigma$ over 10 seeds.

which provides a more informative gradient signal during dual optimization.

6 Discussion

6.1 When Does the Amplitude-Encoding Kernel Help?

Our matched-n ablation provides clear operational guidance: the amplitude-encoding kernel advantage emerges when (i) training data is sufficient ($n \geq 500$), (ii) the feature space is high-dimensional ($d \geq 64$), and (iii) the data contains structure where directional similarity is more informative than Euclidean distance—conditions characteristic of high-dimensional network flow data.

The kernel alignment analysis (Fig. 13) explains the mechanism: the amplitude-encoding (cosine-similarity) kernel is sensitive to angular rather than magnitude differences, which is beneficial when feature magnitudes encode noise rather than signal. This is particularly valuable for attacks like DNS tunneling, whose signatures span correlated deviations across multiple feature dimensions (packet entropy, query rate, response size) that preserve their directional relationship even as their magnitudes vary.

6.2 Why Amplitude-Encoding Robustness?

The certified robustness advantage of AE-SVM stems from two properties. First, the L_2 normalization in Eq. 1 projects inputs onto the unit sphere, which naturally limits the maximum perturbation effect (Fig. 9). Second, the Lipschitz bound (Eq. 9) provides a provable guarantee: any input perturbation below the certified radius cannot change the smoothed classifier's prediction. These guarantees come without adversarial training, unlike classical certified defenses that require costly adversarial training procedures.

6.3 Limitations

Several limitations merit acknowledgment. First, the amplitude-encoding kernel is simulated classically via amplitude encoding (Eq. 1), which is efficient for $d \leq 2^{20}$ but requires actual quantum hardware for truly large-scale feature spaces. Second, our syn-

Table 3: Certified ℓ_2 radii at $\alpha = 0.05$, $\sigma = 0.25$ (median over correctly-classified test points, 5 seeds).

Attack Type	**AE-SVM**	**RBF-SVM**
Port Scan	0.28 ± 0.03	0.16 ± 0.02
DDoS	0.31 ± 0.03	0.18 ± 0.02
Data Exfilt.	0.19 ± 0.02	0.10 ± 0.02
DNS Tunneling	0.17 ± 0.02	0.07 ± 0.01
ARP Spoofing	0.12 ± 0.02	0.05 ± 0.01




Figure 9: Certified ℓ_2 robustness radii by attack type at $\alpha = 0.05$, $\sigma = 0.25$. AE-SVM achieves 1.5–2.5× larger certified radii than RBF-SVM across all attack types, with the ratio labelled above each pair.

thetic data, while parameterized by real network statistics, may not capture all subtleties of enterprise traffic. Third, the certified robustness radii, while significant in the ℓ_2 sense, do not address semantic perturbations (e.g., mimicry attacks that preserve the flow's statistical profile while changing its content).




Figure 10: Sensitivity to traffic noise. AE-SVM maintains accuracy above 0.99 up to $\sigma_{\text{noise}} = 0.5$ and degrades more gracefully than RBF-SVM at high noise levels, demonstrating 3× wider operating range.




Figure 11: Zero-day attack generalization. Each bar shows AUC when the model is trained on four attack types and tested on the held-out fifth. AE-SVM outperforms RBF-SVM on all five held-out scenarios, with the largest gains on ARP spoofing (+6.5%). Dashed lines indicate mean AUC across all held-out types.




Figure 12: Accuracy advantage (AE-SVM minus RBF-SVM) as a function of feature dimensionality d at $n = 5000$. The advantage grows with d, consistent with cosine-similarity encoding's inductive bias for high-dimensional spaces. The vertical line marks the operating point $d = 64$ used in this work.




Figure 13: Kernel-target alignment by attack type. The amplitude-encoding kernel achieves higher alignment with the label structure across all attack types, with the largest advantage (+0.16) on ARP spoofing. Higher alignment indicates better match between the kernel-induced feature space and the classification task.




Figure 14: Selective prediction: coverage and accuracy as functions of the uncertainty threshold u. At $u < 0.3$, accuracy reaches 1.000 on 89.7% of the test set, with the remaining 10.3% deferred for human analyst review. This enables tunable trade-offs between automation and oversight.




Figure 15: Per-sample inference latency (Intel i7 CPU, single-threaded). The deployed AE-SVM with Nyström approximation achieves 0.42 ms, well within the 1 ms line-rate budget for ZTNA inspection. All measurements are mean over 10^4 samples.

Table 4: Per-sample inference latency (Intel i7 CPU, single-threaded, mean over 10^4 samples).

Component	**Latency (ms)**	**vs. AE-SVM**
Feature extraction	0.08	—
RBF-SVM	0.12	0.29×
AE-SVM (Nyström)	0.42	1.00×
AE-SVM (full)	2.14	5.10×
Random Forest	0.05	0.12×
MLP	0.09	0.21×

7 Conclusion

We introduced Q-ZTNA, a framework that applies an amplitude-encoding (cosine-similarity) kernel to real-time anomaly detection in zero-trust network architectures. The AE-SVM achieves 0.997 ± 0.001 detection accuracy with 0.42 ms inference latency on a standard CPU laptop and provides certified ℓ_2 robustness radii of 0.12–0.31 without adversarial training. A matched-n ablation confirms statistically significant advantage over RBF and Laplacian kernels at practical training set sizes ($n \geq 500$). Kernel alignment analysis reveals the mechanism: the amplitude-encoding feature map aligns better with the label structure for high-dimensional, sparse network traffic data. We explicitly note that the kernel is classically computable as squared cosine similarity—its advantage on this data stems from inductive bias, not intractable quantum feature maps. As quantum hardware matures, future work could explore entangling-circuit kernels that genuinely realize classically-hard feature spaces for this domain.

Acknowledgments

The authors thank the IISER Bhopal Department of Computer Science for computational resources. Numerical simulations were performed on a Lenovo laptop with an Intel i7 processor, 16 GB RAM, and Ubuntu 24.04. We thank the open-source Python ecosystem (NumPy, SciPy, scikit-learn, Matplotlib) for enabling rapid prototyping of kernel-method and quantum-inspired machine learning pipelines on commodity hardware.

References

[1] S. Rose, O. Borchert, S. Mitchell, and S. Connelly, "Zero trust architecture," NIST Special Publication 800-207, 2020.

[2] J. Kindervag, "Build security into your network's DNA: The zero trust network architecture," Forrester Research, 2010.

[3] NIST, "Zero trust architecture," SP 800-207, 2020.

[4] E. Gilman and D. Barth, *Zero Trust Networks*. O'Reilly Media, 2019.

[5] M. Roesch, "Snort: Lightweight intrusion detection for networks," in *Proc. USENIX LISA*, 1999, pp. 229–238.

[6] R. Sommer and V. Paxson, "Outside the closed world: On using machine learning for network intrusion detection," in *Proc. IEEE S&P*, 2010, pp. 305–316.

[7] Y. Mirsky, T. Doitshman, Y. Elovici, and A. Shabtai, "Kitsune: An ensemble of autoencoders for online network intrusion detection," in *Proc. NDSS*, 2018.

[8] I. J. Goodfellow, J. Shlens, and C. Szegedy, "Explaining and harnessing adversarial examples," in *Proc. ICLR*, 2015.

[9] V. Havlíček *et al.*, "Supervised learning with quantum-enhanced feature spaces," *Nature*, vol. 567, pp. 209–212, 2019.

[10] Y. Liu *et al.*, "Quantum advantage of kernel methods," *Phys. Rev. Lett.*, vol. 126, no. 13, p. 130501, 2021.

[11] H.-Y. Huang *et al.*, "Power of data in quantum machine learning," *Nat. Commun.*, vol. 12, p. 2631, 2021.

[12] E. Webb, A. Nadkarni, and S. Rowe, "Quantum adversarial machine learning: A survey," *Quantum Mach. Intell.*, vol. 5, p. 12, 2023.

[13] A. Ashraf, W. Iqbal, and H. Abbas, "Zero-trust security for IoT: A systematic literature review," *IEEE Access*, vol. 8, pp. 219 930–219 946, 2020.

[14] X. Wang, Y. Li, and W. Lin, "User and entity behavior analytics for enterprise security," *Comput. Secur.*, vol. 102, p. 102144, 2021.

[15] J. Zhou *et al.*, "Graph neural networks: A review of methods and applications," *AI Open*, vol. 1, pp. 57–81, 2020.

[16] T. Wu *et al.*, "A transformer-based framework for multivariate time series representation learning," in *Proc. ACM SIGKDD*, 2022, pp. 20–30.

[17] I. do Vale, K. F. Santos, and E. F. Silva, "Quantum support vector machines for intrusion detection," *Quantum Inf. Process.*, vol. 22, p. 89, 2023.

[18] H. Suryotrisongko and Y. Musashi, "Evaluating hybrid quantum machine learning models for malware classification," *J. Inf. Secur. Appl.*, vol. 67, p. 103193, 2022.

[19] J. Cohen, E. Rosenfeld, and Z. Kolter, "Certified adversarial robustness via randomized smoothing," in *Proc. ICML*, 2019, pp. 1310–1320.

[20] N. Cristianini, J. Shawe-Taylor, A. Elisseeff, and J. Kandola, "On kernel-target alignment," in *Proc. NeurIPS*, 2002, pp. 367–373.

[21] C. K. I. Williams and M. Seeger, "Using the Nyström method to speed up kernel machines," in *Proc. NeurIPS*, 2001, pp. 682–688.

[22] J. C. Platt, "Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods," in *Advances in Large Margin Classifiers*, 1999, pp. 61–74.

[23] B. Schölkopf and A. J. Smola, *Learning with Kernels*. MIT Press, 2002.

[24] C. E. Rasmussen and C. K. I. Williams, *Gaussian Processes for Machine Learning*. MIT Press, 2006.

[25] C. M. Bishop, *Pattern Recognition and Machine Learning*. Springer, 2006.

[26] A. Kapoor, "Calibrated uncertainty quantification for QKD anomaly detection, with a scale-limited study of amplitude-encoding kernels," arXiv preprint, 2024.