

# Task1

March 25, 2025

Task 1:Quantum Computing part

In this there are 2 subtask we have to perform

We will be using cirq library for implementation

We will start by importing cirq and numpy

```
[1]: import cirq
import numpy as np
```

First Subtask

First create 5 qubits using LineQubit which will create 5 qubits ie q0, q1,q2,q3,q4

```
[2]: qubits = [cirq.LineQubit(i) for i in range(5)]
```

Now we will first create a circuit and then append all the 5 qubits in the circuit by applying Hadamard gate to each qubit

```
[3]: circuit = cirq.Circuit()

circuit.append([cirq.H(q) for q in qubits])
```

Now we have to apply controlled not (CNOT) on (0,1), (1,2), (2,3), (3,4)

```
[4]: circuit.append([cirq.CNOT(qubits[i], qubits[i+1]) for i in range(4)])
```

Now we will swap q0 and q4 using SWAP gate

```
[5]: circuit.append(cirq.SWAP(qubits[0], qubits[4]))
```

Now we have to rotate X any qubit lets say q1 by  $\pi/2$

```
[6]: circuit.append(cirq.rx(np.pi/2)(qubits[1]))
```

Plot the circuit

```
[7]: print("Circuit diagram:")
print(circuit)
```

Circuit diagram:

0: H @ x


```

1:  H X @ Rx(0.5)
2:  H   X @
3:  H     X   @
4:  H       X ×

```

For better visualization we can use SVGcircuits

```
[8]: from cirq.contrib.svg import SVGCircuit
from IPython.display import display, SVG
display(SVGCircuit(circuit))
```



## Second Subtask

We will be using cirq library for this task

In this task we will be using 5 qubits ie 4 normal qubits and one ancilla qubit

### 0.0.1 Role of ancilla qubit:

The ancilla qubit is used as a control mechanism that is used to check similarity between quantum states without measuring them. If we measure the qubits it would collapse their superposition.

## 0.1 Steps of the Swap Test

### 0.1.1 1. Initialize the Ancilla in $|0\rangle$

- The ancilla qubit starts in  $|0\rangle$ .

### 0.1.2 2. Apply Hadamard (H) on the Ancilla

- This puts the ancilla in an **equal superposition**:

$$|+\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}$$

### 0.1.3 3. Controlled SWAP (CSWAP) Operations

- The ancilla controls the **swap** of qubit pairs (q1, q2) and (q3, q4).
- If the ancilla is **|0**, nothing happens.
- If the ancilla is **|1**, the qubits swap.
- This **entangles the ancilla** with the similarity of the states.

### 0.1.4 4. Apply Hadamard Again to the Ancilla

- This transforms the ancilla back to a **new superposition** based on how much the states differ.

### 0.1.5 5. Measure the Ancilla

- **If the ancilla is |0**, the states are **similar** (higher probability).
- **If the ancilla is |1**, the states are **different** (higher probability).

Create 5 qubits

```
[9]: qubits = [cirq.LineQubit(i) for i in range(5)]
      q1,q2,q3,q4,ancilla = qubits
```

Create a empty circuit

```
[10]: circuit = cirq.Circuit()
```

Apply hadmard gate to q1,q3,q4 and rotate q2 x by pi/3

```
[11]: circuit.append(cirq.H(q1))
      circuit.append(cirq.rx(np.pi/3)(q2))
      circuit.append([cirq.H(q3), cirq.H(q4)])
```

Add the ancilla qubit to the circuit for swap test

```
[12]: circuit.append(cirq.H(ancilla))
```

Use controlled swap gate (CSWAP) for q1,q2 and q3,q4

```
[13]: circuit.append(cirq.CSWAP(ancilla, q1, q2))
      circuit.append(cirq.CSWAP(ancilla, q3, q4))
```

Finalizing the swap test we have to apply H gate on ancilla

```
[14]: circuit.append(cirq.H(ancilla))
```

Print the circuit

```
[15]: print("Circuit diagram:")
      print(circuit)
```

Circuit diagram:

0: H x

1: Rx(0.333) x


2: H x

3: H x

4: H @ @ H

For better visualization

```
[16]: display(SVGCircuit(circuit))
```



```
[ ]:
```