



Pulp – Software Repository Management

A brief introduction

Arnold Bechtoldt
Karlsruhe, 12.12.14

- ▶ IT Systems Engineer at inovex GmbH
- ▶ Small to large Open Source Datacenter Management solutions
- ▶ High available web-based application services
- ▶ Contributing to various Open Source projects


Introduction

Preparing Pulp

Using Pulp

Scaling &
High Availability

- ▶ Provides a platform for RPM repository management
- ▶ Built on top of httpd, Celery (task scheduling) and Qpid/ RabbitMQ (message queue)
- ▶ Provides a RESTful API and is part of Red Hat Satellite
- ▶ Want to setup Pulp with Katello? Check the slides “Katello / Pulp / Candlepin - OSD CM: Repository Management” of Jürgen Brunk at inovex.de



1. Setup a plain CentOS 7 system (e.g. using Vagrant/ VirtualBox)
2. Set correct time settings
3. Disable firewall and SELinux (in your lab only 😊)
4. Install EPEL & Pulp RPM repository sources in `/etc/yum.repos.d/`
5. Verify repo connectivity with *yum repolist*

1. Install mongoDB and Qpid message broker packages
2. Configure and setup mongoDB and Qpid
3. Install Pulp server and Pulp admin packages
4. Verify mongoDB and Qpid are running
5. Stop httpd and migrate Pulp mongoDB with *pulp-manage-db*
6. Start pulp_workers, httpd, pulp_celerybeat and pulp_resource_manager

7. Verify all services are running
8. Disable SSL verification in Pulp admin configuration (in your lab only 😊)
9. Verify login works with admin:admin using *pulp-admin*

1. Create a repository:

```
pulp-admin rpm repo create \  
    --repo-id=foreman \  
    --feed=http://yum.theforeman.org/releases/1.1/el6/x86_64/ \  
    --relative-url=foreman/ \  
    --serve-http=true \  
    --serve-https=true
```

2. Sync from upstream:

```
pulp-admin rpm repo sync run \  
    --repo-id=foreman
```

3. Verify existence: *<http://127.0.0.1/pulp/repos/foreman/>*

1. Create a new repository:

```
pulp-admin rpm repo create \  
    --repo-id=mycustomrepo \  
    --relative-url=custom/repo/ \  
    --serve-http=true \  
    --serve-https=true
```

2. Start initial publish:

```
pulp-admin rpm repo publish run \  
    --repo-id=mycustomrepo
```

3. Verify existence: <http://127.0.0.1/pulp/repos/custom/repo/>

4. Prepare packages to upload:

```
yum install --downloadonly --downloadaddir=/var/tmp/saltpkgs/ salt-minion
```

5. Upload packages:

```
pulp-admin rpm repo uploads rpm \  
    --repo-id=mycustomrepo \  
    --dir=/var/tmp/saltpkgs/
```

6. Publish uploaded packages:

```
pulp-admin rpm repo publish run \  
    --repo-id=mycustomrepo
```

7. Verify existence of new packages: *<http://127.0.0.1/pulp/repos/custom/repo/>*

1. List repositories with their names only:

```
pulp-admin repo list -s
```

2. List repositories with details:

```
pulp-admin repo list -s
```

3. List repositories with even more details:

```
pulp-admin repo list --details
```

1. Search for RPM packages:

```
pulp-admin rpm repo content rpm \  
    --repo-id=mycustomrepo \  
    --match='name=salt.*'
```

2. Copy RPM packages to another repo:

```
pulp-admin rpm repo copy rpm \  
    --from-repo-id=foreman \  
    --to-repo-id=mycustomrepo \  
    --match='name=foreman-libvirt.*'
```

3. Publish new packages:

```
pulp-admin rpm repo publish run \  
    --repo-id=mycustomrepo
```

4. Remove RPM packages:

```
pulp-admin rpm repo remove rpm \  
    --repo-id=mycustomrepo \  
    --match='name=foreman-libvirt.*'
```

5. Publish changes:

```
pulp-admin rpm repo publish run \  
    --repo-id=mycustomrepo
```

6. Verify absence of removed packages: <http://127.0.0.1/pulp/repos/custom/repo/>

- ▶ Pulp workers need several Gigabytes of memory to collect & work with metadata
- ▶ Pulp API, resource manager, task scheduler and message queue are lightweight
- ▶ Setting up a redundant mongoDB replica set is a good idea
- ▶ Deploy additional Pulp worker systems to distribute work load of long running tasks (Sync/ Publish)
- ▶ HTTP(S) loadbalancing in front of Apache httpd (delivery/ API)
- ▶ Caching of static content units (RPM packages) *could* be useful

We are hiring!

inovex.de



exciting projects • great technologies • nice colleagues • cool offices

We have excellent job offers in **Karlsruhe**, **Cologne**, **Munich** and **Pforzheim**!

Thank You!

Questions?



Contact

Arnold Bechtoldt
IT Engineering & Operations

inovex GmbH
Office Karlsruhe
Ludwig-Erhard-Allee 6
D-76139 Karlsruhe

arnold.bechtoldt@inovex.de

