



Global Trigger firmware Specification for MP7 platform for Upgrade Phase I

Herbert Bergauer, Babak Rahbaran, Johannes Wittmann
Email: herbert.bergauer@oeaw.ac.at

Institute of High Energy Physics (HEPHY)

<http://www.hephy.at>
<http://globaltrigger.hephy.at>

September 9, 2020

Revision History

Doc Rev	Description of Change	Revision Date
5.1	Inserted text for new muon structure in sections 3.2.2, 3.4.8.1 and 3.4.9.2. Added subsections in section 3.5	2020/08/04
5.0	Additional text in section 3.4.9.2.6.	2020/05/25
4.9	Inserted text in section 3.4.3.2.2 for Calorimeter Overlap Remover conditions and 3.4.9.2.6 for Calo Calo Overlap Remover Correlation conditions.	2020/04/16
4.8	Updated text in sections 3.4.3, 3.4.8 and 3.4.9 for changes which have been done for GTL VHDL version 1.8.0 (module names without version number, "five eta cuts").	2019/08/13
4.7	Inserted "Asymmetry" and "Centrality" of "Energy sums" (GTL VHDL version 1.6.0). Therefore updated sections 3.1, 3.2.1, 3.4.4 added section "Centrality condition" 3.4.7 and updated Table 2	2018/08/13
4.6	Updated text in section "Global Trigger Logic" (3) according to firmware version v1.5.0 of gtl_module.vhd	2018/02/21
4.5	Updated text in section "Framework" (2) according to firmware version v1.2.3 of frame.vhd	2018/01/19
4.4	New "icons" ET_{miss}^{HF} and HT_{miss}^{HF} in Table 2 and Section 3. Updated glossary (see Section 6)	2016/11/11
4.3	Updated table " μ FDL register map" (38) and section "Register map" (4.4.1.1). Moved "List of Tables" and "List of Figures" to the end of document. Inserted link to "Scales for inputs to μ GT" (3.3). Moved section "Software reset" to section "Framework" as subsection (2.7). Removed empty sections "IPBus", "Firmware Configuration" and "Bibliography"	2016/11/03
4.2	Updated sections "Calo-Layer2 optical interfaces" (3.2.1) and "Energy sum quantities conditions" (3.4.4) for towercount trigger bits. Inserted section "Towercount condition" (3.4.6)	2016/10/25
4.1	Updated section "Calo-Layer2 optical interfaces" (3.2.1) for new energy sum quantities and minimum bias trigger bits. Updated sections "Firmware" (1), "Framework" (2) and "Final Desicion Logic" (4).	2016/06/09
4.0	Updated Text in section "Muon Muon Correlation condition module" (3.4.9.2.3).	2016/01/15
3.9	Removed "Double objects requirements condition with spatial correlation", because not used anymore in the future, replaced by Correlation conditions (see sections 3.4.3.2 and 3.4.8.3.	2016/01/08

Doc Rev	Description of Change	Revision Date
3.8	Minor changes in text and updated Figure 11.	2016/01/08
3.7	Changed colour in Figure 12 and updated text for correlation conditions (see section 3.4.9).	2016/01/07
3.6	Updated Figures 11 and 10 and text 3.4.9.2.1.	2015/12/21
3.5	Inserted drawing of VHDL structure of cuts for correlation conditions (see Figure 13).	2015/11/18
3.4	Updated muon η ranges (Table 14) and inserted correlation conditions (see section 3.4.9). Created scheme for conversion of calorimeter η and φ to muon scale for calo-muon-correlation conditions (see Figure 14).	2015/11/17
3.3	Added Text in sections (3.4.3.2.4) and (3.4.8.3.3).	2015/10/08
3.2	Updated Text in section "Final Desicion Logic" (4).	2015/10/06
3.1	Updated Figure 15 and Tables 38, 12 and 24. Remaned section "Calorimeter conditions module - version 2" to "Calorimeter conditions module - version 3" (see 3.4.3.2), section "Muon conditions module" to "Muon conditions module - version 2" and section "Muon comparators module" to "Muon comparators module - version 2" (see 3.4.8.3)	2015/10/02
3.0	Updated text and tables of η ranges for Calorimeter objects (see 3.4.3.1).	2015/09/22
2.9	Renewed Figures in GTL and FDL (see Figure 9, 10 and 11) and FDL(see Figure 15 and 16). Added register bits description of FDL Register map (see section 4.4.1.1).	2015/09/16
2.8	Updated text, tables and listings of section "VHDL-Templates for VHDL-Producer" (see 3.5).	2015/09/15
2.7	Corrected calculation of muon η step width (see 3.4.8.1).	2015/09/10
2.6	Edited text in Tables 12, 23 and 24.	2015/08/28
2.5	Updated definition of η ranges for Calorimeter objects and Muon objects (3.4.3.1 and 3.4.8.1).	2015/08/20
2.4	Added section Calo Muon Correlation condition (3.4.9.2.2).	2015/08/19
2.3	Added section "Register map" (4.4.1.1) for μ FDL.	2015/06/26
2.2	Updated figures (9, 10 and 11) for GTL and edited section "Correlation conditions" (see 3.4.9).	2015/05/08
2.1	Added tables for calorimeter isolation-bits and for muon quality- and isolation-bits definition (10, 16 and 18). Edited section glossary (6) and acronyms.	2015/05/07
2.0	Added text for "Energy sum conditions" (3.4.4) and updated chapters for "Calorimeter conditions" for version 2. Inserted isolation bits for electron/ γ and tau objects (3.4.3.1).	2015/05/06
1.9	Minor changes "Demux Lane Data" (see 2.2) and "Muon data" (see 3.4.8.1).	2014/11/06

Doc Rev	Description of Change	Revision Date
1.8	Edited Section "Energy sum quantities conditions" (see 3.4.4).	2014/10/08
1.7	Added sections "Configuration of optical connections" (2.1), "Demux Lane Data" (2.2) and "Lane Mapping Process" (2.3) to framework. Removed tables of optical interfaces from gtl and referenced to tables in framework.	2014/10/07
1.6	Minor changes in "Calorimeter conditions" (3.4.3) and "Muon conditions" (3.4.8)	2014/07/01
1.5	Updated with minor changes in "Muon conditions" (3.4.8)	2014/06/17
1.4	Fixed bug in Figure 12	2014/04/30
1.3	Updated section "Muon conditions" (3.4.8)	2014/04/22
1.2	Removed section "Muon charge module" and added new section "Muon charge correlation module" (see 3.4.8.2). Edited text in section and subsections "Muon conditions definition" (see 3.4.8.3)	2014/04/15
1.1	Changed Figure 12 and minor changes in text for anti-clockwise behaviour in φ	2014/04/04
1.0	Added definition for "calorimeter conditions over bx", see section ?? .	2014/03/12
0.9	Changed text of condition description in subsections 3.4.3.2 and 3.4.8.3	2014/02/12
0.8	Updated calorimeter data structure in 3.2.1	2013/12/03
0.7	Updated muon data structure in 3.2.2	2013/12/02
0.6	Moved decription of VHDL templates for TME to 3.5	2013/11/18
0.5	Subsection 3.2 added to section 3	2013/11/11
0.4	GTL and FDL firmware implemented for new data structure (GTL firmware version v1.0.0 [fix part of GTL], FDL firmware version v1.0.0)	2013/11/06
0.3	New framework implementation based on new object types definition. Additionally, the ROP is implemented based on production requirements	2013/10/13
0.2	First framework implementation + ROP	2012/07/01
0.1	Document created	2012/02/22

Contents

List of Figures	8
List of Tables	9
1 Firmware overview	11
1.1 Package: lhc_data_pkg	12
2 Framework	13
2.1 Configuration of optical connections	14
2.2 Demux Lane Data	14
2.3 Lane Mapping Process	14
2.3.1 Implementation	14
2.4 Delay Manager	14
2.4.1 Implementation	14
2.5 SIM and SPY Memory	18
2.5.1 Implementation	18
2.5.1.1 SPY Trigger	19
2.5.1.2 SIM/SPY memory	19
2.5.1.3 SPY memory II	22
2.5.1.4 SPY memory III	22
2.5.2 Interface Specification	23
2.6 TCM	23
2.6.1 Counter Overview	23
2.6.2 Bunch Crossing Number and counters derived from it	23
2.6.3 Special counter: bx_nr_d_fdl	24
2.6.4 Counters derived from l1a	24
2.6.5 Errors	24
2.6.6 SW-Registers	25
2.6.7 Hardware Test	29
2.7 Software Reset	29

3	Global Trigger Logic	30
3.1	μ GTL Interface	30
3.2	Definition of optical interfaces	31
3.2.1	Calo-Layer2 optical interfaces	31
3.2.2	Global Muon Trigger optical interfaces	32
3.3	Implementation in firmware	33
3.3.1	Top-of-hierarchy module	34
3.3.2	Package module	35
3.4	μ GTL structure	36
3.4.1	Data $\pm 2bx$	36
3.4.2	Calculation of differences in η and φ	36
3.4.3	Calorimeter conditions	37
3.4.3.1	Calorimeter data	37
3.4.3.2	Calorimeter conditions definition	41
3.4.3.2.1	Calorimeter conditions module	42
3.4.3.2.2	Calorimeter Overlap Remover conditions module	45
3.4.3.2.3	Calorimeter conditions module - template for VHDL-Producer	45
3.4.3.2.4	Calorimeter comparators module	45
3.4.4	Energy sum quantities conditions	48
3.4.4.1	Energy sum quantities data	48
3.4.4.2	Energy sum quantities conditions module (including Asymmetry conditions)	49
3.4.4.3	Energy sum quantities conditions module - template for VHDL-Producer	51
3.4.5	Minimum bias trigger conditions	51
3.4.6	Towercount condition	51
3.4.7	Centrality condition	51
3.4.8	Muon conditions	51
3.4.8.1	Muon data	51
3.4.8.2	Muon charge correlation module	55
3.4.8.3	Muon conditions definition	57
3.4.8.3.1	Muon conditions module	58
3.4.8.3.2	Muon conditions module - template for VHDL-Producer	63

3.4.8.3.3	Muon comparators module	63
3.4.9	Correlation conditions	65
3.4.9.1	Calculation of cuts	65
3.4.9.1.1	ΔR calculation	66
3.4.9.1.2	Invariant mass calculation	66
3.4.9.1.3	Transverse mass calculation	66
3.4.9.1.4	Two-body pt calculation	66
3.4.9.2	Correlation condition modules	66
3.4.9.2.1	Calo Calo Correlation condition module	67
3.4.9.2.2	Calo Muon Correlation condition module	74
3.4.9.2.3	Muon Muon Correlation condition module	82
3.4.9.2.4	Calo Esums Correlation condition module	90
3.4.9.2.5	Muon Esums Correlation condition module	95
3.4.9.2.6	Calo Calo Overlap Remover Correlation condition module	100
3.4.10	External Conditions	100
3.4.11	Algorithms logic	100
3.5	VHDL-Templates for VHDL-Producer	101
3.5.1	Calorimeter conditions - template for VHDL-Producer	101
3.5.2	Energy sum quantities conditions - template for VHDL-Producer	104
3.5.3	Muon conditions - template for VHDL-Producer	105
3.5.4	Calo Calo Correlation condition - template for VHDL-Producer	108
3.5.5	Calo Muon Correlation condition - template for VHDL-Producer	111
3.5.6	Muon Muon Correlation condition - template for VHDL-Producer	114
3.5.7	Calo Esums Correlation condition - template for VHDL-Producer	116
3.5.8	Muon Esums Correlation condition - template for VHDL-Producer	118
4	Final Desicion Logic	121
4.1	μ FDL Interface	121
4.2	MP7 Final-OR hardware solution	122
4.3	Data flow	122
4.4	Main parts	123
4.4.1	Registers and memories	124
4.4.1.1	Register map	124

4.4.2	Algo-bx-masks	133
4.4.3	Rate-counters	133
4.4.4	Prescalers	133
4.4.5	Finor-masks	133
4.4.6	Veto-masks	133
4.4.7	Finor	134
4.5	Implementation in firmware	134
5	Readout-Process	136
6	Glossary	137
	Bibliography	139
	Index	139

List of Figures

1	μ GT firmware. It consists of framework, SERDES module, ALGORITHM LOGIC, ROP and IPBus. The Readout-Process is the module, which is responsible to send the Readout-record to AMC13.	11
2	System architecture overview	13
3	Delay Manager: delay_element	17
4	Memory subsystem	19
5	start of the bunch crossing number with the first bres_d	24
6	normal operation of the bunch crossing number	24
7	set of the software register err_det when bc_res_d is not asserted correctly .	25
8	reset of the software register err_det when err_det_reset_event toggles . . .	25
9	μ GTL firmware	30
10	VHDL file generation by VHDL Producer	33
11	Scheme of μ GTL pipeline structure	36
12	Setting the limits for "window"-comparators for φ	47
13	VHDL structure of cuts for correlation conditions	65
14	Conversion of calorimeter η and φ to muon scales	75
15	μ FDL firmware v1.0.1	121
16	μ FDL pipeline v1.0.1	122

List of Tables

2	Configuration of optical connections	15
3	Current lane mapping	16
4	delay manager registers	18
5	counters of the timer counter manager	23
6	scripts for testing the tcm	29
7	η scale of electron/ γ and tau	39
8	η scale of jet	39
9	φ scale of calorimeter objects	39
10	Definition of e/ γ and tau isolation bits	40
11	Explanation of Listing 4	44
12	LUT contents for isolation comparison of electron/ γ and tau objects	46
13	Explanation of Listing 6	50
14	η scale of muon objects	53
15	φ scale of muon objects	53
16	Definition of muon quality bits	54
17	Definition of muon isolation bits	54
18	Definition of muon impact parameter bits	54
19	Muon charge correlation - Double Muon	55
20	Muon charge correlation - Triple Muon	55
21	Muon charge correlation - Quad Muon	56
22	Explanation of Listing 7	61
22	Explanation of Listing 7	62
23	LUT contents for quality comparison of muon objects	64
24	LUT contents for isolation comparison of muon objects	64
25	Explanation of Listing 8	71
25	Explanation of Listing 8	72
25	Explanation of Listing 8	73
25	Explanation of Listing 8	74
26	Explanation of Listing 9	79
26	Explanation of Listing 9	80
26	Explanation of Listing 9	81

26	Explanation of Listing 9	82
27	Explanation of Listing 10	86
27	Explanation of Listing 10	87
27	Explanation of Listing 10	88
27	Explanation of Listing 10	89
27	Explanation of Listing 10	90
28	Explanation of Listing 11	93
28	Explanation of Listing 11	94
29	Explanation of Listing 10	98
29	Explanation of Listing 10	99
29	Explanation of Listing 10	100
30	Explanation of Listing 13	103
31	Explanation of Listing 14	104
32	Explanation of Listing 15	107
33	Explanation of Listing 16	109
33	Explanation of Listing 16	110
34	Explanation of Listing 17	112
34	Explanation of Listing 17	113
35	Explanation of Listing 18	115
35	Explanation of Listing 18	116
36	Explanation of Listing 16	117
36	Explanation of Listing 16	118
37	Explanation of Listing 17	119
37	Explanation of Listing 17	120
38	μ FDL register map	124
38	μ FDL register map	125
38	μ FDL register map	126

1 Firmware overview

The figure 1 shows the architecture of μ GT. It consists of framework , SERDES, Tx, IPBus, Readout-Process and the ALGORITHM LOGIC, which it consists of the following modules:

1. μ GTL
2. μ FDL

Readout-Process is responsible sending the Read-out record over GbE to AMC13, which will be sent it from there to DAQ.

The IPBus system allows the control of hardware via a ‘virtual bus’, using a standard IP-over-gigabit-Ethernet network connection (section [??]).




Figure 1: μ GT firmware. It consists of framework, SERDES module, ALGORITHM LOGIC, ROP and IPBus. The Readout-Process is the module, which is responsible to send the Readout-record to AMC13.

Moreover the Tx_AMC13 should be instantiate for sending the readout-record to AMC13. This part is outside of framework functionality.

1.1 Package: `lh_data_pkg`

The VHDL record `lh_data_t` (shown in Listing 1) is used as a container for all object streams processed by the system. It is declared in the VHDL package `lh_data_pkg`. For debugging and simulation purposes a second package (`lh_data_debug_util_pkg`) is created which contains functions to convert the `lh_data_t` to a hexadecimal string representation and vice versa. The testbench of the design uses this functions to load the contents of the SIM memory from a file.

Listing 1: `lh_data_t` record specification

```
type lh_data_t is record
    muon : muon_array_t;
    eg : eg_array_t;
    tau : tau_array_t;
    jet : jet_array_t;
    ett : std_logic_vector(ETT_DATA_WIDTH-1 downto 0);
    ht : std_logic_vector(HT_DATA_WIDTH-1 downto 0);
    etm : std_logic_vector(ETM_DATA_WIDTH-1 downto 0);
    htm : std_logic_vector(HTM_DATA_WIDTH-1 downto 0);
    etmhf : std_logic_vector(ETMHF_DATA_WIDTH-1 downto 0);
    htmhf : std_logic_vector(HTMHF_DATA_WIDTH-1 downto 0);
    link_11_fr_0_data : std_logic_vector(LINK_11_FR_0_WIDTH-1 downto
        0);
    link_11_fr_1_data : std_logic_vector(LINK_11_FR_1_WIDTH-1 downto
        0);
    link_11_fr_2_data : std_logic_vector(LINK_11_FR_2_WIDTH-1 downto
        0);
    link_11_fr_3_data : std_logic_vector(LINK_11_FR_3_WIDTH-1 downto
        0);
    link_11_fr_4_data : std_logic_vector(LINK_11_FR_4_WIDTH-1 downto
        0);
    link_11_fr_5_data : std_logic_vector(LINK_11_FR_5_WIDTH-1 downto
        0);
    external_conditions : std_logic_vector(
        EXTERNAL_CONDITIONS_DATA_WIDTH-1 downto 0);
end record;
```

2 Framework

Remark:

with frame v1.2.3 "Delay Manager" (dm.vhd) and "Data Source Multiplexer" (dsmux.vhd) are removed because these features were never used in production system, only for tests. Simmem data not useable anymore, because of removed dsmux. The reason of removing is to get more available resources.

Figure 2 shows the basic components the framework together with Readout-Process.




Figure 2: System architecture overview

The central data type of the framework is shown in Listing 1 (see Section 1.1 for details). In the current configuration it comprises 2304 bits (288 Bytes). Data from the GTH interfaces is demultiplexed (from 240 MHz clock domain to LHC clock domain, see Demux Lane Data 2.2) and mapped to this data type in the LMP (Lane Mapping Process). It is also used as input and output type for the SIM/SPY I memory. The DM (Delay Manager) takes the output of the LMP and applies software configurable delays to the the different object streams (e.g. muon data, jet, tau etc.) in the `lhc_data_t` to produce a consistent output (also regarding to the `bcres` signal). The software configurable multiplexer DSMUX (Data Source Multiplexer) is used to select which data stream is used as input for the processing elements (trigger logic). The output of the DSMUX is routed to the GTL (Global Trigger Logic) and ROP (Read Out Process) and can optionally be stored in the SPY I memory.

2.1 Configuration of optical connections

The configuration of the optical connections to Calo-Layer2 is (currently) done as described in Table 2, where frame means the 32 bits data (240 MHz) within a LHC clock period.

2.2 Demux Lane Data

Data from GTH interfaces is in the 240 MHz clock domain. The demultiplexing to the LHC clock domain (about 40 MHz) is done in `demux_lane_data.vhd`, which is instantiated in `frame.vhd` as often as lanes are used (currently 16 lanes are used).

2.3 Lane Mapping Process

In the Lane Mapping Process module data from the lanes are mapped to objects structure defined in `lhc_data_pkg.vhd`.

2.3.1 Implementation

Currently lane mapping is "fixed" in `lmp.vhd` module, see Table 3

2.4 Delay Manager

Remark:

with frame v1.2.3 "Delay Manager" (`dm.vhd`) and "Data Source Multiplexer" (`dsmux.vhd`) is removed because these features were never used in production system, only for tests. The reason of removing is to get more available resources.

The Delay Manager is responsible for creating a delayed version of the `lhc_data` and the `bcrs` signal on its input. For this purpose it uses an internal memory to record the history of the input signals.

2.4.1 Implementation

The DM is basically a reimplementation of the concept of the last design. The reimplementation was necessary because the new framework version uses the register bank for software registers and the old DM was not flexible enough to handle the `lhc_data_t` introduced in the new framework.

The DM instantiates one `delay_element` for every object type defined in the `lhc_data_t` (e.g. `muon`, `eg`, etc.). The `delay_element` uses RAM blocks to implement the delay line. However, for the delays 0 and 1 this memory can not be used (write latency) and must be bypassed (Figure 3).

Table 2: Configuration of optical connections

link	frame					
	0	1	2	3	4	5
0	reserved	reserved	muon obj. 0 [0..31]	muon obj. 0 [32..63]	muon obj. 1 [0..31]	muon obj. 1 [32..63]
1	reserved	reserved	muon obj. 2 [0..31]	muon obj. 2 [32..63]	muon obj. 3 [0..31]	muon obj. 3 [32..63]
2	reserved	reserved	muon obj. 4 [0..31]	muon obj. 4 [32..63]	muon obj. 5 [0..31]	muon obj. 5 [32..63]
3	reserved	reserved	muon obj. 6 [0..31]	muon obj. 6 [32..63]	muon obj. 7 [0..31]	muon obj. 7 [32..63]
4	electron/ γ obj. 0	electron/ γ obj. 1	electron/ γ obj. 2	electron/ γ obj. 3	electron/ γ obj. 4	electron/ γ obj. 5
5	electron/ γ obj. 6	electron/ γ obj. 7	electron/ γ obj. 8	electron/ γ obj. 9	electron/ γ obj. 10	electron/ γ obj. 11
6	jet obj. 0	jet obj. 1	jet obj. 2	jet obj. 3	jet obj. 4	jet obj. 5
7	jet obj. 6	jet obj. 7	jet obj. 8	jet obj. 9	jet obj. 10	jet obj. 11
8	tau obj. 0	tau obj. 1	tau obj. 2	tau obj. 3	tau obj. 4	tau obj. 5
9	tau obj. 6	tau obj. 7	tau obj. 8	tau obj. 9	tau obj. 10	tau obj. 11
10	ET ETTEM MBT0HFP	HT TOWER- COUNT MBT0HFM	ET_{miss} ASYMET MBT1HFP	HT_{miss} ASYMHT MBT1HFM	$ET_{\text{miss}}^{\text{HF}}$ ASYM- ETHF CENT[3:0]	$HT_{\text{miss}}^{\text{HF}}$ ASYM- HTHF CENT[7:4]
11	free	free	free	free	free	free
12	external- conditions [0..31]	external- conditions [32..63]	reserved	reserved	reserved	reserved
13	external- conditions [64..95]	external- conditions [96..127]	reserved	reserved	reserved	reserved
14	external- conditions [128..159]	external- conditions [160..191]	reserved	reserved	reserved	reserved
15	external- conditions [192..223]	external- conditions [224..255]	reserved	reserved	reserved	reserved

Table 3: Current lane mapping

lane	objects
0	muon objects 0..1
1	muon objects 2..3
2	muon objects 4..5
3	muon objects 6..7
4	electron/ γ objects 0..5
5	electron/ γ objects 6..11
6	jet object 0..5
7	jet object 6..11
8	tau object 0..5
9	tau object 6..11
10	energy sum quantities (incl. minimum bias trigger bits and towercounts)
11	n/a (currently not used)
12	external-conditions [0..63]
13	external-conditions [64..127]
14	external-conditions [128..191]
15	external-conditions [192..255]



Figure 3: Delay Manager: delay_element

The Implementation of the DM is very generic because it makes extensive use of the constants provided by the `lhc_data_pkg`. The `lhc_data_i` input signal is converted into a `std_logic_vector`. The constants `LHC_DATA_SLV_START_INDICES` and `LHC_DATA_SLV_OBJECT_WIDTH` provide the start index of each object in this vector and their width respectively. The number of objects is given by the `LHC_DATA_OBJECT_COUNT` constant. This information is used by a `for-generate` statement to instantiate the required `delay_element` components.

For the `bcrs_o` and the `bcrs_FDL_o` signals two additional `delay_element` components are instantiated.

If only the data width or the array size of an object in the `lhc_data_t` is changed the DM does not need any modification. If, however, a new object is added a new delay register must be added, as described in the register bank section.

The registers for all delays have the same layout (see Register 2.1). The names for the individual (per object) delay registers are given in Table 4. For the software addresses of these registers refer to the `xml/gt_amc514_dm.xml` file.

Register 2.1: DELAY MANAGER REGISTERS

reserved												delay											
31						12						11						0					
0												0											

delay

The delay in lhc clock cycles (40 MHz) used for the specific object data.

Table 4: delay manager registers

object description	register name
bres for TCM	bres_tcm_delay
bres for FDL	bres_fdl_delay
muon data	muons_delay
e/g	eg_delay
tau	tau_delay
jet	jet_delay
ett	ett_delay
ht	ht_delay
etm	etm_delay
htm	htm_delay
external conditions	ex_con_delay

2.5 SIM and SPY Memory

Remark:

with frame v1.2.3 Simmem data not useable anymore, because of removed "Data Source Multiplexer". The reason of removing "Data Source Multiplexer" is to get more available resources.

Under construction!!!

Figure 4 shows the SIM/SPY memory subsystem of the framework. It is used to calibrate the system, i.e. to set the correct delays in the Delay Manager, to record results of the GTL/FDL and output packages of the ROP and to provide simulation data for the system. All source files for the memory subsystem are located in `src/mem` directory.

2.5.1 Implementation

The memory subsystem consists of four main parts, which will be discussed in more detail in the following sections

- SPY Trigger
- SIM/SPY Memory
- SPY Memory II
- SPY Memory III



Figure 4: Memory subsystem

2.5.1.1 SPY Trigger

The SPY trigger controls the SPY memories and decides when data is recorded. It can be configured and controlled using software registers 2.2 and 2.3 provided by the register bank.

When the SPY trigger receives a *spy12* command (next or once) over the software register interface it asserts the *spy1* and *spy2* signals for the appropriate orbit. This means that the *spy* signals go high with the bunch crossing counter reaching the value zero and stay high until it reaches zero again (overflow). Note that when the SIM memory is being used (indicated by the *simmem_in_use_i* input provided by the DSMUX component) the *spy1* output will not be asserted.

When a *spy3* command is received the SPY trigger asserts the *spy3* signal and waits until the *spy3_ack* signal is asserted.

2.5.1.2 SIM/SPY memory

This component combines the SIM memory and the SPY memory I. This optimization is possible because these two memories are never used at the same time. There are basically two use cases for this memory.

- SIM memory: Data is read from the memory and provided to GTL and ROP to test these components.

Register 2.2: SPY TRIGGER ORBIT NUMBER REGISTERS



orbit_nr_low The 32 low bits of the 48 bit orbit number, used for the spy once trigger.

orbit_nr_high The 16 high bits of the 48 bit orbit number, used for the spy once trigger.

- SPY memory: External data is received by the GTX and stored in the memory to check the alignment of the data.

It is very important to guarantee that the spy input signal is not asserted, as long as the memory is used as SIM memory. Note that this functionality is implemented in the SPY trigger component.

The SIM/SPY memory converts the `lh_data_i` input signal to a `std_logic_vector` using the converter function provided by the `lh_data_pkg`. This vector is then divided into chunks of 32 bits (the PCIe data width). For each of these chunks a 32 bit true-dual-port memory (2 read ports, 2 write ports, 2 clock domains) is instantiated. Thus, every memory has a read/write port in both clock domain, the 125MHz PCIe clock domain and the 40MHz LHC clock domain, which can be used simultaneously. The PCIe data-in signal (`sw_i.data`) is connected to PCIe-clock domain write port of the memories. A memory select signal is generated from the LSBs of the software address (`sw_i.addr`). The memory select signal also controls the multiplexer on the output of the memories to generate the `sw_o.data` signal.

Depending on whether the SIM/SPY memory is used to provide simulation data or to store/spy data the address on the LHC-clock domain port of the internal memories is adjusted. If data is recorded (SPY) the bunch crossing counter is used as memory address directly. When the memory is read the read latency (two clock cycles) must be taken into account. This is achieved by subtracting 2 from the bunch crossing number before using it as address. To generate the `lh_data_o` signal the LHC-clock domain data out ports of the internal memories are concatenated and converted back to the `lh_data_t`.

If the `lh_data_t` is changed (e.g. new objects added) no modifications in the SIM/SPY memory are required. The SIM/SPY memory only depends on the (auto-generated) functions

Register 2.3: SPY TRIGGER CONFIGURATION REGISTER

<div>spy12_bsy spy3_bsy spy12_rdy spy3_rdy spy12_err</div>						reserved											<div>clr_spy12_err clr_spy3_rdy clr_spy12_rdy spy12_next spy12_once</div>						
31	30	29	28	27	26												6	5	4	3	2	1	0
0	0	0	0	0	0											0	0	0	0	0	0	0	Reset

spy12_once	Triggers the recording of the selected orbit to SPY memories I and II, when written with 1.
spy12_next	Triggers the recording of the next whole orbit to SPY memories I and II, when written with 1.
spy3	Triggers the recording of the next package that will be sent by the ROP to SPY memory III, when written with 1.
clr_spy12_rdy	Clears the ready flag of the SPY trigger for SPY memories I and II, when written with 1.
clr_spy3_rdy	Clears the ready flag of the SPY trigger for SPY memory III, when written with 1.
clr_spy12_err	Clears the error flag, when written with 1.
spy12_bsy	Indicates that the SPY trigger for SPY memories I and II is busy.
spy3_bsy	Indicates that the SPY trigger for SPY memory III is busy.
spy12_rdy	Indicates that one orbit has been recorded in SPY memories I and II and that the SPY trigger is ready for new commands.
spy3_rdy	Indicates that packet has been recorded in SPY memory III and that the SPY trigger is ready for new commands.
spy12_err	Indicates an error condition (Set only when the selected orbit number for the spy once trigger lies in the past and can therefore not be recorded).

used to convert a `lhcd_data_t` signal to `std_logic_vector` and vice versa (see Section 1.1 for details).

In the current implementation the size every object in the `lhcd_data_t` is a multiple of 32 bit. This is also expected by the SIM/SPY memory. If objects with 16 bit sizes are added the SIM/SPY memory must be modified to support this situation (e.g. zero pad the `lhcd_data_t`). Furthermore take into account that the PCIe memory bus is 32 bits wide. So 16 bit objects should be added to the end of the `lhcd_data_t` (as last entry) to keep software memory access simple.

2.5.1.3 SPY memory II

The SPY memory II is divided into two subcomponents, to store the *algos* and *finor* outputs of the FDL. Both memory can only be read over the SW interface. A write access has no effect. The *algos* memory uses the same architecture as the SIM memory. The *finor* memory uses a true-dual-port memory with asymmetric ports. This memory can be written with a data width of one bit and read with a data width of 32 bit.

2.5.1.4 SPY memory III

The SPY memory III stores the output of the ROP, which is sent to the DAQ. The input data width is configurable to bus widths of 16, 32 or 64 bits. Depending on the input data width the memory uses different architectures.

- 16 Bit
A true-dual-port memory with asymmetric ports (16 and 32 bits) is used.
- 32 Bit
A true-dual-port memory with 32 Bit data width is used.
- 64 Bit
Two true-dual-port memories with 32 Bit data width are used.

2.5.2 Interface Specification

Listing 2: SPY trigger interface specification

```

entity spytrig is
  port
  (
    lhc_clk      : in  std_logic;
    lhc_rst      : in  std_logic;
    orbit_nr     : in  orbit_nr_t;
    bx_nr        : in  bx_nr_t;
    sw_reg_i     : in  sw_reg_spytrigger_in_t;
    sw_reg_o     : out sw_reg_spytrigger_out_t;

    spy1_o       : out std_logic;
    spy2_o       : out std_logic;
    spy3_o       : out std_logic;
    spy3_ack_i   : in  std_logic;

    simmem_in_use_i : in std_logic
  );
end;

```

2.6 TCM

Under construction!!!

The Timer Counter Manager (TCM) provides different counters, listed in table 5.

2.6.1 Counter Overview

Table 5: counters of the timer counter manager

Counter	range	increase condition	reset condition	Comments
bx_nr	0to3563	rising_edge(lhc_clk)	overflow	
event_nr	0to $2^{32}-1$	l1a=1 and rising_edge(lhc_clk)	BGOS: event counter reset	
trigger_nr	0to $2^{48}-1$	l1a=1 and rising_edge(lhc_clk)	BGOS: start run	
orbit_nr	0to $2^{48}-1$	overflow of bx_nr	BGOS: orbit counter reset	
luminosity_seg_nr	0to $2^{32}-1$	rising_edge(orbit_nr(18))	BGOS: orbit counter reset	
start_lumisection	0to1	luminosity_seg_nr increases	after 25ns	'1' for 25ns
bx_nr_d_fdl	0to3563	rising_edge(lhc_clk)	overflow	

2.6.2 Bunch Crossing Number and counters derived from it

All counters except for event_nr and the trigger_nr (which are trivial because they are increased with l1a) are dependent on the bunch crossing counter bx_nr as stated in table 5. The bx_nr is zero at startup, then waits for the the first bcrs_d (bunch crossing reset delayed) and starts counting as depicted in figure 5. It's maximal value is 3563 (0xdeb), then it automatically overflows and starts at zero again (see figure 6). Exactly when bx_nr = 0,

bres_d has to be asserted. Otherwise the counter is out of synchronization. If this happens, the software register err_det is set and the counter waits for the next bres_d to synchronize again. Note that the value of the counter is invalid until it has synchronized again.



Figure 5: start of the bunch crossing number with the first bres_d



Figure 6: normal operation of the bunch crossing number

2.6.3 Special counter: bx_nr_d_fdl

The bx_nr_d_fdl is derived from bres_d_fdl in the same manner as bx_nr is derived from bres_d. bx_nr_d_fdl will automatically resync if the logic described in subsection 2.6.5 detects a synchronization error for bx_nr.

2.6.4 Counters derived from l1a

The counters event_nr and trigger_nr are increased with l1a, i.e. they are increased twice if l1a is high for 2 clock cycles, etc. They differ only in their value range and the condition that resets the counters, see table 5.

2.6.5 Errors

As stated above, bres_d has to be asserted exactly when bx_nr = 0, otherwise the counter is out of sync. Then the software register err_det is set as depicted in figure 7. err_det can be reset via the software event register err_det_reset_event as depicted in figure 8. Furthermore err_det is set if bgos = Resync-0x1 and the counter value is not 3563.

The TCM implements two additional counters (bx_nr_chk and bx_nr_max) for debugging purposes. These counters are not visible by any other module but readable via software. bx_nr_chk is a 32bit Counter that increases with every LHC clock cycle and resets with bres_d. bx_r_max holds the highest value bx_nr_chk ever reached (should be 3563 if the link is aligned).




Figure 7: set of the software register `err_det` when `bc_res_d` is not asserted correctly




Figure 8: reset of the software register `err_det` when `err_det_reset_event` toggles

2.6.6 SW-Registers

All counters except for the `start_lumisection` described in table 5 can be read by software via the following sw registers:


Register 2.4: TCM BUNCH CROSSING NUMBER REGISTER

Register 11: FCR Branch Crossing Number Register																															
reserved												bx_nr																			
31												12				11												0			
0																0															

Register 2.5: TCM EVENT NUMBER REGISTER

event_nr	
31	0
0	


Register 2.6: TCM TRIGGER NUMBER REGISTERS



trigger_nr_l The 32 low bits of the 48 bit trigger number.

trigger_nr_h The 16 high bits of the 48 bit trigger number.


Register 2.7: TCM ORBIT NUMBER REGISTERS



orbit_nr_l The 32 low bits of the 48 bit orbit number.

orbit_nr_h The 16 high bits of the 48 bit orbit number.

Register 2.8: TCM LUMINOSITY SEGMENT NUMBER REGISTER



Register 2.9: TCM BUNCH CROSSING NUMBER FDL REGISTER

<i>reserved</i>												<i>bx_nr_d_fdl</i>															
31											12	11													0		
0												0															

Register 2.10: TCM BUNCH CROSSING NUMBER CHECK REGISTER

bx_nr_chk																															
31																															0
0																															

Register 2.11: TCM BUNCH CROSSING NUMBER MAX REGISTER

<i>bx_nr_max</i>																															
31																															0
0																															

Some additional control register can be used to check and reset `err_det`, disable the check of `bcrs_d` and `bcrs_d_fdl` (`bx_nr` and `bx_nr_d_fdl` automatically reset when they overflow if `cmd_ign_bcrs` is set, `bcrs_d` is ignored) and simulate the `bgos` signal. To do this, a value of the orbit signal has to be written to sw-register `bgos`. The value of the input signal `bgos` is replaced by the value of the sw-register for exactly one clock cycle, when "1" is written to the event register `bgos_event`.

Register 2.12: TCM `CMD_IGN_BCRES`

<i>reserved</i>																<i>cmd_ign_bcrs</i>														
31															1	0														
0																0	Reset													

`cmd_ign_bcrs` `bcrs` is ignored (not checked) when this is set.

Register 2.13: TCM ERR_DET

<div>reserved</div>															<div>err_det</div>	
															1	0
0															0	Reset

err_det Set when out of synchronization.

Register 2.14: TCM ERR_DET_RESET_EVENT

<div>reserved</div>															<div>err_det_reset_event</div>	
															1	0
0															0	Reset

err_det_reset_event Event register: resets err_det.

Register 2.15: TCM BGOS

<div>reserved</div>												<div>bgos</div>			
												4	3	0	
0												0			

Reset

bgos For simulation of the bgos signal.

Register 2.16: TCM BGOS_EVENT

<div>reserved</div>															<div>bgos_event</div>	
															1	0
0															0	Reset

bgos_event Event register: replaces the input signal bgos by the sw-register bgos for exactly one clock cycle.

Register 2.17: TCM LUMINOSITY_SEG_PERIOD_MSK

<i>luminosity_seg_period_msk</i>									
31									0
0	x	4	0	0	0	0	0	0	Reset

luminosity_seg_period_msk luminosity_seg_nr is increased when the or-bit_nr mod lum_seg_period_mask = 0.

2.6.7 Hardware Test

There are various python scripts located in the software/GtControl/branches/fpga-design-2013/python/GtControl directory for testing the tcm module. Please refer to the output of the scripts for information how the tests are performed in detail. See table 6.

Table 6: scripts for testing the tcm

script	purpose
tcm_counter_values.py	outputs the values of all counters defined above
tcm_produce_err_det	produces an err_det by manipulating bgos
tcm_err_det_reset	resets the err_det software register
tcm_trigger_test	tests trigger_nr and event_nr by generating lla signals using llasim
tcm_lum_seg_nr_test	checks the period of two successive increases of the luminosity_seg_nr

2.7 Software Reset

The software reset module (sw_reset) provides the possibility for a software reset via the software event register sw_reset_event.

Register 2.18: SOFTWARE RESET REGISTER

		<i>reserved</i>		<i>sw_reset_event</i>		
31					1	0
					0	Reset

sw_reset_event Event register: Generates a reset signal for exactly one clock cycle.

3 Global Trigger Logic

Remark:

this description is for version 1.10.6 of Global Trigger Logic.

The Global Trigger Logic (μ GTL) firmware contains conditions and Algorithms for trigger decision.




Figure 9: μ GTL firmware

3.1 μ GTL Interface

Inputs:

- Calo-Layer2 data
 - Electron/ γ objects
 - Jet objects
 - Tau objects
 - Energy summary information: Total Et (ET), total Et from ECAL only (ETTEM), total calibrated Et in jets (HT), missing Et (ET_{miss}), missing Et including HF (ET_{miss}^{HF}), missing Ht objects (HT_{miss}), missing Ht including HF (HT_{miss}^{HF}) and "Asymmetry" information (ASYMET, ASYMHT, ASYMETHF, ASYMHTEF)
 - Minimum bias HF bits (included in energy summary information data structure)
 - Towercount bits (number of firing HCAL towers, included in energy summary information data structure)
 - "Centrality" bits
- Global Muon Trigger data

- External conditions
- LHC-clock

Outputs:

- Algorithms


3.2 Definition of optical interfaces

Remark: all definitions in the following chapters are from a CMS Detector Note: "Scales for inputs to μ GT" (see actual version in <http://globaltrigger.hephy.at/upgrade/ugt/downloads/>).


3.2.1 Calo-Layer2 optical interfaces

The configuration of optical connections from Calo-Layer2 to μ GT is shown in Table 2.


The data structure of an electron/ γ object (bits 27..31 are not defined yet, reserved for quality, ...):




The data structure of a jet object (bits 27..31 are not defined yet, reserved for quality, ...):



The data structure of a tau object (bits 27..31 are not defined yet, reserved for quality, ...):




The data structure of "total Et" (ET) quantity [including "total Et from ECAL only" (ET-TEM) and "minimum bias HF+ threshold 0" bits]:




The data structure of "total calibrated Et in jets" (HT) quantity [including "towercount" and "minimum bias HF- threshold 0" bits]:


3 Global Trigger Logic




The data structure of "missing Et" (ET_{miss}) quantity [including "Asymmetry" ASYMET and "minimum bias HF+ threshold 1" bits]:




The data structure of "missing Ht" (HT_{miss}) quantity [including "Asymmetry" ASYMHT and "minimum bias HF- threshold 1" bits]:



The data structure of "missing Et including HF" (ET_{miss}^{HF}) quantity [including "Asymmetry" ASYMETHF and "Centrality" bits (3:0)]:




The data structure of "missing Ht including HF" (HT_{miss}^{HF}) quantity [including "Asymmetry" ASYMHTHF and "Centrality" bits (7:4)]:



3.2.2 Global Muon Trigger optical interfaces

The data structure of a muon object (64 bits - bit 34 = charge sign, bit 35 = charge valid, bit 61 is a spare bit, bit 63..62 = impact parameter):



3.3 Implementation in firmware

Remark: all definitions for scales in the following chapters are from a CMS Detector Note: "Scales for inputs to μ GT" (see actual version in <http://globaltrigger.hephy.at/upgrade/ugt/downloads/>).

The firmware of μ GTL consists of two main parts:

- A top-of-hierarchy file (`gtl_module.vhd`), which contains the pipeline for $\pm 2bx$ data, the instantiations of calculators for differences in η and φ , the instantiations of conditions, the instantiations of charge correlation logic of muons and the Algorithms logic for 512 Algorithms, as well as a package file (`gtl_pkg.vhd`) for declarations. Both files generated by VHDL Producer for every Trigger Menu (see Figure 10). In addition, VHDL Producer creates a VHDL files for the mapping of Algorithms (`algo_mapping_rop.vhd`) for μ FDL.
- A set of VHDL-files for all the modules instantiated in top-of-hierarchy and the modules in the hierarchy. These files, called the "fixed part", are not influenced by VHDL Producer.




Figure 10: VHDL file generation by VHDL Producer

The latency of μ GTL is fixed to 5 bunch crossings, 2 bunch crossings for the pipeline of $\pm 2bx$ data (for data with $+2bx$ and $+1bx$), 2 bunch crossings for conditions (fixed), also for the

conditions requested in the future, 1 bunch crossing for the logic of Algorithms (See Figure 11).

If there are not enough firmware resources in FPGA of one AMC board for 512 Algorithms, more boards could be used. Therefore the 512 Algorithms are **partitioned by TME** (e.g. the first board covers Algorithms 0..200 and the second Algorithms 201..511). Trigger Menu Editor (TME) will give the number of Algorithms per module as constant in the package module `gtl_pkg.vhd`. This means μ GTL and μ FDL firmware considered as a unit for synthesis.

3.3.1 Top-of-hierarchy module

The top-of-hierarchy module (`gtl_module.vhd`) contains

- the pipeline for $\pm 2bx$ data
- the instantiations of charge correlation logic of muons (generated by VHDL Producer)
- the instantiations of calculators for differences in η and φ (generated by VHDL Producer)
- the instantiations of conditions (generated by VHDL Producer)
- a boolean logic for Algorithms (generated by VHDL Producer)

Listing 3 contains the entity-declaration of the top-of-hierarchy file (`gtl_module.vhd`).

Listing 3: Entity declaration of `gtl_module.vhd`

```
entity gtl_module is
  port (
    lhc_clk : in std_logic;
    eg_data : in calo_objects_array(0 to NR_EG_OBJECTS-1);
    jet_data : in calo_objects_array(0 to NR_JET_OBJECTS-1);
    tau_data : in calo_objects_array(0 to NR_TAU_OBJECTS-1);
    ett_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    ht_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    etm_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    htm_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
  )
--
  *****

-- HB 2016-04-18: updates for "min bias trigger" objects (quantities) for Low-
  pileup-run May 2016
  mbtlhfp_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
  mbtlhfm_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
  mbt0hfp_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
  mbt0hfm_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
-- HB 2016-06-07: inserted new esums quantities (ETTEM and ETMHF).
  ettem_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
  etmhfm_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
-- HB 2016-09-16: inserted HTMHF and TOWERCNT
  htmhf_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
  towercount_data : in std_logic_vector(MAX_TOWERCOUNT_BITS-1 downto 0);
```

```
-- HB 2018-08-06: inserted signals for "Asymmetry" and "Centrality" (included in
    esums data structure).
    asymet_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    asymht_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    asymethf_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    asymhthf_data : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    centrality_data : in std_logic_vector(NR_CENTRALITY_BITS-1 downto 0);
--
    *****

    muon_data : in muon_objects_array(0 to NR_MUON_OBJECTS-1);
    external_conditions : in std_logic_vector(NR_EXTERNAL_CONDITIONS-1 downto
        0);
    algo_o : out std_logic_vector(NR_ALGOS-1 downto 0));
end gtl_module;
```

3.3.2 Package module

All the declarations for arrays ('type'), parameters ('constant') and look-up-tables ('constant') used in modules are in `gtl_pkg.vhd` package-file.

3.4 μ GTL structure

3.4.1 Data $\pm 2bx$

The μ GTL input data flow through a register pipeline of four stages. With those data it is possible to have conditions with objects from different bunch crossings (within ± 2 bunch crossings), e.g. for Correlation conditions.

See Figure 11 for a scheme of μ GTL pipeline structure. The data "data_p_1bx" and "data_p_2bx" occur 1 respectively 2 bunch crossings after data for a certain bunch crossing, therefore we got 2 bunch crossings of latency from those data. The data "data_m_1bx" and "data_m_2bx" have no influence on latency, because coming before data for a certain bunch crossing.




Figure 11: Scheme of μ GTL pipeline structure

3.4.2 Calculation of differences in η and φ

Some condition types namely correlation conditions uses differences in η and φ to make the decision. Therefore these differences are calculated out of these conditions, because the dif-

ferences can be used several times in different condition types. The differences in η and φ are calculated in bins. These differences in bins are converted to numbers (by LUTs), which represents values of differences (multiples of units in η and φ). Differences in φ are provided by module `sub_phi_integer_obj_vs_obj.vhd`, which instantiates the module `sub_unsigned_phi.vhd` as many times as the numbers of both objects determine.

In the module `sub_unsigned_phi.vhd` a calculation of a difference of two objects is done, both objects must have the same resolution, namely the higher one. The result is the absolute value of the difference. There are two differences in φ , one "clockwise" and one "anti-clockwise". For the final result the smaller difference is taken.

Differences in η are provided by module `sub_eta_integer_obj_vs_obj.vhd`, which instantiates the module `sub_signed_eta.vhd` as many times as the numbers of both objects determine.

In the module `sub_signed_eta.vhd` a calculation of a difference of two objects is done with a signed subtraction, because of the Two's Complement notation of η values. The result is the absolute value of the difference.

3.4.3 Calorimeter conditions

3.4.3.1 Calorimeter data

The calorimeter trigger processing identifies **electron/ γ** , **jet** and **tau** objects and **energy sum quantities**.

electron/ γ :

Twelve objects are passed to the μ GT for each event.

For each selected object, the Calo-Layer2 sends parameters for E_T and for position and quality information - encoded in 32 bits:

- 9 bits E_T , range = 0..255 GeV (HW index = 0..0x1FF), step = 0.5, the highest bin will mark an overflow (HW index 0x1FF): meaning has to be defined
- 8 (7+1 sign) bits pseudo-rapidity (η) position, range = -3.0 to 3.0, step = 0.087/2, linear scale, 138 bins (HW index = 0xBC..0x44)
- 8 bits azimuth angle (φ) position, range = 2π , step $\approx 2\pi/144$ ($\cong 2.5^\circ$), 144 bins (HW index = 0..0x8F), HW index starting at 0° (anti-clockwise)
- 2 bits isolation (meaning not defined yet!)
- 5 bits quality and spare (not defined yet!)

The data structure of an electron/ γ object (bits 27..31 are not defined yet, reserved for quality, ...):

31	27	26	25	24	17	16	9	8	0
<i>qual/spare</i>				<i>iso</i>	φ		η		E_T

jet:

Twelve objects are passed to the μ GT for each event.

For each selected object, the Calo-Layer2 sends parameters: E_T , for position and quality information - encoded in 32 bits:

- 11 bits E_T , range = 0..1023 GeV (HW index = 0..0x7FF), step = 0.5, the highest bin will mark an overflow (HW index 0x7FF): meaning has to be defined
- 8 (7+1 sign) bits pseudo-rapidity (η) position, range = -5.0 to 5.0, step = 0.087/2, linear scale, 230 bins (HW index = 0x8E..0x72)
- 8 bits azimuth angle (φ) position, range = 2π , step $\approx 2\pi/144$ ($\cong 2.5^\circ$), 144 bins (HW index = 0..0x8F), HW index starting at 0° (anti-clockwise)
- 5 bits quality and spare (not defined yet!)

The data structure of a jet object (bits 27..31 are not defined yet, reserved for quality, ...):

31	27	26	19	18	11	10	0
<i>iso/qu/sp</i>			φ			η	
						E_T	

tau:

Twelve objects are passed to the μ GT for each event.

For each selected object, the Calo-Layer2 sends parameters for E_T and for position and quality information - encoded in 32 bits:

- 9 bits E_T , range = 0..255 GeV (HW index = 0..0x1FF), step = 0.5, the highest bin will mark an overflow (HW index 0x1FF): meaning has to be defined
- 8 (7+1 sign) bits pseudo-rapidity (η) position, range = -3.0 to 3.0, step = 0.087/2, linear scale, 138 bins (HW index = 0xBC..0x44)
- 8 bits azimuth angle (φ) position, range = 2π , step $\approx 2\pi/144$ ($\cong 2.5^\circ$), 144 bins (HW index = 0..0x8F), HW index starting at 0° (anti-clockwise)
- 2 bits isolation (meaning not defined yet!)
- 5 bits quality and spare (not defined yet!)

The data structure of a tau object (bits 27..31 are not defined yet, reserved for quality, ...):

31	27	26	25	24	17	16	9	8	0
<i>qual/spare</i>		<i>iso</i>		φ			η		E_T

The representation of the 8 bits (called "hardware index [HW index]") in η is expected as Two's Complement notation as shown in Table 8.

The representation of the 8 bits in φ is expected as shown in Table 9.

The representation of the 2 bits for isolation (e/γ and tau) is expected as shown in Table 10.

Table 7: η scale of electron/ γ and tau

HW index	η range	η bin
0x44	$68*0.087/2$ to $69*0.087/2$	68
...
0x01	$0.087/2$ to $2*0.087/2$	1
0x00	0 to $0.087/2$	0
0xFF	0 to $-0.087/2$	-1
0xFE	$-0.087/2$ to $-2*0.087/2$	-2
...
0xBC	$-68*0.087/2$ to $-69*0.087/2$	-69

Table 8: η scale of jet

HW index	η range	η bin
0x72	$114*0.087/2$ to $115*0.087/2$	114
...
0x01	$0.087/2$ to $2*0.087/2$	1
0x00	0 to $0.087/2$	0
0xFF	0 to $-0.087/2$	-1
0xFE	$-0.087/2$ to $-2*0.087/2$	-2
...
0x8E	$-114*0.087/2$ to $-115*0.087/2$	-115

Table 9: φ scale of calorimeter objects

HW index	φ range	φ range [degrees]	φ bin
0x00	0 to $2\pi/144$	0 to 2.5	0
0x01	$2\pi/144$ to $2*2\pi/144$	2.5 to 5.0	1
...
0x8F	$143*2\pi/144$ to 2π	357.5 to 360	143

Table 10: Definition of e/γ and tau isolation bits

bits [26..25]	definition
00	not isolated
01	isolated
10	TBD
11	TBD

3.4.3.2 Calorimeter conditions definition

A condition consists of calorimeter objects as input data and a set of requirements, which contain the requirements to be complied.

The requirement for calorimeter conditions contains:

one threshold for E_T , ranges for η , φ LUTs for isolation and differences in η and φ . In addition the selection of the "relative bx" of objects is done in the requirement.

The condition is complied, if every comparison between object parameters and requirements is valid for the following equation:

- E_T greater-equal or equal threshold
- η in range
- φ in range
- isolation as requested (for electron/ γ and tau)

Additional comparisons for "quality information" could be part of the equation - but not defined yet.

There are different types of calorimeter conditions implemented, depending of how many objects have to comply the requirements.

- "Quad objects requirements condition": this condition type consists of requirements for 4 different trigger objects of the same object type. For each object the requirements can be different. To fulfill this condition, there must exist at least one set of 4 different objects, each of which fulfills at least one of the requirements.
- "Triple objects requirements condition": this condition type consists of requirements for 3 different trigger objects of the same object type. For each object the requirements can be different. To fulfill this condition, there must exist at least one set of 3 different objects, each of which fulfills at least one of the requirements.
- "Double objects requirements condition": this condition type consists of requirements for 2 different trigger objects of the same object type. For each object the requirements can be different. To fulfill this condition, there must exist at least one set of 2 different objects, each of which fulfills at least one of the requirements.¹
- "Single object requirement condition": this condition type consists of one requirement for one trigger object of a given object type. To fulfill this condition, there must exist at least one object which fulfills the requirement.

The selection of the mode of E_T -comparator (greater/equal or equal), the E_T -threshold-value, ranges for η and φ set with thresholds, LUTs for isolation and ranges for differences in η and φ set with thresholds are fixed values given by VHDL Producer for every Trigger Menu. The objects have to be of same type and same bunch-crossing.

¹"Double objects requirements condition with spatial correlation" not used anymore, replaced by Correlation conditions

3.4.3.2.1 Calorimeter conditions module

The module for conditions with calorimeter objects (`calo_conditions.vhd`) instantiates the calorimeter comparators module (`calo_comparators.vhd`) as many times as the numbers of objects and requirements determine. Depending on the condition-type, different and-or-structures of object vs. requirement are selected. The selection of condition-type and the number of objects is done by parameters in the generic interface list of the module (see Listing 4, see also the explanations below).

For comparison in η , φ and the differences in η and φ , "window"-comparators are used. In the calorimeter conditions module a cut for two-body pt calculation can be selected (see 3.4.9.1.4). Therefore a threshold value for two-body pt is required.

Listing 4: Entity declaration of `calo_conditions.vhd`

```
entity calo_conditions is
  generic (
    calo_object_slice_1_low: natural;
    calo_object_slice_1_high: natural;
    calo_object_slice_2_low: natural;
    calo_object_slice_2_high: natural;
    calo_object_slice_3_low: natural;
    calo_object_slice_3_high: natural;
    calo_object_slice_4_low: natural;
    calo_object_slice_4_high: natural;
    nr_templates: positive;
    et_ge_mode: boolean;
    obj_type : natural := EG_TYPE;
    et_thresholds: calo_templates_array;
    nr_eta_windows : calo_templates_natural_array;
    eta_w1_upper_limits: calo_templates_array;
    eta_w1_lower_limits: calo_templates_array;
    eta_w2_upper_limits: calo_templates_array;
    eta_w2_lower_limits: calo_templates_array;
    eta_w3_upper_limits: calo_templates_array;
    eta_w3_lower_limits: calo_templates_array;
    eta_w4_upper_limits: calo_templates_array;
    eta_w4_lower_limits: calo_templates_array;
    eta_w5_upper_limits: calo_templates_array;
    eta_w5_lower_limits: calo_templates_array;
    phi_full_range : calo_templates_boolean_array;
    phi_w1_upper_limits: calo_templates_array;
    phi_w1_lower_limits: calo_templates_array;
    phi_w2_ignore : calo_templates_boolean_array;
    phi_w2_upper_limits: calo_templates_array;
    phi_w2_lower_limits: calo_templates_array;
    iso_luts: calo_templates_iso_array;

    twobody_pt_cut: boolean := false;
    pt_width: positive := 1;
    pt_sq_threshold_vector: std_logic_vector (MAX_WIDTH_TBPT_LIMIT_VECTOR-1
      downto 0) := (others => '0');
    sin_cos_width: positive := 1;
    pt_sq_sin_cos_precision : positive := 1
  );
```

```
port(  
    clk: in std_logic;  
    data_i: in calo_objects_array;  
    condition_o: out std_logic;  
    pt : in diff_inputs_array(0 to MAX_CALO_OBJECTS-1) := (others => (others  
        => '0'));  
    cos_phi_integer : in sin_cos_integer_array(0 to MAX_CALO_OBJECTS-1) := (  
        others => 0);  
    sin_phi_integer : in sin_cos_integer_array(0 to MAX_CALO_OBJECTS-1) := (  
        others => 0)  
);  
end calo_conditions;
```

Table 11: Explanation of Listing 4

Item	Explanation
calo_object_slice_1_low	low value of slice for object 1.
calo_object_slice_1_high	high value of slice for object 1.
calo_object_slice_2_low	low value of slice for object 2.
calo_object_slice_2_high	high value of slice for object 2.
calo_object_slice_3_low	low value of slice for object 3.
calo_object_slice_3_high	high value of slice for object 3.
calo_object_slice_4_low	low value of slice for object 4.
calo_object_slice_4_high	high value of slice for object 4.
nr_templates	valid values are 1 (for single), 2 (double), 3 (triple) and 4 (quad) - depending on condition type.
et_ge_mode	'mode-selection' for the E_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
obj_type	valid strings are 'EG_TYPE', 'JET_TYPE', and 'TAU_TYPE'.
et_thresholds	array of four threshold values for comparison in E_T (four thresholds, because of max. 4 requirements).
nr_eta_windows	array of four integer values for number of η cuts.
eta_w1_upper_limits	array of four "upper limits" of "window"-comparator 1 for η .
eta_w1_lower_limits	array of four "lower limits" of "window"-comparator 1 for η .
eta_w2_upper_limits	array of four "upper limits" of "window"-comparator 2 for η .
eta_w2_lower_limits	array of four "lower limits" of "window"-comparator 2 for η .
eta_w3_upper_limits	array of four "upper limits" of "window"-comparator 3 for η .
eta_w3_lower_limits	array of four "lower limits" of "window"-comparator 3 for η .
eta_w4_upper_limits	array of four "upper limits" of "window"-comparator 4 for η .
eta_w4_lower_limits	array of four "lower limits" of "window"-comparator 4 for η .
eta_w5_upper_limits	array of four "upper limits" of "window"-comparator 5 for η .
eta_w5_lower_limits	array of four "lower limits" of "window"-comparator 5 for η .
phi_full_range	array of four boolean to set full range of φ .
phi_w1_upper_limits	array of four "upper limits" of "window"-comparator 1 for φ .
phi_w1_lower_limits	array of four "lower limits" of "window"-comparator 1 for φ .
phi_w2_ignore	array of four boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limits	array of four "upper limits" of "window"-comparator 2 for φ .
phi_w2_lower_limits	array of four "lower limits" of "window"-comparator 2 for φ .
iso_luts	array of four LUTs for comparison of isolation.
twobody_pt_cut	valid strings are 'true' and 'false' (type is boolean).
pt_width	vector length of pt value for two-body pt.
pt_sq_threshold_vector	hex value for threshold of two-body pt comparison (value for pt square).
sin_cos_width	vector length of sine and cosine.
pt_sq_sin_cos_precision	precision of sine and cosine calculation in LUTs.
clk	clock input (LHC clock).
data_i	data, structure defined in obj_type.
condition_o	output of condition (routed to Algorithms logic, see 3.4.11).
pt	pt value for two-body pt.
cos_phi_integer	integer value of cosine for two-body pt.
sin_phi_integer	integer value of sine for two-body pt.

3.4.3.2.2 Calorimeter Overlap Remover conditions module

The Calorimeter Overlap Remover conditions consists of a Calorimeter condition (3.4.3.2.1) and a single condition for a different calo object type. One or more correlation cut(s) ($\Delta\eta$, $\Delta\varphi$ and ΔR - 3.4.9) for overlap removal is required between different calo object types. Overlap Remover conditions `calo_conditions_orm.vhd` are implemented only for calo object types.

3.4.3.2.3 Calorimeter conditions module - template for VHDL-Producer

See in Chapter 3.5.1 and in Listing 13 for a VHDL-template for VHDL-Producer of instantiating a calorimeter condition (`calo_conditions.vhd`).

3.4.3.2.4 Calorimeter comparators module

A comparator between the energy (E_T) and a threshold (`et_threshold`) and a comparison in η with five "window"-comparators and φ with two "window"-comparators is done in this basic module. The values for E_T threshold, the 'mode-selection' for the E_T comparator and the "limits" of the "window"-comparators is given in the generic interface list of the module. Additionally the data-structure of input data (`data_i` in port interface list) is provided as a record in this list. The output signal of the module is in high state, if all comparisons are true.

The comparison in η is done with five "window"-comparators, so one gets max. five ranges for η . The η value (HW index) has a Two's Complement notation, the comparisons is done signed. Number of windows is given for η .

The comparison in φ is done with two "window"-comparators, so one gets two ranges for φ . The comparisons is done unsigned. There are two flags, one for "full-range" and one for "ignore-second-window" for the selection of the ranges.

There are two cases how the limits of one "window"-comparator could be set (see also Figure 12 and Listing 5):

- Upper limit is less than lower limit \Rightarrow φ range between the limits, including the φ bin with value = 0 (HW index).
- Upper limit is greater/equal than lower limit \Rightarrow φ range between the limits, not including the φ bin with value = 0 (HW index).

The comparison of isolation (for electron/ γ and tau) is done with LUTs.

The values of η and φ have to be inside of only one of the required ranges ("or").

The comparison of isolation (for electron/ γ and tau) is done with LUTs (see Table 12). Only the least significant 4 bits of LUT are used, because currently 2 isolation bits are defined.


Table 12: LUT contents for isolation comparison of electron/ γ and tau objects

LUT content (16 bits)	isolation bits [26..25]	trigger
X"0"	xx	no trigger
X"1"	00	trigger on isolation bits = 00
X"2"	01	trigger on isolation bits = 01
X"3"	00 or 01	trigger on isolation bits = 00 or 01
X"4"	10	trigger on isolation bits = 10
X"5"	00 or 10	trigger on isolation bits = 00 or 10
X"6"	01 or 10	trigger on isolation bits = 01 or 10
X"7"	00 or 01 or 10	trigger on isolation bits = 00 or 01 or 10
X"8"	11	trigger on isolation bits = 11
X"9"	00 or 11	trigger on isolation bits = 00 or 11
X"A"	01 or 11	trigger on isolation bits = 01 or 11
X"B"	00 or 01 or 11	trigger on isolation bits = 00 or 01 or 11
X"C"	10 or 11	trigger on isolation bits = 10 or 11
X"D"	00 or 10 or 11	trigger on isolation bits = 00 or 10 or 11
X"E"	01 or 10 or 11	trigger on isolation bits = 01 or 10 or 11
X"F"	00 or 01 or 10 or 11	trigger on isolation bits = 00 or 01 or 10 or 11 (= "ignore" isolation)


Listing 5: VHDL code of "window"-comparator in φ

```
phi_comp_w1 <= '1' when phi_w1_upper_limit < phi_w1_lower_limit and  
    (phi <= phi_w1_upper_limit or phi >= phi_w1_lower_limit) else  
    '1' when phi_w1_upper_limit >= phi_w1_lower_limit and  
    (phi <= phi_w1_upper_limit and phi >= phi_w1_lower_limit)  
    else '0';
```

Upper limit is greater/equal than lower limit



Upper limit is less than lower limit

Figure 12: Setting the limits for "window"-comparators for φ

3.4.4 Energy sum quantities conditions

energy sum quantities:

Consists of following quantities (naming convention see [6](#)):

- **ET**
- **HT**
- ET_{miss}
- HT_{miss}
- **ETTEM**
- $\mathbf{ET}_{\text{miss}}^{HF}$
- $\mathbf{HT}_{\text{miss}}^{HF}$
- **ASYMET**
- **ASYMHT**
- **ASYMETHF**
- **ASYMHTHF**
- **CENT0**
- ..
- **CENT7**

3.4.4.1 Energy sum quantities data

Calo-Layer2 sends 6 frames (each 32 bits) with Energy sum quantities containing the following information:

- E_T , 12 bits, range = 0..2047 GeV (HW index = 0..0xFFF), step = 0.5, the highest bin will mark an overflow (HW index 0xFFF): meaning has to be defined
- azimuth angle (φ) position, 8 bits, range = 2π , step $\approx 2\pi/144$ ($\approx 2.5^\circ$), 144 bins (HW index = 0..0x8F), HW index starting at 0° (anti-clockwise)
- "Towercount", 13 bits, range = 0..8191
- "Minimum bias", 4 bits, range = 0..15
- "Asymmetry", 8 bits, range = 0..255 (used 0..100)
- "Centrality", 8 bits, used as signals

Frame0: The data structure of "total Et" (ET) quantity [including "total Et from ECAL only" (ETTEM) and "minimum bias HF+ threshold 0" bits]:

31	28	27	24	23	12	11	0
<i>MBT0HFP</i>	<i>spare</i>			E_T [<i>ETTEM</i>]		E_T [<i>ET</i>]	

Frame1: The data structure of "total calibrated Et in jets" (HT) quantity [including "tower-count" and "minimum bias HF- threshold 0" bits]:

31	28	27	25	24	12	11	0
<i>MBT0HFM</i>	<i>spare</i>	<i>TOWERCOUNT</i>			E_T		

Frame2: The data structure of "missing Et" (ET_{miss}) quantity [including "Asymmetry" ASYMET and "minimum bias HF+ threshold 1" bits]:

31	28	27	20	19	12	11	0
<i>MBT1HFP</i>	<i>ASYMET</i>			φ	E_T		

Frame3: The data structure of "missing Ht" (HT_{miss}) quantity [including "Asymmetry" ASYMHT and "minimum bias HF- threshold 1" bits]:

31	28	27	20	19	12	11	0
<i>MBT1HFM</i>	<i>ASYMHT</i>			φ	E_T		

Frame4: The data structure of "missing Et including HF" ($ET_{\text{miss}}^{\text{HF}}$) quantity [including "Asymmetry" ASYMETHF and "Centrality" bits (3:0)]:

31	28	27	20	19	12	11	0
<i>CENT[3:0]</i>	<i>ASYMETHF</i>			φ	E_T		

Frame5: The data structure of "missing Ht including HF" ($HT_{\text{miss}}^{\text{HF}}$) quantity [including "Asymmetry" ASYMHTHF and "Centrality" bits (7:4)]:

31	28	27	20	19	12	11	0
<i>CENT[7:4]</i>	<i>ASYMHTHF</i>			φ	E_T		

3.4.4.2 Energy sum quantities conditions module (including Asymmetry conditions)

For the entity-declaration of `esums_conditions.vhd`, see Listing 6.

Listing 6: Entity declaration of esums_conditions.vhd

```

entity esums_conditions is
  generic
    (
      et_ge_mode : boolean;
      obj_type : natural := ETT_TYPE; -- ett=0, ht=1, etm=2, htm=3
      et_threshold: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1 downto 0);
      phi_full_range : boolean;
      phi_w1_upper_limit: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1 downto 0)
      ;
      phi_w1_lower_limit: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1 downto 0)
      ;
      phi_w2_ignore : boolean;
      phi_w2_upper_limit: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1 downto 0)
      ;
      phi_w2_lower_limit: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1 downto 0)
    );
  port(
    clk : in std_logic;
    data_i : in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    condition_o : out std_logic
  );
end esums_conditions;

```

Table 13: Explanation of Listing 6

Item	Explanation
et_ge_mode	'mode-selection' for the E_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
obj_type	valid strings are 'ETT_TYPE', 'HTT_TYPE', 'ETM_TYPE', 'HTM_TYPE' and 'ETMHF_TYPE' and 'ETMHF_TYPE'.
et_threshold	threshold value for comparison in E_T . The size of the std_logic_vector depends on the number of E_T bits.
phi_full_range	boolean to set full range of φ .
phi_w1_upper_limits	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limits	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limits	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limits	"lower limit" of "window"-comparator 2 for φ .
clk	clock input (LHC clock).
data_i	input data, structure defined in obj_type.
condition_o	output of condition (routed to Algorithms logic, see 3.4.11).

A comparator between E_T and a threshold (et_threshold) and, depending on object type, a comparison in φ with two "window"-comparators is done in this module. The value for E_T threshold, the 'mode-selection' for the E_T comparator and the limits for the "window"-comparators are given in the generic interface list of the module. The selection whether a comparison in φ is part of the condition is done with the value of the generic parameter 'obj_type' ('ETM_TYPE', 'ETMHF_TYPE', 'HTM_TYPE' and 'ETMHF_TYPE' force a comparison). The comparison in φ is done in the same way as for calorimeter conditions (see 3.4.3.2.4). Additionally the data-structure of input data (data_i in port interface list)

is provided as a record in this list. The output signal of the module is in high state, if all comparisons are true.

Data for Asymmetry trigger are received on 4 frames on bits 27..20 (8 bits). For every type a comparison with an 8-bit threshold (greater-equal or equal) is done. Asymmetry data are interpreted as counts.

3.4.4.3 Energy sum quantities conditions module - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating `esums_conditions.vhd` is given below (see Listing 14).

3.4.5 Minimum bias trigger conditions

Data for Minimum bias trigger are received on the 4 MSBs of 4 frames used for Energy sum quantities (see 3.4.4).

- MBT0HFP: "minimum bias HF+ threshold 0" bits
- MBT0HFM: "minimum bias HF- threshold 0" bits
- MBT1HFP: "minimum bias HF+ threshold 1" bits
- MBT1HFM: "minimum bias HF- threshold 1" bits

In the `min_bias_hf_conditions.vhd` module there is a comparison with a 4-bit threshold (greater-equal or equal).

3.4.6 Towercount condition

Data for Towercount trigger (number of firing HCAL towers) are received on frame HT (see 3.4.4) on bits 24..12 (13 bits) of HT data structure. In the `towercount_condition.vhd` module there is a comparison with a 13-bit threshold (greater-equal or equal).

3.4.7 Centrality condition

Centrality bits used as a signals for triggers (similar to external signals).


3.4.8 Muon conditions

3.4.8.1 Muon data

Eight Muon objects are provided by Global Muon Trigger. One Muon object has a 64 bits data structure with parameters for p_T , for position, charge, quality and isolation information:

- 10 bits azimuth angle (φ) position, range = 2π , step $\approx 2\pi/576$ ($\approx 0.625^\circ$), 576 bins (HW index = 0..0x23F), HW index starting at 0° (anti-clockwise)
- 9 bits p_T , range = 0..255 GeV (HW index = 0..0x1FF), step = 0.5, the highest bin will mark an overflow (HW index 0x1FF): meaning has to be defined
- 4 bits quality, 16 types for quality (meaning not defined yet!)
- 9 (8+1 sign) bits pseudo-rapidity (η) position, range = -2.45 to 2.45, step = 0.087/8, linear scale, 452 bins (-225..225, HW index = 0x11F..0x0E1)
- 2 bits isolation, 4 types for isolation (meaning not defined yet!)
- 1 bit charge sign, charge sign = '0' means "positive" charge, charge sign = '1' means "negative" charge
- 1 bit charge valid (= '1' means "valid")
- 7 index bits
- 10 bits azimuth angle (φ) position, raw data
- 8 bits unconstraint p_T , range = 0..255 GeV (HW index = 0..0xFF), step = 1.0, the highest bin will mark an overflow (HW index 0xFF)
- 1 spare bit
- 2 bits impact parameter

The data structure of a muon object (64 bits - bit 34 = charge sign, bit 35 = charge valid, bit 61 is a spare bit, bit 63..62 = impact parameter):



The representation of the 9 bits (called "hardware index [HW index]") in η is expected as Two's Complement notation as shown in Table 14.

The central value of the bin 0 ($-0.010875/2$ to $+0.010875/2$) = 0.0, the left edge of the bins will range from $-255 \times 0.010875 - 0.010875/2 = -2.7785625$ to $+255 \times 0.010875 - 0.010875/2 = 2.7676875$. The central value of the bins will range between ± 2.773125 . The physical η range of the muon detectors is about ± 2.45 , so that not all possible η bins will be used.

The representation of the 10 bits in φ is expected as shown in Table 15.

The representation of the 4 bits for quality is expected as shown in Table 16.

Table 14: η scale of muon objects

HW index	η range	η bin
0x0E1	$224.5*0.087/8$ to $225.5*0.087/8$	225
0x0E0	$223.5*0.087/8$ to $224.5*0.087/8$	224
...
0x001	$0.5*0.087/8$ to $1.5*0.087/8$	1
0x000	$0.5*-0.087/8$ to $0.5*0.087/8$	0
0x1FF	$0.5*-0.087/8$ to $1.5*-0.087/8$	-1
0x1FE	$1.5*-0.087/8$ to $-2.5*0.087/8$	-2
...
0x11F	$-224.5*0.087/8$ to $-225.5*0.087/8$	-225

Table 15: φ scale of muon objects

HW index	φ range	φ range [degrees]	φ bin
0x000	0 to $2\pi/576$	0 to 0.625	0
0x001	$2\pi/576$ to $2*2\pi/576$	0.625 to 1.250	1
...
0x23F	$575*2\pi/576$ to 2π	359.375 to 360	575

The representation of the 2 bits for isolation is expected as shown in Table 18.

The representation of the 2 bits for impact parameter is expected as shown in Table 18.

Table 16: Definition of muon quality bits

bits [22..19]	definition
0000	quality "level 0"
0001	quality "level 1"
0010	quality "level 2"
0011	quality "level 3"
0100	quality "level 4"
0101	quality "level 5"
0110	quality "level 6"
0111	quality "level 7"
1000	quality "level 8"
1001	quality "level 9"
1010	quality "level 10"
1011	quality "level 11"
1100	quality "level 12"
1101	quality "level 13"
1110	quality "level 14"
1111	quality "level 15"

Table 17: Definition of muon isolation bits

bits [33..32]	definition
00	not isolated
01	isolated
10	TBD
11	TBD

Table 18: Definition of muon impact parameter bits

bits [63..62]	definition
00	TBD
01	TBD
10	TBD
11	TBD

3.4.8.2 Muon charge correlation module

For definition of muon charge, see [3.4.8](#).

In the muon charge correlation module, the charge correlations are made for different muon conditions-types. The module is instantiated in the top-of-hierarchy module (`gtl_module.vhd`) and not inside of a muon conditions module. The charges of objects (number of objects depends on muon condition type) are compared to get "like sign charge" ("LS") or "opposite sign charge" ("OS"), "LS" means that the charges (charge sign) of objects are the same, "OS" means that at least one object has different charge than the others. This information is used in all instantiated muon conditions. There is no charge correlation for single type conditions. In all cases the "charge valid" bit of the objects must be set.

In TME one can select "LS", "OS" or ignore for charge correlation in muon conditions.

Table 19: Muon charge correlation - Double Muon

x x	I ignore (charge x = +, -, I)
+ +	LS both positive muons
- -	LS both negative muons
I I	LS both muons with the same sign, positive or negative
+ -	OS two muons of opposite sign
- +	OS idem
I I	OS idem

Table 20: Muon charge correlation - Triple Muon

x x x	I ignore (charge x = +, -, I)
+ + +	LS three muons of positive charge
- - -	LS three muons of negative charge
I I I	LS three muons of the same sign (positive or negative)
+ + -	OS a pair plus a positive muon
+ - -	OS a pair plus a negative muon
+ - I	OS a pair plus a negative or positive muon

Table 21: Muon charge correlation - Quad Muon

x x x x	I ignore (charge x = +, -, I)
+ + + +	LS four muons of positive charge
- - - -	LS four muons of negative charge
I I I I	LS four muons of the same sign (positive or negative)
+ + + -	OS a pair plus two positive muons
+ + - -	OS two pairs
+ - - -	OS a pair plus two negative muons
+ - I I	OS a pair plus two negative or positive muons

3.4.8.3 Muon conditions definition

A condition consists of input-data and a set of requirements, which contain the requirements to be complied.

The requirement for muon conditions contains:

a threshold for p_T , ranges for η and φ , a LUT for quality, a LUT for isolation, a requested charge. The condition is complied, if every comparison between object parameters and requirements is valid for the following equation:

- p_T greater-equal or equal threshold
- η in range
- φ in range
- requested charge
- quality LUT
- iso LUT

There are different types of calorimeter conditions implemented, depending of how many objects have to comply the requirements.

- "Quad objects requirements condition": this condition type consists of requirements for 4 different trigger objects of the same object type. For each object the requirements can be different. To fulfill this condition, there must exist at least one set of 4 different objects, each of which fulfills at least one of the requirements.
- "Triple objects requirements condition": this condition type consists of requirements for 3 different trigger objects of the same object type. For each object the requirements can be different. To fulfill this condition, there must exist at least one set of 3 different objects, each of which fulfills at least one of the requirements.
- "Double objects requirements condition": this condition type consists of requirements for 2 different trigger objects of the same object type. For each object the requirements can be different. To fulfill this condition, there must exist at least one set of 2 different objects, each of which fulfills at least one of the requirements.²
- "Single object requirement condition": this condition type consists of one requirement for one trigger object of a given object type. To fulfill this condition, there must exist at least one object which fulfills the requirement.

In addition requested charge correlation must be matched (except for "Single object requirement condition", there is no charge correlation). The calculation of charge correlations is done in an own module in the top-of-hierarchy module (`gtl_module.vhd`).

²"Double objects requirements condition with spatial correlation" not used anymore, replaced by Correlation conditions

3.4.8.3.1 Muon conditions module

A module for conditions with muon objects (`muon_conditions.vhd`) instantiates the muon comparators module (`muon_comparators.vhd`) as many times as the numbers of objects and requirements determine. Depending on the condition-type different and-or-structures of object vs. requirement are selected. The selection of condition-type and the number of objects is done by parameters in the generic interface list of the module (see the following VHDL entity definition in [Listing 7](#)).

Listing 7: Entity declaration of muon_conditions.vhd

```
entity muon_conditions is
  generic (
    muon_object_slice_1_low: natural;
    muon_object_slice_1_high: natural;
    muon_object_slice_2_low: natural;
    muon_object_slice_2_high: natural;
    muon_object_slice_3_low: natural;
    muon_object_slice_3_high: natural;
    muon_object_slice_4_low: natural;
    muon_object_slice_4_high: natural;
    nr_templates: positive;
    pt_ge_mode : boolean;
    pt_thresholds: muon_templates_array;
    nr_eta_windows : muon_templates_natural_array;
    eta_w1_upper_limits: muon_templates_array;
    eta_w1_lower_limits: muon_templates_array;
    eta_w2_upper_limits: muon_templates_array;
    eta_w2_lower_limits: muon_templates_array;
    eta_w3_upper_limits: muon_templates_array;
    eta_w3_lower_limits: muon_templates_array;
    eta_w4_upper_limits: muon_templates_array;
    eta_w4_lower_limits: muon_templates_array;
    eta_w5_upper_limits: muon_templates_array;
    eta_w5_lower_limits: muon_templates_array;
    phi_full_range : muon_templates_boolean_array;
    phi_w1_upper_limits: muon_templates_array;
    phi_w1_lower_limits: muon_templates_array;
    phi_w2_ignore : muon_templates_boolean_array;
    phi_w2_upper_limits: muon_templates_array;
    phi_w2_lower_limits: muon_templates_array;
    requested_charges: muon_templates_string_array;
    qual_luts: muon_templates_quality_array;
    iso_luts: muon_templates_iso_array;
    upt_cuts: muon_templates_boolean_array;
    upt_upper_limits: muon_templates_array;
    upt_lower_limits: muon_templates_array;
    ip_luts: muon_templates_ip_array;
    requested_charge_correlation: string(1 to 2);

    twobody_pt_cut: boolean := false;
    pt_width: positive := 1;
    pt_sq_threshold_vector: std_logic_vector(MAX_WIDTH_TBPT_LIMIT_VECTOR-1
      downto 0) := (others => '0');
    sin_cos_width: positive := 1;
    pt_sq_sin_cos_precision : positive := 1
  );
  port(
    lhc_clk : in std_logic;
    data_i : in muon_objects_array;
    condition_o : out std_logic;
    ls_charcorr_double: in muon_charcorr_double_array := (others => (others
      => '0'));
    os_charcorr_double: in muon_charcorr_double_array := (others => (others
      => '0'));
```

```
ls_charcorr_triple: in muon_charcorr_triple_array := (others => (others
=> (others => '0')));
os_charcorr_triple: in muon_charcorr_triple_array := (others => (others
=> (others => '0')));
ls_charcorr_quad: in muon_charcorr_quad_array := (others => (others => (
others => (others => '0'))));
os_charcorr_quad: in muon_charcorr_quad_array := (others => (others => (
others => (others => '0'))));
pt : in diff_inputs_array(0 to NR_MUON_OBJECTS-1) := (others => (others
=> '0'));
cos_phi_integer : in sin_cos_integer_array(0 to NR_MUON_OBJECTS-1) := (
others => 0);
sin_phi_integer : in sin_cos_integer_array(0 to NR_MUON_OBJECTS-1) := (
others => 0)
);
end muon_conditions;
```

Table 22: Explanation of Listing 7

Item	Explanation
muon_object_slice_1_low	low value of slice for object 1.
muon_object_slice_1_high	high value of slice for object 1.
muon_object_slice_2_low	low value of slice for object 2.
muon_object_slice_2_high	high value of slice for object 2.
muon_object_slice_3_low	low value of slice for object 3.
muon_object_slice_3_high	high value of slice for object 3.
muon_object_slice_4_low	low value of slice for object 4.
muon_object_slice_4_high	high value of slice for object 4.
nr_templates	number of requirements, selector of condition-type. Valid values are 1, 2, 3 and 4.
pt_ge_mode	'mode-selection' for the p_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
pt_thresholds	array of four threshold values for comparison in pt (four threshold, because of max. 4 requirements).
nr_eta_windows	array of four integer values for number of η cuts.
eta_w1_upper_limits	array of four "upper limits" of "window"-comparator 1 for η .
eta_w1_lower_limits	array of four "lower limits" of "window"-comparator 1 for η .
eta_w2_upper_limits	array of four "upper limits" of "window"-comparator 2 for η .
eta_w2_lower_limits	array of four "lower limits" of "window"-comparator 2 for η .
eta_w3_upper_limits	array of four "upper limits" of "window"-comparator 3 for η .
eta_w3_lower_limits	array of four "lower limits" of "window"-comparator 3 for η .
eta_w4_upper_limits	array of four "upper limits" of "window"-comparator 4 for η .
eta_w4_lower_limits	array of four "lower limits" of "window"-comparator 4 for η .
eta_w5_upper_limits	array of four "upper limits" of "window"-comparator 5 for η .
eta_w5_lower_limits	array of four "lower limits" of "window"-comparator 5 for η .
phi_full_range	array of four boolean to set full range of φ .
phi_w1_upper_limits	array of four "upper limits" of "window"-comparator 1 for φ .
phi_w1_lower_limits	array of four "lower limits" of "window"-comparator 1 for φ .
phi_w2_ignore	array of four boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limits	array of four "upper limits" of "window"-comparator 2 for φ .
phi_w2_lower_limits	array of four "lower limits" of "window"-comparator 2 for φ .
requested_charges	array of four strings for requested charge ("pos" means "positive charge", "neg" means "negative charge" and "ign" means "ignore charge").
qual_luts	array of four LUTs (16 bits) for quality.
iso_luts	array of four LUTs (4 bits) for isolation.
upt_cuts	array of four boolean for using unconstraint p_T cuts.
upt_upper_limits	array of four "upper limits" of unconstraint p_T .

Table 22: Explanation of Listing 7

Item	Explanation
upt_lower_limits	array of four "lower limits" of unconstraint p_T .
ip_luts	array of four LUTs (4 bits) for impact parameter.
requested_charge_correlation	string (2 characters) for requested charge correlation ("ls" means "like sign", "os" means "opposite sign" or "ig" means "ignore").
twobody_pt_cut	valid strings are 'true' and 'false' (type is boolean).
pt_width	vector length of pt value for two-body pt.
pt_sq_threshold_vector	hex value for threshold of two-body pt comparison (value for pt square).
sin_cos_width	vector length of sine and cosine.
pt_sq_sin_cos_precision	precision of sine and cosine calculation in LUTs.
lhclclk	clock input (LHC clock).
data_i	input data, structure defined in <code>d_s_i</code> .
condition_o	output of condition (routed to Algorithms logic, see 3.4.11).
ls_charcorr_double	array of "like sign" charge correlation for double condition.
os_charcorr_double	array of "opposite sign" charge correlation for double condition.
ls_charcorr_triple	array of "like sign" charge correlation for triple condition.
os_charcorr_triple	array of "opposite sign" charge correlation for triple condition.
ls_charcorr_quad	array of "like sign" charge correlation for quad condition.
os_charcorr_quad	array of "opposite sign" charge correlation for quad condition.
pt	pt value for two-body pt.
cos_phi_integer	integer value of cosine for two-body pt.
sin_phi_integer	integer value of sine for two-body pt.

3.4.8.3.2 Muon conditions module - template for VHDL-Producer

See in Chapter 3.5 and in Listing 15) for a VHDL-template for VHDL-Producer of instantiating a muon condition (`muon_conditions.vhd`).

3.4.8.3.3 Muon comparators module

A comparator between p_T and a threshold (`pt_threshold`), a comparator between unconstraint p_T and a threshold (`upt_threshold`), a comparison in η with five "window"-comparators and φ with two "window"-comparators, a comparison of quality with LUT, a comparison of isolation with LUT and a comparison of the requested charge is done in this basic module. The values for p_T threshold, unconstraint p_T threshold, the 'mode-selection' for the p_T comparator, the "limits" of the "window"-comparators, the quality LUTs, the isolation LUTs and the requested charge is given in the generic interface list of the module. Additionally the data-structure of input data (`data_i` in port interface list) is provided as a record in this list. The output signal of the module is in high state, if all comparisons are true.

The comparison in η is done with five "window"-comparators, so one gets max. five ranges for η . The η value (HW index) has a Two's Complement notation, the comparisons is done signed. Number of windows is given for η .

The comparison in φ is done with two "window"-comparators, so one gets two ranges for φ . The comparisons is done unsigned. There are two flags, one for "full-range" and one for "ignore-second-window" for the selection of the ranges.

There are two cases how the limits of one "window"-comparator could be set (see also Figure 12 and Listing 5):

- Upper limit is less than lower limit $\Rightarrow \varphi$ range between the limits, including the φ bin with value = 0 (HW index).
- Upper limit is greater/equal than lower limit $\Rightarrow \varphi$ range between the limits, not including the φ bin with value = 0 (HW index).

The values of η and φ have to be inside of only one of the two required ranges ("or").

Charge valid and charge sign bits must be equal to the requested charge.

The comparison of quality is done with LUT. To ignore quality comparison, all bits in the LUT have to be '1'.

The comparison of isolation is done with LUT. To ignore isolation comparison, all bits in the LUT have to be '1' (see Table 24).

Table 23: LUT contents for quality comparison of muon objects

LUT content (16 bits)	quality bits [22..19]	trigger
X"0000"	xxxx	no trigger
X"0001"	0000	trigger on quality "level 0"
X"0002"	0001	trigger on quality "level 1"
X"0003"	0001 or 0000	trigger on quality "level 1" or "level 0"
X"0004"	0010	trigger on quality "level 2"
...
X"8000"	1111	trigger on quality "level 15"
X"C000"	1111 or 1110	trigger on quality "level 15" or "level 14"
...
X"FFFF"	xx	trigger on all quality "levels" (= "ignore")

Table 24: LUT contents for isolation comparison of muon objects

LUT content (4 bits)	isolation bits [33..32]	trigger
X"0"	xx	no trigger
X"1"	00	trigger on isolation bits = 00
X"2"	01	trigger on isolation bits = 01
X"3"	00 or 01	trigger on isolation bits = 00 or 01
X"4"	10	trigger on isolation bits = 10
X"5"	00 or 10	trigger on isolation bits = 00 or 10
X"6"	01 or 10	trigger on isolation bits = 01 or 10
X"7"	00 or 01 or 10	trigger on isolation bits = 00 or 01 or 10
X"8"	11	trigger on isolation bits = 11
X"9"	00 or 11	trigger on isolation bits = 00 or 11
X"A"	01 or 11	trigger on isolation bits = 01 or 11
X"B"	00 or 01 or 11	trigger on isolation bits = 00 or 01 or 11
X"C"	10 or 11	trigger on isolation bits = 10 or 11
X"D"	00 or 10 or 11	trigger on isolation bits = 00 or 10 or 11
X"E"	01 or 10 or 11	trigger on isolation bits = 01 or 10 or 11
X"F"	00 or 01 or 10 or 11	trigger on isolation bits = 00 or 01 or 10 or 11 (= "ignore" isolation)

3.4.9 Correlation conditions

The correlation conditions contain a combination of two "Single object requirement conditions" of two object types or one "Double objects requirement condition" of objects of the same type. In addition with "object requirements" there are cuts for $\Delta\eta$, $\Delta\varphi$, ΔR and mass. Only one correlation cut is allowed in a condition, except the combination of one $\Delta\eta$ and one $\Delta\varphi$ cut.

The following cuts can be used:

- Cuts for $\Delta\eta$ (DETA) and/or $\Delta\varphi$ (DPHI).
- Cut for ΔR (DR).
- Cuts for mass (MASS) of following mass types:
 - Cut for Invariant mass.
 - Cut for Invariant mass with "two-body pt".
 - Cut for Transverse mass.
 - Cut for Transverse mass with "two-body pt".




Figure 13: VHDL structure of cuts for correlation conditions

3.4.9.1 Calculation of cuts

Calculation of $\Delta\eta$ and $\Delta\varphi$ see section "Calculation of differences in η and φ " (3.4.2).

3.4.9.1.1 ΔR calculation

The calculation of ΔR of two objects is done with formula:

$$\Delta R = \sqrt{(\eta_1 - \eta_2)^2 + (\varphi_1 - \varphi_2)^2}.$$

In the TME there are two thresholds for ΔR : "greater/equal lower limit" and "less/equal upper limit", given in floating point notation with one position after decimal point. The comparison in VHDL is done with ΔR^2 (no square root in VHDL), thresholds for ΔR^2 are provided by VHDL-Producer.

3.4.9.1.2 Invariant mass calculation

The calculation of Invariant mass of two objects is done with formula:

$$M = \sqrt{2pt_1pt_2(\cosh(\eta_1 - \eta_2) - \cos(\varphi_1 - \varphi_2))}.$$

In the TME there are two thresholds for M: "greater/equal lower limit" and "less/equal upper limit", given in GeV (floating point notation) with one position after decimal point in even numbers.³ The comparison in VHDL is done with $\frac{M^2}{2}$ (no square root in VHDL), thresholds for $\frac{M^2}{2}$ are provided by VHDL-Producer.

3.4.9.1.3 Transverse mass calculation

The calculation of Transverse mass of two objects is done with formula:

$$M = \sqrt{2pt_1pt_2(1 - \cos(\varphi_1 - \varphi_2))}.$$

In the TME there are two thresholds for M: "greater/equal lower limit" and "less/equal upper limit", given in GeV (floating point notation) with one position after decimal point in even numbers. The comparison in VHDL is done with $\frac{M^2}{2}$ (no square root in VHDL), thresholds for $\frac{M^2}{2}$ are provided by VHDL-Producer.

3.4.9.1.4 Two-body pt calculation

The calculation of two-body pt is done with formula:

$$pt = \sqrt{pt_1^2 + pt_2^2 + 2pt_1pt_2(\cos(\varphi_1)\cos(\varphi_2) + \sin(\varphi_1)\sin(\varphi_2))}$$

In the TME there is one threshold for pt, given in GeV (floating point notation) with one position after decimal point. The comparison in VHDL is done with pt^2 (no square root in VHDL), threshold for pt^2 is provided by VHDL-Producer.

3.4.9.2 Correlation condition modules

As described in section Correlation conditions (3.4.9), correlations of two object types are done. Therefore several modules are provided with possible correlations (objects 1-objects 2):

- Correlation condition with calorimeter objects
(calo_calorimeter_correlation_condition.vhd: electron/ γ -electron/ γ , electron/ γ -jet, electron/ γ -tau, jet-jet, jet-tau and tau-tau are possible.)

³even numbers to get a precision of one position after decimal point after division by 2, because VHDL-Producer calculates thresholds for $\frac{M^2}{2}$, which includes a division by 2.

- Correlation condition with calorimeter objects and muons objects
(calo_muon_correlation_condition.vhd: electron/ γ -muon, jet-muon and tau-muon are possible.)
- Correlation condition with muon objects
(muon_muon_correlation_condition.vhd)
- Correlation condition with calorimeter objects and energy sum quantities (ET_{miss} , ET_{miss}^{HF} and HT_{miss} only)
(calo_esums_correlation_condition.vhd: electron/ γ -etm, jet-etm, tau-etm, electron/ γ -htm, jet-htm, tau-htm, electron/ γ -etmhf, jet-etmhf and tau-etmhf are possible.)
- Correlation condition with muon objects and energy sum quantities (ET_{miss} , ET_{miss}^{HF} and HT_{miss} only)
(muon_esums_correlation_condition.vhd: muon-etm, muon-etmhf and muon-htm are possible.)

3.4.9.2.1 Calo Calo Correlation condition module

The calo calo correlation condition module contains two "Single object requirement conditions" for different types of calo objects (electron/ γ , jet or tau) or same type with data from different bunch-crossings as one possible mode and a "Double objects requirement condition" for calo objects of same type and same bunch-crossing as a second mode (selection is done by a parameter in the generic list of calo_calo_correlation_condition.vhd named "same_bx").

In addition there are "Cuts" for differences in η (DETA) and φ (DPHI) or a calculation of ΔR (DR) or a calculation of mass (MASS), see Figure 13.

The cut of mass is available for Invariant mass or Transverse mass or one of both with two-body pt.

The differences in η and φ are calculated in bins. These differences in bins are converted to numbers (by LUTs, e.g. EG_EG_DIFF_ETA_LUT, EG_EG_DIFF_PHI_LUT, ...), which represents values of differences (multiples of units in η and φ). These values given in the LUTs are calculated as floating-point values (based on the scales of η and φ), which are multiplied by a factor and truncated to an integer value. So, in the LUTs we have integer values, the factor is $10^{\text{precision}}$. This "precision" is a parameter given for certain LUTs.

Remark: Definitions of scales (see Tables 8, 9, 14 and 15):

- Calorimeter objects:
- η bin width = $\frac{0.087}{2}$ (bin 0 from 0.0 to $\frac{0.087}{2}$)
- ϕ bin width = $\frac{2\pi}{144}$ (bin 0 from 0.0 to $\frac{2\pi}{144}$)

The contents of the LUTs for $\cosh(\Delta\eta)$ (EG_EG_COSH_DETA_LUT, ...) and $\cos(\Delta\varphi)$ (EG_EG_COS_DPHI_LUT, ...) for Invariant mass (formular see 3.4.9.1.2) and Transverse mass (formular see 3.4.9.1.3) are created by calculating hyperbolic cosine and cosine, rounding-up

at the 3rd position after decimal point, and multiplying by 1000 to get integer values.⁴

The contents of the LUTs for $\cos(\varphi)$ (CALO_COS_PHI_LUT) and $\sin(\varphi)$ (CALO_SIN_PHI_LUT) for two-body pt (formular see 3.4.9.1.4) are created by calculating cosine and sine, rounding-up at the 3rd position after decimal point and multiplying by 1000 to get integer values.

The condition is complied, if at least one comparison between object parameters and requirements is valid for the both "Single object requirement condition" or the "Double objects requirement condition" and the results of selected "Cuts" are inside of a range (upper and lower limit). This limits are parts of the "generic" list of the entity declaration of the module and are expressed in hex notation. The limits for DETA and DPHI are expressed with a precision of 3rd position after decimal point, for DR and MASS with 1st position after decimal point.

For the VHDL entity declaration of calo calo correlation condition module (version 4) in `calo_calor_correlation_condition.vhd`, see Listing 8.

⁴Definition of "constant CALO_INV_MASS_COSH_COS_PRECISION..." in file `gtl_pkg.vhd`. 1000 from $10^{\text{CALO_INV_MASS_COSH_COS_PRECISION}}$.

Listing 8: Entity declaration of calo_calor_correlation_condition.vhd

```
entity calo_calor_correlation_condition is
  generic(
    same_bx: boolean;

    deta_cut: boolean;
    dphi_cut: boolean;
    dr_cut: boolean;
    mass_cut: boolean;
    mass_type : natural;
    twobody_pt_cut: boolean;

    calo1_object_low: natural;
    calo1_object_high: natural;
    et_ge_mode_calor: boolean;
    obj_type_calor: natural := EG_TYPE;
    et_threshold_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1 downto 0);
    nr_eta_windows_calor : natural;
    eta_w1_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w1_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w2_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w2_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w3_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w3_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w4_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w4_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w5_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    eta_w5_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    phi_full_range_calor: boolean;
    phi_w1_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    phi_w1_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    phi_w2_ignore_calor: boolean;
    phi_w2_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    phi_w2_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
      downto 0);
    iso_lut_calor: std_logic_vector(2**MAX_CALOR_ISO_BITS-1 downto 0);

    calo2_object_low: natural;
    calo2_object_high: natural;
    et_ge_mode_calor2: boolean;
    obj_type_calor2: natural := JET_TYPE;
    et_threshold_calor2: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1 downto 0);
    nr_eta_windows_calor2 : natural;
    eta_w1_upper_limit_calor2: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
```

```
    downto 0);
eta_w1_lower_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
eta_w2_upper_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
eta_w2_lower_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
eta_w3_upper_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
eta_w3_lower_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
eta_w4_upper_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
eta_w4_lower_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
eta_w5_upper_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
eta_w5_lower_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
phi_full_range_cal02: boolean;
phi_w1_upper_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
phi_w1_lower_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
phi_w2_ignore_cal02: boolean;
phi_w2_upper_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
phi_w2_lower_limit_cal02: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
    downto 0);
iso_lut_cal02: std_logic_vector(2**MAX_CALO_ISO_BITS-1 downto 0);

diff_eta_upper_limit_vector: std_logic_vector(
    MAX_WIDTH_DELTA_DPHI_LIMIT_VECTOR-1 downto 0);
diff_eta_lower_limit_vector: std_logic_vector(
    MAX_WIDTH_DELTA_DPHI_LIMIT_VECTOR-1 downto 0);

diff_phi_upper_limit_vector: std_logic_vector(
    MAX_WIDTH_DELTA_DPHI_LIMIT_VECTOR-1 downto 0);
diff_phi_lower_limit_vector: std_logic_vector(
    MAX_WIDTH_DELTA_DPHI_LIMIT_VECTOR-1 downto 0);

dr_upper_limit_vector: std_logic_vector(MAX_WIDTH_DR_LIMIT_VECTOR-1
    downto 0);
dr_lower_limit_vector: std_logic_vector(MAX_WIDTH_DR_LIMIT_VECTOR-1
    downto 0);

mass_upper_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
    downto 0);
mass_lower_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
    downto 0);

pt1_width: positive;
pt2_width: positive;
mass_cosh_cos_precision : positive;
cosh_cos_width: positive;

pt_sq_threshold_vector: std_logic_vector(MAX_WIDTH_TBPT_LIMIT_VECTOR-1
```

```

        downto 0);
    sin_cos_width: positive;
    pt_sq_sin_cos_precision : positive

);
port(
    lhc_clk: in std_logic;
    calo1_data_i: in calo_objects_array;
    calo2_data_i: in calo_objects_array;
    diff_eta: in deta_dphi_vector_array;
    diff_phi: in deta_dphi_vector_array;
    pt1 : in diff_inputs_array;
    pt2 : in diff_inputs_array;
    cosh_deta : in calo_cosh_cos_vector_array;
    cos_dphi : in calo_cosh_cos_vector_array;
    cos_phi_1_integer : in sin_cos_integer_array;
    cos_phi_2_integer : in sin_cos_integer_array;
    sin_phi_1_integer : in sin_cos_integer_array;
    sin_phi_2_integer : in sin_cos_integer_array;
    condition_o: out std_logic
);
end calo_calor_correlation_condition;

```

Table 25: Explanation of Listing 8

Item	Explanation
same_bx	boolean indicating whether data are from same Bx - 'true' for same Bx.
deta_cut	boolean for using DETA cut.
dphi_cut	boolean for using DPHI cut.
dr_cut	boolean for using DR cut.
mass_cut	boolean for using MASS cut.
mass_type	selection of mass type (INVARIANT_MASS_TYPE, INVARIANT_MASS_PT_TYPE, TRANSVERSE_MASS_TYPE or TRANSVERSE_MASS_PT_TYPE are allowed).
calo1_object_low	low index of object range (valid numbers: 0..11).
calo1_object_high	high index of object range (valid numbers: 0..11, but greater or equal calo1_object_low).
et_ge_mode_calol	'mode-selection' for the E_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only).
obj_type_calol	selection of calo1 object type (EG_TYPE, JET_TYPE or TAU_TYPE are allowed)
et_threshold_calol	threshold value for comparison in E_T .
nr_eta_windows_calol	integer value for number of η cuts.
eta_w1_upper_limit_calol	"upper limit" of "window"-comparator 1 for η .
eta_w1_lower_limit_calol	"lower limit" of "window"-comparator 1 for η .
eta_w2_upper_limit_calol	"upper limit" of "window"-comparator 2 for η .
eta_w2_lower_limit_calol	"lower limit" of "window"-comparator 2 for η .

Table 25: Explanation of Listing 8

Item	Explanation
eta_w3_upper_limit_calol	"upper limit" of "window"-comparator 3 for η .
eta_w3_lower_limit_calol	"lower limit" of "window"-comparator 3 for η .
eta_w4_upper_limit_calol	"upper limit" of "window"-comparator 4 for η .
eta_w4_lower_limit_calol	"lower limit" of "window"-comparator 4 for η .
eta_w5_upper_limit_calol	"upper limit" of "window"-comparator 5 for η .
eta_w5_lower_limit_calol	"lower limit" of "window"-comparator 5 for η .
phi_full_range_calol	boolean to set full range of φ .
phi_w1_upper_limit_calol	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_calol	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_calol	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_calol	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_calol	"lower limit" of "window"-comparator 2 for φ .
iso_lut_calol	content of LUT (4 bits) for isolation comparison.
calo2_object_low	low index of object range (valid numbers: 0..11).
calo2_object_high	high index of object range (valid numbers: 0..11, but greater or equal calo2_object_low).
et_ge_mode_calol	'mode-selection' for the E_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
obj_type_calol	selection of calo2 object type (EG_TYPE, JET_TYPE or TAU_TYPE are allowed)
et_threshold_calol	threshold value for comparison in E_T .
nr_eta_windows_calol	integer value for number of η cuts.
eta_w1_upper_limit_calol	"upper limit" of "window"-comparator 1 for η .
eta_w1_lower_limit_calol	"lower limit" of "window"-comparator 1 for η .
eta_w2_upper_limit_calol	"upper limit" of "window"-comparator 2 for η .
eta_w2_lower_limit_calol	"lower limit" of "window"-comparator 2 for η .
eta_w3_upper_limit_calol	"upper limit" of "window"-comparator 3 for η .
eta_w3_lower_limit_calol	"lower limit" of "window"-comparator 3 for η .
eta_w4_upper_limit_calol	"upper limit" of "window"-comparator 4 for η .
eta_w4_lower_limit_calol	"lower limit" of "window"-comparator 4 for η .
eta_w5_upper_limit_calol	"upper limit" of "window"-comparator 5 for η .
eta_w5_lower_limit_calol	"lower limit" of "window"-comparator 5 for η .
phi_full_range_calol	boolean to set full range of φ .
phi_w1_upper_limit_calol	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_calol	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_calol	boolean to ignore "window"-comparator 2 for φ .

Table 25: Explanation of Listing 8

Item	Explanation
phi_w2_upper_limit_calo2	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_calo2	"lower limits" of "window"-comparator 2 for φ .
iso_lut_calo2	content of LUT (4 bits) for isolation comparison.
diff_eta_upper_limit	"upper limit" of "window"-comparator for comparison of differences in η (hex value).
diff_eta_lower_limit	"lower limit" of "window"-comparator for comparison of differences in η (hex value).
diff_phi_upper_limit	"upper limit" of "window"-comparator for comparison of differences in φ (hex value).
diff_phi_lower_limit	"lower limit" of "window"-comparator for comparison of differences in φ (hex value).
dr_upper_limit	"upper limit" of "window"-comparator for comparison of ΔR^2 (hex value).
dr_lower_limit	"lower limit" of "window"-comparator for comparison of ΔR^2 (hex value).
DETA_DPFI_VECTOR_WIDTH	vector width of $\Delta\eta$ and $\Delta\varphi$ for calculation of ΔR^2 .
DETA_DPFI_PRECISION	position after decimal point for DETA and DPFI.
mass_upper_limit	"upper limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
mass_lower_limit	"lower limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
MASS_PRECISION	position after decimal point for $\frac{M^2}{2}$.
pt1_width	number of bits of pt1.
pt2_width	number of bits of pt2.
MASS_COSH_COS_PRECISION	position after decimal point for $\cosh(\Delta\eta)$ and $\cos(\Delta\varphi)$.
cosh_cos_width	number of bits for the maximum value in the LUT for $\cosh(\Delta\eta)$.
pt_sq_threshold	threshold value for comparison in two-body pt (pt^2).
sin_cos_width	number of bits for the maximum value in the LUT for $\cos(\varphi)$ and $\sin(\varphi)$.
PT_PRECISION	position after decimal point for pt^2 .
PT_SQ_SIN_COS_PRECISION	position after decimal point for $\cos(\varphi)$ and $\sin(\varphi)$.
lhclclk	clock input (LHC clock).
calo1_data_i	calorimeter input data, structure defined with obj_type_calo1.
calo2_data_i	calorimeter input data, structure defined with obj_type_calo2.
diff_eta	differences in η , calculated in an instance of module sub_eta_integer_obj_vs_obj.vhd in top-of-hierarchy module (gtl_module.vhd), see 3.4.2.
diff_phi	differences in φ , calculated in an instance of module sub_phi_integer_obj_vs_obj.vhd in top-of-hierarchy module (gtl_module.vhd).
pt1	calo1 E_T values [from LUT, in $GeV \times 10$]. ⁵

⁵value 10 from $10^{\text{CALO_INV_MASS_PT_PRECISION}}$

Table 25: Explanation of Listing 8

Item	Explanation
pt2	calo2 E_T values [from LUT, in $GeV \times 10$].
cosh_deta	$\cosh(\Delta\eta)$ values [from LUT, $\cosh(\Delta\eta) \times 1000$]. ⁶
cos_dphi	$\cos(\Delta\varphi)$ values [from LUT, $\cosh(\Delta\varphi) \times 1000$].
cos_phi_1	$\cos(\varphi)$ values from LUT for calo1.
cos_phi_2	$\cos(\varphi)$ values from LUT for calo2.
sin_phi_1	$\sin(\varphi)$ values from LUT for calo1.
sin_phi_2	$\sin(\varphi)$ values from LUT for calo2.
condition_o	output of condition (routed to Algorithms logic, see 3.4.11).

3.4.9.2.2 Calo Muon Correlation condition module

The calo muon correlation condition module contains a "Single object requirement condition" for one type of calo objects (electron/ γ , jet or tau) and a "Single object requirement condition" for muon objects. In addition with "Cuts" for differences in η (DETA), φ (DPHI) or a calculation of ΔR (DR) or a calculation of mass (MASS).

The cut of mass is available for Invariant mass or Transverse mass or one of both with two-body pt.

The differences in η and φ are calculated in bins. These differences in bins are converted to numbers (by LUTs, e.g. EG_MUON_DIFF_ETA_LUT, EG_MUON_DIFF_PHI_LUT, ...), which represents values of differences (multiples of units in η and φ). These values given in the LUTs are calculated as floating-point values (based on the scales of η and φ), which are multiplied by a factor and truncated to an integer value. So, in the LUTs we have integer values, the factor is $10^{\text{precision}}$. This "precision" is a parameter given for certain LUTs.

Because of the different scales of calorimeter and muon objects in η and φ , there are LUTs for conversion the calorimeter bins to muon bins (in gt1_pkg.vhd: e.g. EG_ETA_CONV_2_MUON_ETA_LUT and EG_PHI_CONV_2_MUON_PHI_LUT).

Remark:

The center value of bins are used as reference value for conversion. The content of EG_ETA_CONV_2_MUON_ETA_LUT is calculated with formular:

"converted-calo-eta[bin] = calo-eta[bin] \times 4 + 2",

of EG_PHI_CONV_2_MUON_PHI_LUT with formular:

"converted-calo-phi[bin] = calo-phi[bin] \times 4 + 2".

The conversion calculations are preliminary, others may be proposed.

Definitions of scales (see Tables 8, 9, 14 and 15):


- Calorimeter objects:

⁶value 1000 from $10^{\text{CALO_INV_MASS_COSH_COS_PRECISION}}$

- η bin width = $\frac{0.087}{2}$ (bin 0 from 0.0 to $\frac{0.087}{2}$)
- ϕ bin width = $\frac{2\pi}{144}$ (bin 0 from 0.0 to $\frac{2\pi}{144}$)

- Muon objects:

- η bin width = $\frac{0.087}{8}$ (bin 0 from $0.5 \times \frac{-0.087}{8}$ to $0.5 \times \frac{+0.087}{8}$)
- ϕ bin width = $\frac{2\pi}{576}$ (bin 0 from 0.0 to $\frac{2\pi}{576}$)

Figure 14: Conversion of calorimeter η and φ to muon scales

The contents of the LUTs for $\cosh(\Delta\eta)$ (EG_MUON_COSH_DETA_LUT, ...) and $\cos(\Delta\varphi)$ (EG_MUON_COS_DPHI_LUT, ...) for Invariant mass (formular see 3.4.9.1.2) and Transverse mass (formular see 3.4.9.1.3) are created by calculating hyperbolic cosine and cosine, rounding-up at the 4th position after decimal point, and multiplying by 10000 ($10^{\text{CALO_MUON_INV_MASS_COSH_COS_PRECISION}}$) to get integer values.⁷

The contents of the LUTs for $\cos(\varphi)$ (CALO_COS_PHI_LUT and MUON_COS_PHI_LUT) and $\sin(\varphi)$ (CALO_SIN_PHI_LUT and MUON_SIN_PHI_LUT) for two-body pt (formular see 3.4.9.1.4) are created by calculating cosine and sine, rounding-up at the 3rd position after decimal point, and multiplying by 1000 to get integer values.

The condition is complied, if at least one comparison between object parameters and requirements is valid for the both "Single object requirement condition" and the results of selected

⁷Definition of "constant CALO_MUON_INV_MASS_COSH_COS_PRECISION ...", "constant EG_ETA_CONV_2_MUON_ETA_LUT ..." and "constant EG_PHI_CONV_2_MUON_PHI_LUT ..." in file gtl_pkg.vhd.

"Cuts" are inside of a range (upper and lower limit). This limits are parts of the "generic" list of the entity declaration of the module and are expressed in hex notation. The limits for DETA and DPHI are expressed with the 3rd position after decimal point, for DR and MASS with the 1st position after decimal point.

For the VHDL entity declaration of calo muon correlation condition module (version 3) in `calo_muon_correlation_condition.vhd`, see Listing [9](#).

Listing 9: Entity declaration of calo_muon_correlation_condition.vhd

```
entity calo_muon_correlation_condition is
  generic(
    deta_cut: boolean;
    dphi_cut: boolean;
    dr_cut: boolean;
    mass_cut: boolean;
    mass_type : natural;
    twobody_pt_cut: boolean;

    calo_object_low: natural;
    calo_object_high: natural;
    et_ge_mode_calo: boolean;
    obj_type_calo: natural := EG_TYPE;
    et_threshold_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1 downto 0);
    nr_eta_windows_calo : natural;
    eta_w1_upper_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w1_lower_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w2_upper_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w2_lower_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w3_upper_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w3_lower_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w4_upper_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w4_lower_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w5_upper_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    eta_w5_lower_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    phi_full_range_calo: boolean;
    phi_w1_upper_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    phi_w1_lower_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    phi_w2_ignore_calo: boolean;
    phi_w2_upper_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    phi_w2_lower_limit_calo: std_logic_vector(MAX_CALO_TEMPLATES_BITS-1
      downto 0);
    iso_lut_calo: std_logic_vector(2**MAX_CALO_ISO_BITS-1 downto 0);

    muon_object_low: natural;
    muon_object_high: natural;
    pt_ge_mode_muon: boolean;
    pt_threshold_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto 0);
    nr_eta_windows_muon : natural;
    eta_w1_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w1_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
```

```
eta_w2_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w2_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w3_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w3_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w4_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w4_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w5_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w5_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
phi_full_range_muon : boolean;
phi_w1_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
phi_w1_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
phi_w2_ignore_muon : boolean;
phi_w2_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
phi_w2_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
    downto 0);
requested_charge_muon: string(1 to 3);
qual_lut_muon: std_logic_vector(2** (D_S_I_MUON_V2.qual_high-D_S_I_MUON_V2
    .qual_low+1)-1 downto 0);
iso_lut_muon: std_logic_vector(2** (D_S_I_MUON_V2.iso_high-D_S_I_MUON_V2.
    iso_low+1)-1 downto 0);
upt_cut_muon : boolean;
upt_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto
    0);
upt_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto
    0);
ip_lut_muon: std_logic_vector(2** (D_S_I_MUON_V2.ip_high-D_S_I_MUON_V2.
    ip_low+1)-1 downto 0);

diff_eta_upper_limit_vector: std_logic_vector(
    MAX_WIDTH_DETA_DPFI_LIMIT_VECTOR-1 downto 0);
diff_eta_lower_limit_vector: std_logic_vector(
    MAX_WIDTH_DETA_DPFI_LIMIT_VECTOR-1 downto 0);

diff_phi_upper_limit_vector: std_logic_vector(
    MAX_WIDTH_DETA_DPFI_LIMIT_VECTOR-1 downto 0);
diff_phi_lower_limit_vector: std_logic_vector(
    MAX_WIDTH_DETA_DPFI_LIMIT_VECTOR-1 downto 0);

dr_upper_limit_vector: std_logic_vector(MAX_WIDTH_DR_LIMIT_VECTOR-1
    downto 0);
dr_lower_limit_vector: std_logic_vector(MAX_WIDTH_DR_LIMIT_VECTOR-1
    downto 0);

mass_upper_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
    downto 0);
```

```

    mass_lower_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
        downto 0);

    pt1_width: positive;
    pt2_width: positive;
    mass_cosh_cos_precision : positive;
    cosh_cos_width: positive;

    pt_sq_threshold_vector: std_logic_vector(MAX_WIDTH_TBPT_LIMIT_VECTOR-1
        downto 0);
    sin_cos_width: positive;
    pt_sq_sin_cos_precision : positive

);
port (
    lhc_clk: in std_logic;
    calo_data_i: in calo_objects_array;
    muon_data_i: in muon_objects_array;
    diff_eta: in deta_dphi_vector_array;
    diff_phi: in deta_dphi_vector_array;
    pt1 : in diff_inputs_array;
    pt2 : in diff_inputs_array;
    cosh_deta : in calo_muon_cosh_cos_vector_array;
    cos_dphi : in calo_muon_cosh_cos_vector_array;
    cos_phi_1_integer : in sin_cos_integer_array;
    cos_phi_2_integer : in sin_cos_integer_array;
    sin_phi_1_integer : in sin_cos_integer_array;
    sin_phi_2_integer : in sin_cos_integer_array;
    condition_o: out std_logic
);
end calo_muon_correlation_condition;

```

Table 26: Explanation of Listing 9

Item	Explanation
deta_cut	boolean for using DETA cut.
dphi_cut	boolean for using DPHI cut.
dr_cut	boolean for using DR cut.
mass_cut	boolean for using MASS cut.
mass_type	selection of mass type (INVARIANT_MASS_TYPE, INVARIANT_MASS_PT_TYPE, TRANSVERSE_MASS_TYPE or TRANSVERSE_MASS_PT_TYPE are allowed).
calo_object_low	low index of object range (valid numbers: 0..11).
calo_object_high	high index of object range (valid numbers: 0..11, but greater or equal calo_object_low).
calo_et_ge_mode_calor	'mode-selection' for the E_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only).
obj_type_calor	selection of calo object type (EG_TYPE, JET_TYPE or TAU_TYPE are allowed)
et_threshold_calor	threshold value for comparison in E_T .

Table 26: Explanation of Listing 9

Item	Explanation
nr_eta_windows_calor	integer value for number of η cuts.
eta_w1_upper_limit_calor	"upper limit" of "window"-comparator 1 for η .
eta_w1_lower_limit_calor	"lower limit" of "window"-comparator 1 for η .
eta_w2_upper_limit_calor	"upper limit" of "window"-comparator 2 for η .
eta_w2_lower_limit_calor	"lower limit" of "window"-comparator 2 for η .
eta_w3_upper_limit_calor	"upper limit" of "window"-comparator 3 for η .
eta_w3_lower_limit_calor	"lower limit" of "window"-comparator 3 for η .
eta_w4_upper_limit_calor	"upper limit" of "window"-comparator 4 for η .
eta_w4_lower_limit_calor	"lower limit" of "window"-comparator 4 for η .
eta_w5_upper_limit_calor	"upper limit" of "window"-comparator 5 for η .
eta_w5_lower_limit_calor	"lower limit" of "window"-comparator 5 for η .
phi_full_range_calor	boolean to set full range of φ .
phi_w1_upper_limit_calor	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_calor	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_calor	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_calor	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_calor	"lower limit" of "window"-comparator 2 for φ .
iso_lut_calor	content of LUT (4 bits) for isolation comparison.
muon_object_low	low index of object range (valid numbers: 0..7).
muon_object_high	high index of object range (valid numbers: 0..7, but greater or equal muon_object_low).
pt_ge_mode_muon	'mode-selection' for the p_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
pt_threshold_muon	threshold value for comparison in p_T .
nr_eta_windows_muon	integer value for number of η cuts.
eta_w1_upper_limit_muon	"upper limit" of "window"-comparator 1 for η .
eta_w1_lower_limit_muon	"lower limit" of "window"-comparator 1 for η .
eta_w2_upper_limit_muon	"upper limit" of "window"-comparator 2 for η .
eta_w2_lower_limit_muon	"lower limit" of "window"-comparator 2 for η .
eta_w3_upper_limit_muon	"upper limit" of "window"-comparator 3 for η .
eta_w3_lower_limit_muon	"lower limit" of "window"-comparator 3 for η .
eta_w4_upper_limit_muon	"upper limit" of "window"-comparator 4 for η .
eta_w4_lower_limit_muon	"lower limit" of "window"-comparator 4 for η .
eta_w5_upper_limit_muon	"upper limit" of "window"-comparator 5 for η .
eta_w5_lower_limit_muon	"lower limit" of "window"-comparator 5 for η .
phi_full_range_muon	boolean to set full range of φ .

Table 26: Explanation of Listing 9

Item	Explanation
phi_w1_upper_limit_muon	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_muon	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_muon	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_muon	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_muon	"lower limits" of "window"-comparator 2 for φ .
requested_charge_muon	string for requested charge ("pos" means "positive charge", "neg" means "negative charge" and "ign" means "ignore charge").
qual_lut_muon	content of LUT (16 bits) for quality comparison.
iso_lut_muon	content of LUT (4 bits) for isolation comparison.
upt_cut_muon	boolean for using unconstraint p_T cuts.
upt_upper_limit_muon	"upper limit" of unconstraint p_T .
upt_lower_limit_muon	"lower limit" of unconstraint p_T .
ip_lut_muon	content of LUTs (4 bits) for impact parameter.
diff_eta_upper_limit	"upper limit" of "window"-comparator for comparison of differences in η (hex value).
diff_eta_lower_limit	"lower limit" of "window"-comparator for comparison of differences in η (hex value).
diff_phi_upper_limit	"upper limit" of "window"-comparator for comparison of differences in φ (hex value).
diff_phi_lower_limit	"lower limit" of "window"-comparator for comparison of differences in φ (hex value).
dr_upper_limit	"upper limit" of "window"-comparator for comparison of ΔR^2 (hex value).
dr_lower_limit	"lower limit" of "window"-comparator for comparison of ΔR^2 (hex value).
DETA_DPFI_VECTOR_WIDTH	vector width of $\Delta\eta$ and $\Delta\varphi$ for calculation of ΔR^2 .
DETA_DPFI_PRECISION	position after decimal point for DETA and DPFI.
mass_upper_limit	"upper limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
mass_lower_limit	"lower limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
MASS_PRECISION	position after decimal point for $\frac{M^2}{2}$.
pt1_width	number of bits of pt1.
pt2_width	number of bits of pt2.
MASS_COSH_COS_PRECISION	position after decimal point for $\cosh(\Delta\eta)$ and $\cos(\Delta\varphi)$.
cosh_cos_width	number of bits for the maximum value in the LUT for $\cosh(\Delta\eta)$.
pt_sq_threshold	threshold value for comparison in two-body pt (pt^2).
sin_cos_width_1	number of bits for the maximum value in the LUT for $\cos(\varphi)$ and $\sin(\varphi)$ of calos.
sin_cos_width_2	number of bits for the maximum value in the LUT for $\cos(\varphi)$ and $\sin(\varphi)$ of muon.

Table 26: Explanation of Listing 9

Item	Explanation
PT_PRECISION	position after decimal point for pt^2 .
PT_SQ_SIN_COS_PRECISION	position after decimal point for $\cos(\varphi)$ and $\sin(\varphi)$.
lhc_clk	clock input (LHC clock).
calo_data_i	calorimeter input data, structure defined with <code>obj_type_calor</code> .
muon_data_i	muon input data.
diff_eta	differences in η , calculated in an instance of module <code>sub_eta_integer_obj_vs_obj.vhd</code> in top-of-hierarchy module (<code>gtl_module.vhd</code>), see 3.4.2.
diff_phi	differences in φ , calculated in an instance of module <code>sub_phi_integer_obj_vs_obj.vhd</code> in top-of-hierarchy module (<code>gtl_module.vhd</code>).
pt1	calo E_T values [from LUT, in $GeV \times 10$]. ⁸
pt2	muon p_T values [from LUT, in $GeV \times 10$].
cosh_deta	$\cosh(\Delta\eta)$ values [from LUT, $\cosh(\Delta\eta) \times 10000$]. ⁹
cos_dphi	$\cos(\Delta\varphi)$ values [from LUT, $\cos(\Delta\varphi) \times 10000$].
cos_phi_1	$\cos(\varphi)$ values from LUT for calo.
cos_phi_2	$\cos(\varphi)$ values from LUT for muon.
sin_phi_1	$\sin(\varphi)$ values from LUT for calo.
sin_phi_2	$\sin(\varphi)$ values from LUT for muon.
condition_o	output of condition (routed to Algorithms logic, see 3.4.11).

3.4.9.2.3 Muon Muon Correlation condition module

The muon muon correlation condition module contains two "Single object requirement conditions" for data from different bunch-crossings as one possible mode and a "Double objects requirement condition" for muon objects at same bunch-crossing as a second mode (selection is done by a parameter in the generic list of `muon_muon_correlation_condition.vhd` named "same_bx"). In the case of a "Double objects requirement condition", requirements for "requested charge correlations" are used and a muon charge correlation module (see 3.4.8.2) is required.

In addition there are "Cuts" for differences in η (DETA), φ (DPHI) or a calculation of ΔR (DR) or a calculation of mass (MASS).

The cut of mass is available for Invariant mass or Transverse mass or one of both with two-body pt .

The differences in η and φ are calculated in bins. These differences in bins are converted to numbers (by LUTs, e.g. `MUON_MUON_DIFF_ETA_LUT`, `MUON_MUON_DIFF_PHI_LUT`).

⁸value 10 from `10CALO_MUON_INV_MASS_PT_PRECISION`

⁹value 10000 from `10CALO_MUON_INV_MASS_COSH_COS_PRECISION`

LUT), which represents values of differences (multiples of units in η and φ). These values given in the LUTs are calculated as floating-point values (based on the scales of η and φ), which are multiplied by a factor and truncated to an integer value. So, in the LUTs we have integer values, the factor is $10^{\text{precision}}$. This "precision" is a parameter given for certain LUTs.

Remark: Definitions of scales (see Tables 14 and 15):

- Muon objects:
- η bin width = $\frac{0.087}{8}$ (bin 0 from $0.5 \times \frac{-0.087}{8}$ to $0.5 \times \frac{+0.087}{8}$)
- ϕ bin width = $\frac{2\pi}{576}$ (bin 0 from 0.0 to $\frac{2\pi}{576}$)

The contents of the LUTs for $\cosh(\Delta\eta)$ (MUON_MUON_COSH_DETA_LUT) and $\cos(\Delta\varphi)$ (MUON_MUON_COS_DPFI_LUT) for Invariant mass (formular see 3.4.9.1.2) and Transverse mass (formular see 3.4.9.1.3) are created by calculating hyperbolic cosine and cosine, rounding-up at the 4th position after decimal point, and multiplying by 10000 to get integer values.¹⁰

The contents of the LUTs for $\cos(\varphi)$ (MUON_COS_PHI_LUT) and $\sin(\varphi)$ (MUON_SIN_PHI_LUT) for two-body pt (formular see 3.4.9.1.4) are created by calculating cosine and sine, rounding-up at the 3rd position after decimal point, and multiplying by 1000 to get integer values.

The condition is complied, if at least one comparison between object parameters and requirements is valid for the both "Single object requirement condition" or the "Double objects requirement condition" and the results of selected "Cuts" are inside of a range (upper and lower limit). This limits are parts of the "generic" list of the entity declaration of the module and are expressed in hex notation. The limits for DETA and DPFI are expressed with a precision of 3rd position after decimal point, for DR and MASS with 1st position after decimal point.

For the VHDL entity declaration of muon muon correlation condition module in muon_muon_correlation_condition.vhd, see Listing 10.

¹⁰Definition of "constant MUON_INV_MASS_COSH_COS_PRECISION" in file gtl_pkg.vhd. 10000 from $10^{\text{MUON_INV_MASS_COSH_COS_PRECISION}}$.

Listing 10: Entity declaration of muon_muon_correlation_condition.vhd

```
entity muon_muon_correlation_condition is
  generic(
    same_bx: boolean;

    deta_cut: boolean;
    dphi_cut: boolean;
    dr_cut: boolean;
    mass_cut: boolean;
    mass_type : natural;
    twobody_pt_cut: boolean;

    muon1_object_low: natural;
    muon1_object_high: natural;
    pt_ge_mode_muon1: boolean;
    pt_threshold_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto 0);
    nr_eta_windows_muon1: natural;
    eta_w1_upper_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w1_lower_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w2_upper_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w2_lower_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w3_upper_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w3_lower_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w4_upper_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w4_lower_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w5_upper_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w5_lower_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    phi_full_range_muon1: boolean;
    phi_w1_upper_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    phi_w1_lower_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    phi_w2_ignore_muon1: boolean;
    phi_w2_upper_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    phi_w2_lower_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    requested_charge_muon1: string(1 to 3);
    qual_lut_muon1: std_logic_vector(2**(D_S_I_MUON_V2.qual_high-
      D_S_I_MUON_V2.qual_low+1)-1 downto 0);
    iso_lut_muon1: std_logic_vector(2**(D_S_I_MUON_V2.iso_high-D_S_I_MUON_V2.
      iso_low+1)-1 downto 0);
    upt_cut_muon1 : boolean;
    upt_upper_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto
      0);
    upt_lower_limit_muon1: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto
      0);
```

```
ip_lut_muon1: std_logic_vector(2** (D_S_I_MUON_V2.ip_high-D_S_I_MUON_V2.
    ip_low+1)-1 downto 0);

muon2_object_low: natural;
muon2_object_high: natural;
pt_ge_mode_muon2: boolean;
pt_threshold_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1 downto 0);
nr_eta_windows_muon2: natural;
eta_w1_upper_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w1_lower_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w2_upper_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w2_lower_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w3_upper_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w3_lower_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w4_upper_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w4_lower_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w5_upper_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
eta_w5_lower_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
phi_full_range_muon2: boolean;
phi_w1_upper_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
phi_w1_lower_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
phi_w2_ignore_muon2: boolean;
phi_w2_upper_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
phi_w2_lower_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1
    downto 0);
requested_charge_muon2: string(1 to 3);
qual_lut_muon2: std_logic_vector(2** (D_S_I_MUON_V2.qual_high-
    D_S_I_MUON_V2.qual_low+1)-1 downto 0);
iso_lut_muon2: std_logic_vector(2** (D_S_I_MUON_V2.iso_high-D_S_I_MUON_V2.
    iso_low+1)-1 downto 0);
upt_cut_muon2 : boolean;
upt_upper_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1 downto
    0);
upt_lower_limit_muon2: std_logic_vector (MAX_MUON_TEMPLATES_BITS-1 downto
    0);
ip_lut_muon2: std_logic_vector(2** (D_S_I_MUON_V2.ip_high-D_S_I_MUON_V2.
    ip_low+1)-1 downto 0);

requested_charge_correlation: string(1 to 2);

diff_eta_upper_limit_vector: std_logic_vector(
    MAX_WIDTH_DELTA_DPHI_LIMIT_VECTOR-1 downto 0);
diff_eta_lower_limit_vector: std_logic_vector(
    MAX_WIDTH_DELTA_DPHI_LIMIT_VECTOR-1 downto 0);
```

```

diff_phi_upper_limit_vector: std_logic_vector(
    MAX_WIDTH_DETA_DPFI_LIMIT_VECTOR-1 downto 0);
diff_phi_lower_limit_vector: std_logic_vector(
    MAX_WIDTH_DETA_DPFI_LIMIT_VECTOR-1 downto 0);

dr_upper_limit_vector: std_logic_vector(MAX_WIDTH_DR_LIMIT_VECTOR-1
    downto 0);
dr_lower_limit_vector: std_logic_vector(MAX_WIDTH_DR_LIMIT_VECTOR-1
    downto 0);

mass_upper_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
    downto 0);
mass_lower_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
    downto 0);

pt_width: positive;
upt_width: positive;
mass_cosh_cos_precision : positive;
cosh_cos_width: positive;

pt_sq_threshold_vector: std_logic_vector(MAX_WIDTH_TBPT_LIMIT_VECTOR-1
    downto 0);
sin_cos_width: positive;
pt_sq_sin_cos_precision : positive

);
port(
    lhc_clk: in std_logic;
    muon1_data_i: in muon_objects_array;
    muon2_data_i: in muon_objects_array;
    ls_charcorr_double: in muon_charcorr_double_array;
    os_charcorr_double: in muon_charcorr_double_array;
    diff_eta: in deta_dphi_vector_array;
    diff_phi: in deta_dphi_vector_array;
    pt1 : in diff_inputs_array;
    pt2 : in diff_inputs_array;
    upt1 : in diff_inputs_array;
    upt2 : in diff_inputs_array;
    cosh_deta : in muon_cosh_cos_vector_array;
    cos_dphi : in muon_cosh_cos_vector_array;
    cos_phi_1_integer : in sin_cos_integer_array;
    cos_phi_2_integer : in sin_cos_integer_array;
    sin_phi_1_integer : in sin_cos_integer_array;
    sin_phi_2_integer : in sin_cos_integer_array;
    condition_o: out std_logic
);
end muon_muon_correlation_condition;

```

Table 27: Explanation of Listing 10

Item	Explanation
same_bx	boolean indicating whether data are from same Bx - 'true' for same Bx.
deta_cut	boolean for using DETA cut.
dphi_cut	boolean for using DPHI cut.

Table 27: Explanation of Listing 10

Item	Explanation
dr_cut	boolean for using DR cut.
mass_cut	boolean for using MASS cut.
mass_type	selection of mass type (INVARIANT_MASS_TYPE, INVARIANT_MASS_PT_TYPE, TRANSVERSE_MASS_TYPE or TRANSVERSE_MASS_PT_TYPE are allowed).
muon_object_low	low index of object range (valid numbers: 0..7).
muon_object_high	high index of object range (valid numbers: 0..7, but greater or equal muon_object_low).
pt_ge_mode_muon1	'mode-selection' for the p_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
pt_threshold_muon1	threshold value for comparison in p_T .
nr_eta_windows_muon1	integer value for number of η cuts.
eta_w1_upper_limit_muon1	"upper limit" of "window"-comparator 1 for η .
eta_w1_lower_limit_muon1	"lower limit" of "window"-comparator 1 for η .
eta_w2_upper_limit_muon1	"upper limit" of "window"-comparator 2 for η .
eta_w2_lower_limit_muon1	"lower limit" of "window"-comparator 2 for η .
eta_w3_upper_limit_muon1	"upper limit" of "window"-comparator 3 for η .
eta_w3_lower_limit_muon1	"lower limit" of "window"-comparator 3 for η .
eta_w4_upper_limit_muon1	"upper limit" of "window"-comparator 4 for η .
eta_w4_lower_limit_muon1	"lower limit" of "window"-comparator 4 for η .
eta_w5_upper_limit_muon1	"upper limit" of "window"-comparator 5 for η .
eta_w5_lower_limit_muon1	"lower limit" of "window"-comparator 5 for η .
phi_full_range_muon1	boolean to set full range of φ .
phi_w1_upper_limit_muon1	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_muon1	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_muon1	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_muon1	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_muon1	"lower limits" of "window"-comparator 2 for φ .
requested_charge_muon1	string for requested charge ("pos" means "positive charge", "neg" means "negative charge" and "ign" means "ignore charge").
qual_lut_muon1	content of LUT (16 bits) for quality comparison.
iso_lut_muon1	content of LUT (4 bits) for isolation comparison.
upt_cut_muon1	boolean for using unconstraint p_T cuts.
upt_upper_limit_muon1	"upper limit" of unconstraint p_T .
upt_lower_limit_muon1	"lower limit" of unconstraint p_T .
ip_lut_muon1	content of LUTs (4 bits) for impact parameter.

Table 27: Explanation of Listing 10

Item	Explanation
pt_ge_mode_muon2	'mode-selection' for the p_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
pt_threshold_muon2	threshold value for comparison in p_T .
nr_eta_windows_muon2	integer value for number of η cuts.
eta_w1_upper_limit_muon2	"upper limit" of "window"-comparator 1 for η .
eta_w1_lower_limit_muon2	"lower limit" of "window"-comparator 1 for η .
eta_w2_upper_limit_muon2	"upper limit" of "window"-comparator 2 for η .
eta_w2_lower_limit_muon2	"lower limit" of "window"-comparator 2 for η .
eta_w3_upper_limit_muon2	"upper limit" of "window"-comparator 3 for η .
eta_w3_lower_limit_muon2	"lower limit" of "window"-comparator 3 for η .
eta_w4_upper_limit_muon2	"upper limit" of "window"-comparator 4 for η .
eta_w4_lower_limit_muon2	"lower limit" of "window"-comparator 4 for η .
eta_w5_upper_limit_muon2	"upper limit" of "window"-comparator 5 for η .
eta_w5_lower_limit_muon2	"lower limit" of "window"-comparator 5 for η .
phi_full_range_muon2	boolean to set full range of φ .
phi_w1_upper_limit_muon2	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_muon2	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_muon2	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_muon2	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_muon2	"lower limits" of "window"-comparator 2 for φ .
requested_charge_muon2	string for requested charge ("pos" means "positive charge", "neg" means "negative charge" and "ign" means "ignore charge").
qual_lut_muon2	content of LUT (16 bits) for quality comparison.
iso_lut_muon2	content of LUT (4 bits) for isolation comparison.
upt_cut_muon2	boolean for using unconstraint p_T cuts.
upt_upper_limit_muon2	"upper limit" of unconstraint p_T .
upt_lower_limit_muon2	"lower limit" of unconstraint p_T .
ip_lut_muon2	content of LUTs (4 bits) for impact parameter.
requested_charge_correlation	string (2 characters) for requested charge correlation ("ls" means "like sign", "os" means "opposite sign" or "ig" means "ignore").
diff_eta_upper_limit	"upper limit" of "window"-comparator for comparison of differences in η (hex value).
diff_eta_lower_limit	"lower limit" of "window"-comparator for comparison of differences in η (hex value).
diff_phi_upper_limit	"upper limit" of "window"-comparator for comparison of differences in φ (hex value).
diff_phi_lower_limit	"lower limit" of "window"-comparator for comparison of differences in φ (hex value).

Table 27: Explanation of Listing 10

Item	Explanation
dr_upper_limit	"upper limit" of "window"-comparator for comparison of ΔR^2 (hex value).
dr_lower_limit	"lower limit" of "window"-comparator for comparison of ΔR^2 (hex value).
DETA_DPHI_VECTOR_WIDTH	vector width of $\Delta\eta$ and $\Delta\varphi$ for calculation of ΔR^2 .
DETA_DPHI_PRECISION	position after decimal point for DETA and DPHI.
mass_upper_limit	"upper limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
mass_lower_limit	"lower limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
MASS_PRECISION	position after decimal point for $\frac{M^2}{2}$.
pt_width	number of bits of pt.
MASS_COSH_COS_PRECISION	position after decimal point for $\cosh(\Delta\eta)$ and $\cos(\Delta\varphi)$.
cosh_cos_width	number of bits for the maximum value in the LUT for $\cosh(\Delta\eta)$.
pt_sq_threshold	threshold value for comparison in two-body pt (pt^2).
sin_cos_width	number of bits for the maximum value in the LUT for $\cos(\varphi)$ and $\sin(\varphi)$.
PT_PRECISION	position after decimal point for pt^2 .
PT_SQ_SIN_COS_PRECISION	position after decimal point for $\cos(\varphi)$ and $\sin(\varphi)$.
lhclclk	clock input (LHC clock).
muon1_data_i	muon1 input data.
muon2_data_i	muon2 input data.
ls_charcorr_double	array of "like sign" charge correlation for double condition.
os_charcorr_double	array of "opposite sign" charge correlation for double condition.
diff_eta	differences in η , calculated in an instance of module <code>sub_eta_integer_obj_vs_obj.vhd</code> in top-of-hierarchy module (<code>gtl_module.vhd</code>), see 3.4.2.
diff_phi	differences in φ , calculated in an instance of module <code>sub_phi_integer_obj_vs_obj.vhd</code> in top-of-hierarchy module (<code>gtl_module.vhd</code>).
pt1	muon1 p_T values [from LUT, in $GeV \times 10$]. ¹¹
pt2	muon2 p_T values [from LUT, in $GeV \times 10$].
upt1	muon1 unconstraint p_T values [from LUT, in $GeV \times 10$]. ¹²
upt2	muon2 unconstraint p_T values [from LUT, in $GeV \times 10$].
cosh_deta	$\cosh(\Delta\eta)$ values [from LUT, $\cosh(\Delta\eta) \times 10000$]. ¹³
cos_dphi	$\cos(\Delta\varphi)$ values [from LUT, $\cos(\Delta\varphi) \times 10000$].
cos_phi_1	$\cos(\varphi)$ values from LUT for muon.
cos_phi_2	$\cos(\varphi)$ values from LUT for muon (different to <code>cos_phi_1</code> , when data from different bunch-crossings).

¹¹value 10 from $10^{\text{MUON_MUON_INV_MASS_PT_PRECISION}}$ ¹²value 10 from $10^{\text{MUON_MUON_INV_MASS_PT_PRECISION}}$ ¹³value 10000 from $10^{\text{MUON_MUON_INV_MASS_COSH_COS_PRECISION}}$

Table 27: Explanation of Listing 10

Item	Explanation
sin_phi_1	$\sin(\varphi)$ values from LUT for muon.
sin_phi_2	$\sin(\varphi)$ values from LUT for muon (different to sin_phi_1, when data from different bunch-crossings).
condition_o	output of condition (routed to Algorithms logic, see 3.4.11).

3.4.9.2.4 Calo Esums Correlation condition module

The calo esums correlation condition module contains two "Single object requirement conditions", one of calo objects (electron/ γ , jet or tau) and one of esums (ET_{miss} , ET_{miss}^{HF} or HT_{miss}).

In addition there are "Cuts" for differences in φ (DPHI) or a calculation of mass (MASS) for Transverse mass or Transverse mass with two-body pt.

The differences in φ are calculated in bins. These differences in bins are converted to numbers (by LUTs, e.g. EG_ETM_DIFF_PHI_LUT, ...), which represents values of differences (multiples of units in φ). These values given in the LUTs are calculated as floating-point values (based on the scales of φ), which are multiplied by a factor and truncated to an integer value. So, in the LUTs we have integer values, the factor is $10^{\text{precision}}$.

The contents of the LUTs $\cos(\Delta\varphi)$ (EG_ETM_COS_DPHI_LUT, ...) for Transverse mass (formular see 3.4.9.1.3) are created by calculating cosine, rounding-up at the 3rd position after decimal point and multiplying by 1000 to get integer values.¹⁴

The contents of the LUTs for $\cos(\varphi)$ (CALO_COS_PHI_LUT) and $\sin(\varphi)$ (CALO_SIN_PHI_LUT) for two-body pt (formular see 3.4.9.1.4) are created by calculating cosine and sine, rounding-up at the 3rd position after decimal point and multiplying by 1000 to get integer values.

The condition is complied, if at least one comparison between object parameters and requirements is valid for the both "Single object requirement condition" and the results of selected "Cuts" are inside of a range (upper and lower limit). This limits are parts of the "generic" list of the entity declaration of the module and are expressed in hex notation. The limits for DPHI are expressed with a precision of 3rd position after decimal point, for MASS with 1st position after decimal point.

For VHDL entity declaration for calo esums correlation condition module in calo_esums_correlation_condition.vhd, see Listing 11.

Listing 11: Entity declaration of calo_esums_correlation_condition.vhd

```
entity calo_esums_correlation_condition is
  generic (
```

¹⁴Definition of "constant CALO_INV_MASS_COSH_COS_PRECISION..." in file gtl_pkg.vhd. 1000 from $10^{\text{CALO_INV_MASS_COSH_COS_PRECISION}}$.

```
dphi_cut: boolean;
mass_cut: boolean;
mass_type : natural;
twobody_pt_cut: boolean;

calo_object_low: natural;
calo_object_high: natural;
et_ge_mode_calor: boolean;
obj_type_calor: natural := EG_TYPE;
et_threshold_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1 downto 0);
nr_eta_windows_calor : natural;
eta_w1_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w1_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w2_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w2_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w3_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w3_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w4_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w4_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w5_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
eta_w5_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
phi_full_range_calor: boolean;
phi_w1_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
phi_w1_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
phi_w2_ignore_calor: boolean;
phi_w2_upper_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
phi_w2_lower_limit_calor: std_logic_vector(MAX_CALOR_TEMPLATES_BITS-1
downto 0);
iso_lut_calor: std_logic_vector(2*MAX_CALOR_ISO_BITS-1 downto 0);

et_ge_mode_esums: boolean;
obj_type_esums: natural := ETM_TYPE;
et_threshold_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1 downto 0)
;
phi_full_range_esums: boolean;
phi_w1_upper_limit_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1
downto 0);
phi_w1_lower_limit_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1
downto 0);
phi_w2_ignore_esums: boolean;
phi_w2_upper_limit_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1
downto 0);
phi_w2_lower_limit_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1
```

```
        downto 0);

diff_phi_upper_limit_vector: std_logic_vector(
    MAX_WIDTH_DETA_DPHI_LIMIT_VECTOR-1 downto 0);
diff_phi_lower_limit_vector: std_logic_vector(
    MAX_WIDTH_DETA_DPHI_LIMIT_VECTOR-1 downto 0);

mass_upper_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
    downto 0);
mass_lower_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
    downto 0);

pt1_width: positive;
pt2_width: positive;
mass_cosh_cos_precision : positive;
cosh_cos_width: positive;

pt_sq_threshold_vector: std_logic_vector(MAX_WIDTH_TBPT_LIMIT_VECTOR-1
    downto 0);
sin_cos_width: positive;
pt_sq_sin_cos_precision : positive

);
port(
    lhc_clk: in std_logic;
    calo_data_i: in calo_objects_array;
    esums_data_i: in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    diff_phi: in deta_dphi_vector_array;
    pt1 : in diff_inputs_array;
    pt2 : in diff_inputs_array;
    cos_dphi : in calo_cosh_cos_vector_array;
    cos_phi_1_integer : in sin_cos_integer_array;
    cos_phi_2_integer : in sin_cos_integer_array;
    sin_phi_1_integer : in sin_cos_integer_array;
    sin_phi_2_integer : in sin_cos_integer_array;
    condition_o: out std_logic
);
end calo_esums_correlation_condition;
```

Table 28: Explanation of Listing 11

Item	Explanation
dphi_cut	boolean for using DPHI cut.
mass_cut	boolean for using MASS cut.
mass_type	selection of mass type (TRANSVERSE_MASS_TYPE or TRANSVERSE_MASS_PT_TYPE are allowed).
calo_object_low	low index of object range (valid numbers: 0..11).
calo_object_high	high index of object range (valid numbers: 0..11, but greater or equal calo_object_low).
et_ge_mode_calor	'mode-selection' for the E_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only).
obj_type_calor	selection of calo1 object type (EG_TYPE, JET_TYPE or TAU_TYPE are allowed)
et_threshold_calor	threshold value for comparison in E_T .
nr_eta_windows_calor	integer value for number of η cuts.
eta_w1_upper_limit_calor	"upper limit" of "window"-comparator 1 for η .
eta_w1_lower_limit_calor	"lower limit" of "window"-comparator 1 for η .
eta_w2_upper_limit_calor	"upper limit" of "window"-comparator 2 for η .
eta_w2_lower_limit_calor	"lower limit" of "window"-comparator 2 for η .
eta_w3_upper_limit_calor	"upper limit" of "window"-comparator 3 for η .
eta_w3_lower_limit_calor	"lower limit" of "window"-comparator 3 for η .
eta_w4_upper_limit_calor	"upper limit" of "window"-comparator 4 for η .
eta_w4_lower_limit_calor	"lower limit" of "window"-comparator 4 for η .
eta_w5_upper_limit_calor	"upper limit" of "window"-comparator 5 for η .
eta_w5_lower_limit_calor	"lower limit" of "window"-comparator 5 for η .
phi_full_range_calor	boolean to set full range of φ .
phi_w1_upper_limit_calor	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_calor	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_calor	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_calor	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_calor	"lower limit" of "window"-comparator 2 for φ .
iso_lut_calor	content of LUT (4 bits) for isolation comparison.
et_ge_mode_esums	'mode-selection' for the E_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
obj_type_esums	selection of esums type (ETM_TYPE, ETMHF_TYPE or HTM_TYPE are allowed)
et_threshold_esums	threshold value for comparison in E_T .
phi_full_range_esums	boolean to set full range of φ .
phi_w1_upper_limit_esums	"upper limit" of "window"-comparator 1 for φ .

Table 28: Explanation of Listing 11

Item	Explanation
phi_w1_lower_limit_esums	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_esums	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_esums	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_esums	"lower limits" of "window"-comparator 2 for φ .
diff_phi_upper_limit	"upper limit" of "window"-comparator for comparison of differences in φ (hex value).
diff_phi_lower_limit	"lower limit" of "window"-comparator for comparison of differences in φ (hex value).
DETA_DPFI_VECTOR_WIDTH	vector width of $\Delta\varphi$.
DETA_DPFI_PRECISION	position after decimal point for DPHI.
mass_upper_limit	"upper limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
mass_lower_limit	"lower limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
MASS_PRECISION	position after decimal point for $\frac{M^2}{2}$.
pt1_width	number of bits of pt1.
pt2_width	number of bits of pt2.
MASS_COSH_COS_PRECISION	position after decimal point for $\cos(\Delta\varphi)$.
cosh_cos_width	number of bits for the maximum value in the LUT for $\cos(\Delta\varphi)$.
pt_sq_threshold	threshold value for comparison in two-body pt (pt^2).
sin_cos_width	number of bits for the maximum value in the LUT for $\cos(\varphi)$ and $\sin(\varphi)$.
PT_PRECISION	position after decimal point for pt^2 .
PT_SQ_SIN_COS_PRECISION	position after decimal point for $\cos(\varphi)$ and $\sin(\varphi)$.
lhclclk	clock input (LHC clock).
calo_data_i	calorimeter input data, structure defined with obj_type_calol.
esums_data_i	esums input data, structure defined with obj_type_esums.
diff_phi	differences in φ , calculated in an instance of module sub_phi_integer_obj_vs_obj.vhd in top-of-hierarchy module (gtl_module.vhd).
pt1	calol E_T values [from LUT, in $GeV \times 10$]. ¹⁵
pt2	esums E_T values [from LUT, in $GeV \times 10$].
cos_dphi	$\cos(\Delta\varphi)$ values from LUT.
cos_phi_1	$\cos(\varphi)$ values from LUT for calol.
cos_phi_2	$\cos(\varphi)$ values from LUT for esums.
sin_phi_1	$\sin(\varphi)$ values from LUT for calol.
sin_phi_2	$\sin(\varphi)$ values from LUT for esums.
condition_o	output of condition (routed to Algorithms logic, see 3.4.11).

¹⁵value 10 from $10^{\text{CALO_INV_MASS_PT_PRECISION}}$

3.4.9.2.5 Muon Esums Correlation condition module

The muon esums correlation condition module contains two "Single object requirement conditions", one of muon objects and one of esums (ET_{miss} , ET_{miss}^{HF} or HT_{miss}).

In addition there are "Cuts" for differences in φ (DPHI) or a calculation of mass (MASS) for Transverse mass or Transverse mass with two-body pt.

The differences in φ are calculated in bins. These differences in bins are converted to numbers (by LUTs, e.g. MUON_ETM_DIFF_PHI_LUT, ...), which represents values of differences (multiples of units in φ). These values given in the LUTs are calculated as floating-point values (based on the scales of φ), which are multiplied by a factor and truncated to an integer value. So, in the LUTs we have integer values, the factor is $10^{\text{precision}}$.

Because of the different scales of muon objects and esums in φ , there are LUTs for conversion the esums bins to muon bins (in `gtl_pkg.vhd`: e.g. ETM_PHI_CONV_2_MUON_PHI_LUT).

Remark:

The center value of bins are used as reference value for conversion. The content of LUT is calculated with formular:

$$\text{"converted-esums-phi[bin]} = \text{esums-phi[bin]} \times 4 + 2"$$

(see Figure 14). The conversion calculations are preliminary, others may be proposed.

Definitions of scales:

- ET_{miss} , ET_{miss}^{HF} or HT_{miss} :
 - ϕ bin width = $\frac{2\pi}{144}$ (bin 0 from 0.0 to $\frac{2\pi}{144}$)
- Muon objects:
 - ϕ bin width = $\frac{2\pi}{576}$ (bin 0 from 0.0 to $\frac{2\pi}{576}$)

The contents of the LUTs for $\cos(\Delta\varphi)$ (MU_ETM_COS_DPHI_LUT, ...) for Transverse mass (formular see 3.4.9.1.3) are created by calculating cosine, rounding-up at the 4th position after decimal point and multiplying by 10000 ($10^{\text{MU_ETM_COSH_COS_PRECISION}}$) to get integer values.¹⁶

The contents of the LUTs for $\cos(\varphi)$ (CALO_COS_PHI_LUT and MUON_COS_PHI_LUT) and $\sin(\varphi)$ (CALO_SIN_PHI_LUT and MUON_SIN_PHI_LUT) for two-body pt (formular see 3.4.9.1.4) are created by calculating cosine and sine, rounding-up at the 3rd position after decimal point and multiplying by 1000 to get integer values.

The condition is complied, if at least one comparison between object parameters and requirements is valid for the both "Single object requirement condition" and the results of selected "Cuts" are inside of a range (upper and lower limit). This limits are parts of the "generic" list of the entity declaration of the module and are expressed in hex notation. The limits for DPHI are expressed with a precision of 3rd position after decimal point, for MASS with 1st position after decimal point.

¹⁶Definition of "constant MU_ETM_COSH_COS_PRECISION ..." and "constant CALO_PHI_CONV_2_MUON_PHI_LUT ..." in file `gtl_pkg.vhd`.

For VHDL entity declaration for muon esums correlation condition module in `muon_esums_correlation_condition.vhd`, see Listing 12.

Listing 12: Entity declaration of `muon_esums_correlation_condition.vhd`

```
entity muon_esums_correlation_condition is
  generic (

    dphi_cut: boolean;
    mass_cut: boolean;
    mass_type : natural;
    twobody_pt_cut: boolean;

    muon_object_low: natural;
    muon_object_high: natural;
    pt_ge_mode_muon: boolean;
    pt_threshold_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto 0);
    nr_eta_windows_muon : natural;
    eta_w1_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w1_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w2_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w2_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w3_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w3_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w4_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w4_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w5_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    eta_w5_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    phi_full_range_muon : boolean;
    phi_w1_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    phi_w1_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    phi_w2_ignore_muon : boolean;
    phi_w2_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    phi_w2_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1
      downto 0);
    requested_charge_muon: string(1 to 3);
    qual_lut_muon: std_logic_vector(2** (D_S_I_MUON_V2.qual_high-D_S_I_MUON_V2.
      qual_low+1)-1 downto 0);
    iso_lut_muon: std_logic_vector(2** (D_S_I_MUON_V2.iso_high-D_S_I_MUON_V2.
      iso_low+1)-1 downto 0);
    upt_cut_muon : boolean;
    upt_upper_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto
      0);
```

```
    upt_lower_limit_muon: std_logic_vector(MAX_MUON_TEMPLATES_BITS-1 downto
        0);
    ip_lut_muon: std_logic_vector(2**(D_S_I_MUON_V2.ip_high-D_S_I_MUON_V2.
        ip_low+1)-1 downto 0);

    et_ge_mode_esums: boolean;
    obj_type_esums: natural := ETM_TYPE;
    et_threshold_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1 downto 0)
        ;
    phi_full_range_esums: boolean;
    phi_w1_upper_limit_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1
        downto 0);
    phi_w1_lower_limit_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1
        downto 0);
    phi_w2_ignore_esums: boolean;
    phi_w2_upper_limit_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1
        downto 0);
    phi_w2_lower_limit_esums: std_logic_vector(MAX_ESUMS_TEMPLATES_BITS-1
        downto 0);

    diff_phi_upper_limit_vector: std_logic_vector(
        MAX_WIDTH_DETA_DPHI_LIMIT_VECTOR-1 downto 0);
    diff_phi_lower_limit_vector: std_logic_vector(
        MAX_WIDTH_DETA_DPHI_LIMIT_VECTOR-1 downto 0);

    mass_upper_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
        downto 0);
    mass_lower_limit_vector: std_logic_vector(MAX_WIDTH_MASS_LIMIT_VECTOR-1
        downto 0);

    pt1_width: positive;
    pt2_width: positive;
    mass_cosh_cos_precision : positive;
    cosh_cos_width: positive;

    pt_sq_threshold_vector: std_logic_vector(MAX_WIDTH_TBPT_LIMIT_VECTOR-1
        downto 0);
    sin_cos_width: positive;
    pt_sq_sin_cos_precision : positive

);
port (
    lhc_clk: in std_logic;
    muon_data_i: in muon_objects_array;
    esums_data_i: in std_logic_vector(MAX_ESUMS_BITS-1 downto 0);
    diff_phi: in deta_dphi_vector_array;
    pt1 : in diff_inputs_array;
    pt2 : in diff_inputs_array;
    cos_dphi : in calo_muon_cosh_cos_vector_array;
    cos_phi_1_integer : in sin_cos_integer_array;
    cos_phi_2_integer : in sin_cos_integer_array;
    sin_phi_1_integer : in sin_cos_integer_array;
    sin_phi_2_integer : in sin_cos_integer_array;
    condition_o: out std_logic
);
end muon_esums_correlation_condition;
```

Table 29: Explanation of Listing 10

Item	Explanation
dphi_cut	boolean for using DPHI cut.
mass_cut	boolean for using MASS cut.
mass_type	selection of mass type (TRANSVERSE_MASS_TYPE or TRANSVERSE_MASS_PT_TYPE are allowed).
muon_object_low	low index of object range (valid numbers: 0..7).
muon_object_high	high index of object range (valid numbers: 0..7, but greater or equal muon_object_low).
pt_ge_mode_muon	'mode-selection' for the p_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
pt_threshold_muon	threshold value for comparison in p_T .
nr_eta_windows_muon	integer value for number of η cuts.
eta_w1_upper_limit_muon	"upper limit" of "window"-comparator 1 for η .
eta_w1_lower_limit_muon	"lower limit" of "window"-comparator 1 for η .
eta_w2_upper_limit_muon	"upper limit" of "window"-comparator 2 for η .
eta_w2_lower_limit_muon	"lower limit" of "window"-comparator 2 for η .
eta_w3_upper_limit_muon	"upper limit" of "window"-comparator 3 for η .
eta_w3_lower_limit_muon	"lower limit" of "window"-comparator 3 for η .
eta_w4_upper_limit_muon	"upper limit" of "window"-comparator 4 for η .
eta_w4_lower_limit_muon	"lower limit" of "window"-comparator 4 for η .
eta_w5_upper_limit_muon	"upper limit" of "window"-comparator 5 for η .
eta_w5_lower_limit_muon	"lower limit" of "window"-comparator 5 for η .
phi_full_range_muon	boolean to set full range of φ .
phi_w1_upper_limit_muon	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_muon	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_muon	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_muon	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_muon	"lower limits" of "window"-comparator 2 for φ .
requested_charge_muon	string for requested charge ("pos" means "positive charge", "neg" means "negative charge" and "ign" means "ignore charge").
qual_lut_muon	content of LUT (16 bits) for quality comparison.
iso_lut_muon	content of LUT (4 bits) for isolation comparison.
upt_cut_muon	boolean for using unconstraint p_T cuts.
upt_upper_limit_muon	"upper limit" of unconstraint p_T .
upt_lower_limit_muon	"lower limit" of unconstraint p_T .
ip_lut_muon	content of LUTs (4 bits) for impact parameter.

Table 29: Explanation of Listing 10

Item	Explanation
et_ge_mode_esums	'mode-selection' for the E_T comparator. Valid strings are 'true' and 'false' (type is boolean), 'true' means comparator works on greater/equal, 'false' means equal (for tests only)
obj_type_esums	selection of esums type (ETM_TYPE or HTM_TYPE are allowed)
et_threshold_esums	threshold value for comparison in E_T .
phi_full_range_esums	boolean to set full range of φ .
phi_w1_upper_limit_esums	"upper limit" of "window"-comparator 1 for φ .
phi_w1_lower_limit_esums	"lower limit" of "window"-comparator 1 for φ .
phi_w2_ignore_esums	boolean to ignore "window"-comparator 2 for φ .
phi_w2_upper_limit_esums	"upper limit" of "window"-comparator 2 for φ .
phi_w2_lower_limit_esums	"lower limits" of "window"-comparator 2 for φ .
diff_phi_upper_limit	"upper limit" of "window"-comparator for comparison of differences in φ (hex value).
diff_phi_lower_limit	"lower limit" of "window"-comparator for comparison of differences in φ (hex value).
DETA_DPFI_VECTOR_WIDTH	vector width of $\Delta\varphi$.
DETA_DPFI_PRECISION	position after decimal point for DPHI.
mass_upper_limit	"upper limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
mass_lower_limit	"lower limit" of "window"-comparator for comparison of $\frac{M^2}{2}$ (hex value).
MASS_PRECISION	position after decimal point for $\frac{M^2}{2}$.
pt1_width	number of bits of pt1.
pt2_width	number of bits of pt2.
MASS_COSH_COS_PRECISION	position after decimal point for $\cos(\Delta\varphi)$.
cosh_cos_width	number of bits for the maximum value in the LUT for $\cos(\Delta\varphi)$.
pt_sq_threshold	threshold value for comparison in two-body pt (pt^2).
sin_cos_width_1	number of bits for the maximum value in the LUT for $\cos(\varphi)$ and $\sin(\varphi)$ of muon.
sin_cos_width_2	number of bits for the maximum value in the LUT for $\cos(\varphi)$ and $\sin(\varphi)$ of esums.
PT_PRECISION	position after decimal point for pt^2 .
PT_SQ_SIN_COS_PRECISION	position after decimal point for $\cos(\varphi)$ and $\sin(\varphi)$.
lhclck	clock input (LHC clock).
muon_data_i	muon input data.
esums_data_i	esums input data, structure defined with obj_type_esums.
diff_phi	differences in φ , calculated in an instance of module sub_phi_integer_obj_vs_obj.vhd in top-of-hierarchy module (gtl_module.vhd).
pt1	muon E_T values [from LUT, in $GeV \times 10$].
pt2	esums E_T values [from LUT, in $GeV \times 10$].

Table 29: Explanation of Listing 10

Item	Explanation
<code>cos_dphi</code>	$\cos(\Delta\varphi)$ values from LUT.
<code>cos_phi_1</code>	$\cos(\varphi)$ values from LUT for muon.
<code>cos_phi_2</code>	$\cos(\varphi)$ values from LUT for esums.
<code>sin_phi_1</code>	$\sin(\varphi)$ values from LUT for muon.
<code>sin_phi_2</code>	$\sin(\varphi)$ values from LUT for esums.
<code>condition_o</code>	output of condition (routed to Algorithms logic, see 3.4.11).

3.4.9.2.6 Calo Calo Overlap Remover Correlation condition module

The Calo Calo Overlap Remover Correlation conditions consists of two modes. One with a Calo Calo Correlation condition with "Double objects requirement condition" for calo objects of same type and same bunch-crossing (3.4.9.2.1) and a single condition for a different calo object type (can have different bunch-crossing too). There has to be at least one correlation cut for the objects of "Double objects requirement condition" and a correlation cut for overlap removal between objects (one or more cut(s) of $\Delta\eta$, $\Delta\varphi$ and ΔR) of different object types ("2plus1"). A second mode ("1plus1") with a Calo Calo Correlation condition with a single condition and a different calo object type (can have different bunch-crossing too) also with a single condition. There has to be at least one correlation cut for the different objects (e.g. invariant mass) and a correlation cut for overlap removal between the objects (one or more cut(s) of $\Delta\eta$, $\Delta\varphi$ and ΔR).

Overlap Remover Correlation conditions `calo_calocalo_correlation_orm_condition.vhd` are implemented only for calo object types.

3.4.10 External Conditions

Maximal 256 External Conditions are possible in Global Trigger. They are provided as inputs in the Algorithms logic of μ GTL. External Conditions will include the "Technical Trigger" of the legacy system.

3.4.11 Algorithms logic

The outputs of all the instantiated conditions are combined in the Algorithms logic with boolean algebra given by TME for every single Algorithm. These Algorithms are registered and provided as inputs for Final Decision Logic.

3.5 VHDL-Templates for VHDL-Producer

The VHDL-Producer software generates a set of VHDL files (`gtl_module_instances.vhd`, `gtl_module_signals.vhd`, `ugt_constants.vhd` and `algo_index.vhd`) which contain the requirements of a certain L1Menu, set in the TME. The templates are created in "Jinja2" (a template engine for python). All the templates described in this section, are located in:

```
../cactusprojects/utm/tmVhdlProducer/templates/vhdl.
```

Insert new text !!!

3.5.1 Calorimeter conditions - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating `calo_conditions.vhd` is given below (see Listing 13).

Listing 13: Template of `calo_conditions.vhd` for VHDL-Producer

```
{%- block instantiate_calorimeter_condition %}
{%- set o1 = condition.objects[0] %}
{%- set o2 = condition.objects[1] %}
{%- set o3 = condition.objects[2] %}
{%- set o4 = condition.objects[3] %}

{{ condition.vhdl_signal }}_i: entity work.calorimeter_conditions
  generic map(({{ o1.sliceLow }}), {{ o1.sliceHigh }}), {{ o2.sliceLow }}), {{ o2.
    sliceHigh }}), {{ o3.sliceLow }}), {{ o3.sliceHigh }}), {{ o4.sliceLow }}), {{
    o4.sliceHigh }}),
  {{ condition.nr_objects }}), {{ o1.operator }}), {{ o1.type }}_TYPE,
  (X"{{ o1.threshold|X04 }}" , X"{{ o2.threshold|X04 }}" , X"{{ o3.threshold|
    X04 }}" , X"{{ o4.threshold|X04 }}"),
  (({{ o1.etaNrCuts }}), {{ o2.etaNrCuts }}), {{ o3.etaNrCuts }}), {{ o4.
    etaNrCuts }}),
  (X"{{ o1.etaW1UpperLimit|X04 }}" , X"{{ o2.etaW1UpperLimit|X04 }}" , X"{{
    o3.etaW1UpperLimit|X04 }}" , X"{{ o4.etaW1UpperLimit|X04 }}"), (X"{{ o1
    .etaW1LowerLimit|X04 }}" , X"{{ o2.etaW1LowerLimit|X04 }}" , X"{{ o3.
    etaW1LowerLimit|X04 }}" , X"{{ o4.etaW1LowerLimit|X04 }}"),
  (X"{{ o1.etaW2UpperLimit|X04 }}" , X"{{ o2.etaW2UpperLimit|X04 }}" , X"{{
    o3.etaW2UpperLimit|X04 }}" , X"{{ o4.etaW2UpperLimit|X04 }}"), (X"{{ o1
    .etaW2LowerLimit|X04 }}" , X"{{ o2.etaW2LowerLimit|X04 }}" , X"{{ o3.
    etaW2LowerLimit|X04 }}" , X"{{ o4.etaW2LowerLimit|X04 }}"),
  (X"{{ o1.etaW3UpperLimit|X04 }}" , X"{{ o2.etaW3UpperLimit|X04 }}" , X"{{
    o3.etaW3UpperLimit|X04 }}" , X"{{ o4.etaW3UpperLimit|X04 }}"), (X"{{ o1
    .etaW3LowerLimit|X04 }}" , X"{{ o2.etaW3LowerLimit|X04 }}" , X"{{ o3.
    etaW3LowerLimit|X04 }}" , X"{{ o4.etaW3LowerLimit|X04 }}"),
  (X"{{ o1.etaW4UpperLimit|X04 }}" , X"{{ o2.etaW4UpperLimit|X04 }}" , X"{{
    o3.etaW4UpperLimit|X04 }}" , X"{{ o4.etaW4UpperLimit|X04 }}"), (X"{{ o1
    .etaW4LowerLimit|X04 }}" , X"{{ o2.etaW4LowerLimit|X04 }}" , X"{{ o3.
    etaW4LowerLimit|X04 }}" , X"{{ o4.etaW4LowerLimit|X04 }}"),
  (X"{{ o1.etaW5UpperLimit|X04 }}" , X"{{ o2.etaW5UpperLimit|X04 }}" , X"{{
    o3.etaW5UpperLimit|X04 }}" , X"{{ o4.etaW5UpperLimit|X04 }}"), (X"{{ o1
    .etaW5LowerLimit|X04 }}" , X"{{ o2.etaW5LowerLimit|X04 }}" , X"{{ o3.
    etaW5LowerLimit|X04 }}" , X"{{ o4.etaW5LowerLimit|X04 }}"),
```

```
(( { o1.phiFullRange } }, { { o2.phiFullRange } }, { { o3.phiFullRange } }, { {
    o4.phiFullRange } } ),
(X"{{ o1.phiW1UpperLimit|X04 }}", X"{{ o2.phiW1UpperLimit|X04 }}", X"{{
    o3.phiW1UpperLimit|X04 }}", X"{{ o4.phiW1UpperLimit|X04 }}"), (X"{{ o1
    .phiW1LowerLimit|X04 }}", X"{{ o2.phiW1LowerLimit|X04 }}", X"{{ o3.
    phiW1LowerLimit|X04 }}", X"{{ o4.phiW1LowerLimit|X04 }}"),
(({ o1.phiW2Ignore } }, { { o2.phiW2Ignore } }, { { o3.phiW2Ignore } }, { { o4.
    phiW2Ignore } } ),
(X"{{ o1.phiW2UpperLimit|X04 }}", X"{{ o2.phiW2UpperLimit|X04 }}", X"{{
    o3.phiW2UpperLimit|X04 }}", X"{{ o4.phiW2UpperLimit|X04 }}"), (X"{{ o1
    .phiW2LowerLimit|X04 }}", X"{{ o2.phiW2LowerLimit|X04 }}", X"{{ o3.
    phiW2LowerLimit|X04 }}", X"{{ o4.phiW2LowerLimit|X04 }}"),
(X"{{ o1.isolationLUT|X01 }}", X"{{ o2.isolationLUT|X01 }}", X"{{ o3.
    isolationLUT|X01 }}", X"{{ o4.isolationLUT|X01 }}"),
{%- if condition.twoBodyPt.enabled == "true" %}
true, { { o1.type|upper } }_PT_VECTOR_WIDTH, X"{{ condition.twoBodyPt.
    threshold|X16 }}",
CALO_SIN_COS_VECTOR_WIDTH, { { o1.type|upper } }_{ { o1.type|upper } }
    _SIN_COS_PRECISION
{%- else %}
false
{%- endif %}
)
port map(lhc_clk, { { o1.type|lower } }_bx_{ { o1.bx } },
{%- if condition.twoBodyPt.enabled == "true" %}
{ { condition.vhdl_signal } },
{ { o1.type|lower } }_pt_vector_bx_{ { o1.bx } }, { { o1.type|lower } }
    _cos_phi_bx_{ { o1.bx } }, { { o1.type|lower } }_sin_phi_bx_{ { o1.bx } });
{%- else %}
{ { condition.vhdl_signal } });
{%- endif %}

{% endblock instantiate_calo_condition %}
{# eof #}
```

Table 30: Explanation of Listing 13

Item	Explanation
vhdl_signal	condition name.
sliceLow	low value of an object slice.
sliceHigh	high value of an object slice.
nr_objects	valid values are 1 (for single), 2 (double), 3 (triple) and 4 (quad) - depending on condition type.
operator	valid strings are 'true' and 'false' - 'true' for greater/equal-, 'false' for equal-mode of E_T comparator.
type	valid strings are 'EG', 'JET', and 'TAU'.
threshold	array with requirements for <code>et_thresholds</code> (4x 16-bit values, hex notation). Valid values depending on the scales of E_T .
nrEtaWindows	array to set number of η cuts.
etaW1UpperLimit, ...	arrays of limits for "window"-comparators for η (4x 16-bit values, hex notation). Valid values depending on the scales for η .
phiFullRange	array to set full range of φ (4x boolean).
phiW1UpperLimit, ...	arrays of limits for "window"-comparators for φ (4x 16-bit values, hex notation). Valid values depending on the scales for φ .
[phiW2Ignore	array to ignore "window"-comparator 2 of φ (4x boolean).
isolationLUT	array for LUTs (4 bits) of isolation).
twoBodyPt.threshold	value of threshold for two-body pt comparison.
bx	valid strings are 'p2', 'p1', '0', 'm1' and 'm2'. This indicates which data in a range of plus/minus 2 bunch-crossing is used in the condition.

3.5.2 Energy sum quantities conditions - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating `esums_conditions.vhd` is given below (see Listing 14).

Listing 14: Template of `esums_conditions.vhd` for VHDL-Producer

```
{%- block instantiate_esums_condition %}
  {%- set o = condition.objects[0] %}
  {%- if o.is_esums_type %}
{{ condition.vhdl_signal }}_i: entity work.esums_conditions
  generic map(({ o.operator }}, {{ o.type|upper }}_TYPE,
  {%- if o.hasCount %}
    X"{{ o.count|X04 }}",
  {%- else %}
    X"{{ o.threshold|X04 }}",
  {%- endif %}
    {{ o.phiFullRange }}, X"{{ o.phiW1UpperLimit|X04 }}", X"{{ o.
      phiW1LowerLimit|X04 }}",
    {{ o.phiW2Ignore }}, X"{{ o.phiW2UpperLimit|X04 }}", X"{{ o.
      phiW2LowerLimit|X04 }}"
  )
  port map(lhc_clk, {{ o.type|lower }}_bx_{{ o.bx }}, {{ condition.vhdl_signal
    }});
  {%- endif %}
{% endblock instantiate_esums_condition %}
{# eof #}
```

Table 31: Explanation of Listing 14

Item	Explanation
<code>vhdl_signal</code>	condition name.
<code>operator</code>	valid strings are 'true' and 'false' - 'true' for greater/equal-, 'false' for equal-mode of E_T comparator.
<code>type</code>	valid strings are 'EG', 'JET', and 'TAU'.
<code>threshold</code>	array with requirements for <code>et_thresholds</code> (4x 16-bit values, hex notation). Valid values depending on the scales of E_T .
<code>phiFullRange</code>	array to set full range of φ (4x boolean).
<code>phiW1UpperLimit, ...</code>	arrays of limits for "window"-comparators for φ (4x 16-bit values, hex notation). Valid values depending on the scales for φ .
<code>phiW2Ignore</code>	array to ignore "window"-comparator 2 of φ (4x boolean).
<code>bx</code>	valid strings are 'p2', 'p1', '0', 'm1' and 'm2'. This indicates which data in a range of plus/minus 2 bunch-crossing is used in the condition.

3.5.3 Muon conditions - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating

muon_conditions.vhd

is given below (see Listing 15).

Listing 15: Template of muon_conditions.vhd for VHDL-Producer

```
{%- block instantiate_muon_condition %}
  {%- set o1 = condition.objects[0] %}
  {%- set o2 = condition.objects[1] %}
  {%- set o3 = condition.objects[2] %}
  {%- set o4 = condition.objects[3] %}
  {%- set bx = o1.bx %}
  {{ condition.vhdl_signal }}_i: entity work.muon_conditions
    generic map(({ o1.sliceLow }}, {{ o1.sliceHigh }}, {{ o2.sliceLow }}, {{ o2.
      sliceHigh }}, {{ o3.sliceLow }}, {{ o3.sliceHigh }}, {{ o4.sliceLow }}, {{
      o4.sliceHigh }}},
    {{ condition.nr_objects }}, {{ o1.operator }},
    (X"{{ o1.threshold|X04 }}" , X"{{ o2.threshold|X04 }}" , X"{{ o3.threshold|
      X04 }}" , X"{{ o4.threshold|X04 }}" ),
    ({{ o1.etaNrCuts }}, {{ o2.etaNrCuts }}, {{ o3.etaNrCuts }}, {{ o4.
      etaNrCuts }}),
    (X"{{ o1.etaW1UpperLimit|X04 }}" , X"{{ o2.etaW1UpperLimit|X04 }}" , X"{{
      o3.etaW1UpperLimit|X04 }}" , X"{{ o4.etaW1UpperLimit|X04 }}" ), (X"{{ o1
      .etaW1LowerLimit|X04 }}" , X"{{ o2.etaW1LowerLimit|X04 }}" , X"{{ o3.
      etaW1LowerLimit|X04 }}" , X"{{ o4.etaW1LowerLimit|X04 }}" ),
    (X"{{ o1.etaW2UpperLimit|X04 }}" , X"{{ o2.etaW2UpperLimit|X04 }}" , X"{{
      o3.etaW2UpperLimit|X04 }}" , X"{{ o4.etaW2UpperLimit|X04 }}" ), (X"{{ o1
      .etaW2LowerLimit|X04 }}" , X"{{ o2.etaW2LowerLimit|X04 }}" , X"{{ o3.
      etaW2LowerLimit|X04 }}" , X"{{ o4.etaW2LowerLimit|X04 }}" ),
    (X"{{ o1.etaW3UpperLimit|X04 }}" , X"{{ o2.etaW3UpperLimit|X04 }}" , X"{{
      o3.etaW3UpperLimit|X04 }}" , X"{{ o4.etaW3UpperLimit|X04 }}" ), (X"{{ o1
      .etaW3LowerLimit|X04 }}" , X"{{ o2.etaW3LowerLimit|X04 }}" , X"{{ o3.
      etaW3LowerLimit|X04 }}" , X"{{ o4.etaW3LowerLimit|X04 }}" ),
    (X"{{ o1.etaW4UpperLimit|X04 }}" , X"{{ o2.etaW4UpperLimit|X04 }}" , X"{{
      o3.etaW4UpperLimit|X04 }}" , X"{{ o4.etaW4UpperLimit|X04 }}" ), (X"{{ o1
      .etaW4LowerLimit|X04 }}" , X"{{ o2.etaW4LowerLimit|X04 }}" , X"{{ o3.
      etaW4LowerLimit|X04 }}" , X"{{ o4.etaW4LowerLimit|X04 }}" ),
    (X"{{ o1.etaW5UpperLimit|X04 }}" , X"{{ o2.etaW5UpperLimit|X04 }}" , X"{{
      o3.etaW5UpperLimit|X04 }}" , X"{{ o4.etaW5UpperLimit|X04 }}" ), (X"{{ o1
      .etaW5LowerLimit|X04 }}" , X"{{ o2.etaW5LowerLimit|X04 }}" , X"{{ o3.
      etaW5LowerLimit|X04 }}" , X"{{ o4.etaW5LowerLimit|X04 }}" ),
    ({{ o1.phiFullRange }}, {{ o2.phiFullRange }}, {{ o3.phiFullRange }}, {{
      o4.phiFullRange }}),
    (X"{{ o1.phiW1UpperLimit|X04 }}" , X"{{ o2.phiW1UpperLimit|X04 }}" , X"{{
      o3.phiW1UpperLimit|X04 }}" , X"{{ o4.phiW1UpperLimit|X04 }}" ), (X"{{ o1
      .phiW1LowerLimit|X04 }}" , X"{{ o2.phiW1LowerLimit|X04 }}" , X"{{ o3.
      phiW1LowerLimit|X04 }}" , X"{{ o4.phiW1LowerLimit|X04 }}" ),
    ({{ o1.phiW2Ignore }}, {{ o2.phiW2Ignore }}, {{ o3.phiW2Ignore }}, {{ o4.
      phiW2Ignore }}),
    (X"{{ o1.phiW2UpperLimit|X04 }}" , X"{{ o2.phiW2UpperLimit|X04 }}" , X"{{
      o3.phiW2UpperLimit|X04 }}" , X"{{ o4.phiW2UpperLimit|X04 }}" ), (X"{{ o1
      .phiW2LowerLimit|X04 }}" , X"{{ o2.phiW2LowerLimit|X04 }}" , X"{{ o3.
      phiW2LowerLimit|X04 }}" , X"{{ o4.phiW2LowerLimit|X04 }}" ),
```

```

    ("{{ o1.charge }}", "{{ o2.charge }}", "{{ o3.charge }}", "{{ o4.charge }}"),
    (X"{{ o1.qualityLUT|X04 }}", X"{{ o2.qualityLUT|X04 }}", X"{{ o3.qualityLUT|X04 }}", X"{{ o4.qualityLUT|X04 }}"),
    (X"{{ o1.isolationLUT|X01 }}", X"{{ o2.isolationLUT|X01 }}", X"{{ o3.isolationLUT|X01 }}", X"{{ o4.isolationLUT|X01 }}"),
    ({{ o1.uptCutSel }}, {{ o2.uptCutSel }}, {{ o3.uptCutSel }}, {{ o4.uptCutSel }}),
    (X"{{ o1.uptUpperLimit|X04 }}", X"{{ o2.uptUpperLimit|X04 }}", X"{{ o3.uptUpperLimit|X04 }}", X"{{ o4.uptUpperLimit|X04 }}"),
    (X"{{ o1.uptLowerLimit|X04 }}", X"{{ o2.uptLowerLimit|X04 }}", X"{{ o3.uptLowerLimit|X04 }}", X"{{ o4.uptLowerLimit|X04 }}"),
    (X"{{ o1.impactParameterLUT|X01 }}", X"{{ o2.impactParameterLUT|X01 }}", X"{{ o3.impactParameterLUT|X01 }}", X"{{ o4.impactParameterLUT|X01 }}"),
    ),
    "{{ condition.chargeCorrelation }}",
    {%- if condition.twoBodyPt.enabled == "true" %}
        true, {{ o1.type|upper }}_PT_VECTOR_WIDTH, X"{{ condition.twoBodyPt.threshold|X16 }}",
        MUON_SIN_COS_VECTOR_WIDTH, {{ o1.type|upper }}_{{ o1.type|upper }}_SIN_COS_PRECISION
    {%- else %}
        false
    {%- endif %}
    )
    port map(lhc_clk, mu_bx_{{ bx }},
    {%- if condition.nr_objects >= 2 and condition.twoBodyPt.enabled == "true" %}
        {{ condition.vhdl_signal }},
        ls_charcorr_double_bx_{{ bx }}_bx_{{ bx }}, os_charcorr_double_bx_{{ bx }}_bx_{{ bx }},
        ls_charcorr_triple_bx_{{ bx }}_bx_{{ bx }}, os_charcorr_triple_bx_{{ bx }}_bx_{{ bx }},
        ls_charcorr_quad_bx_{{ bx }}_bx_{{ bx }}, os_charcorr_quad_bx_{{ bx }}_bx_{{ bx }},
        {{ o1.type|lower }}_pt_vector_bx_{{ o1.bx }}, {{ o1.type|lower }}_cos_phi_bx_{{ o1.bx }}, {{ o1.type|lower }}_sin_phi_bx_{{ o1.bx }});
    {%- elif condition.nr_objects >= 2 and condition.twoBodyPt.enabled == "false" %}
        {{ condition.vhdl_signal }},
        ls_charcorr_double_bx_{{ bx }}_bx_{{ bx }}, os_charcorr_double_bx_{{ bx }}_bx_{{ bx }},
        ls_charcorr_triple_bx_{{ bx }}_bx_{{ bx }}, os_charcorr_triple_bx_{{ bx }}_bx_{{ bx }},
        ls_charcorr_quad_bx_{{ bx }}_bx_{{ bx }}, os_charcorr_quad_bx_{{ bx }}_bx_{{ bx }});
    {%- elif condition.nr_objects == 1 and condition.twoBodyPt.enabled == "true" %}
        {{ condition.vhdl_signal }},
        {{ o1.type|lower }}_pt_vector_bx_{{ o1.bx }}, {{ o1.type|lower }}_cos_phi_bx_{{ o1.bx }}, {{ o1.type|lower }}_sin_phi_bx_{{ o1.bx }});
    {%- else %}
        {{ condition.vhdl_signal }});
    {%- endif %}
    {% endblock instantiate_muon_condition %}
    {# eof #}

```

Table 32: Explanation of Listing 15

Item	Explanation
<code>vhdl_signal</code>	condition name.
<code>sliceLow</code>	low value of an object slice.
<code>sliceHigh</code>	high value of an object slice.
<code>nr_objects</code>	valid values are 1 (for single), 2 (double), 3 (triple) and 4 (quad) - depending on condition type.
<code>operator</code>	valid strings are 'true' and 'false' - 'true' for greater/equal-, 'false' for equal-mode of E_T comparator.
<code>type</code>	valid strings are 'EG', 'JET', and 'TAU'.
<code>threshold</code>	array with requirements for <code>et_thresholds</code> (4x 16-bit values, hex notation). Valid values depending on the scales of E_T .
<code>nrEtaWindows</code>	array to set number of η cuts.
<code>etaW1UpperLimit, ...</code>	arrays of limits for "window"-comparators for η (4x 16-bit values, hex notation). Valid values depending on the scales for η .
<code>phiFullRange</code>	array to set full range of φ (4x boolean).
<code>phiW1UpperLimit, ...</code>	arrays of limits for "window"-comparators for φ (4x 16-bit values, hex notation). Valid values depending on the scales for φ .
<code>[phiW2Ignore</code>	array to ignore "window"-comparator 2 of φ (4x boolean).
<code>charge</code>	array for requested charge (4x strings). Valid strings are 'pos' ("positive charge") and 'neg' ("negative charge") and 'ign' ("ignore").
<code>qualityLUT</code>	array for LUTs (16 bits) of quality.
<code>isolationLUT</code>	array for LUTs (4 bits) of isolation).
<code>twoBodyPt.threshold</code>	value of threshold for two-body pt comparison.
<code>bx</code>	valid strings are 'p2', 'p1', '0', 'm1' and 'm2'. This indicates which data in a range of plus/minus 2 bunch-crossing is used in the condition.

3.5.4 Calo Calo Correlation condition - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating

calo_calor_correlation_condition.vhd

is given below (see Listing 16).

Listing 16: Template of calo_calor_correlation_condition.vhd for VHDL-Producer

```
{%- block instantiate_calor_calor_correlation_condition %}
  {%- set o1 = condition.objects[0] %}
  {%- set o2 = condition.objects[1] %}
  {{ condition.vhdl_signal }}_i: entity work.calor_calor_correlation_condition
    generic map(
      {{ condition.objectsInSameBx }},
      {{ condition.deltaEta.enabled }}, {{ condition.deltaPhi.enabled }}, {{
        condition.deltaR.enabled }}, {{ condition.mass.enabled }}, {{
        condition.mass.type }}, {{ condition.twoBodyPt.enabled }},
      {{ o1.sliceLow }}, {{ o1.sliceHigh }}, {{ o1.operator }}, {{ o1.type|
        upper }}_TYPE,
      X"{{ o1.threshold|X04 }}",
      {{ o1.etaNrCuts }},
      X"{{ o1.etaW1UpperLimit|X04 }}", X"{{ o1.etaW1LowerLimit|X04 }}",
      X"{{ o1.etaW2UpperLimit|X04 }}", X"{{ o1.etaW2LowerLimit|X04 }}",
      X"{{ o1.etaW3UpperLimit|X04 }}", X"{{ o1.etaW3LowerLimit|X04 }}",
      X"{{ o1.etaW4UpperLimit|X04 }}", X"{{ o1.etaW4LowerLimit|X04 }}",
      X"{{ o1.etaW5UpperLimit|X04 }}", X"{{ o1.etaW5LowerLimit|X04 }}",
      {{ o1.phiFullRange }}, X"{{ o1.phiW1UpperLimit|X04 }}", X"{{ o1.
        phiW1LowerLimit|X04 }}",
      {{ o1.phiW2Ignore }}, X"{{ o1.phiW2UpperLimit|X04 }}", X"{{ o1.
        phiW2LowerLimit|X04 }}",
      X"{{ o1.isolationLUT|X01 }}",
      {{ o2.sliceLow }}, {{ o2.sliceHigh }}, {{ o2.operator }}, {{ o2.type|
        upper }}_TYPE,
      X"{{ o2.threshold|X04 }}",
      {{ o2.etaNrCuts }},
      X"{{ o2.etaW1UpperLimit|X04 }}", X"{{ o2.etaW1LowerLimit|X04 }}",
      X"{{ o2.etaW2UpperLimit|X04 }}", X"{{ o2.etaW2LowerLimit|X04 }}",
      X"{{ o2.etaW3UpperLimit|X04 }}", X"{{ o2.etaW3LowerLimit|X04 }}",
      X"{{ o2.etaW4UpperLimit|X04 }}", X"{{ o2.etaW4LowerLimit|X04 }}",
      X"{{ o2.etaW5UpperLimit|X04 }}", X"{{ o2.etaW5LowerLimit|X04 }}",
      {{ o2.phiFullRange }}, X"{{ o2.phiW1UpperLimit|X04 }}", X"{{ o2.
        phiW1LowerLimit|X04 }}",
      {{ o2.phiW2Ignore }}, X"{{ o2.phiW2UpperLimit|X04 }}", X"{{ o2.
        phiW2LowerLimit|X04 }}",
      X"{{ o2.isolationLUT|X01 }}",
      X"{{ condition.deltaEta.upper|X08 }}", X"{{ condition.deltaEta.lower|X08
        }}",
      X"{{ condition.deltaPhi.upper|X08 }}", X"{{ condition.deltaPhi.lower|X08
        }}",
      X"{{ condition.deltaR.upper|X16 }}", X"{{ condition.deltaR.lower|X16 }}",
      X"{{ condition.mass.upper|X16 }}", X"{{ condition.mass.lower|X16 }}",
      {{ o1.type|upper }}_PT_VECTOR_WIDTH, {{ o2.type|upper }}_PT_VECTOR_WIDTH,
      {{ o1.type|upper }}_{{ o2.type|upper }}_COSH_COS_PRECISION, {{ o1.
        type|upper }}_{{ o2.type|upper }}_COSH_COS_VECTOR_WIDTH,
      X"{{ condition.twoBodyPt.threshold|X16 }}", CALO_SIN_COS_VECTOR_WIDTH, {{
        o1.type|upper }}_{{ o2.type|upper }}_SIN_COS_PRECISION
```

```

)
port map(lhc_clk, {{ o1.type|lower }}_bx_{{ o1.bx }}, {{ o2.type|lower }}_bx_
{{ o2.bx }},
diff_{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx
}}_eta_vector, diff_{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.
bx }}_bx_{{ o2.bx }}_phi_vector,
{{ o1.type|lower }}_pt_vector_bx_{{ o1.bx }}, {{ o2.type|lower }}
_pt_vector_bx_{{ o2.bx }},
{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx }}
_cosh_deta_vector, {{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx
}}_bx_{{ o2.bx }}_cos_dphi_vector,
{{ o1.type|lower }}_cos_phi_bx_{{ o1.bx }}, {{ o2.type|lower }}
_cos_phi_bx_{{ o2.bx }}, {{ o1.type|lower }}_sin_phi_bx_{{ o1.bx }},
{{ o2.type|lower }}_sin_phi_bx_{{ o2.bx }},
{{ condition.vhdl_signal }}});
{%- endblock instantiate_calorimeter_correlation_condition %}
{# eof #}

```

Table 33: Explanation of Listing 16

Item	Explanation
vhdl_signal	condition name.
objectsInSameBx	valid strings are 'true' and 'false' - 'true' for data with same Bx.
deltaEta.enabled	valid strings are 'true' and 'false' - 'true' for use of DETA.
deltaPhi.enabled	valid strings are 'true' and 'false' - 'true' for use of DPHI.
deltaR.enabled	valid strings are 'true' and 'false' - 'true' for use of DR.
mass.enabled	valid strings are 'true' and 'false' - 'true' for use of MASS.
mass.type	valid strings are 'INVARIANT_MASS_TYPE' and 'TRANSVERSE_MASS_TYPE'.
twoBodyPt.enabled	valid strings are 'true' and 'false' - 'true' for use of two-body pt.
sliceLow	low value of an object slice.
sliceHigh	high value of an object slice.
operator	valid strings are 'true' and 'false' - 'true' for greater/equal-, 'false' for equal-mode of E_T comparator.
threshold	requirements for e_t thresholds (16-bit values, hex notation). Valid values depending on the scales of E_T .
nrEtaWindows	number of η cuts.
etaW1UpperLimit, ...	limits for "window"-comparators for η (4x 16-bit values, hex notation). Valid values depending on the scales for η .
phiFullRange	set full range of φ (boolean).
phiW1UpperLimit, ...	limits for "window"-comparators for φ (16-bit values, hex notation). Valid values depending on the scales for φ .
[phiW2Ignore	ignore "window"-comparator 2 of φ (boolean).
isolationLUT	LUT (4 bits) of isolation).
deltaEta.upper, ...	limits for "window"-comparator for comparison of differences in η (hex notation). Valid values depending on the scales for η .

Table 33: Explanation of Listing 16

Item	Explanation
<code>deltaPhi.upper, ...</code>	limits for "window"-comparator for comparison of differences in φ (hex notation). Valid values depending on the scales for φ .
<code>deltaR.upper, ...</code>	limits for "window"-comparator for comparison of ΔR^2 (hex notation).
<code>mass.upper, ...</code>	limits for "window"-comparator for comparison of $\frac{M^2}{2}$ (hex notation).
<code>twoBodyPt.threshold</code>	value of threshold for two-body pt comparison.
<code>bx</code>	valid strings are 'p2', 'p1', '0', 'm1' and 'm2'. This indicates which data in a range of plus/minus 2 bunch-crossing is used in the condition.

3.5.5 Calo Muon Correlation condition - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating

calo_muon_correlation_condition.vhd

is given below (see Listing 17).

Listing 17: Template of calo_muon_correlation_condition.vhd for VHDL-Producer

```
{%- block instantiate_calor_muon_correlation_condition %}
  {%- set o1 = condition.objects[0] %}
  {%- set o2 = condition.objects[1] %}
  {{ condition.vhdl_signal }}_i: entity work.calor_muon_correlation_condition
    generic map(
      {{ condition.deltaEta.enabled }}, {{ condition.deltaPhi.enabled }}, {{
        condition.deltaR.enabled }}, {{ condition.mass.enabled }}, {{
        condition.mass.type }}, {{ condition.twoBodyPt.enabled }},
      {{ o1.sliceLow }}, {{ o1.sliceHigh }}, {{ o1.operator }}, {{ o1.type|
        upper }}_TYPE,
      X"{{ o1.threshold|X04 }}",
      {{ o1.etaNrCuts }},
      X"{{ o1.etaW1UpperLimit|X04 }}", X"{{ o1.etaW1LowerLimit|X04 }}",
      X"{{ o1.etaW2UpperLimit|X04 }}", X"{{ o1.etaW2LowerLimit|X04 }}",
      X"{{ o1.etaW3UpperLimit|X04 }}", X"{{ o1.etaW3LowerLimit|X04 }}",
      X"{{ o1.etaW4UpperLimit|X04 }}", X"{{ o1.etaW4LowerLimit|X04 }}",
      X"{{ o1.etaW5UpperLimit|X04 }}", X"{{ o1.etaW5LowerLimit|X04 }}",
      {{ o1.phiFullRange }}, X"{{ o1.phiW1UpperLimit|X04 }}", X"{{ o1.
        phiW1LowerLimit|X04 }}",
      {{ o1.phiW2Ignore }}, X"{{ o1.phiW2UpperLimit|X04 }}", X"{{ o1.
        phiW2LowerLimit|X04 }}",
      X"{{ o1.isolationLUT|X01 }}",
      {{ o2.sliceLow }}, {{ o2.sliceHigh }}, {{ o2.operator }},
      X"{{ o2.threshold|X04 }}",
      {{ o2.etaNrCuts }},
      X"{{ o2.etaW1UpperLimit|X04 }}", X"{{ o2.etaW1LowerLimit|X04 }}",
      X"{{ o2.etaW2UpperLimit|X04 }}", X"{{ o2.etaW2LowerLimit|X04 }}",
      X"{{ o2.etaW3UpperLimit|X04 }}", X"{{ o2.etaW3LowerLimit|X04 }}",
      X"{{ o2.etaW4UpperLimit|X04 }}", X"{{ o2.etaW4LowerLimit|X04 }}",
      X"{{ o2.etaW5UpperLimit|X04 }}", X"{{ o2.etaW5LowerLimit|X04 }}",
      {{ o2.phiFullRange }}, X"{{ o2.phiW1UpperLimit|X04 }}", X"{{ o2.
        phiW1LowerLimit|X04 }}",
      {{ o2.phiW2Ignore }}, X"{{ o2.phiW2UpperLimit|X04 }}", X"{{ o2.
        phiW2LowerLimit|X04 }}",
      X"{{ o2.charge }}", X"{{ o2.qualityLUT|X04 }}", X"{{ o2.isolationLUT|X01
        }}",
      {{ o2.uptCutSel }}, X"{{ o2.uptUpperLimit|X04 }}", X"{{ o2.uptLowerLimit|
        X04 }}", X"{{ o2.impactParameterLUT|X01 }}",
      X"{{ condition.deltaEta.upper|X08 }}", X"{{ condition.deltaEta.lower|X08
        }}",
      X"{{ condition.deltaPhi.upper|X08 }}", X"{{ condition.deltaPhi.lower|X08
        }}",
      X"{{ condition.deltaR.upper|X16 }}", X"{{ condition.deltaR.lower|X16 }}",
      X"{{ condition.mass.upper|X16 }}", X"{{ condition.mass.lower|X16 }}",
      {{ o1.type|upper }}_PT_VECTOR_WIDTH, {{ o2.type|upper }}_PT_VECTOR_WIDTH,
      {{ o1.type|upper }}_{{ o2.type|upper }}_COSH_COS_PRECISION, {{ o1.
        type|upper }}_{{ o2.type|upper }}_COSH_COS_VECTOR_WIDTH,
```



```

X"{{ condition.twoBodyPt.threshold|X16 }}", MUON_SIN_COS_VECTOR_WIDTH, {{
    o1.type|upper }}_{{ o2.type|upper }}_SIN_COS_PRECISION
)
port map(lhc_clk, {{ o1.type|lower }}_bx_{{ o1.bx }}({{ o1.sliceLow }} to {{
    o1.sliceHigh }}), {{ o2.type|lower }}_bx_{{ o2.bx }}({{ o2.sliceLow }} to
    {{ o2.sliceHigh }}),
    diff_{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx
        }}_eta_vector, diff_{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.
            bx }}_bx_{{ o2.bx }}_phi_vector,
    {{ o1.type|lower }}_pt_vector_bx_{{ o1.bx }}, {{ o2.type|lower }}
        _pt_vector_bx_{{ o2.bx }},
    {{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx }}
        _cosh_deta_vector, {{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx
            }}_bx_{{ o2.bx }}_cos_dphi_vector,
    conv_{{ o1.type|lower }}_cos_phi_bx_{{ o1.bx }}, {{ o2.type|lower }}
        _cos_phi_bx_{{ o2.bx }}, conv_{{ o1.type|lower }}_sin_phi_bx_{{ o1.bx
            }}, {{ o2.type|lower }}_sin_phi_bx_{{ o2.bx }},
    {{ condition.vhdl_signal }}});
{%- endblock instantiate_calor_muon_correlation_condition %}
{# eof #}

```

Table 34: Explanation of Listing 17

Item	Explanation
vhdl_signal	condition name.
deltaEta.enabled	valid strings are 'true' and 'false' - 'true' for use of DETA.
deltaPhi.enabled	valid strings are 'true' and 'false' - 'true' for use of DPHI.
deltaR.enabled	valid strings are 'true' and 'false' - 'true' for use of DR.
mass.enabled	valid strings are 'true' and 'false' - 'true' for use of MASS.
mass.type	valid strings are 'INVARIANT_MASS_TYPE' and 'TRANSVERSE_MASS_TYPE'.
twoBodyPt.enabled	valid strings are 'true' and 'false' - 'true' for use of two-body pt.
sliceLow	low value of an object slice.
sliceHigh	high value of an object slice.
operator	valid strings are 'true' and 'false' - 'true' for greater/equal-, 'false' for equal-mode of E_T comparator.
threshold	requirements for <code>et_thresholds</code> and <code>pt_thresholds</code> (16-bit values, hex notation). Valid values depending on the scales of E_T .
nrEtaWindows	number of η cuts.
etaW1UpperLimit, ...	limits for "window"-comparators for η (4x 16-bit values, hex notation). Valid values depending on the scales for η .
phiFullRange	set full range of φ (boolean).
phiW1UpperLimit, ...	limits for "window"-comparators for φ (16-bit values, hex notation). Valid values depending on the scales for φ .
[phiW2Ignore	ignore "window"-comparator 2 of φ (boolean).
charge	requested charge. Valid strings are 'pos' ("positive charge") and 'neg' ("negative charge") and 'ign' ("ignore").
qualityLUT	LUT (16 bits) of quality.

Table 34: Explanation of Listing 17

Item	Explanation
isolationLUT	LUT (4 bits) of isolation).
uptCutSel	set use of unconstraint p_T .
uptUpperLimit, ...	limits for unconstraint p_T .
impactParameterLUT	LUT (4 bits) of impact parameter).
deltaEta.upper, ...	limits for "window"-comparator for comparison of differences in η (hex notation). Valid values depending on the scales for η .
deltaPhi.upper, ...	limits for "window"-comparator for comparison of differences in φ (hex notation). Valid values depending on the scales for φ .
deltaR.upper, ...	limits for "window"-comparator for comparison of ΔR^2 (hex notation).
mass.upper, ...	limits for "window"-comparator for comparison of $\frac{M^2}{2}$ (hex notation).
twoBodyPt.threshold	value of threshold for two-body pt comparison.
bx	valid strings are 'p2', 'p1', '0', 'm1' and 'm2'. This indicates which data in a range of plus/minus 2 bunch-crossing is used in the condition.

3.5.6 Muon Muon Correlation condition - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating

muon_muon_correlation_condition.vhd

is given below (see Listing 18).

Listing 18: Template of muon_muon_correlation_condition.vhd for VHDL-Producer

```
{%- block instantiate_muon_muon_correlation_condition %}
  {%- set o1 = condition.objects[0] %}
  {%- set o2 = condition.objects[1] %}
  {{ condition.vhdl_signal }}_i: entity work.muon_muon_correlation_condition
    generic map(
      {{ condition.objectsInSameBx }},
      {{ condition.deltaEta.enabled }}, {{ condition.deltaPhi.enabled }}, {{
        condition.deltaR.enabled }}, {{ condition.mass.enabled }}, {{
        condition.mass.type }}, {{ condition.twoBodyPt.enabled }},
      {{ o1.sliceLow }}, {{ o1.sliceHigh }}, {{ o1.operator }},
      X"{{ o1.threshold|X04 }}",
      {{ o1.etaNrCuts }},
      X"{{ o1.etaW1UpperLimit|X04 }}", X"{{ o1.etaW1LowerLimit|X04 }}",
      X"{{ o1.etaW2UpperLimit|X04 }}", X"{{ o1.etaW2LowerLimit|X04 }}",
      X"{{ o1.etaW3UpperLimit|X04 }}", X"{{ o1.etaW3LowerLimit|X04 }}",
      X"{{ o1.etaW4UpperLimit|X04 }}", X"{{ o1.etaW4LowerLimit|X04 }}",
      X"{{ o1.etaW5UpperLimit|X04 }}", X"{{ o1.etaW5LowerLimit|X04 }}",
      {{ o1.phiFullRange }}, X"{{ o1.phiW1UpperLimit|X04 }}", X"{{ o1.
        phiW1LowerLimit|X04 }}",
      {{ o1.phiW2Ignore }}, X"{{ o1.phiW2UpperLimit|X04 }}", X"{{ o1.
        phiW2LowerLimit|X04 }}",
      X"{{ o1.charge }}", X"{{ o1.qualityLUT|X04 }}", X"{{ o1.isolationLUT|X01
        }}",
      {{ o1.uptCutSel }}, X"{{ o1.uptUpperLimit|X04 }}", X"{{ o1.uptLowerLimit|
        X04 }}", X"{{ o1.impactParameterLUT|X01 }}",
      {{ o2.sliceLow }}, {{ o2.sliceHigh }}, {{ o2.operator }},
      X"{{ o2.threshold|X04 }}",
      {{ o2.etaNrCuts }},
      X"{{ o2.etaW1UpperLimit|X04 }}", X"{{ o2.etaW1LowerLimit|X04 }}",
      X"{{ o2.etaW2UpperLimit|X04 }}", X"{{ o2.etaW2LowerLimit|X04 }}",
      X"{{ o2.etaW3UpperLimit|X04 }}", X"{{ o2.etaW3LowerLimit|X04 }}",
      X"{{ o2.etaW4UpperLimit|X04 }}", X"{{ o2.etaW4LowerLimit|X04 }}",
      X"{{ o2.etaW5UpperLimit|X04 }}", X"{{ o2.etaW5LowerLimit|X04 }}",
      {{ o2.phiFullRange }}, X"{{ o2.phiW1UpperLimit|X04 }}", X"{{ o2.
        phiW1LowerLimit|X04 }}",
      {{ o2.phiW2Ignore }}, X"{{ o2.phiW2UpperLimit|X04 }}", X"{{ o2.
        phiW2LowerLimit|X04 }}",
      X"{{ o2.charge }}", X"{{ o2.qualityLUT|X04 }}", X"{{ o2.isolationLUT|X01
        }}",
      {{ o2.uptCutSel }}, X"{{ o2.uptUpperLimit|X04 }}", X"{{ o2.uptLowerLimit|
        X04 }}", X"{{ o2.impactParameterLUT|X01 }}",
      X"{{ condition.chargeCorrelation }}",
      X"{{ condition.deltaEta.upper|X08 }}", X"{{ condition.deltaEta.lower|X08
        }}",
      X"{{ condition.deltaPhi.upper|X08 }}", X"{{ condition.deltaPhi.lower|X08
        }}",
      X"{{ condition.deltaR.upper|X16 }}", X"{{ condition.deltaR.lower|X16 }}",
      X"{{ condition.mass.upper|X16 }}", X"{{ condition.mass.lower|X16 }}"
```

```

    {{ o1.type|upper }}_PT_VECTOR_WIDTH, {{ o1.type|upper }}_UPT_VECTOR_WIDTH
    , {{ o1.type|upper }}_{{ o2.type|upper }}_COSH_COS_PRECISION, {{ o1.
    type|upper }}_{{ o2.type|upper }}_COSH_COS_VECTOR_WIDTH,
    X"{{ condition.twoBodyPt.threshold|X16 }}" , MUON_SIN_COS_VECTOR_WIDTH, {{
    o1.type|upper }}_{{ o2.type|upper }}_SIN_COS_PRECISION
)
port map(lhc_clk, {{ o1.type|lower }}_bx_{{ o1.bx }}, {{ o2.type|lower }}_bx_
{{ o2.bx }},
ls_charcorr_double_bx_{{ o1.bx }}_bx_{{ o2.bx }}, os_charcorr_double_bx_
{{ o1.bx }}_bx_{{ o2.bx }},
diff_{{ o1.type|lower }}_{{ o1.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx
}}_eta_vector, diff_{{ o1.type|lower }}_{{ o1.type|lower }}_bx_{{ o1.
bx }}_bx_{{ o2.bx }}_phi_vector,
{{ o1.type|lower }}_pt_vector_bx_{{ o1.bx }}, {{ o1.type|lower }}
_pt_vector_bx_{{ o2.bx }},
{{ o1.type|lower }}_upt_vector_bx_{{ o1.bx }}, {{ o1.type|lower }}
_upt_vector_bx_{{ o2.bx }},
{{ o1.type|lower }}_{{ o1.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx }}
_cosh_delta_vector, {{ o1.type|lower }}_{{ o1.type|lower }}_bx_{{ o1.bx
}}_bx_{{ o2.bx }}_cos_dphi_vector,
{{ o1.type|lower }}_cos_phi_bx_{{ o1.bx }}, {{ o1.type|lower }}
_cos_phi_bx_{{ o2.bx }}, {{ o1.type|lower }}_sin_phi_bx_{{ o1.bx }},
{{ o1.type|lower }}_sin_phi_bx_{{ o2.bx }},
{{ condition.vhdl_signal }});
%- endblock instantiate_muon_muon_correlation_condition %}
{# eof #}

```

Table 35: Explanation of Listing 18

Item	Explanation
vhdl_signal	condition name.
objectsInSameBx	valid strings are 'true' and 'false' - 'true' for data with same Bx.
deltaEta.enabled	valid strings are 'true' and 'false' - 'true' for use of DETA.
deltaPhi.enabled	valid strings are 'true' and 'false' - 'true' for use of DPHI.
deltaR.enabled	valid strings are 'true' and 'false' - 'true' for use of DR.
mass.enabled	valid strings are 'true' and 'false' - 'true' for use of MASS.
mass.type	valid strings are 'INVARIANT_MASS_TYPE' and 'TRANSVERSE_MASS_TYPE'.
twoBodyPt.enabled	valid strings are 'true' and 'false' - 'true' for use of two-body pt.
sliceLow	low value of an object slice.
sliceHigh	high value of an object slice.
operator	valid strings are 'true' and 'false' - 'true' for greater/equal-, 'false' for equal-mode of E_T comparator.
threshold	requirements for pt_thresholds (16-bit values, hex notation). Valid values depending on the scales of E_T .
nrEtaWindows	number of η cuts.
etaW1UpperLimit, ...	limits for "window"-comparators for η (4x 16-bit values, hex notation). Valid values depending on the scales for η .
phiFullRange	set full range of φ (boolean).

Table 35: Explanation of Listing 18

Item	Explanation
phiW1UpperLimit, ...	limits for "window"-comparators for φ (16-bit values, hex notation). Valid values depending on the scales for φ .
[phiW2Ignore	ignore "window"-comparator 2 of φ (boolean).
charge	requested charge. Valid strings are 'pos' ("positive charge") and 'neg' ("negative charge") and 'ign' ("ignore").
qualityLUT	LUT (16 bits) of quality.
isolationLUT	LUT (4 bits) of isolation).
uptCutSel	set use of unconstraint p_T .
uptUpperLimit, ...	limits for unconstraint p_T .
impactParameterLUT	LUT (4 bits) of impact parameter).
deltaEta.upper, ...	limits for "window"-comparator for comparison of differences in η (hex notation). Valid values depending on the scales for η .
deltaPhi.upper, ...	limits for "window"-comparator for comparison of differences in φ (hex notation). Valid values depending on the scales for φ .
deltaR.upper, ...	limits for "window"-comparator for comparison of ΔR^2 (hex notation).
mass.upper, ...	limits for "window"-comparator for comparison of $\frac{M^2}{2}$ (hex notation).
twoBodyPt.threshold	value of threshold for two-body pt comparison.
bx	valid strings are 'p2', 'p1', '0', 'm1' and 'm2'. This indicates which data in a range of plus/minus 2 bunch-crossing is used in the condition.

3.5.7 Calo Esums Correlation condition - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating `calo_esums_correlation_condition.vhd` is given below (see Listing 16).

Listing 19: Template of `calo_esums_correlation_condition.vhd` for VHDL-Producer

```
{%- block instantiate_caloesums_correlation_condition %}
  {%- set o1 = condition.objects[0] %}
  {%- set o2 = condition.objects[1] %}
  {{ condition.vhdl_signal }}_i: entity work.caloesums_correlation_condition
    generic map(
      {{ condition.deltaPhi.enabled }}, {{ condition.mass.enabled }},
      TRANSVERSE_MASS_TYPE, {{ condition.twoBodyPt.enabled }},
      {{ o1.sliceLow }}, {{ o1.sliceHigh }}, {{ o1.operator }}, {{ o1.type|
        upper }}_TYPE,
      X"{{ o1.threshold|X04 }}",
      {{ o1.etaNrCuts }},
      X"{{ o1.etaW1UpperLimit|X04 }}", X"{{ o1.etaW1LowerLimit|X04 }}",
      X"{{ o1.etaW2UpperLimit|X04 }}", X"{{ o1.etaW2LowerLimit|X04 }}"
```

```

X"{{ o1.etaW3UpperLimit|X04 }}", X"{{ o1.etaW3LowerLimit|X04 }}",
X"{{ o1.etaW4UpperLimit|X04 }}", X"{{ o1.etaW4LowerLimit|X04 }}",
X"{{ o1.etaW5UpperLimit|X04 }}", X"{{ o1.etaW5LowerLimit|X04 }}",
{{ o1.phiFullRange }}, X"{{ o1.phiW1UpperLimit|X04 }}", X"{{ o1.
    phiW1LowerLimit|X04 }}",
{{ o1.phiW2Ignore }}, X"{{ o1.phiW2UpperLimit|X04 }}", X"{{ o1.
    phiW2LowerLimit|X04 }}",
X"{{ o1.isolationLUT|X01 }}",
{{ o2.operator }}, {{ o2.type|upper }}_TYPE,
X"{{ o2.threshold|X04 }}",
{{ o2.phiFullRange }}, X"{{ o2.phiW1UpperLimit|X04 }}", X"{{ o2.
    phiW1LowerLimit|X04 }}",
{{ o2.phiW2Ignore }}, X"{{ o2.phiW2UpperLimit|X04 }}", X"{{ o2.
    phiW2LowerLimit|X04 }}",
X"{{ condition.deltaPhi.upper|X08 }}", X"{{ condition.deltaPhi.lower|X08
    }}",
X"{{ condition.mass.upper|X16 }}", X"{{ condition.mass.lower|X16 }}",
{{ o1.type|upper }}_PT_VECTOR_WIDTH, {{ o2.type|upper }}_PT_VECTOR_WIDTH,
{{ o1.type|upper }}_{{ o2.type|upper }}_COSH_COS_PRECISION, {{ o1.
    type|upper }}_{{ o2.type|upper }}_COSH_COS_VECTOR_WIDTH,
X"{{ condition.twoBodyPt.threshold|X16 }}", CALO_SIN_COS_VECTOR_WIDTH, {{
    o1.type|upper }}_{{ o2.type|upper }}_SIN_COS_PRECISION
)
port map(lhc_clk, {{ o1.type|lower }}_bx_{{ o1.bx }}({{ o1.sliceLow }} to {{
    o1.sliceHigh }}), {{ o2.type|lower }}_bx_{{ o2.bx }},
diff_{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx
    }}_phi_vector,
{{ o1.type|lower }}_pt_vector_bx_{{ o1.bx }}, {{ o2.type|lower }}
    _pt_vector_bx_{{ o2.bx }},
{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx }}
    _cos_dphi_vector,
{{ o1.type|lower }}_cos_phi_bx_{{ o1.bx }}, {{ o2.type|lower }}
    _cos_phi_bx_{{ o2.bx }}, {{ o1.type|lower }}_sin_phi_bx_{{ o1.bx }},
    {{ o2.type|lower }}_sin_phi_bx_{{ o2.bx }},
    {{ condition.vhdl_signal }});
{%- endblock instantiate_caloesums_correlation_condition %}
{# eof #}

```

Table 36: Explanation of Listing 16

Item	Explanation
vhdl_signal	condition name.
deltaPhi.enabled	valid strings are 'true' and 'false' - 'true' for use of DPHI.
mass.enabled	valid strings are 'true' and 'false' - 'true' for use of MASS.
mass.type	valid string: 'TRANSVERSE_MASS_TYPE'.
twoBodyPt.enabled	valid strings are 'true' and 'false' - 'true' for use of two-body pt.
sliceLow	low value of an object slice.
sliceHigh	high value of an object slice.
operator	valid strings are 'true' and 'false' - 'true' for greater/equal-, 'false' for equal-mode of E_T comparator.
threshold	requirements for <code>et_thresholds</code> (16-bit values, hex notation). Valid values depending on the scales of E_T .

Table 36: Explanation of Listing 16

Item	Explanation
nrEtaWindows	number of η cuts.
etaW1UpperLimit, ...	limits for "window"-comparators for η (4x 16-bit values, hex notation). Valid values depending on the scales for η .
phiFullRange	set full range of φ (boolean).
phiW1UpperLimit, ...	limits for "window"-comparators for φ (16-bit values, hex notation). Valid values depending on the scales for φ .
[phiW2Ignore	ignore "window"-comparator 2 of φ (boolean).
isolationLUT	LUT (4 bits) of isolation).
deltaPhi.upper, ...	limits for "window"-comparator for comparison of differences in φ (hex notation). Valid values depending on the scales for φ .
mass.upper, ...	limits for "window"-comparator for comparison of $\frac{M^2}{2}$ (hex notation).
twoBodyPt.threshold	value of threshold for two-body pt comparison.
bx	valid strings are 'p2', 'p1', '0', 'm1' and 'm2'. This indicates which data in a range of plus/minus 2 bunch-crossing is used in the condition.

3.5.8 Muon Esums Correlation condition - template for VHDL-Producer

A VHDL-template for VHDL-Producer of instantiating

muon_esums_correlation_condition.vhd

is given below (see Listing 20).

Listing 20: Template of muon_esums_correlation_condition.vhd for VHDL-Producer

```
{%- block instantiate_muon_esums_correlation_condition %}
{%- set o1 = condition.objects[0] %}
{%- set o2 = condition.objects[1] %}
{{ condition.vhdl_signal }}_i: entity work.muon_esums_correlation_condition
generic map(
    {{ condition.deltaPhi.enabled }}, {{ condition.mass.enabled }}, {{
        condition.mass.type }}, {{ condition.twoBodyPt.enabled }},
    {{ o1.sliceLow }}, {{ o1.sliceHigh }}, {{ o1.operator }},
    X"{{ o1.threshold|X04 }}",
    {{ o1.etaNrCuts }},
    X"{{ o1.etaW1UpperLimit|X04 }}", X"{{ o1.etaW1LowerLimit|X04 }}",
    X"{{ o1.etaW2UpperLimit|X04 }}", X"{{ o1.etaW2LowerLimit|X04 }}",
    X"{{ o1.etaW3UpperLimit|X04 }}", X"{{ o1.etaW3LowerLimit|X04 }}",
    X"{{ o1.etaW4UpperLimit|X04 }}", X"{{ o1.etaW4LowerLimit|X04 }}",
    X"{{ o1.etaW5UpperLimit|X04 }}", X"{{ o1.etaW5LowerLimit|X04 }}",
    {{ o1.phiFullRange }}, X"{{ o1.phiW1UpperLimit|X04 }}", X"{{ o1.
        phiW1LowerLimit|X04 }}",
    {{ o1.phiW2Ignore }}, X"{{ o1.phiW2UpperLimit|X04 }}", X"{{ o1.
        phiW2LowerLimit|X04 }}",
```

```

"{{ o1.charge }}", X"{{ o1.qualityLUT|X04 }}", X"{{ o1.isolationLUT|X01
    }}",
{{ o1.uptCutSel }}, X"{{ o1.uptUpperLimit|X04 }}", X"{{ o1.uptLowerLimit|
    X04 }}", X"{{ o1.impactParameterLUT|X01 }}",
{{ o2.operator }}, {{ o2.type|upper }}_TYPE,
X"{{ o2.threshold|X04 }}",
{{ o2.phiFullRange }}, X"{{ o2.phiW1UpperLimit|X04 }}", X"{{ o2.
    phiW1LowerLimit|X04 }}",
{{ o2.phiW2Ignore }}, X"{{ o2.phiW2UpperLimit|X04 }}", X"{{ o2.
    phiW2LowerLimit|X04 }}",
X"{{ condition.deltaPhi.upper|X08 }}", X"{{ condition.deltaPhi.lower|X08
    }}",
X"{{ condition.mass.upper|X16 }}", X"{{ condition.mass.lower|X16 }}",
{{ o1.type|upper }}_PT_VECTOR_WIDTH, {{ o2.type|upper }}_PT_VECTOR_WIDTH,
    {{ o1.type|upper }}_{{ o2.type|upper }}_COSH_COS_PRECISION, {{ o1.
    type|upper }}_{{ o2.type|upper }}_COSH_COS_VECTOR_WIDTH,
X"{{ condition.twoBodyPt.threshold|X16 }}", MUON_SIN_COS_VECTOR_WIDTH, {{
    o1.type|upper }}_{{ o2.type|upper }}_SIN_COS_PRECISION
)
port map(lhc_clk, {{ o1.type|lower }}_bx_{{ o1.bx|lower }}({{ o1.sliceLow }}
to {{ o1.sliceHigh }}), {{ o2.type|lower }}_bx_{{ o2.bx|lower }},
diff_{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx|lower }}_bx_{{
    o2.bx|lower }}_phi_vector,
{{ o1.type|lower }}_pt_vector_bx_{{ o1.bx }}, {{ o2.type|lower }}
    _pt_vector_bx_{{ o2.bx }},
{{ o1.type|lower }}_{{ o2.type|lower }}_bx_{{ o1.bx }}_bx_{{ o2.bx }}
    _cos_dphi_vector,
{{ o1.type|lower }}_cos_phi_bx_{{ o1.bx }}, conv_{{ o2.type|lower }}
    _cos_phi_bx_{{ o2.bx }}, {{ o1.type|lower }}_sin_phi_bx_{{ o1.bx }},
    conv_{{ o2.type|lower }}_sin_phi_bx_{{ o2.bx }},
    {{ condition.vhdl_signal }}});
{%- endblock instantiate_muon_esums_correlation_condition %}
{# eof #}

```

Table 37: Explanation of Listing 17

Item	Explanation
vhdl_signal	condition name.
deltaPhi.enabled	valid strings are 'true' and 'false' - 'true' for use of DPHI.
mass.enabled	valid strings are 'true' and 'false' - 'true' for use of MASS.
mass.type	valid string: 'TRANSVERSE_MASS_TYPE'.
twoBodyPt.enabled	valid strings are 'true' and 'false' - 'true' for use of two-body pt.
sliceLow	low value of an object slice.
sliceHigh	high value of an object slice.
operator	valid strings are 'true' and 'false' - 'true' for greater/equal-, 'false' for equal-mode of E_T comparator.
threshold	requirements for pt_thresholds and et_thresholds (16-bit values, hex notation). Valid values depending on the scales of E_T .
nrEtaWindows	number of η cuts.
etaW1UpperLimit, ...	limits for "window"-comparators for η (4x 16-bit values, hex notation). Valid values depending on the scales for η .

Table 37: Explanation of Listing 17

Item	Explanation
<code>phiFullRange</code>	set full range of φ (boolean).
<code>phiW1UpperLimit, ...</code>	limits for "window"-comparators for φ (16-bit values, hex notation). Valid values depending on the scales for φ .
<code>[phiW2Ignore</code>	ignore "window"-comparator 2 of φ (boolean).
<code>charge</code>	requested charge. Valid strings are 'pos' ("positive charge") and 'neg' ("negative charge") and 'ign' ("ignore").
<code>qualityLUT</code>	LUT (16 bits) of quality.
<code>isolationLUT</code>	LUT (4 bits) of isolation).
<code>uptCutSel</code>	set use of unconstraint p_T .
<code>uptUpperLimit, ...</code>	limits for unconstraint p_T .
<code>impactParameterLUT</code>	LUT (4 bits) of impact parameter).
<code>deltaPhi.upper, ...</code>	limits for "window"-comparator for comparison of differences in φ (hex notation). Valid values depending on the scales for φ .
<code>mass.upper, ...</code>	limits for "window"-comparator for comparison of $\frac{M^2}{2}$ (hex notation).
<code>twoBodyPt.threshold</code>	value of threshold for two-body pt comparison.
<code>bx</code>	valid strings are 'p2', 'p1', '0', 'm1' and 'm2'. This indicates which data in a range of plus/minus 2 bunch-crossing is used in the condition.

4 Final Decision Logic

The Final Decision Logic (μ FDL) firmware contains algo-bx-masks, suppression of algos caused by calibration trigger, prescalers, veto-masks and rate-counters ("before prescalers", "after prescalers" and "post dead time") for each Algorithm and the local Final-OR- and veto-logic.




Figure 15: μ FDL firmware v1.0.1

4.1 μ FDL Interface

Inputs:

- Algorithms from μ GTL
- IPBus interface (for registers, counters and memories)
- LHC-clock
- Reset signal
- BC0, BGo test-enable, L1A
- Begin of lumi-section

Outputs:

- Prescale factor set index to Readout-Process
- Algorithms after GTLogic to Readout-Process
- Algorithms after algo-bx-masks to Readout-Process

- Algorithms after prescalers to Readout-Process
- Algorithms after Final-OR-masks to Readout-Process
- Local Final-OR to Readout-Process
- Local veto to Readout-Process
- Local Final-OR with veto to Readout-Process
- Local Final-OR to mezzanine
- Local veto to mezzanine
- Local Final-OR with veto to mezzanine

4.2 MP7 Final-OR hardware solution

The firmware of μ FDL in this document is based on a hardware configuration with maximum 6 μ GT modules.

4.3 Data flow




Figure 16: μ FDL pipeline v1.0.1

Every Algorithm, in total 512 coming from μ GTL, passes a algo-bx-mask, the logic for suppression of algos caused by calibration trigger and a prescaler, which reduces the trigger rate by a given factor. Prescaled Algorithms signals are combined to a local final-or-signal (Final-OR). For every Algorithm there is a rate-counter before prescaler and after prescaler, which

are incremented by LHC-clock if the Algorithm is true. In addition there are post-dead-time counters, one for each Algorithm, which are incremented, if the Algorithm and the L1A-signal are true at the same bunch-crossing. Algorithms after GTLogic, after algo-bx-masks, after prescalers, the local Final-OR- and local veto-signal are provided for read-out-record.

If there are not enough firmware resources in one μ GT board, more boards could be used. Therefore the 512 Algorithms are partitioned by TME. TME will set the number of Algorithms as constant in the package module `gtl_pkg.vhd`. This means μ GTL and μ FDL firmware considered as a unit for synthesis. In the case of more μ GT boards, the local Final-OR and local veto are routed via a mezzanine board on MP7 (located on "General Purpose I/O connector") to the FINOR-AMC502 module, where the total Final-OR is created and send to TCDS.

A mapping for Algorithms is provided, to give flexibility for setting the index of Algorithms:

- creating a mapping instance (`algo_mapping_rop.vhd`) over TME (see ??), this component will be instantiated in fix part of FDL, and new calculation will done each time over TME.
- TME delivers just the number of Algorithms, which will be built on each card.
- from FDL point of view, FDL see incremented number of Algorithms indexes, e.g. 0, 1, 2, which is e.g. 69, 200, 300.
- TME should take care of assignment of each Algorithm to a number, that means if in card 1 `algo_59` is defined, nobody allows to produce the same number again.

4.4 Main parts

The top-of-hierarchy module (`fdl_module.vhd`) contains

- version registers
- a command pulse register
- prescalers for all Algorithms
- registers for prescale factors
- register for prescale factor set index
- rate-counters for all Algorithms, finor, veto, L1A and post-dead-time
- read only registers for rate-counter values
- algo-bx-masks for all Algorithms
- Final-OR-masks for all Algorithms
- veto-masks for all Algorithms
- the Final-OR-logic

4.4.1 Registers and memories

All registers and memories are 32 bits wide. (A first draft of the definition of the relative addresses is shown in Table 38.)

- Dual-port memories for the algo-bx-masks are implemented. For each Algorithm there is a mask bit at every bunch crossing of one orbit. Therefore in total memories of 4096 x 512 bits are implemented. Because of the 32 bit data interface, 16 memories each with a size of 4096 x 32 bits are instantiated.
- Read-only registers for the value of rate-counters (before and after prescalers, post-dead-time counters) are implemented, 512 registers, one for every Algorithm. Rate-counter value has 32 bits.
- Registers for prescale factor of the prescalers are implemented, 512 registers, one for every Algorithm. A prescale factor value has 24 bits.
- Registers for masks (finor- and veto-masks) are implemented, 512 registers.
- One register for prescale factors set index is implemented. This register contains a value, which is unique for a given set of prescale factors. The content of this register is part of Readout-record.
- One register for command pulses is implemented. One bit of this register (bit 0) is used for "setting the request signal for updating prescale factors high", which enables, that the prescale factors and the prescale factor set index are loaded at the begin of a luminosity segment period. (Other bits are not defined yet.)
- One control register is implemented (the content has to be defined).
- 32 register for L1 Trigger Menu name for μ GTL is implemented.
- 4 register for L1 Trigger Menu UUID for μ GTL is implemented.
- One register for L1 Trigger Menu compiler version is implemented.
- One register for μ FDL firmware version is implemented.
- One register for μ GTL firmware (fixed code) version is implemented.

4.4.1.1 Register map

The register map for μ FDL has a base address of 0x90000000.

Table 38: μ FDL register map

Offset	Register name	Access	Description
0x90000000	Algo BX masks(0)	r/w	4096 memory addresses of algo-bx-masks for Algorithms 0-31.


Table 38: μ FDL register map

Offset	Register name	Access	Description
0x90001000	Algo BX masks (1)	r/w	4096 memory addresses of algo-bx-masks for Algorithms 32-63.
...
0x9000F000	Algo BX masks (15)	r/w	4096 memory addresses of algo-bx-masks for Algorithms 480-511.
0x90010000	Rate counter before prescaler	r	512 read-only registers for rate-counter values before prescalers.
0x90010200	Prescale factors	r/w	512 registers for prescale factors.
0x90010400	Rate counter after prescaler	r	512 read-only registers for rate-counter values after prescalers.
0x90010600	Rate counter post-dead-time	r	512 read-only registers for post-dead-time rate-counter values.
0x90010800	Masks	r/w	512 registers for finor-masks and veto-masks. Bit 0 = finor-mask, bit 1 = veto-mask.
0x90091880	Prescale factors set index	r/w	Register for prescale factors set index.
0x900918C0	L1tm name	r	32 registers for L1 Trigger Menu name for μ GTL.
0x900918E0	L1tm uuid	r	4 registers for L1 Trigger Menu UUID for μ GTL.
0x900918E4	L1tm compiler version	r	Register for L1 Trigger Menu compiler version.
0x900918E5	GTL FW version	r	Register for firmware version of μ GTL VHDL code.
0x900918E6	FDL FW version	r	Register for firmware version of μ FDL VHDL code.
0x900918E7	L1tm FW uuid	r	4 registers for L1 Trigger Menu FW UUID for μ GTL.
0x900918EB	SVN revision number	r	Register for SVN revision number.
0x900918EC	L1tm uuid hash	r	Register for L1 Trigger Menu UUID hash for μ GTL.

Table 38: μ FDL register map


Offset	Register name	Access	Description
0x900918ED	L1tm FW uuid hash	r	Register for L1 Trigger Menu FW UUID hash for μ GTL.
0x900918EE	Module ID	r	Register for Module ID of L1 Trigger Menu.
0x90091900	Command Pulses	r/w	Register for command pulses.
0x90091980	Rate counter finor	r	One read-only registers for finor rate-counter value.
0x90092200	L1A latency delay	r/w	Register for L1A latency delay value (used for post-dead-time counter).
0x90093000	Rate counter L1A	r	One read-only registers for L1A rate-counter value.
0x90094000	Rate counter veto	r	One read-only registers for veto rate-counter value.
0x90095000	Current prescale set index	r	Read-only register for prescale factors set index, which was "updated" with begin of current lumi-section ("prescale_factors_set_index_reg_updated(0)" in VHDL).
0x90095001	Previous prescale set index	r	Read-only register for prescale factors set index, which was "updated" with begin of previous lumi-section for monitoring "prescale_factors_set_index_reg_updated(1)" in VHDL).
0x90096000	Calibration trigger gap	r/w	Register for begin and end (in Bx) of calibration trigger gap.

Register 4.1: RATE COUNTER BEFORE PRESCALER




rate_counter_before_prescaler Rate counter before prescaler. Counts the occurancy of an algo (given by register address) in one luminosity segment.

Register 4.2: PRESCALE FACTOR



prescale_factor Prescale factor of an algo (given by register address). Prescale factor = 0 means disable algo.

Register 4.3: RATE COUNTER AFTER PRESCALER



rate_counter_after_prescaler Rate counter after prescaler. Counts the occurancy of an algo (given by register address) in one luminosity segment.

Register 4.4: RATE COUNTER POST-DEAD-TIME

rate_counter_postdeadtime	
31	0
0	Reset

rate_counter_postdeadtime Rate counter post-dead-time. Counts the occurrence of an algo (given by register address) and L1A at the same bx in one luminosity segment.

Register 4.5: MASKS

reserved		veto_mask finor_mask	
31	2	1	0
0	0	1	Reset

veto_mask Selection of a veto (by an algo, given by register address) for veto-or.

finor_mask Selection of an algo (given by register address) for final-or.

Register 4.6: PRESCALE FACTORS SET INDEX

reserved		prescale_factor_set_index	
31	8	7	0
0	0	0	Reset

prescale_factor_set_index Index for a certain set of prescale factors.

Register 4.7: L1TM COMPILER VERSION

<i>reserved</i>								<i>major</i>								<i>minor</i>								<i>revision</i>								
31	24							23	16							15	8							7	0							
0								0								0								0								Reset

major Major version of L1tm compiler.

minor Minor version of L1tm compiler.

revision Revision version of L1tm compiler.

Register 4.8: GTL FW VERSION

<i>reserved</i>								<i>major</i>								<i>minor</i>								<i>revision</i>								
31	24							23	16							15	8							7	0							
0								0								0								0								Reset

major Major version of GTL firmware.

minor Minor version of GTL firmware.

revision Revision version of GTL firmware.

Register 4.9: FDL FW VERSION

<i>reserved</i>								<i>major</i>								<i>minor</i>								<i>revision</i>								
31	24							23	16							15	8							7	0							
0								0								0								0								Reset

major Major version of FDL firmware.

minor Minor version of FDL firmware.

revision Revision version of FDL firmware.

Register 4.10: COMMAND PULSES REGISTER

31		1		0	Reset
0				0	

reserved (bits 31-1)

request_update_factor_pulse (bit 0)

request_update_factor_pulse Sets the request signal for updating prescale factors high. Updating is done at the next "begin of luminosity segment".

Register 4.11: RATE COUNTER FINOR

31		0	Reset
0			

rate_counter_finor (bits 31-0)

rate_counter_finor Rate counter finor. Counts the occurancy of finor in one luminosity segment.

Register 4.12: L1A LATENCY DELAY


29		6		5	0	Reset
0				0		

reserved (bits 29-6)

l1a_latency_delay (bits 5-0)


l1a_latency_delay L1A latency delay value (used for post-dead-time counter).

Register 4.13: RATE COUNTER L1A




rate_counter_l1a Rate counter L1A. Counts the occurance of L1A in one luminosity segment.

Register 4.14: RATE COUNTER VETO




rate_counter_veto Rate counter veto. Counts the occurance of veto in one luminosity segment.

Register 4.15: CURRENT PRESCALE SET INDEX




prescale_factor_set_index_updated Index for a certain set of prescale factors, which was "updated" with begin of current lumi-section.

Register 4.16: PREVIOUS PRESCALE SET INDEX



prescale_factor_set_index_updated Index for a certain set of prescale factors, which was "updated" with begin of previous lumi-section.

Register 4.17: CALIBRATION TRIGGER GAP



begin_calibration_trigger_gap Begin of calibration trigger gap (in Bx).

end_calibration_trigger_gap End of calibration trigger gap (in Bx).

4.4.2 Algo-bx-masks

Every Algorithm passes a logic where at every bunch-crossing of the orbit the Algorithm is enabled (or not). The algo-bx-masks are implemented as dual-port memories and loaded at the begin of run. The size of the algo-bx-masks memory is number of bunch-crossings per orbit for address length and number of Algorithms for data-depth (3564 [4096] x 512 bits). The address (bx-number) of the memory for masking the Algorithm is delivered by an address-counter for algo-bx-masks memory, which is reseted with a delay-able bcres signal, to get the correct relations between Algorithms and masks from memory.

4.4.3 Rate-counters

Every Algorithm has a rate-counters with 32 bits, because of the length of one luminosity segment period. There are counters before and after prescalers and post-dead-time counters. The counters before and after prescalers are incremented, if the Algorithm signal is in high state and a positive edge of LHC-clock occur. The post-dead-time counters are incremented, if the Algorithm signal is in high state (delayed by L1A latency delay), a L1A signal and a positive edge of LHC-clock occur. The content of a counter is updated into a register (for reading the counter value) and is reseted at the begin of a luminosity segment period. So there is one luminosity segment period time to read the registers with the counter values by software.

4.4.4 Prescalers

Every Algorithm has a prescaler with a prescale factor of 24 bits. The prescaler reduces the trigger-rate per Algorithm with a factor, so e.g. a factor of 2 passes through every second trigger. A prescale factor of 0 inhibits all triggers of the certain Algorithm. The factor is loaded into a register by software and updated at begin of a new luminosity segment period, if the update was enabled by software ('request_update_factor_pulse' was set in "command_pulses" register). The prescaler works with the new factor. A register for "prescale factor set index" contains a value which represents a certain set of prescale factors. The content of this register is seen in the Readout-record too. The "prescale factor set index" is loaded into the register by software and updated at begin of a new luminosity segment period.

4.4.5 Finor-masks

Every Algorithm passes a Final-OR-mask, which enables the Algorithm for Final-OR. The Final-OR-masks are implemented as registers and loaded at the begin of a run.

4.4.6 Veto-masks

Every Algorithm passes a veto-mask, if at least one Algorithm, which is enabled by veto-mask, becomes high state, then Final-OR is disabled as long as the Algorithm is in high state. The veto-masks are implemented as registers and loaded at the begin of a run.

4.4.7 Finor

The Final-OR-signal is a disjunction of all Algorithms passed the Final-OR-bx-masks. An Algorithm enabled by veto-mask, disables the Final-OR. This is done on the FINOR-AMC502 module.

4.5 Implementation in firmware

The entity-declaration of `fdl_module.vhd` is shown in 4.3.

Listing 21 contains the entity-declaration of the `fdl_module.vhd`.

Listing 21: Entity declaration of `fdl_module.vhd`

```
entity fdl_module is
  generic(
    SIM_MODE : boolean := false; -- if SIM_MODE = true, "algo_bx_mask" is
      given by "algo_bx_mask_sim".
    PRESCALE_FACTOR_INIT : ipb_regs_array(0 to MAX_NR_ALGOS-1);
    MASKS_INIT : ipb_regs_array(0 to MAX_NR_ALGOS-1);
    PRESCALE_FACTOR_SET_INDEX_WIDTH : positive := 8;
    PRESCALE_FACTOR_SET_INDEX_REG_INIT : ipb_regs_array(0 to 1) := (others =>
      X"00000000");
    L1A_LATENCY_DELAY_INIT : ipb_regs_array(0 to 1) := (others => X"00000000"
    );
    CNTRL_REG_INIT : ipb_regs_array(0 to 1) := (others => X"00000000");
    -- Input flip-flops for algorithms of fdl_module.vhd - used for tests of
      fdl_module.vhd only
    ALGO_INPUTS_FF: boolean := false
  );
  port(
    ipb_clk          : in std_logic;
    ipb_rst          : in std_logic;
    ipb_in           : in ipb_wbus;
    ipb_out          : out ipb_rbus;
    -- =====
    lhc_clk          : in std_logic;
    lhc_rst          : in std_logic;
    bcre             : in std_logic;
    test_en          : in std_logic;
    l1a              : in std_logic;
    begin_lumi_section : in std_logic;
    algo_i           : in std_logic_vector(NR_ALGOS-1 downto 0);
    bx_nr_out        : out std_logic_vector(11 downto 0);
    prescale_factor_set_index_rop : out std_logic_vector(
      PRESCALE_FACTOR_SET_INDEX_WIDTH-1 downto 0);
    algo_after_gtLogic_rop : out std_logic_vector(MAX_NR_ALGOS-1 downto 0);
    algo_after_bxomask_rop : out std_logic_vector(MAX_NR_ALGOS-1 downto
      0);
    algo_after_prescaler_rop : out std_logic_vector(MAX_NR_ALGOS-1
      downto 0);
    local_finor_rop   : out std_logic;
    local_veto_rop    : out std_logic;
```

```
    finor_2_mezz_lemo      : out std_logic; -- to LEMO
    finor_preview_2_mezz_lemo : out std_logic; -- to LEMO
    veto_2_mezz_lemo       : out std_logic; -- to LEMO
    finor_w_veto_2_mezz_lemo : out std_logic; -- to tp_mux.vhd
    local_finor_with_veto_o  : out std_logic; -- to SPY2_FINOR
-- HB 2016-03-02: v0.0.21 - algo_bx_mask_sim input for simulation use with
    MAX_NR_ALGOS (because of global index).
    algo_bx_mask_sim        : in std_logic_vector(MAX_NR_ALGOS-1 downto 0)
);
end fdl_module;
```


5 Readout-Process

The readout is done via TX-links of MP7 to AMC13.

6 Glossary

electron/ γ = electron/gamma objects over Calo-Layer2 (VHDL: eg)

jet = jet objects over Calo-Layer2 (VHDL: jet)

tau = tau objects over Calo-Layer2 (VHDL: tau)

muon = muon objects over μ GMT (VHDL: muon)

ET = Scalar sum of transverse energy components over Calo-Layer2 (VHDL: ett)

ETTEM = Scalar sum of transverse energy components from ECAL only over Calo-Layer2 (VHDL: ettem)

MBTxHFy = Minimum bias HF bits (VHDL: MBT0HFP, MBT0HFM, MBT1HFP, MBT1HFM)

HT = Magnitude of the vectorial sum of transverse energy of jets (hadronic) over Calo-Layer2 (VHDL: htt)

TOWERCOUNT = tower counts (VHDL: towercount)

ET_{miss} = 2-vector sum of transverse energy over Calo-Layer2 (VHDL: etm)

HT_{miss} = Missing Total transverse energy of jets over Calo-Layer2 (VHDL: htm)

$\mathbf{ET}_{\text{miss}}^{\text{HF}}$ = 2-vector sum of transverse energy including HF over Calo-Layer2 (VHDL: etmhf)

$\mathbf{HT}_{\text{miss}}^{\text{HF}}$ = Missing Total transverse energy of jets including HF over Calo-Layer2 (VHDL: htmhf)

ASYMET = Asymmetry of ET over Calo-Layer2 (VHDL: asymet)

ASYMHT = Asymmetry of HT over Calo-Layer2 (VHDL: asymht)

ASYMETHF = Asymmetry of ET including HF over Calo-Layer2 (VHDL: asymethf)

ASYMHthf = Asymmetry of HT including HF over Calo-Layer2 (VHDL: asymhthf)

CENTx = Centrality bits [7:0] over Calo-Layer2 (VHDL: cent7, cent6, ...)

p_{T} = transverse momentum of muon objects (VHDL: pt)

E_{T} = energy of calorimeter objects (VHDL: et)

η = pseudo-rapidity position (VHDL: eta)

φ = azimuth angle position (VHDL: phi)

isolation = isolation information (VHDL: iso)

quality = quality information (VHDL: qual)

Acronyms

DAQ Data Acquisition

DM Delay Manager Module

FDL Final Decision Logic Module

GTL Global Trigger Logic Module

ROP Readout-Process Module

TCM Timing Counter Manager Module

TCS Trigger Control System

GCT Calorimeter Trigger Layer-2

GMT Global Muon Trigger

GT Global Trigger

References