

Gboost_arodriguezsans_Bar

May 18, 2021

1 Barcelona

1.1 Gradient Boosting Trees

1.1.1 Gradient Boosting Regressor

```
[1]: import numpy as np
import pandas as pd

import matplotlib.pyplot as plt

from sklearn.ensemble import GradientBoostingRegressor
from sklearn.metrics import mean_squared_error
from sklearn.model_selection import cross_val_score
from sklearn.model_selection import train_test_split
from sklearn.model_selection import RepeatedKFold
from sklearn.model_selection import KFold
from sklearn.model_selection import GridSearchCV
from sklearn.model_selection import ParameterGrid
from sklearn.preprocessing import MinMaxScaler
from sklearn.inspection import permutation_importance
from sklearn.metrics import mean_absolute_error, mean_squared_error

import multiprocessing

import warnings
warnings.filterwarnings('once')

[2]: df_total = pd.read_excel('Total.xls')
# Edit columns names + Lower case column names
df_total.columns = map(str.lower, df_total.columns)
df_total.columns
```

```
C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell`
automatically in the future. Please pass the result to `transformed_cell`
argument and any exception that happen during thetransform in
`preprocessing_exc_tuple` in IPython 7.17 and above.
    and should_run_async(code)
```

```
[2]: Index(['sub_region_2', 'fecha', 'provincia_iso', 'num_casos.x',
        'num_casos_prueba_pcr', 'num_casos_prueba_test_ac',
        'num_casos_prueba_ag', 'num_casos_prueba_elisa',
        'num_casos_prueba_desconocida', 'num_casos.y', 'num_hosp', 'num_uci',
        'num_def', 'retail_and_recreation_percent_change_from_baseline',
        'grocery_and_pharmacy_percent_change_from_baseline',
        'parks_percent_change_from_baseline',
        'transit_stations_percent_change_from_baseline',
        'workplaces_percent_change_from_baseline',
        'residential_percent_change_from_baseline', 'total'],
        dtype='object')
```

```
[3]: Bar = df_total.loc[df_total['sub_region_2'] == 'Barcelona']
      #Bar.describe()
```

```
[4]: # Set index
      Bar = Bar.set_index('fecha')
```

```
[5]: # We select columns of interest (mobility ones)
      Bar = Bar[['num_casos.x']+['num_casos_prueba_pcr']+ list(Bar.loc[:
      ↪, 'retail_and_recreation_percent_change_from_baseline': 'total'])]
      #Bar_red
```

```
[6]: # We create train and test datasets as in previous scenarios
      X_train, X_test, y_train, y_test = train_test_split( #Bar,
                                                           Bar.drop(columns =
      ↪ 'num_casos.x'),
                                                           Bar['num_casos.x'],
                                                           shuffle = False, stratify =
      ↪ None,
                                                           train_size=0.942)
```

```
[7]: type(y_test)
```

```
[7]: pandas.core.series.Series
```

```
[8]: type(X_test)
```

```
[8]: pandas.core.frame.DataFrame
```

```
[9]: #X_test
```

```
[10]: # Model generation
      model = GradientBoostingRegressor(n_estimators = 10,
                                       loss           = 'ls',
                                       max_features  = 'auto',
                                       random_state  = 123)
```

```

model.fit(X_train, y_train)

# Prediction
predictions = model.predict(X = X_test)
rmse = mean_squared_error(y_test, predictions, squared = False)
print(f" RMSE: {rmse}")

```

RMSE: 290.122681564536

```

[11]: # Validation with k-cross-validation and neg_root_mean_squared_error
train_scores = []
cv_scores     = []

# Values used
estimator_range = range(1, 500, 25)

# Train esach model with each values for n_estimators and extract its error
# test and k-cross-validation.
for n_estimators in estimator_range:
    model = GradientBoostingRegressor(
        n_estimators = n_estimators,
        loss          = 'ls',
        max_features = 'auto',
        random_state = 123)

    # Error train
    model.fit(X_train, y_train)
    predictions = model.predict(X = X_train)
    rmse = mean_squared_error(
        y_true = y_train,
        y_pred = predictions,
        squared = False
    )
    train_scores.append(rmse)

    # Error cv
    scores = cross_val_score(
        estimator = model,
        X          = X_train,
        y          = y_train,
        scoring    = 'neg_root_mean_squared_error',
        cv         = 5,
        n_jobs     = multiprocessing.cpu_count() - 1,
    )

    # aggregate scores cross_val_score() and pass to possitive
    cv_scores.append(-1*scores.mean())

```


```

# plot error evolution
fig, ax = plt.subplots(figsize=(6, 4))
ax.plot(estimator_range, train_scores, label="train scores")
ax.plot(estimator_range, cv_scores, label="cv scores")
ax.plot(estimator_range[np.argmin(cv_scores)], min(cv_scores),
        marker='o', color = "red", label="min score")
ax.set_ylabel("root_mean_squared_error")
ax.set_xlabel("n_estimators")
ax.set_title("Evolution cv-error vs n° trees")
plt.legend();
print(f"Optimal n_estimators: {estimator_range[np.argmin(cv_scores)]}")

```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell`
automatically in the future. Please pass the result to `transformed_cell`
argument and any exception that happen during the transform in
`preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)

Optimal n_estimators: 376



```

[12]: # Validation k-cross-validation and neg_root_mean_squared_error
results = {}

```

```

# Values used
learning_rates = [0.001, 0.01, 0.1]
n_estimators   = [10, 20, 100, 200, 300, 400, 500, 1000, 2000, 5000]

# model train for each combination of learning_rate + n_estimator
# we get the error for train and k-cross-validation.
for learning_rate in learning_rates:
    train_scores = []
    cv_scores    = []

    for n_estimator in n_estimators:

        model = GradientBoostingRegressor(
            n_estimators = n_estimator,
            learning_rate = learning_rate,
            loss          = 'ls',
            max_features  = 'auto',
            random_state  = 123
        )

        # Error train
        model.fit(X_train, y_train)
        predictions = model.predict(X = X_train)
        rmse = mean_squared_error(
            y_true = y_train,
            y_pred = predictions,
            squared = False
        )
        train_scores.append(rmse)

        # Error CV
        scores = cross_val_score(
            estimator = model,
            X          = X_train,
            y          = y_train,
            scoring    = 'neg_root_mean_squared_error',
            cv         = 3,
            n_jobs     = multiprocessing.cpu_count() - 1
        )
        # aggregate scores cross_val_score() and pass to positive
        cv_scores.append(-1*scores.mean())

    results[learning_rate] = {'train_scores': train_scores, 'cv_scores':
    ↪cv_scores}

```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
 DeprecationWarning: `should_run_async` will not call `transform_cell`


automatically in the future. Please pass the result to `transformed_cell` argument and any exception that happen during thetransform in `preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)

```
[13]: # plot error evolution
fig, axs = plt.subplots(nrows=1, ncols=2, figsize=(12, 4))

for key, value in results.items():
    axs[0].plot(n_estimators, value['train_scores'], label=f"Learning rate_
    ↳{key}")
    axs[0].set_ylabel("root_mean_squared_error")
    axs[0].set_xlabel("n_estimators")
    axs[0].set_title("Evolution train error vs learning rate")

    axs[1].plot(n_estimators, value['cv_scores'], label=f"Learning rate {key}")
    axs[1].set_ylabel("root_mean_squared_error")
    axs[1].set_xlabel("n_estimators")
    axs[1].set_title("Evolution cv-error vs learning rate")
plt.legend();
```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell` automatically in the future. Please pass the result to `transformed_cell` argument and any exception that happen during thetransform in `preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)



```
[14]: # Validation k-cross-validation and neg_root_mean_squared_error
train_scores = []
cv_scores    = []
```

```

# Values used
max_depths = [1, 3, 5, 10, 20]

# Train model for each max_depth
for max_depth in max_depths:

    model = GradientBoostingRegressor(
        n_estimators = 100,
        loss          = 'ls',
        max_depth     = max_depth,
        max_features  = 'auto',
        random_state  = 123
    )

    # Error train
    model.fit(X_train, y_train)
    predictions = model.predict(X = X_train)
    rmse = mean_squared_error(
        y_true = y_train,
        y_pred = predictions,
        squared = False
    )
    train_scores.append(rmse)


    # Error CV
    scores = cross_val_score(
        estimator = model,
        X          = X_train,
        y          = y_train,
        scoring    = 'neg_root_mean_squared_error',
        cv         = 5,
        n_jobs     = multiprocessing.cpu_count() - 1
    )

    # aggregate scores cross_val_score() pass to positive
    cv_scores.append(-1*scores.mean())

# plots errors evolution
fig, ax = plt.subplots(figsize=(6, 3.84))
ax.plot(max_depths, train_scores, label="train scores")
ax.plot(max_depths, cv_scores, label="cv scores")
ax.plot(max_depths[np.argmin(cv_scores)], min(cv_scores),
        marker='o', color = "red", label="min score")
ax.set_ylabel("root_mean_squared_error")
ax.set_xlabel("max_depth")
ax.set_title("Evolution cv-error vs depth trees")
plt.legend();
print(f"Optimal max_depth: {max_depths[np.argmin(cv_scores)]}")

```

Optimal max_depth: 3



```
[15]: # Grid hyperparameters
param_grid = {'max_features' : ['auto', 'sqrt', 'log2'],
              'max_depth'    : [None, 1, 3, 5, 10, 20],
              'subsample'    : [0.5, 1],
              'learning_rate' : [0.001, 0.01, 0.1]
            }

# Grid-search with cv
grid = GridSearchCV(
    estimator = GradientBoostingRegressor(
        n_estimators = 1000,
        random_state = 123,
        # Early stop #
        validation_fraction = 0.1,
        n_iter_no_change = 5,
        tol = 0.0001
    ),
    param_grid = param_grid,
    scoring = 'neg_root_mean_squared_error',
    n_jobs = multiprocessing.cpu_count() - 1,
    cv = RepeatedKFold(n_splits=3, n_repeats=1, random_state=123),
    refit = True,
```



```

        verbose      = 0,
        return_train_score = True
    )

grid.fit(X = X_train, y = y_train)

# Results
results = pd.DataFrame(grid.cv_results_)
results.filter(regex = '(param.*|mean_t|std_t)') \
    .drop(columns = 'params') \
    .sort_values('mean_test_score', ascending = False) \
    .head(4)

```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell`
automatically in the future. Please pass the result to `transformed_cell`
argument and any exception that happen during thetransform in
`preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)

```

[15]: param_learning_rate param_max_depth param_max_features param_subsample \
42          0.01          1          auto          0.5
85          0.1          3          auto          1
84          0.1          3          auto          0.5
43          0.01          1          auto          1

      mean_test_score  std_test_score  mean_train_score  std_train_score
42      -34.769307      8.284038      -21.374647      7.083668
85      -43.690610     14.844964     -17.924675     14.837714
84      -44.277225      9.237654     -11.548560      0.675477
43      -45.275335     13.817673     -24.863461     12.650241

```

```

[16]: # Best hyperparameters by cv
print("-----")
print("Best hyperparameters by cv")
print("-----")
print(grid.best_params_, ":", grid.best_score_, grid.scoring)

```

Best hyperparameters by cv

```
{'learning_rate': 0.01, 'max_depth': 1, 'max_features': 'auto', 'subsample':
0.5} : -34.769306894000444 neg_root_mean_squared_error
```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell`
automatically in the future. Please pass the result to `transformed_cell`
argument and any exception that happen during thetransform in

`preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)

```
[17]: # Error test
model = grid.best_estimator_
predictions = model.predict(X = X_test)
rmse = mean_squared_error(
    y_true = y_test,
    y_pred = predictions,
    squared = False
)
print(f"rmse test: {rmse}")
```

rmse test: 28.34568080645437

```
[18]: importance_predictors = pd.DataFrame({'#predictor': Bar.columns,
                                           'predictor': Bar.drop(columns = 'num_casos.
                                           ↪x').columns,
                                           'importance': model.feature_importances_})
print("Importance of predictors")
print("-----")
importance_predictors.sort_values('importance', ascending=False)
```

Importance of predictors

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell`
automatically in the future. Please pass the result to `transformed_cell`
argument and any exception that happen during the transform in
`preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)

```
[18]:
```

	predictor	importance
0	num_casos_prueba_pcr	1.0
1	retail_and_recreation_percent_change_from_base...	0.0
2	grocery_and_pharmacy_percent_change_from_baseline	0.0
3	parks_percent_change_from_baseline	0.0
4	transit_stations_percent_change_from_baseline	0.0
5	workplaces_percent_change_from_baseline	0.0
6	residential_percent_change_from_baseline	0.0
7	total	0.0

```
[19]: importance = permutation_importance(
    estimator = model,
    X          = X_train,
    y          = y_train,
    n_repeats  = 5,
```

```

        scoring      = 'neg_root_mean_squared_error',
        n_jobs        = multiprocessing.cpu_count() - 1,
        random_state  = 123
    )

    # Store results (mean / sd)
    df_importance = pd.DataFrame(
        {k: importance[k] for k in ['importances_mean',
        → 'importances_std']}
    )
    df_importance['feature'] = X_train.columns
    df_importance.sort_values('importances_mean', ascending=False)

```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
 DeprecationWarning: `should_run_async` will not call `transform_cell`
 automatically in the future. Please pass the result to `transformed_cell`
 argument and any exception that happen during the transform in
 `preprocessing_exc_tuple` in IPython 7.17 and above.
 and should_run_async(code)

```

[19]: importances_mean importances_std \
0      1148.56166      21.286321
1           0.00000      0.000000
2           0.00000      0.000000
3           0.00000      0.000000
4           0.00000      0.000000
5           0.00000      0.000000
6           0.00000      0.000000
7           0.00000      0.000000

                                feature
0                                num_casos_prueba_pcr
1  retail_and_recreation_percent_change_from_base...
2  grocery_and_pharmacy_percent_change_from_baseline
3                parks_percent_change_from_baseline
4  transit_stations_percent_change_from_baseline
5                workplaces_percent_change_from_baseline
6    residential_percent_change_from_baseline
7                                total

```

```

[20]: # Calculate the mean absolute error (MAE)
mae = mean_absolute_error(predictions, y_test)
print('MAE: ' + str(round(mae, 5)))

# Calculate the root mean squarred error (RMSE)
rmse = np.sqrt(mean_squared_error(y_test, predictions))
print('RMSE: ' + str(round(rmse, 5)))

```

MAE: 22.83728
RMSE: 28.34568

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell`
automatically in the future. Please pass the result to `transformed_cell`
argument and any exception that happen during the transform in
`preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)

```
[21]: predictions_df = pd.DataFrame(predictions)
      predictions_df.rename(columns={0: 'Pred'}, inplace=True)
      y_test_df = pd.DataFrame(y_test)
      y_test_df.reset_index(drop=True, inplace=True)
      y_test_df
      predictions_df['yt'] = y_test_df['num_casos.x']
      predictions_df
```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell`
automatically in the future. Please pass the result to `transformed_cell`
argument and any exception that happen during the transform in
`preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)


```
[21]:
```

	Pred	yt
0	1433.336326	1444
1	1449.676218	1477
2	1337.660770	1320
3	1390.921179	1353
4	1449.676218	1477
5	1079.767930	1078
6	1006.216141	994
7	1786.908303	1785
8	1764.008930	1763
9	1578.444153	1616
10	1698.050571	1735
11	972.864145	974
12	1283.685019	1262
13	1337.660770	1311
14	2479.184912	2440
15	2179.823619	2244
16	2173.908974	2197

```
[22]: _ = predictions_df.plot()
```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:
DeprecationWarning: `should_run_async` will not call `transform_cell`

automatically in the future. Please pass the result to `transformed_cell` argument and any exception that happen during the transform in `preprocessing_exc_tuple` in IPython 7.17 and above.
and should_run_async(code)



1.2 XGboost (Supervised)

Following code is extracted from Brownlee (2020) for check purposes.

Brownlee, J., 2021. How to Use XGBoost for Time Series Forecasting. [online] Machine Learning Mastery. Available at: <https://machinelearningmastery.com/xgboost-for-time-series-forecasting/> [Accessed 17 May 2021].

```
[23]: from numpy import asarray
from pandas import DataFrame
from pandas import concat
from xgboost import XGBRegressor
from matplotlib import pyplot

# transform a time series dataset into a supervised learning dataset
def series_to_supervised(data, n_in=1, n_out=1, dropnan=True):
    n_vars = 1 if type(data) is list else data.shape[0]
    df = DataFrame(data)
    cols = list()
    # input sequence (t-n, ... t-1)
    for i in range(n_in, 0, -1):
        cols.append(df.shift(i))
```

```

    # forecast sequence (t, t+1, ... t+n)
    for i in range(0, n_out):
        cols.append(df.shift(-i))
    # put it all together
    agg = concat(cols, axis=1)
    # drop rows with NaN values
    if dropnan:
        agg.dropna(inplace=True)
    return agg.values

# split a univariate dataset into train/test sets
def train_test_split(data, n_test):
    return data[:-n_test, :], data[-n_test:, :]

# fit an xgboost model and make a one step prediction
def xgboost_forecast(train, testX):
    # transform list into array
    train = asarray(train)
    # split into input and output columns
    trainX, trainy = train[:, :-1], train[:, -1]
    # fit model
    model = XGBRegressor(objective='reg:squarederror', n_estimators=1000)
    model.fit(trainX, trainy)
    # make a one-step prediction
    yhat = model.predict(asarray([testX]))
    return yhat[0]

# walk-forward validation for univariate data
def walk_forward_validation(data, n_test):
    predictions = list()
    # split dataset
    train, test = train_test_split(data, n_test)
    # seed history with training dataset
    history = [x for x in train]
    # step over each time-step in the test set
    for i in range(len(test)):
        # split test row into input and output columns
        testX, testy = test[i, :-1], test[i, -1]
        # fit model on history and make a prediction
        yhat = xgboost_forecast(history, testX)
        # store forecast in list of predictions
        predictions.append(yhat)
        # add actual observation to history for the next loop
        history.append(test[i])
        # summarize progress
        print('>expected=%.1f, predicted=%.1f' % (testy, yhat))
    # estimate prediction error

```

```

        error = mean_squared_error(test[:, -1], predictions, squared = False)
        #error = mean_absolute_error(test[:, -1], predictions)
        return error, test[:, -1], predictions

# load the dataset
values = Bar['num_casos.x'].values
# transform the time series data into supervised learning
data = series_to_supervised(values, n_in=14)
# evaluate
mae, y, yhat = walk_forward_validation(data,17)
#print('MAE: %.3f' % mae)
print('RMSE: %.3f' % mae)
# plot expected vs predicted
plt.plot(y, label='Expected')
plt.plot(yhat, label='Predicted')
plt.legend()
plt.show()

```

C:\ProgramData\Anaconda3\lib\site-packages\ipykernel\ipkernel.py:287:

DeprecationWarning: `should_run_async` will not call `transform_cell` automatically in the future. Please pass the result to `transformed_cell` argument and any exception that happen during the transform in `preprocessing_exc_tuple` in IPython 7.17 and above.

and should_run_async(code)

C:\ProgramData\Anaconda3\lib\site-packages\xgboost\data.py:119: UserWarning: Use subset (sliced data) of np.ndarray is not recommended because it will generate extra copies and increase memory consumption

warnings.warn(

```

>expected=1444.0, predicted=954.1
>expected=1477.0, predicted=1116.8
>expected=1320.0, predicted=1386.6
>expected=1353.0, predicted=1484.4
>expected=1477.0, predicted=1305.3
>expected=1078.0, predicted=1252.3
>expected=994.0, predicted=1036.6
>expected=1785.0, predicted=1206.6
>expected=1763.0, predicted=1665.1
>expected=1616.0, predicted=1585.4
>expected=1735.0, predicted=1728.1
>expected=974.0, predicted=1717.4
>expected=1262.0, predicted=974.1
>expected=1311.0, predicted=1602.3
>expected=2440.0, predicted=1512.8
>expected=2244.0, predicted=2853.6
>expected=2197.0, predicted=2475.1
RMSE: 407.815

```

