



STERLING
VENTILATION

PRODUCT BROCHURE · DEMO

ENGINEERED VENTILATION PRODUCTS

Natural, smoke and mechanical ventilation equipment engineered, certified and delivered for buildings and critical infrastructure across the Asia-Pacific region.

- 01 NATURAL VENTILATION
- 02 SMOKE VENTILATION
- 03 MECHANICAL VENTILATION

Demonstration document — replace with the approved product brochure before publication.



NATURAL VENTILATION

SV-LRV	Louvred Roof Ventilator	Certified aerodynamic free area to 4.2 m ²
SV-WA	Window Actuator	24 V chain and spindle drives, 150–1000 mm stroke
SV-DRV	Dome Roof Ventilator	Daylight and ventilation, optional SHEVS variant
SV-RV	Ridge Ventilator	Continuous modular runs, 450–1500 mm throat
SV-FLV	Facade Louvre Ventilator	Free area to 62%, Class A rain defence

SMOKE VENTILATION

SV-SC	Smoke Curtain	D120 / DH120 to EN 12101-1, drops to 8 m
SV-SHEV	Smoke Ventilator	EN 12101-2, B300, WL 1500, Re 1000
SV-SCD	Smoke Control Damper	EIS 120 to EN 12101-8 / EN 1366-10
SV-F400	Smoke Extract Fan	EN 12101-3 F300 / F400, to 40 m ³ /s
SV-SCP	Smoke Control Panel	EN 12101-9 / -10, 1–64 zones
SV-SPU	Stair Pressurisation Unit	EN 12101-6, 50 Pa modulated

MECHANICAL VENTILATION

SV-AXL	Axial Flow Fan	0.5–45 m ³ /s to 1200 Pa, adjustable pitch
SV-CFG	Centrifugal Fan	Backward curved, to 3500 Pa
SV-JET	Car Park Jet Fan	F300, 25–110 N thrust, from 260 mm deep
SV-AHU	Air Handling Unit	Double skin, EC plug-fan arrays
SV-TVF	Tunnel Ventilation Fan	Reversible, 250–400 °C / 2 h



Smoke Curtain

Automatic smoke containment classified D120 / DH120 to EN 12101-1.

CLASSIFICATION

Standard	EN 12101-1
Classification	D120 (smoke) / DH120 (smoke + heat)
Fabric	Woven glass fibre, heat-reflective coated
Deployment	Gravity fail-safe, controlled descent ~0.1 m/s

DIMENSIONS

Maximum drop	8 m single panel, unlimited multi-panel
Maximum width	5 m per panel, joined for longer runs
Headbox	Extruded aluminium, 165 × 165 mm minimum
Bottom bar	Aluminium, 40 mm profile

ELECTRICAL

Motor supply	24 V DC, UPS backed
Standby duration	30 / 60 minutes to project requirement
Interfaces	Fire alarm volt-free, BMS monitoring
Self test	Automatic weekly cycle with event log

NOTE

Performance data shown is indicative. Project-specific selection, calculations and certification are issued with the technical submission.



GET IN TOUCH

Talk to our engineers

Technical enquiries reach an engineer, not a call centre. Send us the building, the fire strategy or the constraint you are working around.

SINGAPORE — HEAD OFFICE

[Street address]
Singapore [postal code]
+65 0000 0000
enquiry@sterlingventilation.com

INDIA — ENGINEERING & OPERATIONS

[Street address]
[City] [PIN]
+91 00000 00000
india@sterlingventilation.com

DIRECT CHANNELS

Engineering & modelling · engineering@sterlingventilation.com
Service & maintenance · service@sterlingventilation.com

PROTECTING PEOPLE. PRESERVING LIFE.