

Basic API Documentation

Base URL (local development): <http://10.100.3.10:3000>

All endpoints accept and return JSON.

Authentication

POST /sign_up

Create a new user account and receive access + refresh tokens.

Request body

```
{  
  "name": "Jane Doe",  
  "phone": "+46123456789",  
  "email": "jane@example.com",  
  "password": "secret123"  
}
```

Responses

- 201 Created

```
{  
  "access_token": "<JWT access token>",  
  "refresh_token": "<JWT refresh token>",  
  "user": {  
    "_id": "uuid-string",  
    "name": "Jane Doe",  
    "role": "user",  
    "email": "jane@example.com",  
    "phone": "+46123456789",  
    "password": "secret123",  
    "created_at": "2025-01-01T12:00:00.000Z"  
  }  
}
```

- 400 Bad Request

- Missing body or any of: name, phone, email, password.
 - User already exists for given email.
-

POST /login

Log in an existing user and receive new tokens.

Request body

```
{  
  "email": "jane@example.com",  
  "password": "secret123"  
}
```

Responses

- **201 Created**

```
{  
  "access_token": "<JWT access token>",  
  "refresh_token": "<JWT refresh token>",  
  "user": {  
    "_id": "uuid-string",  
    "name": "Jane Doe",  
    "role": "user",  
    "email": "jane@example.com",  
    "phone": "+46123456789",  
    "password": "secret123",  
    "created_at": "2025-01-01T12:00:00.000Z"  
  }  
}
```

- **400 Bad Request**

– Missing `email` or `password`.

- **404 Not Found**

– No user for that email.

- **401 Unauthorized**

– Wrong password.

POST /refresh_token

Exchange a valid refresh token for a new pair of access + refresh tokens.

Request body

```
{  
  "refresh_token": "<JWT refresh token>"  
}
```

Responses

- **200 OK**

```
{
  "access_token": "<new JWT access token>",
  "refresh_token": "<new JWT refresh token>",
  "user": {
    "_id": "uuid-string",
    "name": "Jane Doe",
    "role": "user",
    "email": "jane@example.com",
    "phone": "+46123456789",
    "password": "secret123",
    "created_at": "2025-01-01T12:00:00.000Z"
  }
}
```

- **400 Bad Request**
 - Missing `refresh_token`.
 - **401 Unauthorized**
 - Invalid or non-refresh token.
 - **404 Not Found**
 - User in token no longer exists.
-

Products

GET /products

Get the list of products. **Requires a valid access token.**

Headers

- `Authorization: Bearer <access_token>`

Responses

- **200 OK**

```
[
  {
    "id": "product-id-1",
    "name": "Example Product",
    "price": 100
    // ...other fields depending on the dataset...
  }
  // more products...
]
```

- **401 Unauthorized**

- Missing or invalid/expired access token.