

---

# **fdasrsf Documentation**

***Release 2.4.2***

**J. Derek Tucker**


**Jul 21, 2023**




# CONTENTS

<b>1</b>	<b>User Guide</b>	<b>3</b>
1.1	Elastic Functional Alignment . . . . .	3
1.2	Elastic Functional Principal Component Analysis . . . . .	6
1.2.1	Vertical fPCA . . . . .	7
1.2.2	Horizontal fPCA . . . . .	8
1.2.3	Joint fPCA . . . . .	8
1.3	Elastic Curve Alignment . . . . .	10
1.3.1	Shape PCA . . . . .	12
<b>2</b>	<b>Functional Alignment</b>	<b>15</b>
<b>3</b>	<b>Functional Principal Component Analysis</b>	<b>17</b>
<b>4</b>	<b>Elastic Functional Boxplots</b>	<b>21</b>
<b>5</b>	<b>Functional Principal Least Squares</b>	<b>23</b>
<b>6</b>	<b>Elastic Regression</b>	<b>25</b>
<b>7</b>	<b>Elastic Principal Component Regression</b>	<b>33</b>
<b>8</b>	<b>Elastic GLM Regression</b>	<b>37</b>
<b>9</b>	<b>Elastic Functional Tolerance Bounds</b>	<b>39</b>
<b>10</b>	<b>Elastic Functional Clustering</b>	<b>43</b>
<b>11</b>	<b>Elastic Image Warping</b>	<b>45</b>
<b>12</b>	<b>Curve Registration</b>	<b>47</b>
<b>13</b>	<b>SRVF Geodesic Computation</b>	<b>51</b>
<b>14</b>	<b>Utility Functions</b>	<b>57</b>
<b>15</b>	<b>Curve Functions</b>	<b>65</b>
<b>16</b>	<b>UMAP EFDA Metrics</b>	<b>75</b>
<b>17</b>	<b>References</b>	<b>77</b>
<b>18</b>	<b>Indices and tables</b>	<b>79</b>

<b>Python Module Index</b>	<b>81</b>
<b>Index</b>	<b>83</b>




A python package for functional data analysis using the square root slope framework and curves using the square root velocity framework which performs pair-wise and group-wise alignment as well as modeling using functional component analysis and regression.





## USER GUIDE

Contents:



## 1.1 Elastic Functional Alignment

Otherwise known as time warping in the literature is at the center of elastic functional data analysis. Here our goal is to separate out the horizontal and vertical variability of the functional data

```
[1]: import fdasrsf as fs
import numpy as np
```

Load in our example data

```
[2]: data = np.load('../bin/simu_data.npz')
time = data['arr_1']
f = data['arr_0']
```

We will then construct the fdawarp object

```
[3]: obj = fs.fdawarp(f,time)
```


Next we will align the functions using the elastic framework

```
[4]: obj.srsf_align(parallel=True)


Initializing...
Compute Karcher Mean of 21 function in SRSF space...
updating step: r=1
updating step: r=2
```

Display plots demonstrating the alignment

```
[5]: obj.plot()
```









## 1.2 Elastic Functional Principal Component Analysis

After we have aligned our data we can compute functional principal component analysis (fPCA) on the aligned data, warping functions, and jointly

```
[1]: import fdasrsf as fs
import numpy as np
```

We will load in our example data again and compute the alignment

```
[2]: data = np.load('../bin/simu_data.npz')
time = data['arr_1']
f = data['arr_0']
obj = fs.fdawarp(f,time)
obj.srsf_align(parallel=True)
```

```
Initializing...
Compute Karcher Mean of 21 function in SRSF space...
updating step: r=1
updating step: r=2
```



### 1.2.1 Vertical fPCA

We will first compute fPCA on the aligned functions, by constructing the object and computing the PCA for the number of components, default=3)

```
[3]: vpca = fs.fdavpca(obj)
     vpca.calc_fpca(no=3)
```

We then can plot the principal directions

```
[4]: vpca.plot()
```




## 1.2.2 Horizontal fPCA

We can then compute PCA on the set of warping functions

```
[5]: hpca = fs.fdahpca(obj)
      hpca.calc_fpca(no=3)
```

We then can plot the principal directions

```
[6]: hpca.plot()
```




## 1.2.3 Joint fPCA

We can also compute the fPCA on jointly on the phase/amplitude space if we feel there is correlation between the variabilities

```
[7]: jpca = fs.fdajpca(obj)
      jpca.calc_fpca(no=3)
```

We then can plot the principal directions

```
[8]: jpca.plot()
```



## 1.3 Elastic Curve Alignment

Otherwise known as time warping in the literature is at the center of elastic functional data analysis. Here our goal is to separate out the horizontal and vertical variability of the open/closed curves

```
[1]: import fdasrsf as fs
import numpy as np
```

Load in our example data

```
[2]: data = np.load('../bin/MPEG7.npz', allow_pickle=True)
Xdata = data['Xdata']
curve = Xdata[0,1]
n,M = curve.shape
K = Xdata.shape[1]

beta = np.zeros((n,M,K))
for i in range(0,K):
    beta[:, :, i] = Xdata[0,i]
```

We will then construct the fdacurve object

```
[3]: obj = fs.fdacurve(beta, N=M)
```

We then will compute karcher mean of the curves

```
[4]: obj.karcher_mean()


Computing Karcher Mean of 20 curves in SRVF space..
updating step: 1
updating step: 2
updating step: 3
updating step: 4
updating step: 5
updating step: 6
updating step: 7
```

We then can align the curves to the karcher mean

```
[5]: obj.srvf_align(rotation=False)
```

Plot the results

```
[6]: obj.plot()
```




### 1.3.1 Shape PCA

We then can compute the Karcher covariance and compute the shape pca


```
[7]: obj.karcher_cov()
     obj.shape_pca()
```

Plot the principal directions

```
[8]: obj.plot_pca()
```










## FUNCTIONAL ALIGNMENT





## FUNCTIONAL PRINCIPAL COMPONENT ANALYSIS

Vertical and Horizontal Functional Principal Component Analysis using SRSF

moduleauthor:: J. Derek Tucker <jdtuck@sandia.gov>

**class** fPCA.fdahpca(*fdawarp*)

This class provides horizontal fPCA using the SRVF framework

Usage: obj = fdahpca(warp\_data)

### Parameters

- **warp\_data** – fdawarp class with alignment data
- **gam\_pca** – warping functions principal directions
- **psi\_pca** – srvf principal directions
- **latent** – latent values
- **U** – eigenvectors
- **coef** – coefficients
- **vec** – shooting vectors
- **mu** – Karcher Mean
- **tau** – principal directions

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 15-Mar-2018

**calc\_fpca**(*no=3, stds=array([-1, 0, 1])*)

This function calculates horizontal functional principal component analysis on aligned data

### Parameters

- **no** (*int*) – number of components to extract (default = 3)
- **stds** – number of standard deviations along geodesic to compute (default = -1,0,1)

### Return type

fdahpca object of numpy ndarray

### Return q\_pca

srsf principal directions

### Return f\_pca

functional principal directions

### Return latent

latent values

**Return coef**

coefficients

**Return U**

eigenvectors

**plot()**

plot plot elastic horizontal fPCA results

Usage: obj.plot()

**class fPCA.fdajpca(fdawarp)**

This class provides joint fPCA using the SRVF framework

Usage: obj = fdajpca(warp\_data)

**Parameters**

- **warp\_data** – fdawarp class with alignment data
- **q\_pca** – srvf principal directions
- **f\_pca** – f principal directions
- **latent** – latent values
- **coef** – principal coefficients
- **id** – point used for  $f(0)$
- **mqn** – mean srvf
- **U** – eigenvectors
- **mu\_psi** – mean psi
- **mu\_g** – mean g
- **C** – scaling value
- **stds** – geodesic directions

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 18-Mar-2018

**calc\_fpca(no=3, stds=array([-1., 0., 1.]), id=None, parallel=False, cores=-1)**

This function calculates joint functional principal component analysis on aligned data

**Parameters**

- **no** (*int*) – number of components to extract (default = 3)
- **id** (*int*) – point to use for  $f(0)$  (default = midpoint)
- **stds** – number of standard deviations along geodesic to compute (default = -1,0,1)
- **parallel** (*bool*) – run in parallel (default = F)
- **cores** (*int*) – number of cores for parallel (default = -1 (all))

**Return type**

fdajpca object of numpy ndarray

**Return q\_pca**

srsf principal directions

**Return f\_pca**

functional principal directions

**Return latent**

latent values

**Return coef**

coefficients

**Return U**

eigenvectors

**plot()**

plot plot elastic vertical fPCA result

Usage: obj.plot()

**class fPCA.fdavpca(*fdawarp*)**

This class provides vertical fPCA using the SRVF framework

Usage: obj = fdavpca(warp\_data)

**Parameters**

- **warp\_data** – fdawarp class with alignment data
- **q\_pca** – srvf principal directions
- **f\_pca** – f principal directions
- **latent** – latent values
- **coef** – principal coefficients
- **id** – point used for  $f(0)$
- **mqn** – mean srvf
- **U** – eigenvectors
- **stds** – geodesic directions

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 15-Mar-2018

**calc\_fpca(*no=3, id=None, stds=array([-1, 0, 1])*)**

This function calculates vertical functional principal component analysis on aligned data

**Parameters**

- **no** (*int*) – number of components to extract (default = 3)
- **id** (*int*) – point to use for  $f(0)$  (default = midpoint)
- **stds** – number of standard deviations along geodesic to compute (default = -1,0,1)

**Return type**

fdavpca object containing

**Return q\_pca**

srsf principal directions

**Return f\_pca**

functional principal directions

**Return latent**

latent values


**Return coef**

coefficients

**Return U**  
eigenvectors

**plot()**

plot plot elastic vertical fPCA result Usage: obj.plot()





## ELASTIC FUNCTIONAL BOXPLOTS

Elastic Functional Boxplots

moduleauthor:: J. Derek Tucker <jdtuck@sandia.gov>

**class** boxplots.ampbox(*fdawarp*)

This class provides amplitude boxplot for functional data using the SRVF framework

Usage: obj = ampbox(warp\_data)

### Parameters

- **warp\_data** (*fdawarp*) – fdawarp class with alignment data
- **Q1** – First quartile
- **Q3** – Second quartile
- **Q1a** – First quantile based on alpha
- **Q3a** – Second quantile based on alpha
- **minn** – minimum extreme function
- **maxx** – maximum extreme function
- **outlier\_index** – indexes of outlier functions
- **f\_median** – median function
- **q\_median** – median srvf
- **plt** – surface plot mesh

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 15-Mar-2018

**construct\_boxplot**(*alpha=0.05, k\_a=1*)

This function constructs the amplitude boxplot using the elastic square-root slope (srsf) framework.

### Parameters

- **alpha** – quantile value (e.g.,=.05, i.e., 95%)
- **k\_a** – scalar for outlier cutoff (e.g.,=1)

**plot()**

plot box plot and surface plot

Usage: obj.plot()

**class** boxplots.**phbox**(*fdawarp*)

This class provides phase boxplot for functional data using the SRVF framework

Usage: `obj = phbox(warp_data)`

**Parameters**

- **warp\_data** (*fdawarp*) – fdawarp class with alignment data
- **Q1** – First quartile
- **Q3** – Second quartile
- **Q1a** – First quantile based on alpha
- **Q3a** – Second quantile based on alpha
- **minn** – minimum extreme function
- **maxx** – maximum extreme function
- **outlier\_index** – indexes of outlier functions
- **median\_x** – median warping function
- **psi\_median** – median srvf of warping function
- **plt** – surface plot mesh

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 15-Mar-2018

**construct\_boxplot**(*alpha=0.05, k\_a=1*)

This function constructs phase boxplot for functional data using the elastic square-root slope (srsf) framework.


**Parameters**

- **alpha** – quantile value (e.g.,=.05, i.e., 95%)
- **k\_a** – scalar for outlier cutoff (e.g.,=1)

**plot**()

plot box plot and surface plot

Usage: `obj.plot()`



## FUNCTIONAL PRINCIPAL LEAST SQUARES

Partial Least Squares using SVD

moduleauthor:: J. Derek Tucker <[jdtuck@sandia.gov](mailto:jdtuck@sandia.gov)>

fPLS.**pls\_svd**(time, qf, qg, no, alpha=0.0)

This function computes the partial least squares using SVD

### Parameters

- **time** – vector describing time samples
- **qf** – numpy ndarray of shape (M,N) of N functions with M samples
- **qg** – numpy ndarray of shape (M,N) of N functions with M samples
- **no** – number of components
- **alpha** – amount of smoothing (Default = 0.0 i.e., none)

### Return type

numpy ndarray

### Return wqf

f weight function

### Return wqg


g weight function

### Return alpha

smoothing value

### Return values

singular values





## ELASTIC REGRESSION

Warping Invariant Regression using SRSF

moduleauthor:: J. Derek Tucker <jdtuck@sandia.gov>

**class** regression.elastic\_logistic(*f, y, time*)

This class provides elastic logistic regression for functional data using the SRVF framework accounting for warping

Usage: obj = elastic\_logistic(f,y,time)

### Parameters

- **f** (*np.ndarray*) – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy array of N responses
- **time** (*np.ndarray*) – vector of size M describing the sample points
- **B** – optional matrix describing Basis elements
- **alpha** – alpha parameter of model
- **beta** – beta(t) of model
- **fn** – aligned functions - numpy ndarray of shape (M,N) of M functions with N samples
- **qn** – aligned srvfs - similar structure to fn
- **gamma** – calculated warping functions
- **q** – original training SRSFs
- **b** – basis coefficients
- **Loss** – logistic loss

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 29-Oct-2021

**calc\_model**(*B=None, lam=0, df=20, max\_itr=20, cores=-1, smooth=False*)

This function identifies a regression model with phase-variability using elastic pca

### Parameters

- **B** – optional matrix describing Basis elements
- **lam** – regularization parameter (default 0)
- **df** – number of degrees of freedom B-spline (default 20)
- **max\_itr** – maximum number of iterations (default 20)
- **cores** – number of cores for parallel processing (default all)

**predict**(*newdata=None*)

This function performs prediction on regression model on new data if available or current stored data in object Usage: obj.predict()

obj.predict(newdata)

#### Parameters

- **newdata** (*dict*) – dict containing new data for prediction (needs the keys below, if None predicts on training data)
- **f** – (M,N) matrix of functions
- **time** – vector of time points
- **y** – truth if available
- **smooth** – smooth data if needed
- **sparam** – number of times to run filter

**class regression.elastic\_mlogistic**(*f, y, time*)

This class provides elastic multinomial logistic regression for functional data using the SRVF framework accounting for warping

Usage: obj = elastic\_mlogistic(f,y,time)

#### Parameters

- **f** (*np.ndarray*) – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy array of N responses
- **time** (*np.ndarray*) – vector of size M describing the sample points
- **B** – optional matrix describing Basis elements
- **alpha** – alpha parameter of model
- **beta** – beta(t) of model
- **fn** – aligned functions - numpy ndarray of shape (M,N) of N functions with M samples
- **qn** – aligned srvfs - similar structure to fn
- **gamma** – calculated warping functions
- **q** – original training SRSFs
- **b** – basis coefficients
- **Loss** – logistic loss

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 29-Oct-2021

**calc\_model**(*B=None, lam=0, df=20, max\_itr=20, delta=0.01, cores=- 1, smooth=False*)

This function identifies a regression model with phase-variability using elastic pca

#### Parameters

- **B** – optional matrix describing Basis elements
- **lam** – regularization parameter (default 0)
- **df** – number of degrees of freedom B-spline (default 20)
- **max\_itr** – maximum number of iterations (default 20)

- **cores** – number of cores for parallel processing (default all)

**predict**(*newdata=None*)

This function performs prediction on regression model on new data if available or current stored data in object Usage: obj.predict()

obj.predict(newdata)

#### Parameters

- **newdata** (*dict*) – dict containing new data for prediction (needs the keys below, if None predicts on training data)
- **f** – (M,N) matrix of functions
- **time** – vector of time points
- **y** – truth if available
- **smooth** – smooth data if needed
- **sparam** – number of times to run filter

**class regression.elastic\_regression**(*f, y, time*)

This class provides elastic regression for functional data using the SRVF framework accounting for warping

Usage: obj = elastic\_regression(f,y,time)

#### Parameters

- **f** – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy array of N responses
- **time** – vector of size M describing the sample points
- **B** – optional matrix describing Basis elements
- **alpha** – alpha parameter of model
- **beta** – beta(t) of model
- **fn** – aligned functions - numpy ndarray of shape (M,N) of M functions with N samples
- **qn** – aligned srvfs - similar structure to fn
- **gamma** – calculated warping functions
- **q** – original training SRSFs
- **b** – basis coefficients
- **SSE** – sum of squared error

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 29-Oct-2021

**calc\_model**(*B=None, lam=0, df=20, max\_itr=20, cores=-1, smooth=False*)

This function identifies a regression model with phase-variability using elastic pca

#### Parameters

- **B** – optional matrix describing Basis elements
- **lam** – regularization parameter (default 0)
- **df** – number of degrees of freedom B-spline (default 20)
- **max\_itr** – maximum number of iterations (default 20)

- **cores** – number of cores for parallel processing (default all)

**predict**(*newdata=None*)

This function performs prediction on regression model on new data if available or current stored data in object Usage: obj.predict()

obj.predict(newdata)

#### Parameters

- **newdata** (*dict*) – dict containing new data for prediction (needs the keys below, if None predicts on training data)
- **f** – (M,N) matrix of functions
- **time** – vector of time points
- **y** – truth if available
- **smooth** – smooth data if needed
- **sparam** – number of times to run filter

regression.**logistic\_warp**(*beta, time, q, y*)

calculates optimal warping for function logistic regression

#### Parameters

- **beta** – numpy ndarray of shape (M,N) of N functions with M samples
- **time** – vector of size N describing the sample points
- **q** – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy ndarray of shape (1,N) responses

#### Return type

numpy array

#### Return gamma

warping function

regression.**logit\_gradient**(*b, X, y*)

calculates gradient of the logistic loss

#### Parameters

- **b** – numpy ndarray of shape (M,N) of N functions with M samples
- **X** – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy ndarray of shape (1,N) responses

#### Return type

numpy array

#### Return grad

gradient of logistic loss

regression.**logit\_hessian**(*s, b, X, y*)

calculates hessian of the logistic loss

#### Parameters

- **s** – numpy ndarray of shape (M,N) of N functions with M samples



- **b** – numpy ndarray of shape (M,N) of N functions with M samples
- **X** – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy ndarray of shape (1,N) responses

**Return type**

numpy array

**Return out**

hessian of logistic loss

`regression.logit_loss(b, X, y)`logistic loss function, returns  $\text{Sum}\{-\log(\phi(t))\}$ **Parameters**

- **b** – numpy ndarray of shape (M,N) of N functions with M samples
- **X** – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy ndarray of shape (1,N) of N responses

**Return type**

numpy array

**Return out**

loss value

`regression.mlogit_gradient(b, X, Y)`

calculates gradient of the multinomial logistic loss

**Parameters**

- **b** – numpy ndarray of shape (M,N) of N functions with M samples
- **X** – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy ndarray of shape (1,N) responses

**Return type**

numpy array

**Return grad**

gradient

`regression.mlogit_loss(b, X, Y)`

calculates multinomial logistic loss (negative log-likelihood)

**Parameters**

- **b** – numpy ndarray of shape (M,N) of N functions with M samples
- **X** – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy ndarray of shape (1,N) responses

**Return type**

numpy array

**Return nll**

negative log-likelihood

`regression.mlogit_warp_grad(alpha, beta, time, q, y, max_itr=8000, tol=1e-10, delta=0.008, display=0)`  
calculates optimal warping for functional multinomial logistic regression

**Parameters**

- **alpha** – scalar
- **beta** – numpy ndarray of shape (M,N) of N functions with M samples
- **time** – vector of size M describing the sample points
- **q** – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy ndarray of shape (1,N) responses
- **max\_itr** – maximum number of iterations (Default=8000)
- **tol** – stopping tolerance (Default=1e-10)
- **delta** – gradient step size (Default=0.008)
- **display** – display iterations (Default=0)

**Return type**

tuple of numpy array

**Return gam\_old**

warping function

`regression.phi(t)`

calculates logistic function, returns  $1 / (1 + \exp(-t))$

**Parameters**

**t** – scalar

**Return type**

numpy array

**Return out**

return value

`regression.regression_warp(beta, time, q, y, alpha)`

calculates optimal warping for function linear regression

**Parameters**


- **beta** – numpy ndarray of shape (M,N) of M functions with N samples
- **time** – vector of size N describing the sample points
- **q** – numpy ndarray of shape (M,N) of M functions with N samples
- **y** – numpy ndarray of shape (1,N) of M functions with N samples responses
- **alpha** – numpy scalar

**Return type**

numpy array

**Return gamma\_new**

warping function





## ELASTIC PRINCIPAL COMPONENT REGRESSION

Warping Invariant PCR Regression using SRSF

moduleauthor:: J. Derek Tucker <jdtuck@sandia.gov>

**class** pcr\_regression.elastic\_lpcr\_regression(*f, y, time*)

This class provides elastic logistic pcr regression for functional data using the SRVF framework accounting for warping

Usage: obj = elastic\_lpcr\_regression(f,y,time)

### Parameters

- **f** – (M,N) % matrix defining N functions of M samples
- **y** – response vector of length N (-1/1)
- **warp\_data** – fdawarp object of alignment
- **pca** – class dependent on fPCA method used object of fPCA

:param information :param alpha: intercept :param b: coefficient vector :param Loss: logistic loss :param PC: probability of classification :param ylabels: predicted labels

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 18-Mar-2018

**calc\_model**(*pca\_method='combined', no=5, smooth\_data=False, sparam=25, parallel=False*)

This function identifies a logistic regression model with phase-variability using elastic pca

### Parameters

- **pca\_method** – string specifying pca method (options = “combined”, “vert”, or “horiz”, default = “combined”)
- **no** – scalar specify number of principal components (default=5)
- **smooth\_data** – smooth data using box filter (default = F)
- **sparam** – number of times to apply box filter (default = 25)
- **parallel** – calculate in parallel (default = F)

**predict**(*newdata=None*)

This function performs prediction on regression model on new data if available or current stored data in object Usage: obj.predict()

obj.predict(newdata)

### Parameters

- **newdata** (*dict*) – dict containing new data for prediction (needs the keys below, if None predicts on training data)
- **f** – (M,N) matrix of functions
- **time** – vector of time points
- **y** – truth if available
- **smooth** – smooth data if needed
- **sparam** – number of times to run filter

**class** pcr\_regression.elastic\_mlpcr\_regression(*f, y, time*)

This class provides elastic multinomial logistic pcr regression for functional data using the SRVF framework accounting for warping

Usage: obj = elastic\_mlpcr\_regression(f,y,time)

#### Parameters

- **f** – (M,N) % matrix defining N functions of M samples
- **y** – response vector of length N
- **Y** – coded label matrix
- **warp\_data** – fdawarp object of alignment
- **pca** – class dependent on fPCA method used object of fPCA

:param information :param alpha: intercept :param b: coefficient vector :param Loss: logistic loss :param PC: probability of classification :param ylabels: predicted labels

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 18-Mar-2018

**calc\_model**(*pca\_method='combined', no=5, smooth\_data=False, sparam=25, parallel=False*)

This function identifies a logistic regression model with phase-variability using elastic pca

#### Parameters

- **f** (*np.ndarray*) – numpy ndarray of shape (M,N) of N functions with M samples
- **y** – numpy array of N responses
- **time** (*np.ndarray*) – vector of size M describing the sample points
- **pca\_method** – string specifying pca method (options = “combined”, “vert”, or “horiz”, default = “combined”)
- **no** – scalar specify number of principal components (default=5)
- **smooth\_data** – smooth data using box filter (default = F)
- **sparam** – number of times to apply box filter (default = 25)
- **parallel** – run model in parallel (default = F)

**predict**(*newdata=None*)

This function performs prediction on regression model on new data if available or current stored data in object Usage: obj.predict()

obj.predict(newdata)

#### Parameters

- **newdata** (*dict*) – dict containing new data for prediction (needs the keys below, if None predicts on training data)
- **f** – (M,N) matrix of functions
- **time** – vector of time points
- **y** – truth if available
- **smooth** – smooth data if needed
- **sparam** – number of times to run filter

**class** pcr\_regression.**elastic\_pcr\_regression**(*f, y, time*)

This class provides elastic pcr regression for functional data using the SRVF framework accounting for warping

Usage: obj = elastic\_pcr\_regression(f,y,time)

#### Parameters

- **f** – (M,N) % matrix defining N functions of M samples
- **y** – response vector of length N
- **warp\_data** – fdawarp object of alignment
- **pca** – class dependent on fPCA method used object of fPCA
- **alpha** – intercept
- **b** – coefficient vector
- **SSE** – sum of squared errors

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 18-Mar-2018

**calc\_model**(*pca\_method='combined', no=5, smooth\_data=False, sparam=25, parallel=False, C=None*)

This function identifies a regression model with phase-variability using elastic pca

#### Parameters

- **pca\_method** – string specifying pca method (options = “combined”, “vert”, or “horiz”, default = “combined”)
- **no** – scalar specify number of principal components (default=5)
- **smooth\_data** – smooth data using box filter (default = F)
- **sparam** – number of times to apply box filter (default = 25)
- **parallel** – run in parallel (default = F)
- **C** – scale balance parameter for combined method (default = None)

**predict**(*newdata=None*)


This function performs prediction on regression model on new data if available or current stored data in object Usage: obj.predict()

obj.predict(newdata)

#### Parameters

- **newdata** (*dict*) – dict containing new data for prediction (needs the keys below, if None predicts on training data)
- **f** – (M,N) matrix of functions

- **time** – vector of time points
- **y** – truth if available
- **smooth** – smooth data if needed
- **sparam** – number of times to run filter





## ELASTIC GLM REGRESSION

Warping Invariant GML Regression using SRSF

moduleauthor:: Derek Tucker <jdtuck@sandia.gov>

**class** elastic\_glm\_regression.**elastic\_glm\_regression**(*f, y, time*)

This class provides elastic glm regression for functional data using the SRVF framework accounting for warping

Usage: obj = elastic\_glm\_regression(f,y,time)

### Parameters

- **f** – (M,N) % matrix defining N functions of M samples
- **y** – response vector of length N
- **time** – time vector of length M
- **alpha** – intercept
- **b** – coefficient vector
- **B** – basis matrix
- **lambda** – regularization parameter
- **SSE** – sum of squared errors

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 18-Mar-2018

**calc\_model**(*link='linear', B=None, lam=0, df=20, max\_itr=20, smooth\_data=False, sparam=25, parallel=False*)

This function identifies a regression model with phase-variability using elastic pca

### Parameters

- **link** – string of link function ('linear', 'quadratic', 'cubic')
- **B** – optional matrix describing Basis elements
- **lam** – regularization parameter (default 0)
- **df** – number of degrees of freedom B-spline (default 20)
- **max\_itr** – maximum number of iterations (default 20)
- **smooth\_data** – smooth data using box filter (default = F)
- **sparam** – number of times to apply box filter (default = 25)
- **parallel** – run in parallel (default = F)

**predict**(*newdata=None, parallel=True*)

This function performs prediction on regression model on new data if available or current stored data in object Usage: obj.predict()

obj.predict(newdata)

#### Parameters

- **newdata** (*dict*) – dict containing new data for prediction (needs the keys below, if None predicts on training data)
- **f** – (M,N) matrix of functions
- **time** – vector of time points
- **y** – truth if available
- **smooth** – smooth data if needed
- **sparam** – number of times to run filter

elastic\_glm\_regression.**rand**(*d0, d1, ..., dn*)

Random values in a given shape.

---

**Note:** This is a convenience function for users porting code from Matlab, and wraps *random\_sample*. That function takes a tuple to specify the size of the output, which is consistent with other NumPy functions like *numpy.zeros* and *numpy.ones*.

---

Create an array of the given shape and populate it with random samples from a uniform distribution over [0, 1).

**d0, d1, ..., dn**


[int, optional] The dimensions of the returned array, must be non-negative. If no argument is given a single Python float is returned.

**out**

[ndarray, shape (d0, d1, ..., dn)] Random values.

random

```
>>> np.random.rand(3,2)
array([[ 0.14022471,  0.96360618], #random
       [ 0.37601032,  0.25528411], #random
       [ 0.49313049,  0.94909878]]) #random
```



## ELASTIC FUNCTIONAL TOLERANCE BOUNDS

Functional Tolerance Bounds using SRSF

moduleauthor:: J. Derek Tucker <[jdtuck@sandia.gov](mailto:jdtuck@sandia.gov)>

`tolerance.bootTB(f, time, a=0.05, p=0.99, B=500, no=5, parallel=True)`

This function computes tolerance bounds for functional data containing phase and amplitude variation using bootstrap sampling

### Parameters

- **f** (*np.ndarray*) – numpy ndarray of shape (M,N) of N functions with M samples
- **time** (*np.ndarray*) – vector of size M describing the sample points
- **a** – confidence level of tolerance bound (default = 0.05)
- **p** – coverage level of tolerance bound (default = 0.99)
- **B** – number of bootstrap samples (default = 500)
- **no** – number of principal components (default = 5)
- **parallel** – enable parallel processing (default = T)

### Return type

tuple of boxplot objects

### Return amp

amplitude tolerance bounds

### Rtype out\_med

ampbox object

### Return ph

phase tolerance bounds

### Rtype out\_med

phbox object

### Return out\_med

alignment results

### Rtype out\_med

fdawarp object

`tolerance.mvtol_region(x, alpha, P, B)`

Computes tolerance factor for multivariate normal

Krishnamoorthy, K. and Mondal, S. (2006), Improved Tolerance Factors for Multivariate Normal Distributions, Communications in Statistics - Simulation and Computation, 35, 461–478.

#### Parameters

- **x** – (M,N) matrix defining N variables of M samples
- **alpha** – confidence level
- **P** – coverage level
- **B** – number of bootstrap samples

#### Return type

double

#### Return tol

tolerance factor

`tolerance.pcaTB(f, time, a=0.5, p=0.99, no=5, parallel=True)`

This function computes tolerance bounds for functional data containing phase and amplitude variation using fPCA

#### Parameters

- **f** (*np.ndarray*) – numpy ndarray of shape (M,N) of N functions with M samples
- **time** (*np.ndarray*) – vector of size M describing the sample points
- **a** – confidence level of tolerance bound (default = 0.05)
- **p** – coverage level of tolerance bound (default = 0.99)
- **no** – number of principal components (default = 5)
- **parallel** – enable parallel processing (default = T)

#### Return type

tuple of boxplot objects

#### Return warp

alignment data from time\_warping

#### Return pca

functional pca from jointFPCA

#### Return tol

tolerance factor

`tolerance.rwishart(df, p)`

Computes a random wishart matrix

#### Parameters


- **df** – degree of freedom
- **p** – number of dimensions

#### Return type

double

#### Return R

matrix





## ELASTIC FUNCTIONAL CLUSTERING

Elastic Functional Clustering

moduleauthor:: J. Derek Tucker <[jdtuck@sandia.gov](mailto:jdtuck@sandia.gov)>

```
kmeans.kmeans_align(f, time, K, seeds=None, lam=0, showplot=True, smooth_data=False, parallel=False,
                    alignment=True, omethod='DP2', MaxItr=50, thresh=0.01)
```

This function clusters functions and aligns using the elastic square-root slope (srsf) framework.

### Parameters

- **f** – numpy ndarray of shape (M,N) of N functions with M samples
- **time** – vector of size M describing the sample points

:param K number of clusters :param seeds indexes of cluster center functions (default = None) :param lam controls the elasticity (default = 0) :param showplot shows plots of functions (default = T) :param smooth\_data smooth data using box filter (default = F) :param parallel enable parallel mode using code{`link{jjoblib}`} and

code{`doParallel`} package (default=F)

:param alignment whether to perform alignment (default = T) :param omethod optimization method (DP,DP2,RBFGS) :param MaxItr maximum number of iterations :param thresh cost function threshold :type f: np.ndarray :type time: np.ndarray

### Return type

dictionary

### Return fn

aligned functions - matrix (N x M) of M functions with N samples which is a list for each cluster

### Return qn

aligned SRSFs - similar structure to fn

### Return q0

original SRSFs

### Return labels

cluster labels

### Return templates

cluster center functions


### Return templates\_q

cluster center SRSFs

### Return gam

warping functions - similar structure to fn

**Return qun**  
Cost Function





## ELASTIC IMAGE WARPING

image warping using SRVF framework

moduleauthor:: J. Derek Tucker <[jdtuck@sandia.gov](mailto:jdtuck@sandia.gov)>

`image.reparam_image(It, Im, gam=None, b=None, stepsize=0.0001, itermax=20)`

This function warps an image to another using SRVF framework

### Parameters

- **Im** – numpy ndarray of shape (N,N) representing a NxN image
- **Im** – numpy ndarray of shape (N,N) representing a NxN image
- **gam** – numpy ndarray of shape (N,N) representing an initial warping function
- **b** – numpy ndarray representing basis matrix

### Return type

numpy ndarray

### Return gamnew

diffeomorphism

### Return Inew


warped image

### Return H

energy

### Return stepsize

final stepsize





## CURVE REGISTRATION

statistic calculation for SRVF (curves) open and closed using Karcher Mean and Variance

moduleauthor:: J. Derek Tucker <jdtuck@sandia.gov>

**class** `curve_stats.fdacurve(beta, mode='O', N=200, scale=False)`

This class provides alignment methods for open and closed curves using the SRVF framework

Usage: `obj = fdacurve(beta, mode, N, scale)` :param beta: numpy ndarray of shape (n, M, N) describing N curves in  $R^M$  :param mode: Open ('O') or closed curve ('C') (default 'O') :param N: resample curve to N points :param scale: scale curve to length 1 (true/false) :param q: (n,T,K) matrix defining n dimensional srvf on T samples with K srvfs :param betan: aligned curves :param qn: aligned srvfs :param basis: calculated basis :param beta\_mean: karcher mean curve :param q\_mean: karcher mean srvf :param gams: warping functions :param v: shooting vectors :param C: karcher covariance :param s: pca singular values :param U: pca singular vectors :param coef: pca coefficients :param pca\_principal\_directions: :param qun: cost function :param samples: random samples :param gamr: random warping functions :param cent: center :param scale: scale :param len: length of curve :param len\_q: length of srvf :param mean\_scale\_mean\_length: :param mean\_scale\_q\_mean\_length :param E: energy

Author : J. D. Tucker (JDT) <jdtuck AT sandia.gov> Date : 26-Aug-2020

**karcher\_cov()**

This calculates the mean of a set of curves

**karcher\_mean(rotation=True, parallel=False, cores=-1, method='DP')**

This calculates the mean of a set of curves :param rotation: compute optimal rotation (default = T) :param parallel: run in parallel (default = F) :param cores: number of cores for parallel (default = -1 (all)) :param method: method to apply optimization (default="DP") options are "DP" or "RBFGS"

**plot()**

plot curve mean results

**sample\_shapes(no=3, numSamp=10)**

Computes sample shapes from mean and covariance

### Parameters

- **no** – number of direction (default 3)
- **numSamp** – number of samples (default 10)

**shape\_pca(no=10)**

Computes principal direction of variation specified by no. N is Number of shapes away from mean. Creates  $2*N+1$  shape sequence

### Parameters

- **no** – number of direction (default 3)

**srvf\_align**(rotation=True, parallel=False, cores=-1, method='DP')

This aligns a set of curves to the mean and computes mean if not computed :param rotation: compute optimal rotation (default = T) :param parallel: run in parallel (default = F) :param cores: number of cores for parallel (default = -1 (all)) :param method: method to apply optimization (default="DP") options are "DP" or "RBFSS"

curve\_stats.**randn**(d0, d1, ..., dn)

Return a sample (or samples) from the "standard normal" distribution.

---

**Note:** This is a convenience function for users porting code from Matlab, and wraps *standard\_normal*. That function takes a tuple to specify the size of the output, which is consistent with other NumPy functions like *numpy.zeros* and *numpy.ones*.

---

---

**Note:** New code should use the *~numpy.random.Generator.standard\_normal* method of a *~numpy.random.Generator* instance instead; please see the random-quick-start.

---

If positive int\_like arguments are provided, *randn* generates an array of shape (d0, d1, ..., dn), filled with random floats sampled from a univariate "normal" (Gaussian) distribution of mean 0 and variance 1. A single float randomly sampled from the distribution is returned if no argument is provided.

**d0, d1, ..., dn**

[int, optional] The dimensions of the returned array, must be non-negative. If no argument is given a single Python float is returned.

**Z**

[ndarray or float] A (d0, d1, ..., dn)-shaped array of floating-point samples from the standard normal distribution, or a single such float if no parameters were supplied.

*standard\_normal* : Similar, but takes a tuple as its argument. *normal* : Also accepts mu and sigma arguments. *random.Generator.standard\_normal*: which should be used for new code.


For random samples from the normal distribution with mean mu and standard deviation sigma, use:

```
sigma * np.random.randn(...) + mu
```

```
>>> np.random.randn()
2.1923875335537315 # random
```

Two-by-four array of samples from the normal distribution with mean 3 and standard deviation 2.5:

```
>>> 3 + 2.5 * np.random.randn(2, 4)
array([[ -4.49401501,  4.00950034, -1.81814867,  7.29718677], # random
       [ 0.39924804,  4.68456316,  4.99394529,  4.84057254]]) # random
```





## SRVF GEODESIC COMPUTATION

geodesic calculation for SRVF (curves) open and closed

moduleauthor:: J. Derek Tucker <[jdtuck@sandia.gov](mailto:jdtuck@sandia.gov)>

`geodesic.back_parallel_transport(u1, alpha, basis, T=100, k=5)`

backwards parallel translates q1 and q2 along manifold

### Parameters

- **u1** – numpy ndarray of shape (2,M) of M samples
- **alpha** – numpy ndarray of shape (2,M) of M samples
- **basis** – list numpy ndarray of shape (2,M) of M samples
- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

### Return type

numpy ndarray

### Return utilde

translated vector

`geodesic.calc_alphadot(alpha, basis, T=100, k=5)`

calculates derivative along the path alpha

### Parameters

- **alpha** – numpy ndarray of shape (2,M) of M samples
- **basis** – list of numpy ndarray of shape (2,M) of M samples
- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

### Return type

numpy ndarray

### Return alphadot

derivative of alpha

`geodesic.calculate_energy(alphadot, T=100, k=5)`

calculates energy along path

### Parameters

- **alphadot** – numpy ndarray of shape (2,M) of M samples

- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

**Return type**

numpy scalar

**Return E**

energy

`geodesic.calculate_gradE(u, utilde, T=100, k=5)`

calculates gradient of energy along path

**Parameters**

- **u** – numpy ndarray of shape (2,M) of M samples
- **utilde** – numpy ndarray of shape (2,M) of M samples
- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

**Return type**

numpy scalar

**Return gradE**

gradient of energy

**Return normgradE**

norm of gradient of energy

`geodesic.cov_integral(alpha, alphadot, basis, T=100, k=5)`

Calculates covariance along path alpha

**Parameters**

- **alpha** – numpy ndarray of shape (2,M) of M samples (first curve)
- **alphadot** – numpy ndarray of shape (2,M) of M samples
- **basis** – list numpy ndarray of shape (2,M) of M samples
- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

**Return type**

numpy ndarray

**Return u**

covariance

`geodesic.find_basis_normal_path(alpha, k=5)`

computes orthonormalized basis vectors to the normal space at each of the k points (q-functions) of the path alpha

**Parameters**

- **alpha** – numpy ndarray of shape (2,M) of M samples (path)
- **k** – number of samples along path (Default = 5)

**Return type**

numpy ndarray



**Return basis**

basis vectors along the path

`geodesic.geod_dist_path_strt(beta, k=5)`

calculate geodisc distance for path straightening

**Parameters**

- **beta** – numpy ndarray of shape (2,M) of M samples
- **k** – number of samples along path (Default = 5)

**Return type**

numpy scalar

**Return dist**

geodesic distance

`geodesic.geod_sphere(beta1, beta2, k=5, scale=False, rotation=True, center=True)`

This function calculates the geodesics between open curves beta1 and beta2 with k steps along path

**Parameters**

- **beta1** – numpy ndarray of shape (2,M) of M samples
- **beta2** – numpy ndarray of shape (2,M) of M samples
- **k** – number of samples along path (Default = 5)
- **scale** – include length (Default = False)
- **rotation** – include rotation (Default = True)
- **center** – center curves at origin (Default = True)

**Return type**

numpy ndarray

**Return dist**

geodesic distance

**Return path**

geodesic path

**Return PsiQ**

geodesic path in SRVF

`geodesic.init_path_geod(beta1, beta2, T=100, k=5)`Initializes a path in  $\mathcal{C}$ . beta1, beta2 are already standardized curves. Creates a path from beta1 to beta2 in shape space, then projects to the closed shape manifold.**Parameters**

- **beta1** – numpy ndarray of shape (2,M) of M samples (first curve)
- **beta2** – numpy ndarray of shape (2,M) of M samples (end curve)
- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

**Return type**

numpy ndarray

**Return alpha**

a path between two q-functions

**Return beta**

a path between two curves

**Return O**

rotation matrix

`geodesic.init_path_rand(beta1, beta_mid, beta2, T=100, k=5)`

Initializes a path in  $\mathcal{C}$ . `beta1`, `beta_mid` `beta2` are already standardized curves. Creates a path from `beta1` to `beta_mid` to `beta2` in shape space, then projects to the closed shape manifold.

**Parameters**

- **beta1** – numpy ndarray of shape (2,M) of M samples (first curve)
- **betamid** – numpy ndarray of shape (2,M) of M samples (mid curve)
- **beta2** – numpy ndarray of shape (2,M) of M samples (end curve)
- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

**Return type**

numpy ndarray

**Return alpha**

a path between two q-functions

**Return beta**

a path between two curves

**Return O**

rotation matrix

`geodesic.path_straightening(beta1, beta2, betamid=None, init='rand', T=100, k=5)`

Perform path straightening to find geodesic between two shapes in either the space of closed curves or the space of affine standardized curves. This algorithm follows the steps outlined in section 4.6 of the manuscript.

**Parameters**

- **beta1** – numpy ndarray of shape (2,M) of M samples (first curve)
- **beta2** – numpy ndarray of shape (2,M) of M samples (end curve)
- **betamid** – numpy ndarray of shape (2,M) of M samples (mid curve Default = None, only needed for init “geod”)
- **init** – initialize path geodesic or random (Default = “rand”)
- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

**Return type**

numpy ndarray

**Return dist**

geodesic distance

**Return path**

geodesic path

**Return pathsqnc**

geodesic path sequence

**Return E**

energy

`geodesic.plot_geod(path)`

Plots the geodesic path as a sequence of curves

**Parameters**
**path** – numpy ndarray of shape (2,M,K) of M sample points of K samples along path

`geodesic.update_path(alpha, beta, gradE, delta, T=100, k=5)`

Update the path along the direction -gradE

**Parameters**

- **alpha** – numpy ndarray of shape (2,M) of M samples
- **beta** – numpy ndarray of shape (2,M) of M samples
- **gradE** – numpy ndarray of shape (2,M) of M samples
- **delta** – gradient parameter
- **T** – Number of samples of curve (Default = 100)
- **k** – number of samples along path (Default = 5)

**Return type**


numpy scalar

**Return alpha**

updated path of srvfs

**Return beta**

updated path of curves





## UTILITY FUNCTIONS

Utility functions for SRSF Manipulations

moduleauthor:: J. Derek Tucker <[jdtuck@sandia.gov](mailto:jdtuck@sandia.gov)>

`utility_functions.SqrtMean(gam, parallel=False, cores=-1)`

calculates the srsf of warping functions with corresponding shooting vectors

**Parameters**

- **gam** – numpy ndarray of shape (M,N) of M warping functions with N samples
- **parallel** – run in parallel (default = F)
- **cores** – number of cores for parallel (default = -1 (all))

**Return type**

2 numpy ndarray and vector

**Return mu**

Karcher mean psi function

**Return gam\_mu**

vector of dim N which is the Karcher mean warping function

**Return psi**

numpy ndarray of shape (M,N) of M SRSF of the warping functions

**Return vec**

numpy ndarray of shape (M,N) of M shooting vectors

`utility_functions.SqrtMeanInverse(gam)`

finds the inverse of the mean of the set of the diffeomorphisms gamma

**Parameters**

**gam** – numpy ndarray of shape (M,N) of N warping functions with M samples

**Return type**

vector

**Return gamI**

inverse of gam

`utility_functions.SqrtMedian(gam)`

calculates the median srsf of warping functions with corresponding shooting vectors

**Parameters**

**gam** – numpy ndarray of shape (M,N) of M warping functions with N samples

**Return type**

2 numpy ndarray and vector

**Return gam\_median**

Karcher median warping function

**Return psi\_meidan**

vector of dim N which is the Karcher median srsf function

**Return psi**

numpy ndarray of shape (M,N) of M SRSF of the warping functions

**Return vec**

numpy ndarray of shape (M,N) of M shooting vectors

`utility_functions.cumtrapzmid(x, y, c, mid)`

cumulative trapezoidal numerical integration taken from midpoint

**Parameters**

- **x** – vector of size N describing the time samples
- **y** – vector of size N describing the function
- **c** – midpointtic
- **mid** – midpiont location

**Return type**

vector

**Return fa**

cumulative integration

`utility_functions.diffop(n, binsize=1)`

Creates a second order differential operator

**Parameters**

- **n** – dimension
- **binsize** – dx (default = 1)

**Return type**

numpy ndarray

**Return m**

matrix describing differential operator

`utility_functions.elastic_depth(f, time, method='DP2', lam=0.0, parallel=True)`

calculates the elastic depth between functions in matrix f

**Parameters**

- **f** – matrix of size MxN (M time points for N functions)
- **time** – vector of size M describing the sample points
- **method** – method to apply optimization (default="DP2") options are "DP", "DP2", "RBFGS"
- **lam** – controls the elasticity (default = 0.0)

**Return type**

scalar

**Return amp**

amplitude depth

**Return phase**

phase depth

`utility_functions.elastic_distance(f1, f2, time, method='DP2', lam=0.0)`

” calculates the distances between function, where f1 is aligned to f2. In other words calculates the elastic distances

**Parameters**

- **f1** – vector of size N
- **f2** – vector of size N
- **time** – vector of size N describing the sample points
- **method** – method to apply optimization (default=”DP2”) options are “DP”, ”DP2”, ”RBFGS”
- **lam** – controls the elasticity (default = 0.0)

**Return type**

scalar

**Return Dy**

amplitude distance

**Return Dx**

phase distance

`utility_functions.f_K_fold(Nobs, K=5)`

generates sample indices for K-fold cross validation

:param Nobs number of observations :param K number of folds

**Return type**

numpy ndarray

**Return train**

train indexes (Nobs\*(K-1)/K X K)

**Return test**

test indexes (Nobs\*(1/K) X K)

`utility_functions.f_to_srsf(f, time, smooth=False)`

converts f to a square-root slope function (SRSF)

**Parameters**

- **f** – vector of size N samples
- **time** – vector of size N describing the sample points

**Return type**

vector

**Return q**

srsf of f

`utility_functions.geigen(Amat, Bmat, Cmat)`

generalized eigenvalue problem of the form

$\max \text{tr } L'AM / \sqrt{\text{tr } L'BL \text{tr } M'CM}$  w.r.t. L and M

:param Amat numpy ndarray of shape (M,N) :param Bmat numpy ndarray of shape (M,N) :param Bmat numpy ndarray of shape (M,N)

**Return type**

numpy ndarray

**Return values**

eigenvalues

**Return Lmat**

left eigenvectors

**Return Mmat**

right eigenvectors

utility\_functions.**gradient\_spline**(time, f, smooth=False)

This function takes the gradient of f using b-spline smoothing

**Parameters**

- **time** – vector of size N describing the sample points
- **f** – numpy ndarray of shape (M,N) of M functions with N samples
- **smooth** – smooth data (default = F)

**Return type**

tuple of numpy ndarray

**Return f0**

smoothed functions functions

**Return g**

first derivative of each function

**Return g2**

second derivative of each function

utility\_functions.**innerprod\_q**(time, q1, q2)

calculates the innerproduct between two srsfs

:param time vector descrbing time samples :param q1 vector of srsf 1 :param q2 vector of srsf 2

**Return type**

scalar

**Return val**

inner product value

utility\_functions.**invertGamma**(gam)

finds the inverse of the diffeomorphism gamma

**Parameters**

**gam** – vector describing the warping function

**Return type**

vector

**Return gamI**

inverse of gam

utility\_functions.**optimum\_reparam**(q1, time, q2, method='DP2', lam=0.0, penalty='roughness', grid\_dim=7)

calculates the warping to align srsf q2 to q1



**Parameters**

- **q1** – vector of size N or array of NxM samples of first SRSF
- **time** – vector of size N describing the sample points
- **q2** – vector of size N or array of NxM samples of second SRSF
- **method** – method to apply optimization (default="DP2") options are "DP","DP2","RBFSGS"
- **lam** – controls the amount of elasticity (default = 0.0)
- **penalty** – penalty type (default="roughness") options are "roughness", "l2gam", "l2psi", "geodesic". Only roughness implemented in all methods. To use others method needs to be "RBFSGS"
- **grid\_dim** – size of the grid, for the DP2 method only (default = 7)

**Return type**

vector

**Return gam**

describing the warping function used to align q2 with q1

`utility_functions.optimum_reparam_pair(q, time, q1, q2, lam=0.0)`

calculates the warping to align srsf pair q1 and q2 to q

**Parameters**

- **q** – vector of size N or array of NxM samples of first SRSF
- **time** – vector of size N describing the sample points
- **q1** – vector of size N or array of NxM samples of second SRSF
- **q2** – vector of size N or array of NxM samples of second SRSF
- **lam** – controls the amount of elasticity (default = 0.0)

**Return type**

vector

**Return gam**

describing the warping function used to align q2 with q1

`utility_functions.outlier_detection(q, time, mq, k=1.5)`

calculates outlier's using geodesic distances of the SRSFs from the median

**Parameters**

- **q** – numpy ndarray of N x M of M SRS functions with N samples
- **time** – vector of size N describing the sample points
- **mq** – median calculated using `time_warping.srsf_align()`
- **k** – cutoff threshold (default = 1.5)

**Returns**

q\_outlier: outlier functions

`utility_functions.randomGamma(gam, num)`

generates random warping functions

**Parameters**

- **gam** – numpy ndarray of N x M of M of warping functions

- **num** – number of random functions

**Returns**

rgam: random warping functions

`utility_functions.resamplefunction(x, n)`

resample function using n points

**Parameters**

- **x** – functions
- **n** – number of points

**Return type**

numpy array

**Return xn**

resampled function

`utility_functions.rgam(N, sigma, num, mu_gam=None)`

Generates random warping functions

**Parameters**

- **N** – length of warping function
- **sigma** – variance of warping functions
- **num** – number of warping functions

:param mu\_gam mean warping function (default identity) :return: gam: numpy ndarray of warping functions

`utility_functions.smooth_data(f, sparam=1)`

This function smooths a collection of functions using a box filter

**Parameters**

- **f** – numpy ndarray of shape (M,N) of M functions with N samples
- **sparam** – Number of times to run box filter (default = 25)

**Return type**

numpy ndarray

**Return f**

smoothed functions functions

`utility_functions.srsf_to_f(q, time, f0=0.0)`

converts q (srsf) to a function

**Parameters**

- **q** – vector of size N samples of srsf
- **time** – vector of size N describing time sample points
- **f0** – initial value

**Return type**

vector

**Return f**

function

`utility_functions.update_progress(progress)`

This function creates a progress bar

**Parameters**

**progress** – fraction of progress

`utility_functions.warp_f_gamma(time, f, gam)`

warps a function f by gam

:param time vector describing time samples :param q vector describing srsf :param gam vector describing warping function

**Return type**

numpy ndarray

**Return f\_temp**

warped srsf

`utility_functions.warp_q_gamma(time, q, gam)`

warps a srsf q by gam

:param time vector describing time samples :param q vector describing srsf :param gam vector describing warping function

**Return type**

numpy ndarray

**Return q\_temp**

warped srsf

`utility_functions.zero_crossing(Y, q, bt, time, y_max, y_min, gmax, gmin)`

finds zero-crossing of optimal gamma,  $\text{gam} = s \cdot \text{gmax} + (1-s) \cdot \text{gmin}$  from elastic regression model

**Parameters**


- **Y** – response
- **q** – predicitive function
- **bt** – basis function
- **time** – time samples
- **y\_max** – maximum repsonse for warping function gmax
- **y\_min** – minimum response for warping function gmin
- **gmax** – max warping function
- **gmin** – min warping fuction

**Return type**

numpy array

**Return gamma**

optimal warping function



## CURVE FUNCTIONS

functions for SRVF curve manipulations

moduleauthor:: J. Derek Tucker <[jdtuck@sandia.gov](mailto:jdtuck@sandia.gov)>

`curve_functions.Basis_Normal_A(q)`

Find Normal Basis

**Parameters**

**q** – numpy ndarray (n,T) defining T points on n dimensional SRVF

:rtype list :return delg: basis

`curve_functions.calc_j(basis)`

Calculates Jacobian matrix from normal basis

**Parameters**

**basis** – list of numpy ndarray of shape (2,M) of M samples basis

**Return type**

numpy ndarray

**Return j**

Jacobian

`curve_functions.calculate_variance(beta)`

This function calculates variance of curve beta

**Parameters**

**beta** – numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return variance**

variance

`curve_functions.calculatecentroid(beta)`

This function calculates centroid of a parameterized curve

**Parameters**

**beta** – numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return centroid**

center coordinates

`curve_functions.curve_to_q(beta, mode='O')`

This function converts curve beta to srvf q

**Parameters**

- **beta** – numpy ndarray of shape (2,M) of M samples
- **mode** – Open ('O') or closed curve ('C') (default 'O')

**Return type**

numpy ndarray

**Return q**

srvf of curve

**Return lenb**

length of curve

**Return lenq**

length of srvf

`curve_functions.curve_zero_crossing(Y, q, bt, y_max, y_min, gmax, gmin)`

finds zero-crossing of optimal gamma,  $\text{gam} = s \cdot \text{gmax} + (1-s) \cdot \text{gmin}$  from elastic curve regression model

**Parameters**

- **Y** – response
- **beta** – predictive function
- **bt** – basis function
- **y\_max** – maximum response for warping function gmax
- **y\_min** – minimum response for warping function gmin
- **gmax** – max warping function
- **gmin** – min warping function

**Return type**

numpy array

**Return gamma**

optimal warping function

**Return O\_hat**

rotation matrix

`curve_functions.elastic_distance_curve(beta1, beta2, closed=0, rotation=True, scale=False, method='DP')`

Calculates the two elastic distances between two curves :param beta1: numpy ndarray of shape (2,M) of M samples :param beta2: numpy ndarray of shape (2,M) of M samples :param closed: open (0) or closed (1) curve (default=0) :param rotation: compute optimal rotation (default=True) :param scale: include scale (default=False) :param method: method to apply optimization (default="DP") options are "DP" or "RBFGS"

**Return type**

tuple

**Return dist**

shape distance

**Return dx**

phase distance

`curve_functions.elastic_shooting(q1, v, mode=0)`

Calculates shooting vector from v to q1

**Parameters**

- **q1** – vector of srvf
- **v** – shooting vector
- **mode** – closed or open (1/0)

:rtype numpy ndarray :return q2n: vector of srvf

`curve_functions.elastic_shooting_vector(q1, q2, mode=0)`

Calculates shooting between two srvfs

**Parameters**

- **q1** – vector of srvf
- **q2** – vector of srvf
- **mode** – closed or open (1/0)

:rtype numpy ndarray :return v: shooting vector :return d: distance :return q2n: aligned srvf

`curve_functions.find_basis_normal(q)`

Finds the basis normal to the srvf

**Parameters**

**q1** – numpy ndarray of shape (2,M) of M samples

**Return type**

list of numpy ndarray

**Return basis**

list containing basis vectors

`curve_functions.find_best_rotation(q1, q2, allow_reflection=False, only_xy=False)`

This function calculates the best rotation between two srvfs using procustes rigid alignment

**Parameters**

- **q1** – numpy ndarray of shape (2,M) of M samples
- **q2** – numpy ndarray of shape (2,M) of M samples
- **allow\_reflection** – bool indicating if reflection is allowed (i.e. if the determinant of the optimal rotation can be -1)
- **only\_xy** – bool indicating if rotation should only be allowed in the first two dimensions of the space

**Return type**

numpy ndarray

**Return q2new**

optimal rotated q2 to q1

**Return R**

rotation matrix

`curve_functions.find_rotation_and_seed_coord(beta1, beta2, closed=0, rotation=True, method='DP')`

This function returns a candidate list of optimally oriented and registered (seed) shapes w.r.t. beta1

**Parameters**

- **beta1** – numpy ndarray of shape (2,M) of M samples
- **beta2** – numpy ndarray of shape (2,M) of M samples
- **closed** – Open (0) or Closed (1)
- **rotation** – find rotation (default=True)
- **method** – method to apply optimization (default="DP") options are "DP" or "RBFGS"

**Return type**

numpy ndarray

**Return beta2new**

optimal aligned beta2 to beta1

**Return q2best**

optimal aligned q2 to q1

**Return Rbest**

rotation matrix

**Return gamIbest**

warping function

`curve_functions.find_rotation_and_seed_q(q1, q2, closed=0, rotation=True, method='DP')`

This function returns a candidate list of optimally oriented and registered (seed) srvs w.r.t. q1

**Parameters**

- **q1** – numpy ndarray of shape (2,M) of M samples
- **q2** – numpy ndarray of shape (2,M) of M samples
- **closed** – Open (0) or Closed (1)
- **rotation** – find rotation (default=True)
- **method** – method to apply optimization (default="DP") options are "DP" or "RBFGS"

**Return type**

numpy ndarray

**Return q2best**

optimal aligned q2 to q1

**Return Rbest**

rotation matrix

**Return gamIbest**

warping function

`curve_functions.find_rotation_and_seed_unique(q1, q2, closed=0, rotation=True, method='DP')`

This function returns a candidate list of optimally oriented and registered (seed) shapes w.r.t. beta1

**Parameters**

- **beta1** – numpy ndarray of shape (2,M) of M samples
- **beta2** – numpy ndarray of shape (2,M) of M samples
- **closed** – Open (0) or Closed (1)
- **rotation** – find rotation (default=True)
- **method** – method to apply optimization (default="DP") options are "DP" or "RBFGS"



**Return type**

numpy ndarray

**Return beta2new**

optimal rotated beta2 to beta1

**Return O**

rotation matrix

**Return tau**

seed

`curve_functions.gram_schmidt(basis)`

Performs Gram Schmidt Orthogonalization of a basis\_o

**param basis**

list of numpy ndarray of shape (2,M) of M samples

**rtype**

list of numpy ndarray

**return basis\_o**

orthogonalized basis

`curve_functions.group_action_by_gamma(q, gamma)`

This function reparameterized srvf q by gamma

**Parameters**

- **f** – numpy ndarray of shape (2,M) of M samples
- **gamma** – numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return qn**

reparameterized srvf

`curve_functions.group_action_by_gamma_coord(f, gamma)`

This function reparameterized curve f by gamma

**Parameters**

- **f** – numpy ndarray of shape (2,M) of M samples
- **gamma** – numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return fn**

reparameterized curve

`curve_functions.innerprod_q2(q1, q2)`

This function calculates the inner product in srvf space

**Parameters**

- **q1** – numpy ndarray of shape (2,M) of M samples
- **q2** – numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return val**

inner product

`curve_functions.inverse_exp(q1, q2, beta2)`

Calculate the inverse exponential to obtain a shooting vector from q1 to q2 in shape space of open curves

**Parameters**

- **q1** – numpy ndarray of shape (2,M) of M samples
- **q2** – numpy ndarray of shape (2,M) of M samples
- **beta2** – numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return v**

shooting vectors

`curve_functions.inverse_exp_coord(beta1, beta2, closed=0, method='DP')`

Calculate the inverse exponential to obtain a shooting vector from beta1 to beta2 in shape space of open curves

**Parameters**

- **beta1** – numpy ndarray of shape (2,M) of M samples
- **beta2** – numpy ndarray of shape (2,M) of M samples
- **closed** – open (0) or closed (1) curve
- **method** – method to apply optimization (default="DP") options are "DP" or "RBFGS"

**Return type**

numpy ndarray

**Return v**

shooting vectors

**Return dist**

distance

`curve_functions.optimum_reparam_curve(q1, q2, lam=0.0, method='DP')`

calculates the warping to align srsf q2 to q1

**Parameters**

- **q1** – matrix of size nxN or array of NxM samples of first SRVF
- **time** – vector of size N describing the sample points
- **q2** – matrix of size nxN or array of NxM samples of second SRVF
- **lam** – controls the amount of elasticity (default = 0.0)
- **method** – method to apply optimization (default="DP") options are "DP" or "RBFGS"

**Return type**

vector

**Return gam**

describing the warping function used to align q2 with q1

`curve_functions.parallel_translate(w, q1, q2, basis, mode=0)`

parallel translates q1 and q2 along manifold

**Parameters**

- **w** – numpy ndarray of shape (2,M) of M samples
- **q1** – numpy ndarray of shape (2,M) of M samples
- **q2** – numpy ndarray of shape (2,M) of M samples
- **basis** – list of numpy ndarray of shape (2,M) of M samples
- **mode** – open 0 or closed curves 1 (default 0)

**Return type**

numpy ndarray

**Return wbar**

translated vector

`curve_functions.pre_proc_curve(beta, T=100)`

This function prepcoessed a curve beta to set of closed curves

**Parameters**

- **beta** – numpy ndarray of shape (2,M) of M samples
- **T** – number of samples (default = 100)

**Return type**

numpy ndarray

**Return betanew**

projected beta

**Return qnew**

projected srvf

**Return A**

alignment matrix (not used currently)

`curve_functions.project_curve(q)`

This function projects srvf q to set of close curves

**Parameters**

**q** – numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return qproj**

project srvf

`curve_functions.project_tangent(w, q, basis)`

projects srvf to tangent space w using basis

**Parameters**

- **w** – numpy ndarray of shape (2,M) of M samples
- **q** – numpy ndarray of shape (2,M) of M samples
- **basis** – list of numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return wproj**

projected q

`curve_functions.psi(x, a, q)`

This function formats variance output

**Parameters**

- **x** – numpy ndarray of shape (2,M) of M samples curve
- **a** – numpy ndarray of shape (2,1) mean
- **q** – numpy ndarray of shape (2,M) of M samples srvf

**Return type**

numpy ndarray

**Return psi1**

variance

**Return psi2**

cross variance

**Return psi3**

curve end

**Return psi4**

curve end

`curve_functions.q_to_curve(q, scale=1)`

This function converts srvf to beta

**Parameters**

- **q** – numpy ndarray of shape (n,M) of M samples
- **scale** – scale of curve

**Return type**

numpy ndarray

**Return beta**

parameterized curve

`curve_functions.resamplecurve(x, N=100, time=None, mode='O')`

This function resamples a curve to have N samples

**Parameters**

- **x** – numpy ndarray of shape (2,M) of M samples
- **N** – Number of samples for new curve (default = 100)
- **time** – timing vector (Default=None)
- **mode** – Open ('O') or closed curve ('C') (default 'O')

**Return type**

numpy ndarray

**Return xn**

resampled curve

`curve_functions.scale_curve(beta)`

scales curve to length 1

**Parameters**

**beta** – numpy ndarray of shape (2,M) of M samples

**Return type**

numpy ndarray

**Return beta\_scaled**

scaled curve

**Return scale**

scale factor used

`curve_functions.shift_f(f, tau)`

shifts a curve f by tau

**Parameters**

- **f** – numpy ndarray of shape (2,M) of M samples


- **tau** – scalar

**Return type**

numpy ndarray

**Return fn**

shifted curve





## UMAP EFDA METRICS

Distance metrics for functions and curves in  $R^n$  for use with UMAP (<https://github.com/lmcinnes/umap>)

moduleauthor:: J. Derek Tucker <[jdtuck@sandia.gov](mailto:jdtuck@sandia.gov)>

`umap_metric.efda_distance(q1, q2, alpha=0)`

” calculates the distances between two curves, where q2 is aligned to q1. In other words calculates the elastic distances/ This metric is set up for use with UMAP or t-sne from scikit-learn

### Parameters

- **q1** – vector of size N
- **q2** – vector of size N
- **alpha** – weight between phase and amplitude (default = 0, returns amplitude)

### Return type

scalar

### Return dist

amplitude distance

`umap_metric.efda_distance_curve(beta1, beta2, closed)`

” calculates the distances between two curves, where beta2 is aligned to beta1. In other words calculates the elastic distance. This metric is set up for use with UMAP or t-sne from scikit-learn

### Parameters

- **beta1** – vector of size  $n \times M$
- **beta2** – vector of size  $n \times M$
- **closed** –  
(0) if open curves and (1) if closed curves

### Return type

scalar

### Return dist

shape distance





## REFERENCES

- Tucker, J. D. 2014, Functional Component Analysis and Regression using Elastic Methods. Ph.D. Thesis, Florida State University.
- Robinson, D. T. 2012, Function Data Analysis and Partial Shape Matching in the Square Root Velocity Framework. Ph.D. Thesis, Florida State University.
- Huang, W. 2014, Optimization Algorithms on Riemannian Manifolds with Applications. Ph.D. Thesis, Florida State University.
- Srivastava, A., Wu, W., Kurtek, S., Klassen, E. and Marron, J. S. (2011). Registration of Functional Data Using Fisher-Rao Metric. *arXiv:1103.3817v2 [math.ST]*.
- Tucker, J. D., Wu, W. and Srivastava, A. (2013). Generative models for functional data using phase and amplitude separation. *Computational Statistics and Data Analysis* 61, 50-66.
- J. D. Tucker, W. Wu, and A. Srivastava, "Phase-Amplitude Separation of Proteomics Data Using Extended Fisher-Rao Metric," *Electronic Journal of Statistics*, Vol 8, no. 2. pp 1724-1733, 2014.
- J. D. Tucker, W. Wu, and A. Srivastava, "Analysis of signals under compositional noise With applications to SONAR data," *IEEE Journal of Oceanic Engineering*, Vol 29, no. 2. pp 318-330, Apr 2014.
- Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33 (7), 1415-1428.
- S. Kurtek, A. Srivastava, and W. Wu. Signal estimation under random time-warpings and nonlinear signal alignment. In *Proceedings of Neural Information Processing Systems (NIPS)*, 2011.
- Wen Huang, Kyle A. Gallivan, Anuj Srivastava, Pierre-Antoine Absil. "Riemannian Optimization for Elastic Shape Analysis", Short version, The 21st International Symposium on Mathematical Theory of Networks and Systems (MTNS 2014).
- Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.
- W. Xie, S. Kurtek, K. Bharath, and Y. Sun, A geometric approach to visualization of variability in functional data, *Journal of American Statistical Association* 112 (2017), pp. 979-993.
- Lu, Y., R. Herbei, and S. Kurtek, 2017: Bayesian registration of functions with a Gaussian process prior. *Journal of Computational and Graphical Statistics*, 26, no. 4, 894-904.
- Lee, S. and S. Jung, 2017: Combined analysis of amplitude and phase variations in functional data. *arXiv:1603.01775 [stat.ME]*, 1-21.
- J. D. Tucker, J. R. Lewis, and A. Srivastava, "Elastic Functional Principal Component Regression," *Statistical Analysis and Data Mining*, vol. 12, no. 2, pp. 101-115, 2019.
- J. D. Tucker, J. R. Lewis, C. King, and S. Kurtek, "A Geometric Approach for Computing Tolerance Bounds for Elastic Functional Data," *Journal of Applied Statistics*, 10.1080/02664763.2019.1645818, 2019.

- T. Harris, J. D. Tucker, B. Li, and L. Shand, “Elastic depths for detecting shape anomalies in functional data,” *Technometrics*, 10.1080/00401706.2020.1811156, 2020.
- M. K. Ahn, J. D. Tucker, W. Wu, and A. Srivastava. “Regression Models Using Shapes of Functions as Predictors” *Computational Statistics and Data Analysis*, 10.1016/j.csda.2020.107017, 2020.
- J. D. Tucker, L. Shand, and K. Chowdhary. “Multimodal Bayesian Registration of Noisy Functions using Hamiltonian Monte Carlo”, *Computational Statistics and Data Analysis*, accepted, 2021.
- X. Zhang, S. Kurtek, O. Chkrebtii, and J. D. Tucker, “Elastic k-means clustering of functional data for posterior exploration, with an application to inference on acute respiratory infection dynamics”, *arXiv:2011.12397 [stat.ME]*, 2020.
- Q. Xie, S. Kurtek, E. Klassen, G. E. Christensen and A. Srivastava. Metric-based pairwise and multiple image registration. *IEEE European Conference on Computer Vision (ECCV)*, September, 2014

## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`



## PYTHON MODULE INDEX

### b

[boxplots](#), 21

### c

[curve\\_functions](#), 65

[curve\\_stats](#), 47

### e

[elastic\\_glm\\_regression](#), 37

### f

[fPCA](#), 17

[fPLS](#), 23

### g

[geodesic](#), 51

### i

[image](#), 45

### k

[kmeans](#), 43

### p

[pcr\\_regression](#), 33

### r

[regression](#), 25

### t

[tolerance](#), 39

### u

[umap\\_metric](#), 75

[utility\\_functions](#), 57



## A

ampbox (class in boxplots), 21

## B

back\_parallel\_transport() (in module geodesic), 51

Basis\_Normal\_A() (in module curve\_functions), 65

bootTB() (in module tolerance), 39

boxplots  
module, 21

## C

calc\_alphadot() (in module geodesic), 51

calc\_fpca() (fPCA.fdahpca method), 17

calc\_fpca() (fPCA.fdajpca method), 18

calc\_fpca() (fPCA.fdavpca method), 19

calc\_j() (in module curve\_functions), 65

calc\_model() (elastic\_glm\_regression.elastic\_glm\_regression  
method), 37

calc\_model() (pcr\_regression.elastic\_lpcr\_regression  
method), 33

calc\_model() (pcr\_regression.elastic\_mlpcr\_regression  
method), 34

calc\_model() (pcr\_regression.elastic\_pcr\_regression  
method), 35

calc\_model() (regression.elastic\_logistic method), 25

calc\_model() (regression.elastic\_mlogistic method), 26

calc\_model() (regression.elastic\_regression method),  
27

calculate\_energy() (in module geodesic), 51

calculate\_gradE() (in module geodesic), 52

calculate\_variance() (in module curve\_functions),  
65

calculatecentroid() (in module curve\_functions), 65

construct\_boxplot() (boxplots.ampbox method), 21

construct\_boxplot() (boxplots.phbox method), 22

cov\_integral() (in module geodesic), 52

cumtrapzmid() (in module utility\_functions), 58

curve\_functions  
module, 65

curve\_stats  
module, 47

curve\_to\_q() (in module curve\_functions), 65

curve\_zero\_crossing() (in module curve\_functions),  
66

## D

diffop() (in module utility\_functions), 58

## E

efda\_distance() (in module umap\_metric), 75

efda\_distance\_curve() (in module umap\_metric), 75

elastic\_depth() (in module utility\_functions), 58

elastic\_distance() (in module utility\_functions), 59

elastic\_distance\_curve() (in module  
curve\_functions), 66

elastic\_glm\_regression  
module, 37

elastic\_glm\_regression (class in elas-  
tic\_glm\_regression), 37

elastic\_logistic (class in regression), 25

elastic\_lpcr\_regression (class in pcr\_regression),  
33

elastic\_mlogistic (class in regression), 26

elastic\_mlpcr\_regression (class in pcr\_regression),  
34

elastic\_pcr\_regression (class in pcr\_regression), 35

elastic\_regression (class in regression), 27

elastic\_shooting() (in module curve\_functions), 66

elastic\_shooting\_vector() (in module  
curve\_functions), 67

## F

f\_K\_fold() (in module utility\_functions), 59

f\_to\_srsf() (in module utility\_functions), 59

fdacurve (class in curve\_stats), 47

fdahpca (class in fPCA), 17

fdajpca (class in fPCA), 18

fdavpca (class in fPCA), 19

find\_basis\_normal() (in module curve\_functions), 67

find\_basis\_normal\_path() (in module geodesic), 52

find\_best\_rotation() (in module curve\_functions),  
67

find\_rotation\_and\_seed\_coord() (in module  
curve\_functions), 67

`find_rotation_and_seed_q()` (in module *curve\_functions*), 68  
`find_rotation_and_seed_unique()` (in module *curve\_functions*), 68

`fPCA`  
 module, 17  
`fPLS`  
 module, 23

## G

`geigen()` (in module *utility\_functions*), 59  
`geod_dist_path_strt()` (in module *geodesic*), 53  
`geod_sphere()` (in module *geodesic*), 53  
`geodesic`  
 module, 51  
`gradient_spline()` (in module *utility\_functions*), 60  
`gram_schmidt()` (in module *curve\_functions*), 69  
`group_action_by_gamma()` (in module *curve\_functions*), 69  
`group_action_by_gamma_coord()` (in module *curve\_functions*), 69

## I

`image`  
 module, 45  
`init_path_geod()` (in module *geodesic*), 53  
`init_path_rand()` (in module *geodesic*), 54  
`innerprod_q()` (in module *utility\_functions*), 60  
`innerprod_q2()` (in module *curve\_functions*), 69  
`inverse_exp()` (in module *curve\_functions*), 70  
`inverse_exp_coord()` (in module *curve\_functions*), 70  
`invertGamma()` (in module *utility\_functions*), 60

## K

`karcher_cov()` (*curve\_stats.fdacurve* method), 47  
`karcher_mean()` (*curve\_stats.fdacurve* method), 47  
`kmeans`  
 module, 43  
`kmeans_align()` (in module *kmeans*), 43

## L

`logistic_warp()` (in module *regression*), 28  
`logit_gradient()` (in module *regression*), 28  
`logit_hessian()` (in module *regression*), 28  
`logit_loss()` (in module *regression*), 29

## M

`mlogit_gradient()` (in module *regression*), 29  
`mlogit_loss()` (in module *regression*), 29  
`mlogit_warp_grad()` (in module *regression*), 29  
`module`  
 boxplots, 21  
 curve\_functions, 65

*curve\_stats*, 47  
`elastic_glm_regression`, 37  
`fPCA`, 17  
`fPLS`, 23  
`geodesic`, 51  
`image`, 45  
`kmeans`, 43  
`pcr_regression`, 33  
`regression`, 25  
`tolerance`, 39  
`umap_metric`, 75  
`utility_functions`, 57  
`mvtol_region()` (in module *tolerance*), 39

## O

`optimum_reparam()` (in module *utility\_functions*), 60  
`optimum_reparam_curve()` (in module *curve\_functions*), 70  
`optimum_reparam_pair()` (in module *utility\_functions*), 61  
`outlier_detection()` (in module *utility\_functions*), 61

## P

`parallel_translate()` (in module *curve\_functions*), 70  
`path_straightening()` (in module *geodesic*), 54  
`pcaTB()` (in module *tolerance*), 40  
`pcr_regression`  
 module, 33  
`phbox` (class in *boxplots*), 21  
`phi()` (in module *regression*), 30  
`plot()` (*boxplots.ampbox* method), 22  
`plot()` (*boxplots.phbox* method), 22  
`plot()` (*curve\_stats.fdacurve* method), 47  
`plot()` (*fPCA.fdahpca* method), 18  
`plot()` (*fPCA.fdaipca* method), 19  
`plot()` (*fPCA.fdavpca* method), 20  
`plot_geod()` (in module *geodesic*), 55  
`pls_svd()` (in module *fPLS*), 23  
`pre_proc_curve()` (in module *curve\_functions*), 71  
`predict()` (*elastic\_glm\_regression.elastic\_glm\_regression* method), 37  
`predict()` (*pcr\_regression.elastic\_lpcr\_regression* method), 33  
`predict()` (*pcr\_regression.elastic\_mlpkr\_regression* method), 34  
`predict()` (*pcr\_regression.elastic\_pcr\_regression* method), 35  
`predict()` (*regression.elastic\_logistic* method), 25  
`predict()` (*regression.elastic\_mlogistic* method), 27  
`predict()` (*regression.elastic\_regression* method), 28  
`project_curve()` (in module *curve\_functions*), 71  
`project_tangent()` (in module *curve\_functions*), 71  
`psi()` (in module *curve\_functions*), 72



## Q

`q_to_curve()` (in module *curve\_functions*), 72

## R

`rand()` (in module *elastic\_glm\_regression*), 38

`randn()` (in module *curve\_stats*), 48

`randomGamma()` (in module *utility\_functions*), 61

`regression`

module, 25

`regression_warp()` (in module *regression*), 30

`reparam_image()` (in module *image*), 45

`resamplecurve()` (in module *curve\_functions*), 72

`resamplefunction()` (in module *utility\_functions*), 62

`rgam()` (in module *utility\_functions*), 62

`rwishart()` (in module *tolerance*), 40

## S

`sample_shapes()` (*curve\_stats.fdacurve* method), 47

`scale_curve()` (in module *curve\_functions*), 72

`shape_pca()` (*curve\_stats.fdacurve* method), 47

`shift_f()` (in module *curve\_functions*), 73

`smooth_data()` (in module *utility\_functions*), 62

`SqrtMean()` (in module *utility\_functions*), 57

`SqrtMeanInverse()` (in module *utility\_functions*), 57

`SqrtMedian()` (in module *utility\_functions*), 57

`srsf_to_f()` (in module *utility\_functions*), 62

`srvf_align()` (*curve\_stats.fdacurve* method), 47

## T

`tolerance`

module, 39

## U

`umap_metric`

module, 75

`update_path()` (in module *geodesic*), 55

`update_progress()` (in module *utility\_functions*), 62

`utility_functions`

module, 57

## W

`warp_f_gamma()` (in module *utility\_functions*), 63

`warp_q_gamma()` (in module *utility\_functions*), 63

## Z

`zero_crossing()` (in module *utility\_functions*), 63