

Exchangeable Array and Random Graph

Dongwoo Kim
ANU

April 11, 2016

1 Exchangeable array

Definition 1 (Jointly exchangeable array). A random 2-array $(X_{ij})_{i,j \in \mathbb{N}}$ is jointly exchangeable if

$$(X_{ij}) \stackrel{d}{=} (X_{\pi(i)\pi(j)}) \quad \text{for } i, j \in \mathbb{N}^2 \quad (1)$$

for any permutation π of \mathbb{N} .

Definition 2 (Aldous, Hoover Theorem). [1, 3] A random 2-array $(X_{ij})_{i,j \in \mathbb{N}}$ is jointly exchangeable if and only if there exists a random measurable function $f : [0, 1]^3 \rightarrow \mathbf{X}$ such that

$$(X_{ij}) \stackrel{d}{=} (f(U_i, U_j, U_{ij})), \quad (2)$$

where $(U_i)_{i \in \mathbb{N}}$ and $(U_{ij})_{i,j \in \mathbb{N}}$ with $U_{ij} = U_{ji}$ are a sequence and matrix of i.i.d. Uniform[0,1] random variables.

For the undirected graph case $\mathcal{X} = \{0, 1\}$, the theorem can be simplified further through a random function called *graphon* $W : [0, 1]^2 \rightarrow [0, 1]$, symmetric in its arguments, where

$$f(U_i, U_j, U_{ij}) = \begin{cases} 1 & U_{ij} < W(U_i, U_j) \\ 0 & \text{otherwise} \end{cases}$$

Definition 3 (Sparse Graph). Let the number of nodes in a graph be n . The graph is sparse if the number of edges are $o(n^2)$ or dense if the number of edges are $\Theta(n^2)$.

Remark 1 (Graphon is trivially dense). Every graph represented by graphon W are either empty or dense. The asymptotic proportion of edges is $p = \frac{1}{2} \int W(x, y) dx dy$ and the graph is hence either empty ($p = 0$) or dense (since $O(pn^2) = O(n^2)$).

In [4], the authors place a Gaussian process prior over graphon $W : [0, 1]^2 \rightarrow \mathbb{R}$ and transform the output through the logistic function to model the edge probability between nodes.

For the undirected graph case where $X_{ij} = X_{ji}$, one can sample upper triangle of the adjacency matrix, and use the same result for the lower triangle. However, for the directed graph case, by the theorem, both X_{ij} and X_{ji} rely on single parameter U_{ij} which means one should jointly sample (X_{ij}, X_{ji}) together from three parameters U_i, U_j, U_{ij} . Also, asymmetric graphon W might be employed for directed random graph. However, [2] show that asymmetric graphon is inappropriate to impose certain structures on a graph such as the partial ordering and propose a class of priors for directed graphs.

References

- [1] David J Aldous. Representations for partially exchangeable arrays of random variables. *Journal of Multivariate Analysis*, 11(4):581–598, 1981.
- [2] Diana Cai, Nathanael Ackerman, and Cameron Freer. Priors on exchangeable directed graphs. pages 1–17, 2015.
- [3] Douglas N Hoover. Relations on probability spaces and arrays of random variables. *Preprint, Institute for Advanced Study, Princeton, NJ*, 2, 1979.
- [4] James Lloyd, Peter Orbanz, Zoubin Ghahramani, and Daniel Roy. Random function priors for exchangeable arrays with applications to graphs and relational data. In *Advances in Neural Information Processing Systems 26*, pages 1–9, 2013.